

EQUIPMENT SCHEDULE

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-H-04-99M	2000	33	73

MARK	ITEM	CAPACITY	ELEC.	REMARKS
ACCU 1	NOM. 2 TON AIR COOLED COND. UNIT	COMB. RATING: 22,800 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 600 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 12.9 FAN FLA 0.7	
FC 1	NOM. 600 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 0.53	
ACCU 2	NOM. 1.5 TON AIR COOLED COND. UNIT	COMB. RATING: 18,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 500 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 8.0 FAN FLA 0.7	
FC 2	NOM. 500 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 0.53	
ACCU 3	NOM. 3 TON AIR COOLED COND. UNIT	COMB. RATING: 34,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 840 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 17.9 FAN FLA 0.7	
FC 3	NOM. 840 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 1.30	
ACCU 4	NOM. 3 TON AIR COOLED COND. UNIT	COMB. RATING: 34,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 840 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 17.9 FAN FLA 0.7	
FC 4	NOM. 840 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 1.30	
ACCU 5	NOM. 3 TON AIR COOLED COND. UNIT	COMB. RATING: 34,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 800 CFM OF 67 DEG. F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 12.9 FAN FLA 0.7	
FC 5	NOM. 800 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 0.53	
ACCU 6	NOM. 2 TON AIR COOLED COND. UNIT	COMB. RATING: 22,800 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 600 CFM OF 67 DEG. F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 12.9 FAN FLA 0.7	
FC 6	NOM. 600 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 0.53	
ACCU 7	NOM. 1.5 TON AIR COOLED COND. UNIT	COMB. RATING: 18,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 500 CFM OF 67 DEG. F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 8.0 FAN FLA 0.7	
FC 7	NOM. 500 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 0.53	
ACCU 8	NOM. 1.5 TON AIR COOLED COND. UNIT	COMB. RATING: 18,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 500 CFM OF 67 DEG. F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 8.0 FAN FLA 0.7	
FC 8	NOM. 500 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 0.53	
ACCU 9	NOM. 1.5 TON AIR COOLED COND. UNIT	COMB. RATING: 18,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 500 CFM OF 67 DEG. F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 8.0 FAN FLA 0.7	
FC 9	NOM. 500 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 0.53	
ACCU 10	NOM. 1.5 TON AIR COOLED COND. UNIT	COMB. RATING: 18,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 500 CFM OF 67 DEG. F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 8.0 FAN FLA 0.7	
FC 10	NOM. 500 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 0.53	
ACCU 11	NOM. 3 TON AIR COOLED COND. UNIT	COMB. RATING: 34,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 840 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 17.9 FAN FLA 0.7	
FC 11	NOM. 840 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 1.30	
ACCU 12	NOM. 3 TON AIR COOLED COND. UNIT	COMB. RATING: 34,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 840 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 17.9 FAN FLA 0.7	
FC 12	NOM. 840 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 1.30	
ACCU 13	NOM. 3 TON AIR COOLED COND. UNIT	COMB. RATING: 34,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 840 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 17.9 FAN FLA 0.7	
FC 13	NOM. 840 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 1.30	
ACCU 14	NOM. 2.5 TON AIR COOLED COND. UNIT	COMB. RATING: 30,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 840 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 15.0 FAN FLA 0.7	
FC 14	NOM. 840 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 1.30	

MARK	ITEM	CAPACITY	ELEC.	REMARKS
ACCU 15	NOM. 4 TON AIR COOLED COND. UNIT	COMB. RATING: 47,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 1200 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 26.4 FAN FLA 1.45	
FC 15	NOM. 1200 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 1.60	
ACCU 16	NOM. 1.5 TON AIR COOLED COND. UNIT	COMB. RATING: 18,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 500 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 8.0 FAN FLA 0.7	
FC 16	NOM. 500 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 0.53	
ACCU 17	NOM. 2.5 TON AIR COOLED COND. UNIT	COMB. RATING: 30,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 840 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 15.0 FAN FLA 0.7	
FC 17	NOM. 840 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 1.30	
ACCU 18	NOM. 2.5 TON AIR COOLED COND. UNIT	COMB. RATING: 30,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 840 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 15.0 FAN FLA 0.7	
FC 18	NOM. 840 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 1.30	
ACCU 19	NOM. 1.5 TON AIR COOLED COND. UNIT	COMB. RATING: 18,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 500 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 8.0 FAN FLA 0.7	
FC 19	NOM. 500 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 0.53	
ACCU 20	NOM. 2 TON AIR COOLED COND. UNIT	COMB. RATING: 22,800 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 600 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 12.9 FAN FLA 0.7	
FC 20	NOM. 600 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 0.53	
ACCU 21	NOM. 3 TON AIR COOLED COND. UNIT	COMB. RATING: 34,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 840 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 17.9 FAN FLA 0.7	
FC 21	NOM. 840 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 1.30	
ACCU 22	NOM. 2.0 TON AIR COOLED COND. UNIT	COMB. RATING: 22,800 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 600 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 12.9 FAN FLA 0.7	
FC 22	NOM. 600 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 0.53	
ACCU 23	NOM. 4 TON AIR COOLED COND. UNIT	COMB. RATING: 47,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 1200 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 26.4 FAN FLA 1.45	
FC 23	NOM. 1200 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 1.60	
ACCU 24	NOM. 4 TON AIR COOLED COND. UNIT	COMB. RATING: 47,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 1200 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 26.4 FAN FLA 1.45	
FC 24	NOM. 1200 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 1.60	
ACCU 25	NOM. 1.5 TON AIR COOLED COND. UNIT	COMB. RATING: 18,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 500 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 8.0 FAN FLA 0.7	
FC 25	NOM. 500 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 0.53	
ACCU 26	NOM. 1.5 TON AIR COOLED COND. UNIT	COMB. RATING: 18,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 500 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 8.0 FAN FLA 0.7	
FC 26	NOM. 500 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 0.53	
ACCU 27	NOM. 3 TON AIR COOLED COND. UNIT	COMB. RATING: 34,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 840 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 17.9 FAN FLA 0.7	
FC 27	NOM. 840 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 1.30	
ACCU 28	NOM. 1.5 TON AIR COOLED COND. UNIT	COMB. RATING: 18,000 BTUH @ 95 DEG.F D.B. AIR ENT. COND., 500 CFM OF 67 DEG.F AIR ENT. EVAP. COIL	208/230V, 1PH. COMP. RLA 8.0 FAN FLA 0.7	
FC 28	NOM. 500 CFM FAN COIL UNIT		208/230V, 1PH. FAN FLA 0.53	

MARK	ITEM	CAPACITY	ELEC.	REMARKS
PAC 1	NOM. 1.5 TON AIR COOLED PACKAGE A/C UNIT	18,000 BTUH, 460 CFM	115V, 1PH. COMB. RLA 8.3	
EF 1	UPBLAST CENTRIFUGAL ROOF EXHAUSTER	1045 CFM @ 0.4" S.P.	208/230V, 1PH. 1/4 H.P. MOTOR	
EF 2	UPBLAST CENTRIFUGAL ROOF EXHAUSTER	780 CFM @ 0.4" S.P.	115V, 1PH. 1/4 H.P. MOTOR	
EF 3	UPBLAST CENTRIFUGAL ROOF EXHAUSTER	650 CFM @ 0.5" S.P.	208/230V, 1PH. 1/4 H.P. MOTOR	
EF 4	UPBLAST CENTRIFUGAL ROOF EXHAUSTER	13,500 CFM @ 0.375" S.P.	208/230V, 1 PH. 5 H.P. MOTOR	
EF 5	CYCLONE DUST COLLECTOR UNIT	4670 CFM @ 7.9" S.P.	208V, 3PH. 15 H.P. MOTOR	

DATE	_____
DESIGNED BY	_____
TRACED BY	_____
QUANTITIES BY	_____
CHECKED BY	_____
ORIGINAL PLAN	_____
NOTE BOOK	_____
No.	_____

6/12/00	Revised Equipment Schedule
Date	Revision

STATE OF HAWAII

DEPARTMENT OF TRANSPORTATION

HIGHWAYS DIVISION

EQUIPMENT SCHEDULE

HILO BASEYARD

IMPROVEMENTS

PROJECT NO. HWY-H-04-99M

Scale: Noted

Date: May 2000

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION

NYMR Y. TAMIMI

LICENSED PROFESSIONAL ENGINEER

No. 7936-M

HAWAII, U.S.A.

6/12/00

Revised Equipment Schedule

DWG. No.

M-14

SHEET No. 1 OF 1 SHEETS

ADD. 1 33