

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	STP-019-1(18)	1995	26	30

<u>LEGEND FOR</u>	
<u>AS-BUILT POSTINGS</u>	
	Squiggly line for as-built deletion
	Double line for as-built deletion
Roadway	Text for as-built posting

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

STRIPING AND PAVEMENT
MARKING SCHEDULE

QUEEN KAAHUMANU HWY RESURFACING
HONOKOHAU TO KEAHOLE
F. A. PROJECT No. STP-019-1(18)

Scale: As Shown Date: Feb, 1995

SHEET No. 1 OF 2 SHEETS

Station	Traffic Regime		Thermoplastic or Tape type () (linear feet)																Pavement Markers (each)				
			4" Double Yellow (I)	4" Double Yellow Guidelines (I)	4" Yellow C.L. (I)	12" Yellow Diagonal (II)	4" White Stripe (I)	4" White E.P (II)	8" White Stripe (I)	8" White Stripe (II)	12" White Diagonal (II)	4" White Edge Line Extension (III)	4" White Guide Lines (III)	12" Stop Bar (III)	Solid White Arrow			Solid White Words (III)	A	C	D	H	J
	Rt. (III)	St. (III)													Lt. (III)								
215+50																							
229+17.91	EQUATION STATION																						
228+00	N	N	3775			1230	490	3905	510	461	400	400	360	12		7	4	≠3-Only	****212	189		187	
233+17	AIRPORT RD OPEN			100				40		295	65		110	12					****128	17	6		
233+57	N	N	300			65	70	420	105	258	225			15	2	1		≠	8	39		16	
235+00	N	N	365			135	110	360	70				180		1	1		1-Only	12	22		20	
236+80	N	N	1800			495	275	1800					180		2	2		1-Only	****156	60		90	
245+80	N	N	170					340												10	9		
247+50	P	N			410			820												22	11	11	44
251+60	P	P																			20		76
259+20																							
	TOTAL		***20,867	60	1,410	3,501	4,453	48,527	2,182	2,409	1,475	1,950	2,305	184	20	33	17	24 ≠	****872	1,764	695	768	1,084

Diagram illustrating the cross-section of a two-lane highway with various safety features and dimensions:

- Left Lane:**
 - Direction of Traffic: Indicated by an arrow pointing left.
 - Double 4' Yellow Guide Lines (Thermoplastic Extrusion): Located on the left side of the lane.
 - Varies: Dimension for the left lane width.
 - 20'-0" Typical: Dimension for the lane width.
 - Varies*: Dimension for the shoulder width.
- Right Lane:**
 - Direction of Traffic: Indicated by an arrow pointing right.
 - 4" Double Solid Yellow Stripe w/Type HL Raised Pavement Markers @ 20'-0" o.c. (Tape, Type II or Thermoplastic Extrusion): Located on the right side of the lane.
 - 12" Yellow Stripe (Tape, Type II or Thermoplastic Extrusion): Located on the right side of the lane.
 - 45°: Angle of the shoulder slope.
 - Varies*: Dimension for the shoulder width.
 - Varies**: Dimension for the right lane width.

- Private Driveway

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

STRIPING AND PAVEMENT
MARKING SCHEDULE

QUEEN KAAHUMANU HWY RESURFACING
HONOKOHAU TO KEAHOLE
F. A. PROJECT NO. STP-019-1(18)

Scale: As Shown Date: Feb., 1995

SHEET No. 2 OF 2 SHEETS