

FED. ROAD DIST.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	FLH-019-1(26)	2000	19	46


GUARDRAIL NOTES

- The locations and limits of guardrails shown on the plans are approximate. The Contractor shall stake-out guardrail locations in the field for acceptance by the Engineer.
- Unless otherwise noted all guardrail elements shall be 12' - 6" nominal length.
- For all Modified Type 'G' end treatments:
  - Provide a curve radius to extend the flare away from the travelway.
  - Use the 'Rounded End Section' in lieu of the 'Flared End Section' (Refer to Plan Sheet 28).
- Placement of Asphalt Concrete Mix V from edge of shoulder to 1 - 0" beyond the guardrail post applies to the entire length of guardrail, including flared segments and end treatments.
- All existing posts and guardrails for removal shall be disposed of by the contractor at no cost to the State. This work shall be considered incidental to the contract Item No. 606.3110 - Strong Post W-Beam Guardrail.
- The Contractor shall provide new edge of pavement striping (equal or better than existing) and Type 'C' markers at each work site destroyed by his operation as determined by the Engineer. The Contractor shall also replace striping or reflector markers damaged by his operations. Payment for this work shall be incidental to various Contract Items.
- Removal and reinstallation or relocation of existing signs for the purpose of guardrail removal and installation shall be incidental to Item No. 606.3110 - Strong Post W-Beam Guardrail. Signs damaged by the contractor's operations shall be repaired or replaced at no cost to the State.
- All end treatments (Terminal, modified "A-I", "G", Fleet 350, etc.) not completed by day's end shall be properly delineated with Triton Barriers as directed by the Engineer. Payment for use of the Triton Barrier shall be considered incidental to guardrail installation.
- Replacement of existing guardrails shall be completed within the same day. No unshielded areas shall be permitted at the end of the work day.
- References on the plans to Standard Metal Guardrails and Posts shall be considered the same as Strong Post W-Beam Guardrail.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
	DRAWN BY	
	TRACED BY	
	NOTED BY	
NOTE BOOK Bqthg'd N. dgn	QUANTITIES BY	
	CHECKED BY	

STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION	
GUARDRAIL NOTES	
QUEEN KA'AHUMANU HIGHWAY INTERSECTION IMPROVEMENTS TO KALOKO-HONOKOHAU NATIONAL HISTORICAL PARK	
PROJECT NO. FLH-019-1(26)	
Scale: Noted	Date: Feb., 1998
SHEET No. 1 OF 15 SHEETS	


FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	FLH-019-1(26)	2000	20	46



TYPICAL @ MODIFIED "A-1" & FLEAT 350 END TREATMENT

REFLECTOR MARKER NOTES:

1. All reflector markers located behind guardrail and other locations shall be installed with flexible delineator posts.
2. Exact location of Reflector Markers shall be determined in the field by the Engineer.
3. Color of flexible delineator posts shall be white except for RM-3, RM-3 bidirectional, and RM-3/RM-2 combinations shall be yellow posts.
4. RM-2 shall be white.



TYPICAL @ "G" & MODIFIED "A-1" END TREATMENT

NOTE:

\* Exact location of Reflector Markers shall be determined in the field by the Engineer.

TYPICAL REFLECTOR MARKER INSTALLATION  
AT GUARDRAILS

Not To Scale

STATE OF HAWAII

DEPARTMENT OF TRANSPORTATION

HIGHWAYS DIVISION

GUARDRAIL REFLECTOR

MARKER DETAIL

QUEEN KA'AHUMANU HIGHWAY

INTERSECTION IMPROVEMENTS

PROJECT NO. FLH-019-1(26)

Scale: Noted

Date: Mar., 1998


SHEET No. 2

OF 15


SHEETS

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTED	DRAWN BY	
DESIGNED BY	CHECKED BY	
APPROVED BY		

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	FLH-019-1(26)	2000	21	46




TOP  
SIDE  
RECYCLED PLASTIC BLOCKOUT (TYPE I)





RECYCLED POLYETHYLENE  
OFFSET BLOCK (TYPE II)

- GENERAL NOTES
- All hardware, posts and fasteners shall be hot-dip zinc coated galvanized after fabrication. No punching, drilling or cutting will be permitted after galvanizing.
  - Where conditions require, special post lengths in increments of 6 inches may be specified.
  - All fasteners, posts, and rail elements (i.e. FBB03, PWE01, RWM02b, etc.) shall conform to the latest edition and amendments of "A Guide to Standardized Highway Barrier Rail Hardware," a report prepared and approved by the AASHTO-AGC-ARTBA Joint Cooperative Committee, Subcommittee On New Highway Materials, Task Force 13 Report. Dimensions of fasteners, posts and rail elements have been converted from metric units into their present form.
  - The Recycled Plastic Block or Offset Block shall be approved by the State.
  - If paving under guardrails is provided for in the contract, the Contractor shall grout around the guardrail post and seal all cracks in the paved area that was caused during the guardrail post installation. If required by the inspector/engineer, the Contractor shall tamper the paved area around the guardrail post prior to grouting. The cost for this work shall not be paid for separately, but shall be considered incidental to the various guardrail items.
  - When standards for the fill slope area cannot be met, a site specific, engineer approved design may be used.



Exploded View  
(Rail and washer not shown)  
STEEL POST AND BLOCK DETAIL



ELEVATION  
TYPICAL GUARDRAIL INSTALLATION

GUARDRAIL TYPE	DIMENSION		
	H	A	B
Strong Post w/W Beam	1'-9 5/8"	1'-6"	1'-0"
Rubrail	2'-0"	1'-6"	2'-0"
Modified Thrie Beam	2'-0"	2'-0"	1'-0"

ORIGINAL PLAN	DATE
SURVEY PLOTTED BY	
DRAWN BY	
DESIGNED BY	
CHECKED BY	
NOTED BY	
DATE	



STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**GUARDRAIL DETAILS & NOTES**  
**QUEEN KA'AHUMANU HIGHWAY**  
**INTERSECTION IMPROVEMENTS TO**  
**KALOKO-HONOKOHAU NATIONAL HISTORICAL PARK**  
**PROJECT NO. FLH-019-1(26)**  
Scale: Noted Date: Aug., 1999


SHEET No. 3 OF 15 SHEETS




FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	FLH-019-1(26)	2000	22	46






**STRONG POST W-BEAM GUARDRAIL (SGR04a)**



**STRONG POST W-BEAM GUARDRAIL WITH RECYCLED OFFSET BLOCK OR PLASTIC BLOCKOUT**



**W-BEAM STRONG POST (PWE01)**



ORIGINAL PLAN	DATE	BY
DRAWN BY		
DESIGNED BY		
CHECKED BY		
NOTED BY		
SCALE		
DATE		


STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**STRONG POST W-BEAM GUARDRAIL**  
**QUEEN KA'AHUMANU HIGHWAY**  
**INTERSECTION IMPROVEMENTS TO**  
**KALOKO-HONOKOHAU NATIONAL HISTORICAL PARK**  
**PROJECT NO. FLH-019-1(26)**  
Scale: Noted      Date: Aug., 1999


SHEET No. 4 OF 15 SHEETS




FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	FLH-019-1(26)	2000	23	46




W-BEAM TERMINAL CONNECTOR (RWE02b)



W-BEAM END SECTION (FLARED RWE01b)



W-BEAM END SECTION (BUFFER RWE06b)



W-BEAM END SECTION (ROUNDED RWE03a)

SURVEY PLOTTED BY	DATE
DRAWN BY	
TRACED BY	
CHECKED BY	
NOTED BY	
QUANTITIES BY	
CHECKED BY	
ORIGINAL PLAN	
NOTE BOOK	
804/ha3	
No. 2/99	

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**STRONG POST W-BEAM GUARDRAIL**


QUEEN KA'AHUMANU HIGHWAY  
INTERSECTION IMPROVEMENTS TO  
KALO KO - HONOKOHAU NATIONAL HISTORICAL PARK

PROJECT NO. FLH-019-1(26)


Scale: Noted Date: Aug., 1999

SHEET No. 5 OF 13 SHEETS


FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	FLH-019-1(26)	2000	24	46



ELEVATION  
STRONG POST RUBRAIL  
(W-BEAM) GUARDRAIL




SIDE  
FRONT  
W-BEAM STRONG POST (PWE02)




DESIGNATOR	L
FBB01	1 3/8"
FBB02	2"
FBB03	10"

GUARDRAIL BOLTS AND  
RECESSED NUT




DESIGNATOR	BASE METAL THICKNESS
RWB01b	17/128"

W-BEAM BACK-UP-PLATE (RWB01b)




ELEVATION  
STRONG POST RUBRAIL (W-BEAM) GUARDRAIL WITH  
RECYCLED OFFSET BLOCK OR PLASTIC BLOCKOUT



DESIGNATOR	BASE METAL THICKNESS
RWM02b	17/128"

2 SPACE W-BEAM GUARDRAIL (RWM02b)



HEX BOLT & NUT (FBX16a)

ORIGINAL PLAN	DATE	BY
SURVEY PLOTTED BY		
DRAWN BY		
DESIGNED BY		
CHECKED BY		
NOTED BY		
APPROVED BY		
NO.		

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION


STRONG POST RUBRAIL  
(W-BEAM) GUARDRAIL  
QUEEN KA'AHUMANU HIGHWAY  
INTERSECTION IMPROVEMENTS  
PROJECT NO. FLH-019-1(26)

Scale: As Shown  
Date: Aug., 1999

SHEET No. 6 OF 15 SHEETS




FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	FLH-019-1(26)	2000	25	46




**TRANSITION SECTION \***

\* Post spacing not to be used for Thrie Beam connection to structures.




**BACKUP PLATE (RTB01b)**


(Use at Posts where Splices do not occur)



**SECTION THRU RAIL ELEMENT (RTM02b)**




**RAIL SPLICE**




**END SECTION (BUFFER RTE03b or RTE04b)**


Slotted Holes 2 1/32" x 1/8"




**TRANSITION SECTION (RWT01b)**




**PLAN**




**SECTION (ROUNDED) (RTE02b)**




**PLAN**




**TERMINAL CONNECTOR (RTE01b)**




**SPACER BLOCK PWB03**




**STEEL WASHER FOR 5/8" BOLT**



**HEX BOLT & NUT (FBX16a)**




**W-BEAM STRONG POST (PWE04)**



DESIGNATOR	L
FBB01	1 3/8"
FBB02	2"
FBB03	10"

**GUARDRAIL BOLTS AND RECESSED NUT**



**STRONG POST MODIFIED THRIE-BEAM GUARDRAIL (SGR09b)**

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION



**STRONG POST MODIFIED THRIE-BEAM GUARDRAIL**

QUEEN KA'AHUMANU HIGHWAY  
INTERSECTION IMPROVEMENTS  
PROJECT NO. FLH-019-1(26)

Scale: As Shown Date: Aug., 1999


SHEET No. 7 OF 15 SHEETS

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	FLH-019-1(26)	2000	26	46



NOTES:

1. All Guardrail and Concrete Barrier Designs at Obstructions shall be approved by the Engineer.
2. If  $X < 2'-0"$ , Concrete Barrier or special guardrail design.  
 $2'-0" \leq X < 3'-0"$ , Strong Post Rubrail or Modified Thrie-Beam with reduced post spacing.  
 $3'-0" \leq X$ , Strong Post W-Beam or Modified Thrie-Beam with 6'-3" post spacing. (Normal Installation)
3. If a pedestrian walkway or bicycle route is located behind the guardrail, the Engineer should install the Modified Thrie-Beam System. The rubrail termini may become a hazard to pedestrians & bicyclists.



DETAIL OF GUARDRAIL INSTALLATION AT OBSTRUCTION

DESIGNED BY	DATE
DRAWN BY	
CHECKED BY	
IN CHARGE	
NOTED BY	
ORIGINAL	
PLAN	
NO. 1	
NO. 2	
NO. 3	
NO. 4	
NO. 5	
NO. 6	
NO. 7	
NO. 8	
NO. 9	
NO. 10	
NO. 11	
NO. 12	
NO. 13	
NO. 14	
NO. 15	
NO. 16	
NO. 17	
NO. 18	
NO. 19	
NO. 20	
NO. 21	
NO. 22	
NO. 23	
NO. 24	
NO. 25	
NO. 26	
NO. 27	
NO. 28	
NO. 29	
NO. 30	
NO. 31	
NO. 32	
NO. 33	
NO. 34	
NO. 35	
NO. 36	
NO. 37	
NO. 38	
NO. 39	
NO. 40	
NO. 41	
NO. 42	
NO. 43	
NO. 44	
NO. 45	
NO. 46	


STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**GUARDRAIL DETAILS**  
**(AT OBSTRUCTION)**  
**QUEEN KA'AHUMANU HIGHWAY**  
**INTERSECTION IMPROVEMENTS**  
**PROJECT NO. FLH-019-1(26)**  
Scale: NTS Date: Aug., 1999

SHEET No. 8 OF 15 SHEETS




FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	FLH-019-1(26)	2000	27	46



**NOTES:**

1. Metal Guardrail connection to concrete structures requires End Post Connection. See Structure Plans.
2. Depending on the existing field conditions, the Engineer shall determine which guardrail end terminal should be installed.
3. Refer to State's most current approved Product List for NCHRP 350 approved Guardrail End Terminals.



ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTED BY	DRAWN BY	
DESIGNED BY	CHECKED BY	
DATE		

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**GUARDRAIL DETAILS**  
**APPROACH END FLARE**  
**QUEEN KA'AHUMANU HIGHWAY**  
**INTERSECTION IMPROVEMENTS**  
**PROJECT NO. FLH-019-1(26)**  
Scale: NTS Date: Aug., 1999

SHEET No. 9 OF 15 SHEETS






FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	FLH-019-1(26)	2000	29	46


General Notes

1. All posts are 8'-0" in length within the 50'-0" pay limit for the Modified Type "A-1" Flare.
2. All fasteners, posts, blocks and rail elements shall conform to the latest edition and amendments of "A Guide to Standardized Highway Barrier Rail Hardware," a report prepared and approved by the AASHTO-AGCARTBA Joint Cooperative Committee.
3. Limit of payment for Modified Type "A-1" Flare shall be 50'-0" from End Shoe including Anchor Block and GRP work.
4. Excavation, Anchor Block, Backfill and GRP work shall be considered incidental to the Modified Type "A-1" Flare.




PLAN

Design speed mph	a:b
68	15:1
62	13:1
56	12:1
50	11:1
43	10:1
37	9:1
31	7:1




ELEVATION (Profile Along Rail)

- \* Posts at 3'-1 1/2" o.c.
- \*\* Posts at 1'-6 3/4" o.c.



ANCHOR BLOCK IN CUT SECTION



PLAN - ANCHOR BLOCK IN CUT SECTION

STATE OF HAWAII

DEPARTMENT OF TRANSPORTATION

HIGHWAYS DIVISION

MODIFIED TYPE "A-1" FLARE

QUEEN KA'AHUMANU HIGHWAY

INTERSECTION IMPROVEMENTS TO

KALOKO-HONOKOHAU NATIONAL HISTORICAL PARK

PROJECT NO. FLH-019-1(26)

Scale: Noted

Date: Aug., 1999


SHEET No. 11

OF 15


SHEETS

ORIGINAL PLAN	DATE
SURVEY PLATTED BY	
DRAWN BY	
DESIGNED BY	
CHECKED BY	
NOTED BY	
APPROVED BY	
DATE	



FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	FLH-019-1(26)	2000	30	46



STRONG POST W-BEAM GUARDRAIL



ANCHOR ASSEMBLY  
CONCRETE BLOCK ANCHOR



CONCRETE BLOCK ANCHOR  
(3' X 3' X 3')

BACKSLOPE ANCHOR TERMINAL END ANCHORAGE DETAILS  
MODIFIED TYPE "A-1" FLARE

Note:  
All fasteners, posts, blocks and rail elements shall conform to the latest edition and amendments of "A Guide to Standardized Highway Barrier Rail Hardware," a report prepared and approved by the AASHTO-AGCARTBA Joint Cooperative Committee.

ORIGINAL PLAN	DATE	BY
SURVEY PLACED BY		
DRAWN BY		
DESIGNED BY		
CHECKED BY		
NOTED BY		
QUANTITIES BY		
DATE		



STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**MODIFIED TYPE "A-1" FLARE**  
 QUEEN KA'AHUMANU HIGHWAY  
 INTERSECTION IMPROVEMENTS TO  
 KALOKO-HONOKOHAU NATIONAL HISTORICAL PARK  
 PROJECT NO. FLH-019-1(26)  
 Scale: none Date: Aug., 1999

SHEET No. 12 OF 15 SHEETS



FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	FLH-019-1(26)	2000	31	46









#### GENERAL NOTES

- Wood posts are required with the fleet.
- All bolts, nuts, cable assemblies, cable anchors and bearing plates shall be galvanized.
- The soil tube shall not protrude more than 4" above ground (measured along a 5' cord). Site grading may be necessary to meet this requirement.
- The soil tubes may be driven with an approved driving head. They shall not be driven with the wood post in the tube. If the soil tubes are placed in drilled holes, the backfill material must be satisfactorily compacted to prevent settlement.
- When rock is encountered during excavation, a 12" Dia. post hole, 20" deep may be used if approved by the engineer. Granular material will be placed in the bottom of the hole approx. 2 1/2" deep to provide drainage. The soil tubes will be field cut to length, placed in the hole and backfilled with adequately compacted material excavated from the hole.
- The breakaway cable assembly must be taut. A locking device, (vice grips or channel lock pliers) should be used to prevent the cable from twisting when tightening nuts.
- The wood blockouts shall be "toe nailed" to the rectangular wood posts to prevent them from turning when the wood shrinks.
- For curb installations, the soil tubes and posts shall be installed at the proper ground elevation behind the curb. The posts will require field drilling new holes to accommodate the rail to the post connecting bolt to maintain the proper height of the rail above the gutter pan. The excess post length above the rail will be removed if directed by the engineer.

ITEM NO.	QTY	BILL OF MATERIALS
S3000	1	IMPACT HEAD
F1303	1	W-BEAM GUARDRAIL END SECTION, 12 GA.
F1304	1	W-BEAM GUARDRAIL CENTER SEC., 12 GA.
G1203	1	W-BEAM GUARDRAIL, 12 GA.
S730	2	*FOUNDATION SOIL TUBE, 6" x 8" x 6'
E740	1	PIPE SLEEVE
E750	1	BEARING PLATE, 8" x 8" x 5/8"
S760	1	CABLE ANCHOR BOX
E770	1	BCT CABLE ANCHOR ASSEMBLY
E780	1	GROUND STRUT
P650	2	5.5" x 7.5" x 45" WOOD POSTS
P671	5	6" x 8" x 6' WOOD CRT POST
P675	5	6" x 8" x 14" TIMBER BLOCKOUT
HARDWARE		
B580122	24	5/8" Dia. x 1 1/4" SPLICE BOLT
B580754	2	5/8" Dia. x 7 1/2" HEX BOLT
B581004	2	5/8" Dia. x 10" HEX BOLT
B581002	1	5/8" Dia. x 10" H.G.R. BOLT (POST 2 ONLY)
B581802	5	5/8" Dia. x 18" H.G.R. BOLT (POST 3-7)
N050	34	5/8" Dia. H.G.R. NUT (SPLICE 24, SOIL TUBES 2, STRUT 2, POST 2, 1/2 POST 3 THRU 7, 5J)
W050	10	5/8" Dia. H.G.R. WASHER
N100	2	1" ANCHOR CABLE HEX NUT
W100	2	1" ANCHOR CABLE WASHER
E350	2	3/8" x 3" LAG SCREW
SB58A	8	CABLE ANCHOR BOX SHOULDER BOLTS
N055A	8	1/2" A325 STRUCTURAL NUTS
W050A	16	1 1/16" OD x 9/16" ID A325 STR. WASHER

#### Foundation Tube Options For Posts 1 & 2

- \*6'-0" Split Foundation Tubes S730
- \*6'-0" Solid Foundation Tubes E731
- \*5'-0" Foundation Tubes S735 W/Soil Plates SP600
- \*4'-6" Foundation Tubes E735 W/Soil Plates SP600



STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**FLEAT-350**  
**FLARED ENERGY ABSORBING TERMINAL**




QUEEN KA'AHUMANU HIGHWAY  
GUARDRAIL AND SHOULDER IMPROVEMENTS  
PROJECT NO. FLH-019-1(26)

Scale: As Shown Date: Aug., 1999

SHEET No. 13 OF 15 SHEETS



FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	FLH-019-1(26)	2000	32	46





\*\*not supplied by Road Systems.

**GENERAL NOTES:**

- Wood posts are required with the Sequential Kinking Terminal.
- All bolts, nuts, cable assemblies, cable anchors and bearing plates shall be galvanized.
- When the Sequential Kinking Terminal is selected as the end treatment for MBGF installation, the MBGF shall be flared at a rate of 50:1 to prevent the impact head from encroaching on the shoulder.
- The soil tube shall not protrude more than 4" above ground (measured along a 5' cord). Site grading may be necessary to meet this requirement. Soil tubes shall be installed for all wood posts.
- The soil tubes may be driven with an approved driving head. They shall not be driven with the wood post in the tube. If the soil tubes are placed in drilled holes, the backfill material must be satisfactorily compacted to prevent settlement.

**GENERAL NOTES: (continued)**

- When rock is encountered during excavation, a 12" Dia. post hole, 20" deep may be used if approved by the engineer. Granular material will be placed in the bottom of the hole approx. 2 1/2" deep to provide drainage. The soil tubes will be field cut to length, placed in the hole and backfilled with adequately compacted material excavated from the hole.
- The breakaway cable assembly must be taut. A locking device, (vice grips or channel lock pliers) should be used to prevent the cable from twisting when tightening nuts.
- The wood blockouts shall be "toe nailed" to the rectangular wood posts to prevent them from turning when the wood shrinks.
- A special site evaluation should be considered prior to using the Sequential Kinking Terminal where there is less than 25' between the outlet side of the Sequential Kinking Terminal and any adjacent driving lane.



SURVEY PLOTTED BY	DATE
DRAWN BY	
TRACED BY	
NOTED BY	
QUANTITIES BY	
CHECKED BY	
ORIGINAL PLAN	
NOTE BOOK	
REVISION	
DATE	
BY	
REASON	

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**SKT-350**

**SEQUENTIAL KINKING TERMINAL**


QUEEN KA'AHUMANU HIGHWAY  
INTERSECTION IMPROVEMENTS  
PROJECT NO. FLH-019-1(26)

Scale: As Shown Date: Aug., 1999


SHEET No. 14 OF 15 SHEETS



FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	FLH-019-1(26)	2000	33	46



BILL OF MATERIAL		
PC	QTY	DESCRIPTION
60G	1	12/25/63/S (GUARDRAIL)
62G	1	12/25/63/S ANC (GUARDRAIL)
704A	1	CABLE ANCHOR BRACKET
705G	1	2" x 5 1/2" PIPE
740G	8	46 TUBE SLEEVE
766G	8	1/4" x 18" x 24" SOIL PLATE
782G	1	5/8" x 8" x 8" BEARING PLATE
985A	1	ET-2000 EXTRUDER
3000G	1	CABLE 3/4 x 6'6"
3300G	11	5/8" WASHER
3340G	47	7/8" HEX NUT
3360G	16	5/8" x 1 1/4" SPLICE BOLT
3478G	16	5/8" x 7 1/2" HEX HD BOLT
3497G	8	5/8" x 9 1/2" HEX HD BOLT
3580G	7	5/8" x 18" POST BOLT
3900G	2	1" WASHER
3910G	2	1" HEX NUT
4075B	7	WD BLOCK 1'2 6" x 8" DR
4147B	8	WD 3'9 POST 5 1/2 x 7 1/2
4228G	2	3/8" x 4" LAG SCREW
9918A	1	6'3 STRUT



ORIGINAL PLAN	DATE
DRAWN BY	
DESIGNED BY	
CHECKED BY	
NOTED BY	
DATE	

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

ET-2000 - OPTION "A"

QUEEN KA'AHUMANU HIGHWAY  
INTERSECTION IMPROVEMENTS TO  
KALOKO-HONOKOHAU NATIONAL HISTORICAL PARK

PROJECT NO. FLH-019-1(26)

Scale: Noted Date: Aug., 1999

SHEET No. 15 OF 15 SHEETS