


Construction Notes:

- 1. Locations Of Existing Underground Structures And Utilities Such As Pipelines, Conduits, Cables, Etc., Shown On Plans Are Approximate Only. It is Not The Intent Of These Plans To Show The Exact Location Of All Underground Utilities And Structures. It Is The Responsibility Of The Contractor To Verify The Locations Of All Existing Utilities With The Respective Owners. Existing Utilities Damaged By The Contractor Shall Be Repaired By The Contractor At His Own Cost.
- 2. The Contractor Shall Verify And Check All Dimensions And Details Shown On The Drawings Prior To The Start Of Construction. Any Discrepancy Shall Be Immediately Brought To The Attention Of The Engineer For Clarification.
- 3. The Contractor Shall Notify All Agencies To Verify, Tone And Locate Their Existing Utilities Within The Project Area Prior To Excavating. The Contractor Shall Coordinate All Work.
- 4. The Locations Of The New Pullboxes, Conduits, Piezo Sensors And Loop Detectors Shall Be Staked Out In The Field By The Contractor And Approval Of The Locations Shall Be Obtained From The Engineer Prior To Construction And Installation.
- 5. All Traffic Signal Work Shall Conform To The Requirements Of The "Manual On Uniform Traffic Control Devices Millennium Edition", Federal Highway Administration (2000) And Amendments.




- 6. Maintenance Of Traffic Through The Construction Area Shall Be In Accordance With Part VI Of The "Manual On Uniform Traffic Control Devices Millennium Edition, Federal Highway Administration (2000) As Amended And As Specified In The Special Provisions. The Contractor Shall Furnish And Maintain Adequate Barricades, Blinkers, Construction Signs, Etc., For The Safety Of The Motoring Public.
- 7. At The End Of Each Day's Work, The Contractor Shall Remove All Equipment And Other Obstructions To Permit Free And Safe Passage Of Public Traffic.
- 8. A Representative Of The Piezo Sensor's Manufacturer Shall Be Present To Supervise The Installation And Testing Of The Piezo Sensors. Coordination And Costs Associated With The Abovementioned Item Are The Responsibility Of The Contractor.
- 9. See Civil Drawings For Additional Information Regarding Existing Site Conditions.

	ELECTRICAL SYMBOL LIST	
SYMBOL	DESCRIPTION	
	Existing Traffic Signal Pullbox	
	New Type "A" Pullbox	
	Existing Controller Cabinet	
-e	—e—-— Existing Ductline	
New Ductline		
	Conduit To Sawcut Transition	
	Existing Sensor Loop	
	New Sensor Loop	
	Existing Piezo Sensor	
	New Piezo Sensor	
	Existing Sawcut And Cables/Leads	
	New Sawcut And Cables/Leads	
•	New Pole And Solar Panel Assembly	
<u>_</u>	Ground	
×	Denotes Demolition/Removal	

Traffic Signal Notes:

- 1. A Solid #8 Bare Copper Wire Shall Be Pulled Within All Conduits For Equipment Ground. Cost Shall Be Incidental To The Installation Of The Cable.
- 2. Conduits And Pullbox Location As Shown On The Plans Are Schematic. They May Be Modified By The Contractor With The Approval Of The Engineer.
- 3. All Work For The Installation Or Modification Of The Weigh-In-Motion System Shall Conform To The Latest Revisions Of The "Hawaii Standard Specifications for Road And Bridge Construction, 1994" And The "Standard Plans" Of The Department Of Transportation, Highways Division And As Shown On These Drawings.
- 4. Furnishing And Installing The Conduit Stubouts (Pullboxes To Edge Of Pavement Will Not Be Paid For Separately But Shall Be Considered Incidental To The Various Contract Items.
- 5. All Cable And Elements For Grounding Shall Be New.
- 6. Contractor Shall Verify Condition And Operation Of The Existing Controller And Associated Electronics Prior To Making Any Modifications. Provision Of Power, Labor And Materials For Verification Of Operation Is The Responsibility Of The Contractor. Contractor Shall Submit Written Procedures For Verifying Operation Of The Existing Controller And Items Requiring Remediation To The Engineer For Approval.



APRIL 30, 2004

EXPIRATION DATE OF THE LICENSE

STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION

ELECTRICAL SITE PLAN

Queen Kaahumanu Highway Resurfacing Kekaha Kai State Park to Hapuna Federal-Aid Project No. NH-019-1(33)


Scale: As Noted


Date: March 2003 SHEET No. E-1 OF 4 SHEETS

10' 5' 0 SCALE: 1"= 10'

3/5/03-13:47 Y: $\087\e87-93\87-93\sc{S01.dwg}$

SURVEY PLOTTE
DRAWN BY
TRACED BY
DESIGNED BY
QUANTITIES BY
CHECKED BY





└─ 3—Type 4 Cables To IMSA SPEC 51—5


TYPICAL SECTION THROUGH SENSOR LOOP

<u>SECTION</u>

Type 4 Cables
To IMSA SPEC


51-5.2 X No. Of

Loops "Upstream"




- 1. Seal Roadway End Of Conduit After Installation Of Conductors
- 2. Install Bulkhead Across Conduit Trench.
- 3. Place Hot Tar In Sawcut.
- 4. Backfill Over Conduit With New A.C.

CONDUIT TO SAWCUT TRANSITION




TYPICAL SENSOR LOOP WIRING DIAGRAM Not To Scale



FED. ROAD DIST. NO. STATE

FED. AID PROJ. NO.



LICENSED

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

PROJECT ENGINEER for ECS, Inc.

APRIL 30, 2004

EXPIRATION DATE OF THE LICENSE

Not To Scale

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION


LOOP DETECTOR DETAILS

Queen Kaahumanu Highway Resurfacing Kekaha Kai State Park to Hapuna Federal-Aid Project No. NH-019-1(33)

Scale: As Noted


Date: March 2003 SHEET No. E-3 OF 4 SHEETS


FISCAL SHEET TOTAL YEAR NO. SHEETS




Not To Scale

<u>SECTION</u>







SECTION A-A




TYPE "A" PULLBOX Not To Scale



TYPICAL FLASHING COMPOUND WATERPROOFING DETAILS Not To Scale



TYPICAL CONSTRUCTION JOINT DETAIL Not To Scale



ELEVATION

POLYMER CONCRETE COVER Not To Scale

FED. ROAD DIST. NO. STATE FISCAL YEAR SHEET NO. FED. AID PROJ. NO. SHEETS NH-019-I(33) 2003 HAWAII

<u>General Notes:</u>

- 1. Provide A Minimum Of One 16¢ ~ X 2.5m Copperweld Ground Rod In Each Pullbox. When Directed By The Traffic Signal Inspector/Engineer, Install Additional Ground Rods. Cost Of Ground Rods Shall Be Incidental To The Pullboxes.
- 2. All Pre-Cast Concrete Pullboxes Shall Be Manufactured In Two Pieces.
- 3. The Pullbox With Cover Shall Be Capable Of Supporting An MS 18 Loading.
- 4. The Maximum Weight Of The Pullbox Cover Shall Not Exceed 27 Kilograms.
- 5. The Openings For The Conduits On All Pullboxes Shall Be Pre-Cast Concrete Knockouts.
- 6. After Installing The Conduits In The Openings Of The Pullboxes, The Contractor Shall Fill The Excess Opening In The Pre-Cast Knockouts With Concrete
- 7. Prior To Installing The Pullboxes, The Contractor Shall Level The Bottom Of The Trench And Achieve A Minimum Of 95% Relative Compaction Of The Bottom Of The Trench.
- 8. All Concrete Shall Be Class A (25Mpa, Minimum)
- 9. Rebars Shall Be Grade 300 And All Lapped Splices Shall Be 360mm Minimum.
- 10. The #57 Or #67 Size Aggregate Shall Conform To Latest Version Of AASHTO M43 (ASTM D 448).
- 11. Dimension Are In Metric.



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION. PROJECT ENGINEER for ECS, Inc. APRIL 30, 2004

EXPIRATION DATE OF THE LICENSE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION

> TRAFFIC SIGNAL PULLBOX DETAILS

Queen Kaahumanu Highway Resurfacing Kekaha Kai State Park to Hapuna Federal-Aid Project No. NH-019-1(33)

Scale: As Noted

Date: March 2003 SHEET No. E-4 OF 4 SHEETS


3/5/03-13:49 Y:\087\e87-93\87-93T02.dwg

Construction Notes:


- 1. Refer To Sheet E-1 For Additional Construction Notes.
- 2. All Necessary Permits Shall Be Obtained By The Contractor At His Own Cost.
- 3. All Work Shall Be Constructed In Accordance With The Following Construction Standards And Specifications.
 - a. General Order No. 6 And No. 10 Public Utilities Commission, State Of Hawaii.
 - b. Construction Standards Of Department Of Transportation, State Of Hawaii.
 - c. Current Standard Specifications For Road And Bridge Construction, State of Hawaii.
 - d. Standard Details For Public Works Construction, Department Of Public Works, County Of Hawaii.
- 4. The Contractor Shall Exercise Proper Care When Excavating In Areas With Existing Underground Facilities, Damages To The Existing Facilities Shall Be Immediately Reported To The Respective Utility Companies, County Or State Agency. The Repair Work Shall Be Provided At No Additional Cost To This Project.
- 5. See Civil Drawings For Additional Information Regarding Existing And New Site Conditions And Locations Of Intersections.

Traffic Signal Notes:


- 1. Refer To Sheet E-1 For Additional Traffic Signal Notes.
- 2. Restoration Of Existing Pavements And Improvements Unavoidably Damaged Shall Be Incidental To The Various Contract Ítems. Řestoration Shall Be Equal To Original Or Better Than Original Condition.
- 3. Contractor Shall Verify Condition And Operation Of Existing Controller And Electronics Prior To Making Any Modifications. Provision Of Labor And Materials For Verification Of Operation Is The Responsibility Of The Contractor. Contractor Shall Submit Written Procedures For Verifying Operation Of The Existing Controller And Items Requiring Remediation To The Engineer For Approval.
- 4. Contractor Shall Provide Necessary Labor And Materials To Program And Test Existing Controller After New Loop Detectors Are Provided. Refer To Phase Assignment








Phase Assignment Diagrams Obtained From Queen Kaahumanu Highway Traffic Operational Improvements At Waikoloa Beach Drive And Waikoloa Road, Project No. 19C-01-02, Construction Drawings.



LOOP DETECTOR ASSIGNMENTS			
LD-#	AMPLIFIER UNIT	CHANNEL	PHASE-NOTES
1 & 2	A	1	ø6 Or ø2 (Hand Wired Together)
3	A	1	ø1 & ø6 (Internally Switched)
4	В	3	Ø4
5 & 6	В	2	ø2 & ø6 (Hand Wired Together)
7	A	2	ø5 Or ø2 (Internally Switched)
8	С	1	ø8
2A	С	1	Programmable Extend
6A	D	1	Programmable Extend



LOOP DETECTOR ASSIGNMENTS				
LD-#	AMPLIFIER UNIT	CHANNEL	PHASE-NOTES	
1,2	A	1	Ø6	
3	Α	2	ø1 & ø6 (Internally Switched)	
4	В	1	ø4 Queue W/Externally Programmable Delay & Inhibit (Internally Switched)	
5,6	Α	3	ø2	
2A	С	1	Programmable Extend	
6A	D	1	Programmable Extend	

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	NH-019-I(33)	2003	74S-1	74

	<u>ELEC</u>	TRICAL SYMBOL LIST		
SYMBOL EXISTING NEW		DESCRIPTION		
		Traffic Signal Controller And Cabinet		
M		Metering Equipment		
[U]		Uninterruptible Power Supply Unit		
		Transformer		
		Traffic Signal Standard		
□ \$		Street Light Standard		
		Traffic Signal Pullbox, Type "A"		
E 2		Traffic Signal Pullbox, Type "B"		
		Traffic Signal Pullbox, Type "C" Or Electrical Handhole		
E===3		Loop Detector		
_e		Underground Traffic Signal/Electrical Ductline		
	(1)	Note Indicator		

<u>Note:</u>

Electrical Symbol List On This Sheet Applies To Sheet No. E-4A To E-4E Only.

LICENSED PROFESSIONAL ENGINEER No. 3880-E No. 3880-E
THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

PROJECT ENGINEER for ECS, Inc.

APRIL 30, 2004
EXPIRATION DATE OF THE LICENSE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION ELECTRICAL SYMBOL LIST, PHASE ASSIGNMENTS AND ADDITIONAL NOTES

Sheet Added To Contract Plan Per Addendum No.1


DESCRIPTION


Queen Kaahumanu Highway Resurfacing Kekaha Kai State Park to Hapuna Federal-Aid Project No. NH-019-1(33)


Scale: As Noted


6/10/03


Date: March 2003 SHEET No. E-4A OF 4 SHEETS













6/9/03-9:34 Y:\087\e87-93\87-93 B02.dwg





THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION. PROJECT ENGINEER for ECS, Inc.

APRIL 30, 2004

EXPIRATION DATE OF THE LICENSE

Sheet Added To Contract Plan Per 6/10/03 Addendum No.1 DATE REV. DESCRIPTION STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION

LOOP DETECTOR DETAILS

Queen Kaahumanu Highway Resurfacing Kekaha Kai State Park to Hapuna

Federal-Aid Project No. NH-019-1(33) Scale: As Noted Date: March 2003

SHEET No. E-4D OF 4 SHEETS

FED. ROAD DIST. NO. STATE

HAW.

FED. AID PROJ. NO.

FISCAL SHEET TOTAL YEAR NO. SHEETS

74S-4

- existing

stubout

-Curb Or Edge Of

Pavement

— А. С.

Pavement


-existing

stubout


existing

2" conduit


2003



Not To Scale



EXISTING POLYMER CONCRETE COVER Not To Scale



<u>Notes:</u>

6/10/03

DATE


REV.

- 1. The Pullbox With Cover Shall Be Capable Of Supporting An MS18 Loading.
- 2. All Concrete Shall Be Class A (25MPa Minimum).
- 3. Rebars Shall Be Grade 300.
- 4. Slope Of Relocated Or New Cover And Frame Shall Match Slope Of New Finished

EXISTING HANDHOLE ADJUSTMENT E-4E Not To Scale

General Notes: (This Sheet Only)

- 1. All Dimensions Are In Millimeters Unless Otherwise Indicated.
- 2. Details Of Type "A" and "B" Traffic Signal Pullboxes Provided For Informational Purposes Only.



STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION EXISTING HANHOLE

ADJUSTMENT DETAILS

Sheet Added To Contract Plan Per Addendum No.1

DESCRIPTION

Queen Kaahumanu Highway Resurfacing Kekaha Kai State Park to Hapuna Federal-Aid Project No. NH-019-1(33)

Scale: As Noted Date: March 2003 SHEET No. E-4E OF 4 SHEETS

PROJECT ENGINEER for ECS, Inc. APRIL 30, 2004

EXPIRATION DATE OF THE LICENSE

6/9/03-9:34 Y:\087\e87-93\87-93 B03.dwg

Not To Scale

74S - 5