




FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER9(3) 1979	66	89	

1/8" Raised Letters



TOP VIEW OF COVER AND PORTION OF FRAME



SECTIONAL VIEW OF FRAME AND COVER

BOTTOM OF COVER

STREET SURVEY MONUMENT CASTINGS

Scale: 3" = 1'-0"

Street Survey
Monument Castings

3/8" x 4" Brass Pin

Class "A" Concrete
(6" Min. depth from top
of pavement to be formed).

8" W.I. Pipe filled with
#6 crushed rock ASTM D 448

3" Galv. Pipe filled
with concrete.


Class "A" Concrete

NOTE:

Where the excavation extends into solid
rock the depth may be decreased if ap-
proved by the Engineer.

STREET SURVEY MONUMENT

Scale: 1 1/2" = 1'-0"



Existing ground or finish elevation
on shoulder or median.

1/2" x 2 1/2" Brass Plug
feathered at bottom to be set
after pavement is completed.

8" x 8" Class "A" Concrete

DETAIL FOR C AND REFERENCE SURVEY MONUMENT

Scale: 1 1/2" = 1'-0"

NO.	REVISION	APPROVED BY	DATE

APPROVAL RECOMMENDED:
M. Higashima
HIGHWAY DESIGN ENGINEER
DATE: 12-10-69

APPROVED:
John S. Salas
ASSISTANT CHIEF, ENGINEERING
DATE: 12-10-69


STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
LAND TRANSPORTATION FACILITIES DIVISION

STANDARD DETAILS

CENTERLINE, REFERENCE SURVEY
AND C & C STREET SURVEY
MONUMENTS

Scale: As Shown


D.ROAD ST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAWAII	ER 9(3)	1979	67	89



EXTERIOR & INTERIOR KEY

ROOF FRAMING PLAN

SCALE : $\frac{3}{8}$ " = 1'-0"



ELEVATION C


TYPICAL WALL SECTION

SCALE: $\frac{3}{4}$ " = 1'-0"

APPROVAL RECOMMENDED:


M. Hinozawa
HIGHWAY DESIGN ENGINEER

APPROVED:
Stewart S. S. S. S.
ASSISTANT CHIEF ENGINE



FLOOR PLAN

SCALE: $\frac{1}{2}$ " = 1'-0"



FOUNDATION FRAMING PLAN

SCALE: 3' " = 1'-0"

NO.	REVISION	APPROVED BY	DATE

**STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
AND TRANSPORTATION FACILITIES DIVISION**


FIELD OFFICE

10. The following table shows the number of hours worked by each employee in a company.

10. The following table shows the number of hours worked by each employee.

NOTED

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ERO(3)	1970	70	80




CASEMENT DETAIL

SCALE: 3" = 1'- 0"

CABINET DETAIL

SCALE: 3/4" = 1'- 0"




ELEVATION D

SCALE: 3/8" = 1'- 0"


ELEVATION C

SCALE: 3/8" = 1'- 0"



ELEVATION C1

SCALE: 3/8" = 1'- 0"



ELEVATION A1

SCALE: 3/8" = 1'- 0"

APPROVAL RECOMMENDED:

M. J. Huozens
HIGHWAY DESIGN ENGINEER

12-4-69
DATE

APPROVED:

John S. Sodin
ASSISTANT CHIEF, ENGINEERING

12-10-69
DATE

NO.	REVISION	APPROVED BY	DATE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
LAND TRANSPORTATION FACILITIES DIVISION


PROJECT SITE LABORATORY

Scale: As Noted


SHEET No. 5 OF 24 SHEETS DD 6364

ORIGINAL PLAN
SURVEY PLOTTED BY
DRAWN BY
TRACED BY
DESIGNED BY
QUANTITIES BY
CHECKED BY
No. _____

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAWAII	ERD(3)	1970	71	89




TYPICAL WORK TABLE DRAWER DETAIL



TYPICAL STOOL DETAIL

SCALE: 1/2" = 1'-0"

NOTE: CONTRACTOR MAY WITH THE APPROVAL OF THE ENGINEER FURNISH THE FIELD OFFICE OR PROJECT SITE LABORATORY WITH STOOLS OTHER THAN THE TYPE SHOWN IN THE DETAIL.




TYPICAL DETAIL JALOUSIES WINDOWS

SCALE: 3" = 1'-0"


APPROVAL RECOMMENDED:
Mr. Horowitz
HIGHWAY DESIGN ENGINEER
APPROVED:
John S. Sodik
ASSISTANT CHIEF, ENGINEERING

12-4-69
DATE
12-10-69
DATE



TYP. SWING OUT DOOR

TYPICAL SINGLE OR DOUBLE EXTERIOR DOOR DETAIL



AT ENDS OF BLDG. ALONG SIDES OF BLDG.

TYPICAL 2X4 STUD & 4X6 FLOOR JOIST BASE CONNECTION DETAILS

NO.	REVISION	APPROVED BY	DATE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
LAND TRANSPORTATION FACILITIES DIVISION
FIELD OFFICE
&
PROJECT SITE LABORATORY

Scale: As Noted

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ERD(3)	1979	72	89

GENERAL NOTES

1. Grates and Frames shall be hot dip galvanized after fabrication, see specifications.
2. All welds $\frac{3}{8}$ " unless otherwise noted.
3. Refer to "Spacing Table" for Types 61614 & 61616 Drop Intake and Frame & Grates dimensions.
4. The Frame & Grate materials shall conform to the specifications of ASTM Designation Structural Steel A283, Grade D and the Standard Specifications.
5. Culvert shall leave Drop Intake from any position and any direction indicated by plans or ordered by the Engineer. Culverts may both enter and leave Drop Intake so that Drop Intake will act as manhole.
6. Manhole Rungs (12" o.c.) are required when "H" is greater than 4 feet 6 inches. Only one rung (16 inches from the bottom) is required if "H" is 4 feet 6 inches or less. Manhole Rungs may be placed at any location as ordered by the Engineer.

SPACING TABLE

TYPE	NO. BARS	A	B	C	D
61614	11	2'-0"	1'-11 $\frac{1}{2}$ "	1 $\frac{1}{4}$ "	1'-6"
61616	17	3'-0"	2'-11 $\frac{1}{2}$ "	1 $\frac{1}{8}$ "	2'-0"

NO.	REVISION	APPROVED BY	DATE
1	Curb for Top of Fill Gutters	H1	6-7-71
2	Spacing on manhole rungs to conform to OSHA.	H1	12-1-71


APPROVAL RECOMMENDED: *J. Valans* 12-7-69
HYDRAULIC DESIGN ENGINEER DATE

APPROVED: *J. Valans* 12-11-71
ASSISTANT CHIEF, ENGINEERING DATE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION


STANDARD DETAILS

TYPE 61614 & 61616
GRATED DROP INTAKES




PLAN

Scale: $1\frac{1}{2}" = 1'-0"$



SECTION


Scale: $1\frac{1}{2}" = 1'-0"$



FRAME


Scale: $3" = 1'-0"$

DETAILS OF TYPE 61614 OR 61616 STEEL FRAME AND GRATE




PLAN

Scale: $1\frac{1}{2}" = 1'-0"$




SECTION

Scale: $1\frac{1}{2}" = 1'-0"$




GRATE


Scale: $3" = 1'-0"$



PLAN



SECTION A-A



SECTION B-B


DETAILS OF 61614 OR 61616 DROP INTAKE

Scale: $\frac{3}{4}" = 1'-0"$



* For Minimum size box of 3'-0", use 8" and eliminate reinforcing steel shown in the top portion.

* * For Culverts larger than 30", the minimum dimension shall be D.

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER 7(3)	1979	73	89



PLAN VIEW



FRONT ELEVATION

NOTE:

D = Diameter of Pipe Culvert
R = Rise of Pipe-Arch Culvert
S = Span of Pipe-Arch Culvert

DETAILS OF CRM INLET STRUCTURE

Scale: 1/2" = 1'-0"

ORIGINAL	PLATE	REMOVED BY	DATE
PLAN	REMOVED BY	DESIGNED BY	DATE
NOTE BOOK	REMOVED BY	QUANTITIES BY	DATE
No.	REMOVED BY	CHECKED BY	DATE

APPROVAL RECOMMENDED: *G. Adams* 12-17-69
HYDRAULIC DESIGN ENGINEER DATE

APPROVED: *B. L. S. Reddy* 12-17-69
ASSISTANT CHIEF, ENGINEERING DATE




NO.	REVISION	APPROVED BY	DATE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
STANDARD DETAILS
CRM INLET STRUCTURE

Scale: As Noted Date: July, 1969
SHEET No. 8 OF 24 SHEETS DH 16


73

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-9(3)	1979	74	89




HEIGHT AND LATERAL LOCATION OF SIGNS
TYPICAL INSTALLATION

ORIGINAL:	DATE:
CHIEF:	DATE:
PLATE:	DATE:
NOTES:	DATE:
QUANTITIES:	DATE:
CHECKED:	DATE:



BACK BRACE DETAILS
FOR BALANCED SIGN INSTALLATION



TYPICAL BAND BRACKET FOR
MOUNTING TRAFFIC SIGNS

NO.	REVISION	APPROVED BY	DATE
1	Supercedes Sht. DT-100 approved 12/30/69	H.T.	11/15/77

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
LAND TRANSPORTATION FACILITIES DIVISION

STANDARD DETAILS
MISCELLANEOUS SIGN DETAILS


Not to scale June, 1977

SHEET NO. 9 OF 24 SHEETS DT 100


APPROVAL RECOMMENDED:
Eiichi Tanaka
TRAFFIC ENGINEER
11/10/77
DATE

APPROVED:
Heribert Z. Saliech
ASSISTANT CHIEF, ENGINEERING
11/15/77
DATE


FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-9(3)	1979	75	89




R1-1 30"x 30"
R1-1-A 36"x 36"




R1-2 36"x 36"x 36"
R1-2-A 48"x 48"x 48"
R1-3 12"x 6"
R1-3-A 18"x 9"




R2-1(50) 24"x 30"
R2-1(50)-A 48"x 60"



R2-2(40) 24"x 24"
R2-2(40)-A 48"x 48"



R2-4a(50/40) 24"x 48"
R2-4a(50/40)-A 48"x 96"
R2-5b(30) 24"x 30"
R2-5b(30)-A 48"x 60"




R2-5b(30) 24"x 30"



R3-1 24"x 24"




R3-2 24"x 24"



R3-3 24"x 24"
R3-3-A 48"x 48"



R3-4 24"x 24"
R3-4-A 48"x 48"
R3-5(L) 30"x 36"
R3-5(L)-A 48"x 60"



R3-6(L) 30"x 36"
R3-6(L)-A 48"x 60"




R3-6(L) 30"x 36"
R3-6(L)-A 48"x 60"



R3-7(R) 30"x 30"
R3-7(R)-A 48"x 48"




R3-8(L) 30"x 30"
R3-8(L)-A 36"x 36"
R3-8(L)-B 48"x 48"



R3-9 24"x 30"




R4-1 24"x 30"




R4-2 24"x 30"




R4-3 24"x 30"
R4-3-A 48"x 60"



R4-5 24"x 30"




R4-6(500) 24"x 30"



R4-7 24"x 30"
R4-8 24"x 30"




R5-1 30"x 30"
R5-1-A 48"x 48"



R5-2 24"x 24"
24"x 18"



R5-2 24"x 24"
24"x 18"




R5-4 24"x 30"



R5-6 24"x 24"
24"x 18"




R5-9 36"x 24"




R6-1 (R) 36"x 12"




R6-2(R) 18"x 24"




R7-1 12"x 18"
R7-1-A 24"x 30"




R7-4 12"x 18"
R7-4-A 24"x 30"



R7-107(R) 12"x 18"



R7-108 12"x 18"



R7-201 12"x 6"
R7-201-A 24"x 12"



R8-1 24"x 30"



R8-2 24"x 30"



R8-3 24"x 30"




R8-4 30"x 24"
R8-4-A 48"x 36"



R8-5 24"x 30"




R8-6 24"x 30"
R8-7-A 48"x 36"




R8-7 30"x 24"
R8-7-A 48"x 36"




R8-8 18"x 24"




R9-2 12"x 18"




R9-3 12"x 18"




R9-4 18"x 24"




R10-1 12"x 18"



R10-2 12"x 18"



R10-3 9"x 12"




R10-4 9"x 12"




R10-5 24"x 30"



R10-6 24"x 36"



R10-7 24"x 30"




R10-8 24"x 30"



R10-9 24"x 30"




R10-10 24"x 30"



R11-1 24"x 30"



R11-2 48"x 30"



R11-3(10) 60"x 30"



R11-4 60"x 30"



R11-5(10) 24"x 30"

GENERAL NOTES

- I. Sign details shall conform to the FHWA publications "Manual on Uniform Traffic Control Devices for Streets and Highways," 1971, and "Standard Highway Signs," 1972, and as amended.
2. All regulatory signs shall be reflectorized unless otherwise specified.
3. All regulatory signs shall have 3/8" bolt holes drilled at appropriate locations.
4. Numerals in () indicates numerals to be inserted for sign message. (R) or (L) indicates right or left.

APPROVAL RECOMMENDED:
Eduardo Tanaka
TRAFFIC ENGINEER

DATE
3/17/72

APPROVED:
Robert J. Redden
ASSISTANT CHIEF, ENGINEERING


DATE
3-20-72

NO.	REVISION	APPROVED BY	DATE
1	Supersedes Sh. DT 101 Approved 12-30-69	H.C.	3/20/72
2	Revised General Note 1.	H.C.	10/10/74

STATE OF HAWAII DEPARTMENT OF TRANSPORTATION LAND TRANSPORTATION FACILITIES DIVISION
STANDARD DETAILS
REGULATORY SIGNS
NOT TO SCALE
SHEET No. 10 OF 24 SHEETS DT 101


ORIGINAL PLAN
DRAWN BY
DESIGNED BY
QUANTITY CHECKED BY
No. _____

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-9(3)	1979	77	89



General Notes

- I. Sign details shall conform to the latest editions of the following FHWA publications:
 - a. "Standard Alphabets for Highway Signs," and as amended.
 - b. "Standard Highway Signs," and as amended,
 - c. "Manual on Uniform Traffic Control Devices for Streets and Highways," and as amended,
 2. All signs shall be reflectorized with reflective sheeting, unless otherwise specified.
 3. All signs shall have $\frac{3}{8}$ " bolt holes drilled at appropriate locations.
 4. Numerals in () indicate numerals to be inserted for sign message. (R) or (L) indicates right or left.
 5. Signs prefixed with "CW" on the plans shall indicate orange and black construction signs, and shall be reflectorized with reflective sheeting.



ORIGINAL PLAN	SURVEY PLOTTED BY _____	DATE _____
	DRAWN BY _____	" _____
	TRACED BY _____	" _____
	DESIGNED BY _____	" _____
	QUANTITIES BY _____	" _____
	CHECKED BY _____	" _____
NOTE BOOK No. _____		

APPROVAL RECOMMENDED: Euchi Tanaka 5/2/78
TRAFFIC ENGINEER DATE

APPROVED: *Herbert J. Daleish* 5/3/18
ASSISTANT CHIEF, ENGINEERING DATE

NO.	REVISION	APPROVED BY	DATE
	Supersedes Sht. DT 103 approved 3/20/72	H.P.	5/3/18

STATE OF HAWAII

DEPARTMENT OF TRANSPORTATION
LAND TRANSPORTATION FACILITIES DIVISION

MISCELLANEOUS SIGNS

O SCALE DATE: MAY 15

SHEET NO. 12 OF 24 SHEETS DT 10

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-9(3)	1972	78	89



CW20-1a 48" x 48"



CW20-2d 48" x 48"



CW20-3b 48" x 48"



CW20-4d 48" x 48"



CW20-5d(L) 48" x 48"



CW20-7c 48" x 48"



CW21-1 30" x 30"




CW21-2 30" x 30"




CW21-3 36" x 36"



CW21-4 36" x 36"



CW21-5 30" x 30"



CW21-6 30" x 30"




CW22-1b 48" x 48"




CW22-2 42" x 36"



CW22-3 42" x 36"



CG 20-1(5) 60" x 36"




CG 20-2 60" x 24"



CM4-9(R) 30" x 24"




CM4-10(R) 48" x 18"



CG 20-4 36" x 18"



CW23-1 36" x 36"



CW23-2b 48" x 48"



CW23-3(R) 48" x 48"

GENERAL NOTES

1. Sign details shall conform to the FHWA publications "Manual on Uniform Traffic Control Devices for Streets and Highways," 1971, and "Standard Highway Signs," 1972, and as amended.
2. All construction signs shall be reflectorized.
3. All construction signs shall have 3/8" bolt holes drilled at appropriate locations.
4. Numerals in () indicates numerals to be inserted for sign message. (R) or (L) indicates right or left.
5. For "CW" series signs, suffixes a,b,c and d are as follows:
a-1500 FT, b-1000 FT,
c-500 FT and d-AHEAD.

APPROVAL RECOMMENDED:
Eduardo Tanaka 3/23/72
 TRAFFIC ENGINEER

APPROVED:
John S. Walsh 3/23/72
 ASSISTANT CHIEF, ENGINEERING

NO.	REVISION	APPROVED BY	DATE
1	Supersedes Sh. DT 104 Approved 12-30-69	H.T.	3/23/72
2	Revised General Note 1	H.T.	10/16/74
3	Revised General Note 2	H.T.	9-16-75
4	Revised General Note 2 and sign CG20-1(5)	H.T.	9-14-76

STATE OF HAWAII
 DEPARTMENT OF TRANSPORTATION
 LAND TRANSPORTATION FACILITIES DIVISION

STANDARD DETAILS


CONSTRUCTION SIGNS

NOT TO SCALE

SHEET No. 13 OF 24 SHEETS DT 104


SURVEY PLOTTED BY
DRAWN BY
TELEGRAPHED BY
CHECKED BY
ORIGINAL PLAN
NOTE BOOK
No.

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-9(3)	1979	79	89



STATE ROUTE MARKER DETAIL

Not to Scale




STATE ROUTE MARKER


MI-6(00) 24"x 24"

Scale: 1/4" = 1"


ORIGINAL PLAN	DATE
SURVEY PLOTTED BY	
DRAWN BY	
TRACED BY	
DESIGNED BY	
QUANTITIES BY	
CHECKED BY	
NOTE BOOK	
No. _____	




M2-1 21"x 15"




M5-1(L) 21"x 15"




M5-2(L) 21"x 15"




M6-1 21"x 15"




M6-2(R) 21"x 15"




M6-3 21"x 15"




M6-4 21"x 15"



M6-5(R) 21"x 15"



M6-6(R) 21"x 15"



M6-7(R) 21"x 15"



M3-1 24"x 12"
M3-1-A 36"x 18"



M4-1 24"x 12"



M4-2 24"x 12"



M4-3 24"x 12"



M4-5 24"x 12"



M4-6 24"x 12"



M4-7 24"x 12"



M4-8 24"x 12"

GENERAL NOTES

- Marker details shall conform to the FHWA publications "Manual on Uniform Traffic Control Devices for Streets and Highways," 1971, "Standard Alphabets for Highway Signs," 1966, and "Standard Highway Signs," 1972, and as amended.
- All markers shall be reflectorized unless otherwise specified.
- All markers shall have $\frac{3}{8}$ " bolt holes drilled at appropriate locations.
- Numerals in () indicates numerals to be inserted for marker message. (R) or (L) indicates right or left.
- Sign message of Cardinal Direction Marker (M3 series) shall be denoted by the following:
M3-1 : NORTH
M3-2 : EAST
M3-3 : SOUTH
M3-4 : WEST
- Markers prefixed with "IM" on the plans shall have a white legend on a blue background.

APPROVAL RECOMMENDED:

Etsushi Tanaka
TRAFFIC ENGINEER

6/6/72
DATE

APPROVED:

Robert S. Paluszak
ASSISTANT CHIEF, ENGINEERING

C-1-72
DATE

AUXILIARY MARKERS

Not to Scale


NO.	REVISION	APPROVED BY	DATE
1	Supersedes Sht. DT 105 Approved 12-30-69	H.T.	6/11/72
2	Revised General Note I	H.T.	10/16/74

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
LAND TRANSPORTATION FACILITIES DIVISION

STANDARD DETAILS
**STATE ROUTE MARKER
AND AUXILIARY MARKERS**

Scale: As Shown
SHEET N° 14 OF 24 SHEETS DT 105


FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	HEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-9(3)	1979	80	89




FRONT ELEVATION

TYPE "B" ASSEMBLY


Not to Scale



REAR ELEVATION




PLAN




FRONT ELEVATION

SIDE ELEVATION

DETAIL "C"




FRONT ELEVATION




REAR ELEVATION

TYPE "A" ASSEMBLY

Not to Scale




PLAN




FRONT ELEVATION

DETAIL "A"


NOTE:
For height and lateral location of Route Marker Assembly, see plan sheet DT 100.



PLAN



ELEVATION



SECTION

APPROVAL RECOMMENDED:
Eduardo Tanaka
TRAFFIC ENGINEER
DATE: 12/29/69

APPROVED:
John D. Reid
ASSISTANT CHIEF, ENGINEERING
DATE: 12-30-69

NO.	REVISION	APPROVED BY	DATE
I	Revisions to Route Marker Assemblies.	H.T.	6/1/72

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
LAND TRANSPORTATION FACILITIES DIVISION

STANDARD DETAILS


ROUTE MARKER ASSEMBLIES

Scale: As Shown


SHEET No. 15 OF 24 SHEETS DT 107

SO


FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-9(3)	1979	81	89



REFLECTOR MARKER MOUNTING DETAIL



TYPICAL SECTION OF ROAD DELINEATOR



GENERAL NOTES:

1. Clearance markers (RM-3, RM-4) shall be installed with the edge of the marker in line with the inner edge of the obstruction.
2. (R) or (L) indicates right or left and shall be as shown on the plans.
3. Reflector markers RM-1 and RM-2 shall be:
 - a) Yellow if placed along the left edge of divided roadways, one-way roadways, and ramps in the direction of travel.
 - b) White if placed along the right edge of divided roadways, one-way roadways, and ramps in the direction of travel.
4. For reflector marker RM-9, reflective sheeting material may be used as an alternate.
5. For RM-4, the stripes shall slope downward at an angle of 45° in the direction of traffic.

ORIGINAL	SURVEY PLOTTED BY
PLAN	DRAINED BY
NOTE BOOK	TRACED BY
No.	QUANTITATED BY
	CHECKED BY

APPROVAL RECOMMENDED:
Eiji Tanaka
TRAFFIC ENGINEER
DATE *11/17/77*

APPROVED:
Robert S. Sakakishu
ASSISTANT CHIEF, ENGINEERING
DATE *11/15/77*

NO.	REVISION	APPROVED BY	DATE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
LAND TRANSPORTATION FACILITIES DIVISION

STANDARD DETAILS


MISCELLANEOUS REFLECTOR MARKERS

Not to scale

June, 1977

SHEET NO. 16 OF 24 SHEETS DT 110


FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-9(3)	1979	82	89



MILEPOST MARKER PLATE DETAILS

Scale: $\frac{3}{16}$ " = 1"

MILEPOST PLATE SCHEDULE (INCHES)															
NAME	SIZE	A	B	C	D	E	F	G	H	J	K	L	M	LETTER SERIES	NUMERAL SERIES
DIO-1	10 x 18	10	18	1/2	2	4	2	6		4	1/2	3 5/8	3 7/8	B	C
DIO-4	12 x 24	12	24	1/2	3	4	3	10		4	1/2	4 5/8	4 7/8	C	C
DIO-2	10 x 27	10	27	1/2	2	4	2	6	3	4	1/2	3 5/8	3 7/8	B	C
DIO-5	12 x 36	12	36	1/2	3	4	3	10	3	3	1/2	4 5/8	4 7/8	C	C
DIO-3	10 x 36	10	36	1/2	2	4	2	6	3	4	1/2	3 5/8	3 7/8	B	C
DIO-6	12 x 48	12	48	1/2	3	4	3	10	2 1/2	3	1/2	4 5/8	4 7/8	C	C



HIGHWAY ROUTE NUMBER PLATE DETAIL


Scale: $\frac{3}{16}$ " = 1"

MILEPOST MARKER FRACTION DETAIL

Scale: $\frac{3}{16}$ " = 1"


MILEPOST PLATE SCHEDULE WITH FRACTION OF A MILE						
NAME	SIZE	G	P	Q	S	NUMERAL SERIES
DIO-1a	10" x 2 7/8"	6"	4"	3"	6"	C
DIO-4a	12" x 3 6/8"	10"	4"	5"	7"	C
DIO-2a	10" x 3 6/8"	6"	4"	3"	6"	C
DIO-5a	12" x 4 8/8"	10"	4"	5"	6"	C
DIO-3a	10" x 4 5/8"	6"	4"	3"	6"	C
DIO-6a	12" x 6 0/8"	10"	4"	5"	6"	C

*One-foot minimum clearance above top of guard rail.




TYPICAL ROADSIDE INSTALLATION

Scale: $\frac{1}{2}$ " = 1' - 0"



GALVANIZED SQUARE TUBE POST



GALVANIZED FLANGED CHANNEL POST

TYPICAL MOUNTING DETAILS

Scale: $\frac{1}{2}$ " = 1"

NO.	REVISION	APPROVED BY	DATE

STATE OF HAWAII DEPARTMENT OF TRANSPORTATION LAND TRANSPORTATION FACILITIES DIVISION			
STANDARD DETAILS			
MILEPOSTS			
SCALE: As Shown		DATE: December, 1977	
SHEET NO. 17 OF 24 SHEETS DT 116			

APPROVAL RECOMMENDED:
Eischi Tanaka
TRAFFIC ENGINEER


1/17/78
DATE

APPROVED:
Robert S. Salas
ASSISTANT CHIEF, ENGINEERING
1/18/78
DATE

* For moment calculations only. Post shall be from top of foundation to top of sign.
 ** For fills with side slopes flatter than 4:1, Minimum Footing Depth shall be 4½ feet.


DATA TABLE FOR TYPE VI FOOTING

POST SIZE	MAXIMUM SIGN AREA	POST HEIGHT TO CENTER OF SIGN *	DIMENSIONS										ANCHOR BOLT DIA.	MINIMUM FOOTING DEPTH			
			H	J	K	M	N	O	P	S	T	U	V	CUT	FILL**		
8 J10	50 sq. ft.	14'	14"	5"	24"	17½"	15½"	6"	1¼"	9"	6"	10"	2"	1"	1½" Ø	4½'	4½'
8 WF24	90 sq. ft.	21'														5'	
8 WF35	190 sq. ft.	15'	16½"	6¾"	30"	20"	1¾"	6"	1¾"	11¾"	6½"	10"	1¾"	1"	1¼" Ø	6'	7'
IOWF45	190 sq. ft.	25'															
IOWF45	200 sq. ft.	25'															
I2WF50	230 sq. ft.	25'															
I2WF50	250 sq. ft.	23'															



TYPICAL DESTINATION & GROUND MOUNTED EXPRESSWAY SIGN

Not to Scale



BALLAST BOX

BALLASTS

WEATHERPROOF BALLAST BOX

Scale: 1½" = 1'-0"

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER9(3)	1979	83	89





PHOTO-CELL DETAIL

Scale: 1½" = 1'-0"



ELEVATION

TYPE VI FOOTING

Scale: 1" = 1'-0"

APPROVAL RECOMMENDED: *Euchi Tanaka* DATE 12-29-69

APPROVED: *John B. Zabel* DATE 12-29-69

ASSISTANT CHIEF, ENGINEERING

NO. REVISION APPROVED BY DATE

STATE OF HAWAII DEPARTMENT OF TRANSPORTATION

LAND TRANSPORTATION FACILITIES DIVISION

STANDARD DETAILS

DESTINATION & GROUND MOUNTED

EXPRESSWAY SIGNS



Scale: As Shown

SHEET No. 18 OF 24 SHEETS DT 203


ED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-9(3)	1979	84	89

	BASE CONNECTION DATA TABLE										FUSE PLATE DATA TABLE									FOUNDATION DATA														
Post Size	Bolt Size & Torque	A	B	C	D	E	t1	t2	W	R	F	G	H	J	K	L	N	d1	t3	Bolt Dia.	Wt. of each Fuse ⚡	Stub Length	Stub Projection	Footing Diameter	Bars V Size									
6 B 8.5	$\frac{5}{8}'' \phi \times 2\frac{3}{4}''$ Torque = 450 "#	5"	2"	$1\frac{1}{4}''$	$2\frac{3}{4}''$	$1\frac{1}{8}''$	$\frac{3}{4}''$	$\frac{1}{2}''$	$\frac{1}{4}''$	$\frac{11}{32}''$	$3\frac{5}{8}''$	2"	$1\frac{1}{8}''$	4"	$2\frac{1}{4}''$	$\frac{7}{8}''$	$\frac{1}{2}''$	$\frac{9}{16}''$	$\frac{1}{4}''$	$\frac{1}{2}'' \phi$	1.09#	2'-0"	3"	2'-0"	#5									
6 B 12											$3\frac{3}{4}''$	2"	$1\frac{1}{8}''$	4"	$2\frac{1}{4}''$	$\frac{7}{8}''$	$\frac{5}{8}''$	$\frac{11}{16}''$	$\frac{3}{8}''$	$\frac{5}{8}'' \phi$	1.60#	2'-0"	3"	2'-0"	#5									
6 B 15.5											$4\frac{1}{2}''$	$2\frac{1}{2}''$	$1\frac{1}{4}''$	6"	$3\frac{1}{2}''$	$1\frac{1}{4}''$	$\frac{3}{4}''$	$\frac{13}{16}''$	$\frac{1}{2}''$	$\frac{3}{4}'' \phi$	3.75#	2'-6"	3"	2'-0"	#6									
8 WF 17											$4\frac{1}{2}''$	$2\frac{1}{2}''$	$1\frac{1}{4}''$	$5\frac{1}{4}''$	$2\frac{3}{4}''$	$1\frac{1}{4}''$	$\frac{3}{4}''$	$\frac{13}{16}''$	$\frac{1}{2}''$	$\frac{3}{4}'' \phi$	3.27#	2'-6"	3"	2'-0"	#7									
8 WF 20											$4\frac{7}{8}''$	$2\frac{1}{2}''$	$1\frac{1}{2}''$	$5\frac{1}{4}''$	$2\frac{3}{4}''$	$1\frac{1}{4}''$	$\frac{7}{8}''$	$\frac{15}{16}''$	$\frac{9}{16}''$	$\frac{7}{8}'' \phi$	3.93#	3'-0"	$2\frac{1}{2}''$	2'-0"	#8									
10 WF 21											$5\frac{3}{8}''$	3"	$1\frac{1}{2}''$	$5\frac{3}{4}''$	$2\frac{3}{4}''$	$1\frac{1}{2}''$	$\frac{7}{8}''$	$\frac{15}{16}''$	$\frac{9}{16}''$	$\frac{7}{8}'' \phi$	4.75#	3'-0"	$2\frac{1}{2}''$	2'-0"	#9									
10 WF 25											$5\frac{3}{8}''$	3"	$1\frac{1}{2}''$	$5\frac{3}{4}''$	$2\frac{3}{4}''$	$1\frac{1}{2}''$	$\frac{7}{8}''$	$\frac{15}{16}''$	$\frac{9}{16}''$	$\frac{7}{8}'' \phi$	4.79#	3'-0"	$2\frac{1}{2}''$	2'-0"	#10									
12 WF 27											$5\frac{3}{8}''$	3"	$1\frac{1}{2}''$	$6\frac{1}{2}''$	$3\frac{1}{2}''$	$1\frac{1}{2}''$	$\frac{7}{8}''$	$\frac{15}{16}''$	$\frac{9}{16}''$	$\frac{7}{8}'' \phi$	5.42#	3'-0"	$2\frac{1}{2}''$	2'-0"	#11									
3 I 5.7	$\frac{1}{2}'' \phi \times 2\frac{1}{2}''$ Torque = 200 "#	SEE DETAIL "A"										$3\frac{1}{8}''$	$1\frac{1}{2}''$	$1\frac{1}{8}''$	$2\frac{5}{8}''$	$1\frac{1}{2}''$	$\frac{9}{16}''$	$\frac{1}{2}''$	$\frac{9}{16}''$	$\frac{1}{4}''$	$\frac{1}{2}'' \phi$	0.64#	1'-6"	$3\frac{1}{2}''$	1'-6"	#5								
4 I 7.7	SEE DETAIL "A"										$3\frac{1}{8}''$	$1\frac{1}{2}''$	$1\frac{1}{8}''$	$2\frac{5}{8}''$	$1\frac{1}{2}''$	$\frac{9}{16}''$	$\frac{1}{2}''$	$\frac{9}{16}''$	$\frac{1}{4}''$	$\frac{1}{2}'' \phi$	0.64#	1'-6"	$3\frac{1}{2}''$	1'-6"	#5									

SEE DETAIL "A




FOUNDATION DETAIL




SECTION "A-A" SECTION "B-B"

NOTE:
Sections shown are for
installations on right shoulder
and in gore. Reverse plate
slot bevels for installations
on left shoulder.




SECTION "C-C" SECTION "D-D"



DETAIL "A"
SIGN POST & STUB POST


(For 4I 7.7 and 3I 5.7 Shapes)




SIGN POST & STUB POST

PROCEDURE FOR ASSEMBLY
OF BASE CONNECTION :


1. Assemble post to stub with bolts and with one flat washer on each bolt between plates.
2. Shim as required to plumb post.
3. Tighten all bolts the max. possible with 12" to 15" wrench to bed washers & shims and to clean bolt threads then loosen each bolt in turn & retighten bolts in systematic order to prescribed torque. (See Table)
4. Burr threads at junction with nut using a center punch to prevent nut loosening.



STIFFENER PLATE DETAIL



FUSE PLATE DETAIL



SHIM DETAIL

Furnish 2 \sim .012" \pm thick and 2 \sim .032" \pm thick shims per post. Shims shall be fabricated from brass shim stock or strip conforming to A.S.T.M. - B 36.

GENERAL NOTES

- 12

AIL

st Cut

s=t3

IL

I. Design conforms with AASHO Specifications for the design and Construction of Structural Supports for Highway Signs.

2. Materials and Fabrication shall conform to the requirements of the Standard Specifications and Special Provisions.

3. All holes shall be drilled. All plate cuts shall preferably be saw cuts, however; flame cutting will be permitted provided all edges are ground. Metal projecting beyond the plane of the plate face will not be tolerated.

4. Tighten the high strength bolts in the base connection only to the torque shown, do not overtighten. All bolts other than high strength bolts shall conform to ASTM A 307, Class A.

5. All structural steel, bolts, nuts and washers shall be galvanized as per the Standard Specifications and Special Provisions. Structural steel to be galvanized after fabrication except as noted.

6. Structural steel shall conform with the requirements of ASTM ^ 441

7. Galvanizing of all posts shall be projection above concrete plus 6" minimum.

8. All friction fuse bolts shall be tightened in the shop following a method approved by the Engineer. Tightening shall be to such a degree as to obtain the following minimum residual tension in each bolt:

<u>Bolt Size</u>	<u>Min. Tension</u>	<u>Bolt Size</u>	<u>Min. Tension</u>
$\frac{1}{2}''\varnothing$	12050 Lbs.	$\frac{3}{4}''\varnothing$	28400 Lbs.
$\frac{5}{8}''\varnothing$	19200 Lbs.	$\frac{7}{8}''\varnothing$	36050 Lbs.

**STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
LAND TRANSPORTATION FACILITIES DIVISION**

STANDARD DETAILS

BREAK-AWAY SIGN SUPPORTS

FOR


ROUND MOUNTED GUIDE SIGNS

Not to Scale

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER9(3)	1979	85	89


(GROUND MOUNTED SIGNS)
SUPPORT SPACING TABLE

PANEL THICK.	LENGTH OF SIGN	NO. OF SUPPORTS	OVERHANG B	SUPPORT SPACING C
1"	6'-0"	2	12"	48"
1"	6'-6"	2	15"	48"
1"	7'-0"	2	15"	54"
1"	7'-6"	2	16"	54"
1"	8'-0"	2	18"	60"
1"	8'-6"	2	20"	62"
1"	9'-0"	2	22"	64"
1"	9'-6"	2	23"	68"
1"	10'-0"	2	24"	72"
1"	10'-6"	2	24"	78"
1"	11'-0"	2	24"	84"
1"	11'-6"	2	27"	84"
1"	12'-0"	2	30"	84"
1"	12'-6"	2	30"	90"
1"	13'-0"	2	30"	96"
1"	13'-6"	2	30"	102"
1"	14'-0"	2	30"	108"
1"	14'-6"	2	36"	102"
1"	15'-0"	2	36"	108"
2.5"	15'-6"	2	36"	114"
2.5"	16'-0"	2	39"	114"
2.5"	16'-6"	2	39"	120"
2.5"	17'-0"	2	39"	126"
2.5"	17'-6"	2	42"	126"
2.5"	18'-0"	2	42"	132"
2.5"	18'-6"	2	45"	132"
2.5"	19'-0"	2	45"	138"
2.5"	19'-6"	2	45"	144"
2.5"	20'-0"	2	48"	144"
2.5"	20'-6"	2	48"	150"
2.5"	21'-0"	2	51"	150"
2.5"	21'-6"	2	51"	156"
2.5"	22'-0"	2	51"	162"
2.5"	23'-0"	2	54"	168"
2.5"	23'-6"	2	54"	174"
2.5"	24'-0"	2	57"	174"




TYPICAL SIGN ASSEMBLY

Scale: $\frac{3}{4}$ " = 1'-0"



SECTION "A-A"


Scale: $\frac{1}{2}$ " = 1"



END MOUNTING INTERMEDIATE MOUNTING

ZEE MOUNTING DETAILS

Scale: $\frac{1}{2}$ " = 1"




SECTION "B-B"

Scale: $\frac{1}{2}$ " = 1"

SECTION "B-B"

(Alternate)
Scale: $\frac{1}{2}$ " = 1"



SECTION "A-A"

(Alternate)
Scale: $\frac{1}{2}$ " = 1"

APPROVAL RECOMMENDED:

Etsushi Tanaka
TRAFFIC ENGINEER

12/29/69
DATE

APPROVED:

John S. [Signature]
ASSISTANT CHIEF, ENGINEERING

12-30-59
DATE

CLOSURE DETAIL

SECTION "C-C"

FULL SCALE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
LAND TRANSPORTATION FACILITIES DIVISION

STANDARD DETAILS

LAMINATED ALUMINUM
SIGN PANELS
(GROUND MOUNTED)


Scale: As Shown

SHEET No. 20 OF 24 SHEETS DT 206

PRINTED ON NO. 1000 CLEARPRINT

S 5

MARKER SIZE	MULTIPLY DIMENSIONS BY	NUMERAL SIZE
		2 Digit - Series D 3 Digit - Series C
21"	1.3	8"
32"	2.0	12"
42"	2.63	16"



STATE ROUTE MARKER FOR GUIDE SIGNS


Scale: Half Size

NOTE:

1. State Route Markers on Guide signs shall have black numerals on a white reflectorized background mounted on a flat aluminum cut-out.
2. Numerals shall conform to the FHWA publication "Standard Alphabets for Highway Signs," 1966.
3. Cut-outs shall be fastened on sign panel with aluminum blind rivets. See Standard Specifications.

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-9(3)	1979	8G	89

RADII FOR SIGNS		
Least Dimension of Sign	W	R
2' - 0" to 4' - 6"	2"	3"
4' - 9" to 5' - 6"	2"	6"
5' - 9" to 7' - 6"	2"	9"
7' - 9" and greater	2"	12"



BORDER DETAIL FOR GUIDE SIGNS

Not to Scale

NOTE:

1. Area outside corner radius need not be trimmed.
2. All borders shall be white reflectorized cut-outs.
3. All Guide signs shall have borders.

APPROVAL RECOMMENDED:

Euchi Tanaka 4/11/72
TRAFFIC ENGINEER DATE

APPROVED:

Robert Z. Oalsishi 4/12/72
ASSISTANT CHIEF, ENGINEERING DATE

NO.	REVISION	APPROVED BY	DATE
1	Supersedes Sht. DT 209 Approved 12-30-69	H.C.	4/12/72
2	Revised Notes and Schedules	H.C.	4-14-70

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
LAND TRANSPORTATION FACILITIES DIVISION

STANDARD DETAILS


STATE ROUTE MARKER AND BORDER DETAIL FOR GUIDE SIGNS

Scale: As Shown
SHEET No. 21 OF 24 SHEETS DT 209


SG

ORIGINAL
SURVEY PLATED BY
PLAN IN DRAWING
NOTES BOOK
DESIGNED BY
CHECKED BY
RECHECKED BY


FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-7(3)	1979	87	89



TWO - LANE PASSING PERMITTED AND PASSING PROHIBITED




TWO - LANE PASSING PROHIBITED ZONES







MULTI - LANE LANE LINES AND CENTER LINE

NOTE: Type H
(Reflective Surface
facing oncoming traffic)






TWO - LANE



TYPE C RED-CLEAR REFLECTIVE MARKER

TYPE A NON-REFLECTIVE WHITE MARKER



TYPE H ONE-WAY YELLOW REFLECTIVE MARKER

TYPE D TWO-WAY YELLOW REFLECTIVE MARKER

DIVIDED HIGHWAY AND FREEWAY

GENERAL NOTES

- Pavement marking and striping shall conform to the latest "Manual on Uniform Traffic Control Devices for Streets and Highways," and as amended.
- Layout and installation of pavement marking and striping shall be done by the Contractor. The Contractor shall check the layouts with the Engineer prior to performing work.

LEGEND


- Type A
- Type C
- Type D
- Type H
- Type J

APPROVAL RECOMMENDED:
Eduki Tanaka
TRAFFIC ENGINEER


DATE
11/10/71

APPROVED:
Donald E. Sato
ASSISTANT CHIEF, ENGINEERING

DATE
11/18/71



CHANNELIZING LINES OR SOLID LANE LINES



MEDIAN NOSE DELINEATION

MISCELLANEOUS

No.	REVISION	APPROVED BY	DATE
1	Add reflector marker in each line gap.	H.C.	10-21-72
2	Revised General Notes.	H.T.	10-21-72
3	Change 4" white edge stripe to 4" solid yellow edge stripe to left edge of a travel path and Add Type H Reflector Marker.	H.C.	5-22-74
4	Revised details, General Notes & Title Box.	H.T.	1-18-77
5	Revised dimensions on Type A & J Markers.	H.T.	4-18-78


STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
LAND TRANSPORTATION FACILITIES DIVISION

STANDARD DETAILS


RAISED PAVEMENT MARKERS AND STRIPING

Not to Scale
October 1971
SHEET No. 22 OF 24 SHEETS DT 300


FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	HEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-7(3)	1977	88	89




4" GUIDE LINE




TRANSVERSE RIGHT SHOULDER MARKING




TRANSVERSE LEFT SHOULDER MARKING




TRANSVERSE MEDIAN MARKING



CHANNELIZING ISLAND




PAVEMENT DIAMOND



NOTE: Traffic Cone Usage Required.

MULTI-LANE REVERSIBLE LANES



MULTI-LANE LANE CHANGE RESTRICTION ZONES

GENERAL NOTES:

- Pavement marking and striping shall conform to the latest edition of the "Manual on Uniform Traffic Control Devices for Streets and Highways," by the FHWA, and as amended.
- Layout of pavement markings and striping shall be done by the Contractor. The Contractor shall check layout of markings and striping with the Engineer prior to performing work.
- For additional pavement marking details, see sheet DT 300.

APPROVAL RECOMMENDED:
Eishi Tanaka
TRAFFIC ENGINEER
DATE: 5/2/78

APPROVED:
Robert D. Dakin
ASSISTANT CHIEF, ENGINEERING
DATE: 5/3/78

NO.	REVISION	APPROVED BY	DATE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
LAND TRANSPORTATION FACILITIES DIVISION

STANDARD DETAILS

MISCELLANEOUS PAVEMENT MARKINGS


Scale: Not to Scale Date: April, 1978
SHEET NO. 23 OF 24 SHEETS DT 302

SS

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-9(3)	1977	89	89

GENERAL NOTES:


- Pavement marking and striping shall conform to the latest edition of the "Manual on Uniform Traffic Control Devices for Streets and Highways," by the FHWA, and as amended.
- Layout of pavement markings and striping shall be done by the Contractor. The Contractor shall check layout of markings and striping with the Engineer prior to performing work.
- For additional pavement marking details, see sheet DT 300.




ELONGATED

PAVEMENT ARROWS

Scale: 3/8" = 1"




STANDARD



PLAN

CROSSWALK & STOP LINE

Scale: Not to Scale



DETAIL "A"

APPROVAL RECOMMENDED: Eiichi Yanaka 5/2/78
TRAFFIC ENGINEER DATE

APPROVED: Hubert R. Galitsky 5/3/78
ASSISTANT CHIEF, ENGINEERING DATE

NO.	REVISION	APPROVED BY	DATE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
LAND TRANSPORTATION FACILITIES DIVISION
STANDARD DETAILS
MISCELLANEOUS PAVEMENT MARKINGS

Scale: As Shown Date: March, 1978

SHEET No. 24 OF 24 SHEETS DT 306