

STATION	Skew (to nearest 5 degrees)	Pay Item Number	Pay Item Description (unit)	SURVEY AND STAKING, DRAINAGE STRUCTURE EACH	REMOVAL OF HEADWALL EACH	BERMS LNFT	PLACED RIPRAP, CLASS 1 CUYD	PLACED RIPRAP, CLASS 2 CUYD	PLACED RIPRAP, CLASS 3 CUYD	PLACED RIPRAP, CLASS 4 CUYD	GROUTED RIPRAP, CLASS 2 CUYD	GROUTED RIPRAP, CLASS 3 CUYD	12-INCH PIPE CULVERT LNFT	24-INCH PIPE CULVERT LNFT	36-INCH PIPE CULVERT LNFT	42-INCH PIPE CULVERT LNFT	48-INCH PIPE CULVERT LNFT	60-INCH PIPE CULVERT LNFT	END SECTION FOR 24-INCH PIPE CULVERT (Concrete) EACH	END SECTION FOR 36-INCH PIPE CULVERT (CAP) EACH	END SECTION FOR 42-INCH PIPE CULVERT (CAP) EACH	END SECTION FOR 48-INCH PIPE CULVERT (CAP) EACH	END SECTION FOR 60-INCH PIPE CULVERT (CAP) EACH	MANHOLE (Type A) EACH	STONE MASONRY HEADWALL FOR 24-INCH PIPE CULVERT EACH	STONE MASONRY HEADWALL FOR 36-INCH PIPE CULVERT EACH	CONCRETE CUYD	EARTHWORK GEOTEXTILE, TYPE IV-E SQYD	STATE	PROJECT	SHEET NO.	TOTAL SHEETS		
																													HI	HI A-AD 6(6)	B14	B24		
																													REMARKS					
201+13 R						0			35.51																				131	Stilling Basin				
201+25						80																												
205+00 LT						165																												
209+27 R						80																												
209+65 L																																		
213+01 R						235																												
218+40 R						372																												
223+02 R						277																												
223+73 L																																		
228+30 L						639																												
231+00 R								128.18																						234	Toe Protection			
245+34 R								25.44																					71	Run-down				
248+01 R								29.75																					51	Toe Protection				
253+06	20		1						36.70		57.24				110						2								53					
269+51 R									94.89																				114	Toe Protection				
271+43 R									50.35																				71	Toe Protection				
272+07 R								19.08																					41	Run-down				
279+92 (21+39)	25		1						76.02		138.75				111							2							113					
280+50 R								69.33																					115	Toe Protection				
284+57 R										757.70																			842	Toe Protection				
289+50			1											42												2								
293+51 L									76.30																				109	Toe Protection				
293+79 R										146.90																			166	Toe Protection				
297+50 L									118.20																				165	Toe Protection				
299+00 L								38.30																					90	Run-down				
307+69						0																												
309+44 L						222																												
310+52 L								38.40																					68	Run-down				
312+08 R						0																												
335+13 R								66.38																					123	Toe Protection				
335+92 L						0																												
337+28 L												117.66																	254	Run-down				
338+35 to 342+46 L									194.55	563.50																			651	Roadside Ditch				
346+50 L																													278	Toe Protection				
350+73 L						137																												
351+80 R								24.91																					66	Run-down				
353+15 L						194																												
355+04 L						0																												
356+44 L						109																												
358+11 L						69																												
360+04 R						87																												
367+57 L								48.64																					89	Toe Protection				
373+00 L										115.40																			133	Toe Protection				
373+00 R								35.00																					66	Toe Protection				
375+75 R								22.32																					38	Toe Protection				
383+01 L								32.96																					63	Toe Protection				
384+58 R										202.18																			236	Toe Protection				
386+67 R										34.65																			56	Run-down				
386+96 to 389+50 R								113.87																					220	Roadside Ditch				
390+92 R										59.70																			69	Toe Protection				
391+50 R									38.88																				73	Run-down				
391+98 R									125.92																				155	Roadside Ditch				
394+06 L												75.48																	115	Run-down				
394+57 to 401+11 L										778.45																			912	Roadside Ditch				
401+15 L											215.76																		302	Run-down				
402+78 L								46.67																					114	Swale				
404+78 L						287																												
418+31 R								49.79																					82	Toe Protection				
423+45 R						0																												
423+78 R								0.00																					102	Run-down				
423+85 L									0.00																				57	Run-down				
435+33	40		1					28.61	129.27		47.21				190						2								112					
434+80 L																													190	Toe Protection				
436+06 R																													227	Toe Protection				
438+50 R								61.03																					44	Toe Protection				

STATION	Skew (to nearest 5 degrees)	Pay Item Number	Pay Item Description (unit)	SURVEY AND STAKING, DRAINAGE STRUCTURE EACH	REMOVAL OF HEADWALL EACH	BERMS LNFT	PLACED RIPRAP, CLASS 1 CUYD	PLACED RIPRAP, CLASS 2 CUYD	PLACED RIPRAP, CLASS 3 CUYD	PLACED RIPRAP, CLASS 4 CUYD	GROUTED RIPRAP, CLASS 2 CUYD	GROUTED RIPRAP, CLASS 3 CUYD	12-INCH PIPE CULVERT LNFT	24-INCH PIPE CULVERT LNFT	36-INCH PIPE CULVERT LNFT	42-INCH PIPE CULVERT LNFT	48-INCH PIPE CULVERT LNFT	60-INCH PIPE CULVERT LNFT	END SECTION FOR 24-INCH PIPE CULVERT (Concrete) EACH	END SECTION FOR 36-INCH PIPE CULVERT (CAP) EACH	END SECTION FOR 42-INCH PIPE CULVERT (CAP) EACH	END SECTION FOR 48-INCH PIPE CULVERT (CAP) EACH	END SECTION FOR 60-INCH PIPE CULVERT (CAP) EACH	MANHOLE (Type A) EACH	STONE MASONRY HEADWALL FOR 24-INCH PIPE CULVERT EACH	STONE MASONRY HEADWALL FOR 36-INCH PIPE CULVERT EACH	CONCRETE CUYD	EARTHWORK GEOTEXTILE, TYPE IV-E SQYD	No pay item	REMARKS				
																															STATE	PROJECT	SHEET NO.	TOTAL SHEETS
																															HI	HI A-AD 6(6)	B14	B24
444+77 R						107				462.22																			493	Toe Protection				
451+29 L									172.43																				261	Toe Protection				
454+00 R									187.69																				231	Toe Protection				
458+95 R																													113	Toe Protection				
459+51 L								125.38																					77	Toe Protection				
460+89 L																													33	Toe Protection				
461+34 R									0.00																				113	Rundown				
462+31 R										89.10																			688	Roadside Ditch				
462+95 to 471+08 R								460.64																					681	Roadside Ditch				
478+41 to 483+50 L									412.93																									
488+35 (61+10)			1												100												2							
490+77	45		1						38.30		38.48				222					2									54					
495+51 L									66.89																				91	Toe Protection				
499+66 L								89.25																					157	Toe Protection				
506+00 R								13.42																					21	Toe Protection				
508+70 L								21.73																					61	Rundown				
516+01 R								38.28																					69	Toe Protection				
522+21 R								29.36																					95	Rundown				
522+28 L								27.11																					36	Rundown				
529+74 R										81.60																			100	Rundown				
530+19 R								117.17																					263	Roadside Ditch				
534+86 R									57.22																				79	Toe Protection				
535+50 R									46.51																				91	Rundown				
539+74 R								35.48																					68	Toe Protection				
542+82 R							0.00																						63	Rundown				
548+49	25		1						200.83		62.56						196							1				90.03	172	Concrete: Energy Dissipator				
549+50 R									48.06																				80	Toe Protection				
550+16 R									31.08																				75	Rundown				
550+53 to 563+03 R								910.31																					1,095	Roadside Ditch				
575+95 L						431																												
579+76 L								234.51																					462	Swale				
583+21 L						8180																												
588+54 R																																		
599+97 L									298.51																				442	Toe Protection				
609+92 R								239.76																					475	Toe Protection				
610+00 L								122.22																					221	Toe Protection				
613+20 L								59.50																					89	Toe Protection				
613+96 L									16.75																				48	Rundown				
614+01 R								42.93																					63	Rundown				
622+97 R						230																												
626+27 R								310.53																					588	Toe Protection				
631+45 R								28.80																					86	Rundown				
652+10	50		1						120.30		85.00		400				233						2						123					
654+23																													82	Rundown				
660+29 R							17.20																						169					
673+24	25		1						127.41		50.67				108					2									212	Toe Protection				
674+28 R									144.96																				97	Rundown				
677+38 L									54.27																									
Mamalahoa Hwy (Hwy 190)																																		
773+10 R												0.00																	167	Rundown				
773+90 R									152.77																				223	Roadside Ditch				
775+03 R									125.28																				127	Rundown				
778+61 R	0		1	1					58.91		45.33			62					1						1									
782+10 R												74.37																	125	Rundown				
783+85 R	20		1	1						26.66			50						1						1									
			11	2	4,539	17.20	3,677.34	3,445.39	3,291.40	551.90	785.26	400	154	430	300	344	196	2	4	4	4	1	2	2	2	90.03	16,420							
SCHEDULE B + X																																		