## **SECTION 629 - PAVEMENT MARKINGS**

Make the following amendments to said Section:

(I) Amend Subsection 629.03(B) – Temporary Pavement Markings by revising the third paragraph from line 62 to 63 to read:

"Maintain and replace temporary pavement markings, flexible delineators, and barricades."

(II) Amend Table 629.03 – 1 – Temporary Pavement Markings to read as follows:

"TABLE 629.03-1 TEMPORARY PAVEMENT MARKINGS			
ТҮРЕ	PAVEMENT MARKINGS		
Passing Permitted - Both Sides	Single 4-inch yellow stripe 5 feet in length spaced 20 feet on center with Type D markers spaced 40 feet on center and located on center of 5-foot length of stripe.		
Passing Prohibited - Both Sides	Double solid 4-inch yellow stripes with Type D markers placed 20 feet on center on one of 4-inch yellow stripes selected by the Engineer.		
Passing Permitted - One Side Only	Single continuous 4-inch yellow stripe with Type D markers placed on stripe 20 feet on center on no-passing side and single 4-inch yellow stripes 5 feet in length spaced 20 feet on center on passing side.		
Lane Lines - Lane Changing Permitted	Single 4-inch yellow or white stripe 5 feet in length spaced 20 feet on center with Type C or Type D markers spaced 40 feet on center.		
Lane Lines - Lane Changing Prohibited	Double solid 4-inch white stripes with Type C markers placed 20 feet on center on one of the 4-inch white stripes selected by the Engineer.		
Crosswalk	Two 12-inch white transverse lines spaced 8 feet on center or as ordered by the Engineer.		
Stop Line	Single 12-inch white transverse line.		
Note: Paint may be used for temporary markings in areas where final paving is not complete."			

(III) Amend Subsection 629.03(C) – Permanent Pavement Markings by adding the following after line 267:

19 20	(IV) A	mend
21	ioliows.	
22	"629.04	Mea
23		
24	(A	(A)
25	•	mar
26		doc
27		line
28		in th
29		_
30		e 1
31		foot
32 33		-
34		incl
35		Barı
36		of p
37		pav
38		•
39		-
40		pav
41		prov
42		stip
43		pav
44 45		pav
43 46	(E	3) T
<del>4</del> 7	(L	type
48		t) PC
49	(0	) T
50	,	ínch
51		pair
52		Eng
53		less
54		as a
55		-
56 57		the
58		strip
59		Jul
60		-
61		foot
62		
63		-
64		acc

65

**629.04 – Measurement** by revising lines 292 to 294 to read as

## surement.

he Engineer will measure thermoplastic and preformed pavement king tape per linear foot in accordance with the contract uments. The longitudinal pavement markings will be measured per ar foot as a single stripe for the width specified in the contract and ne proposal.

The Engineer will measure the transverse markings by the linear , per lane, or per each according to the contract.

The Engineer will not measure temporary pavement markings uding flexible delineator posts with reflector makers or Type I ricades and temporary signs installed for the longitudinal guidance public traffic over reconstructed areas, cold planed surfaces, newly ed surfaces or other unmarked or scarified areas for payment.

The Contractor shall consider the work required for the removal of ement markings incidental to the various contract items, except as vided in the proposal or elsewhere in the contract. If the contract ulates that the Engineer will make payment for the removal of ement markings, the Engineer will measure the removal of ement markings.

- he Engineer will measure the pavement markers per each for the es shown in the proposal.
- The Engineer will measure the painted stripes that are twelve (12) nes wide or less as a single stripe. The Engineer will measure the nted stripes over twelve (12) inches wide as two (2) stripes. The ineer will measure the double stripes that are twelve (12) inches or in total width including the transverse space between the stripes a single stripe.

The Engineer will measure the longitudinal pavement markings by linear foot according to the contract. Longitudinal gaps for skip ping will not be included in the measurement.

The Engineer will measure the transverse markings by the linear , per lane, or per each according to the contract.

The Engineer will measure the curb markings by the linear foot ording to the contract."

113	, , , ,	The Engineer will pay for pavement arrows (single or multiple arrow		
114	heads), symbols, and words at the contract price pe	r each according to		
115	the contract.			
116				
117	The Engineer will pay for the accepted quantitie	s of curb markings		
118	at the contract price per linear foot.			
119				
120	, ,	The Engineer will pay for the following pay items when included i		
121	the proposal schedule:			
122				
123	Pay Item	Pay Unit		
124				
125	Inch Pavement Striping ()	Linear Foot		
126				
127	Inch Pavement Striping ()	Linear Foot		
128	(Stop Bar at Crosswalks Only)			
129				
130	Pavement Word (Thermoplastic Extrusion)	Each		
131				
132	Pavement Arrow (Thermoplastic Extrusion)	Each		
133				
134	Pavement Symbol (Thermoplastic Extrusion)	Each		
135		_		
136	Yield Line (Thermoplastic Extrusion)	Lane		
137		_		
138	Crosswalk Marking (Thermoplastic Extrusion)	Lane		
139		_		
140	Crosswalk Marking (Thermoplastic Extrusion)	Lane		
141	(Crosswalks Only)			
142				
143	Type Pavement Marker	Each		
144				
145	Removing and Disposing of	Linear Foot		
146				
147	Removing and Disposing of	Each		
148		_		
149	Removing and Disposing of	Lane		
150				
151	Thermoplastic Rumble Bars	Linear Foot		
152				
153				
154	END OF SECTION 629			