

1 Make this section a part of the Standard Specifications:

2
3 **"SECTION 404 - SLURRY SEAL**

4
5 **404.01 Description.** This section describes furnishing and applying slurry seal
6 on an existing asphalt surface.

7
8 **404.02 Materials.**

9
10 Emulsified Asphalt (Type CQS-1h with 2% Polymer Latex) 702.04

11
12 Aggregate for Slurry Seal 703.11

13
14 Filler 703.15

15
16 Water 712.01

17
18 **(A) General.** Slurry seal shall include uniform blend of emulsified
19 asphalt, aggregate, water, and if required by job-mix formula, filler.

20
21 **(B) Job-Mix Formula and Tests.** Unless otherwise specified, design
22 and test job-mix formula in accordance with ASTM D 3910 and
23 International Slurry Seal Association (ISSA) technical bulletins, for Type III
24 slurry seal, and as indicated in the contract documents.

25
26 Tolerance of plus or minus 1 percent will be allowed in residual
27 asphalt content from that specified in job-mix formula accepted by the
28 Engineer.

29
30 **(C) Submittals.** Submit slurry seal job-mix formula for each type of
31 slurry seal mix indicated in the contract documents as follows:

32
33 **(1)** Design percent of aggregate passing each required sieve size.

34
35 **(2)** Design percent of residual asphalt added to aggregate, based
36 on dry weight of aggregate.

37
38 **(3)** Source of aggregate.

39
40 **(4)** Grade of emulsified asphalt.

41
42 **(5)** Test data used to develop job-mix formula.

43
44 **(6)** Slurry seal equipment calibration and production settings for
45 approved job-mix formula.
46

If design requirements are modified after the Engineer accepts job-mix formula, submit new job-mix formula before using slurry seal produced from modified mix design.

(D) Material Storage & Handling. A barrier shall be placed under the aggregate stockpile to prevent underlying material from being incorporated into the slurry seal aggregate. Prior to loading aggregates into mixing machine bins, aggregates shall be screened to remove oversized material.

404.03 Construction.

(A) Test Section. Before production and after calibration as specified in Subsection 404.03(C)(6) - Equipment Calibration, apply slurry seal onto test section using same mixture, equipment, and method proposed for use in the work. Test section shall be at least 10 feet by 50 feet and applied under typical project environmental conditions. A separate test section is required for each piece of equipment that will be used on the project. The test sections shall also include a demonstration of the equipment change-out procedure for material resupply to verify the consistency of the slurry material upon restart and the ability to construct an acceptable construction joint. The Engineer will determine location of test section. Prior to continuation of slurry seal production, mixture samples may be taken and the test strip will be evaluated to verify mix consistency, proportioning, application rate, and set time.

(B) Paving Plan. Submit a slurry seal paving plan for review and acceptance prior to the start of slurry seal activity. The paving plan shall include the sequence of work for the slurry application areas, equipment application runs, and designated handwork application areas.

(C) Weather Limitation. Application of slurry seal will not be allowed under the following conditions:

(1) On wet surfaces as determined by the Engineer.

(2) When air temperature is below 60 degrees F and falling. Slurry seal may be applied when air temperature is above 50 degrees F and rising. Air temperature will be measured in shade and away from artificial heat.

(3) When weather conditions prevent proper method of construction.

94 **(D) Equipment.**

95
96 **(1) General.** Keep equipment, tools, and machinery clean and
97 maintained in satisfactory condition.

98
99 **(2) Mixing Equipment.** Use self-propelled machine specifically
100 designed and manufactured to lay slurry seal. Mixing machine shall
101 be either truck-mounted or continuous-run design. A continuous-run
102 machine is defined as one that is equipped to self-load while
103 continuing to lay slurry seal. Either type machine shall be able to
104 accurately deliver and proportion aggregate, emulsified asphalt,
105 water, and if specified by job-mix formula, filler to maintain
106 adequate supply to the proportioning controls.

107
108 If continuous-run machine is used, equip to allow operator to
109 have full control of forward and reverse speeds during slurry seal
110 application; and to include opposite-side driver stations and forward
111 and reverse speed controls.

112
113 **(3) Proportioning Devices.** Provide and label individual volume
114 or weight controls for proportioning each material to be added to
115 mix.

116
117 **(4) Spreading Equipment.** Spread mixture uniformly by means
118 of conventional surfacing spreader box attached to mixer and
119 equipped to agitate and spread material evenly throughout box.
120 Provide front seal that prevents loss of mixture at road contact point
121 and adjustable rear seal the functions as final strike-off. Design and
122 operate spreader box and rear strike-off such that uniform
123 consistency is achieved to produce free flow of material to rear
124 strike-off. Equip spreader box with means to side shift box to
125 compensate for variations in pavement geometry. Burlap drag or
126 other accepted screed may be attached to rear of spreader box to
127 provide uniform, highly textured mat.

128
129 **(5) Auxiliary Equipment.** Provide other tools or equipment,
130 such as brushes, hose equipment, tank trucks, water distributors
131 and flushers, power sweepers, and power blowers.

132
133 **(6) Equipment Calibration.** Calibrate in the Engineer's
134 presence all equipment to be used in performance of the work.
135 Submittal of previous calibration documents may be used in lieu of
136 calibration in the Engineer's presence if documented calibration
137 were made within one calendar year of submittal. Include individual
138 calibration of each material at various settings, which can be
139 related to machine's metering devices. No machine will be allowed

140 to be used on project until calibration has been completed and
141 accepted.
142

143 After calibration and prior to production, make test strips for
144 each machine. Test strips shall be part of test section specified in
145 Subsection 404.03(A) - Test Section. Upon failure of test for mix
146 consistency, proportioning, or rate of application, or combination
147 thereof, additional test strips at no increase in contract price or
148 contract time will be required until each machine is accepted for
149 work. Machine failing to pass specified tests after three trials will
150 not be allowed to be used on project.
151

152 **(E) Preparation of Surfaces.** Immediately before applying slurry seal,
153 clean existing pavement in accordance with Section 310 - Brooming Off.
154

155 Remove all pavement markers and eradicate the existing
156 thermoplastic pavement striping.
157

158 Cold plane the existing pavement to provide a smooth transition
159 between the slurry seal and any existing pavement or structure. The cold
160 planed or ground transition shall be a minimum width of one foot from the
161 edge of the existing pavement or structure and deep enough for the slurry
162 seal to match the grades of the existing pavement or structure. This work
163 shall be completed and paid for under the pay item, Cold Planing.
164

165 Distressed areas on the existing pavement indicated for removal
166 and replacement with hot-mix asphalt shall be completed at least seven
167 days prior to the start of slurry seal placement. The reconstructed areas
168 shall not be higher than the existing pavement surface and may be
169 recessed up to 1/8-inch below the existing pavement surface. This work
170 shall be completed and paid for under the pay item, Reconstruction of
171 Weakened Pavement Areas.
172

173 Application of Crack Sealer shall be in accordance with section 408
174 – Crack Seal. Crack Sealing shall be completed at least thirty (30)
175 calendar days prior to the start of slurry seal placement. This work shall
176 be completed and paid for under the pay item, Crack Seal.
177

178 Contaminated areas on the existing pavement including but not
179 limited to chemical spills/stains and accumulation of debris or organic
180 matter shall be removed, cleaned with an approved biodegradable
181 cleaning solution, and thoroughly rinsed. Persistent stains shall be
182 removed by spot-grinding or torching and sealed with an approved oil spot
183 primer. High pressure washing is not permitted.
184

185 Manholes, valve boxes, drop inlets and other service entrances as
186 well as survey and centerline monuments, shall be protected from the

slurry seal by a suitable method. Contractors shall be held liable for any service entrances and monuments covered up resulting from construction. The clean up of any service entrances and monuments shall be at the expense of the contractor.

The Engineer shall approve surface prior to application of slurry surfacing.

(F) Application of Slurry Seal. Apply slurry seal in accordance with ASTM D 3910, ISSA A105, and as indicated in the contract documents. Pour slurry seal into spreader box in sufficient quantity to completely cover full width of spreader. Do not overload the spreader or allow slurry seal to flow out of the sides of the spreader box. The slurry seal shall possess sufficient stability so that the premature breaking of the material in the spreader box does not occur. The mixture shall be homogeneous during and following mixing and spreading. It shall be free of excess water and emulsion and free of segregation of the emulsion and aggregate fines from the coarser aggregate. Spraying of additional water into the spreader box will not be permitted.

Apply slurry seal in one uniformly blended coat. Use hand spreaders only in areas where spreader box cannot be used.

Lumping, balling, or unmixed aggregate in the slurry seal shall not be permitted. No streaks, such as those caused by oversized aggregate, shall be left in the finished surface. If excess oversize develops, the job will be stopped until the Contractor is able to prove that the situation has been corrected. All cost and time expense related to the stoppage will be the responsibility of the Contractor.

(G) Joints, Trimming Edges, Removal of Excess Material, and Corrective Measures. Excess buildup, uncovered areas, or unsightly appearance shall not be permitted. All excess slurry seal build-up on longitudinal and transverse joints shall be removed. Place longitudinal joints on lane lines. Half passes and odd-width passes may only be used in minimum amounts and only when authorized by the Engineer. The contractor shall provide suitable width-spreading equipment to minimize the number of longitudinal joints throughout the project. Longitudinal lane line joints shall not overlap more than six inches.

Excess slurry seal on areas such as shoulders, gutters, curbs, utility covers, and pavement markers and striping to remain shall be removed.

All deficiencies in the slurry seal, resulting from but not limited to poor workmanship, contractor's operations, removal of temporary traffic control measures, and early opening to vehicular traffic, shall be repaired

before acceptance. All corrective measures shall be considered incidental to the slurry seal. The corrective methods shall be approved by the Engineer.

(H) Protection of Slurry Seal. Except for construction equipment used for slurry seal operations, keep traffic off slurry seal until such time that mixture has cured sufficiently so that slurry seal will not adhere to and be picked up by vehicle tires. Ensure that cured slurry seal adheres firmly to existing surface.

404.04 Measurement. The Engineer will measure slurry seal per square yard in accordance with the contract documents.

The Engineer will not measure preparation of surfaces except for cold planing and distressed asphalt reconstruction work. All other work mentioned in the preparation of surfaces shall be considered incidental to slurry seal activities.

404.05 Payment. The Engineer will pay for the accepted slurry seal at the contract unit price basis, as shown in the proposal schedule. Payment will be full compensation for the work prescribed in this section and the contract documents.

The Engineer will pay for the following pay item when included in the proposal schedule:

Pay Item	Pay Unit
Slurry Seal	Square Yard

Engineer will pay 100 percent of the contract bid price upon completion of the slurry seal installation.”

END OF SECTION 404