1 2	SECTION 407 – TACK COAT
3	Make the following amendment to said Section:
4	
5	(I) Amend Section 407.03(D) - Application of Tack Coat, from lines 66 to 68
6	to read:
7	
8	"For multiple lift construction of HMA or PMA, tack coat application will
9	not be waived. Remove all deleterious material to bonding before applying the
10	tack coat to the entire surface to receive the next lift."
11	(II) A 10 (1 (0000) A II (1 (0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1
12	(II) Amend Section 407.03(D) - Application of Tack Coat, from lines 70 to 72
13	to read:
14	
15	"Before placing HMA or PMA course, apply tack coat to contact surfaces
16	of curbs, gutters, manholes, other structures, vertical faces of existing
17	pavements, and exposed transverse and longitudinal edges of each course.
18	Apply tack coat on all surfaces that will have an asphalt pavement placed on it in
19	a uniform, full coverage manner, e.g., no visible streak, holidays in the
20	application, no differences in the application rate, i.e., the thickness of the tack
21	coat. The exception to this requirement shall be surfaces that will have pavement
22	joint adhesive applied to it which shall not require any tack coat."
23	
24	
25	
26	
7	END OF SECTION 407

END OF SECTION 407