SECTION 629 - PAVEMENT MARKINGS

Make the following amendments to said Section:

(I) Amend Subsection 629.03(B) – Temporary Pavement Markings by revising the third paragraph from line 62 to 63 to read:

"Maintain and replace temporary pavement markings, flexible delineators, and barricades."

(II) Amend **Table 629.03 – 1 – Temporary Pavement Markings** to read as follows:

"TABLE 629.03-1 TEMPORARY PAVEMENT MARKINGS			
ТҮРЕ	PAVEMENT MARKINGS		
Passing Permitted - Both Sides	Single 4-inch yellow stripe 5 feet in length spaced 20 feet on center with Type D markers spaced 40 feet on center and located on center of 5-foot length of stripe.		
Passing Prohibited - Both Sides	Double solid 4-inch yellow stripes with Type D markers placed 20 feet on center on one of 4-inch yellow stripes selected by the Engineer.		
Passing Permitted - One Side Only	Single continuous 4-inch yellow stripe with Type D markers placed on stripe 20 feet on center on no-passing side and single 4-inch yellow stripes 5 feet in length spaced 20 feet on center on passing side.		
Lane Lines - Lane Changing Permitted	Single 4-inch yellow or white stripe 5 feet in length spaced 20 feet on center with Type C or Type D markers spaced 40 feet on center.		
Lane Lines - Lane Changing Prohibited	Double solid 4-inch white stripes with Type C markers placed 20 feet on center on one of the 4-inch white stripes selected by the Engineer.		
Crosswalk	Two 12-inch white transverse lines spaced 8 feet on center or as ordered by the Engineer.		
Stop Line	Single 12-inch white transverse line.		
Note: Paint may be used for temporary markings in areas where final paving is not complete."			

(III) Amend **629.04 – Measurement** by revising lines 292 to 294 to read as follows:

"629.04 Measurement.

(A) The Engineer will measure thermoplastic and preformed pavement marking tape per linear foot in accordance with the contract documents. The longitudinal pavement markings will be measured per linear foot as a single stripe for the width specified in the contract and in the proposal. The Engineer will include the longitudinal gaps for skip striping, up to thirty (30) feet long, in the measurement.

The Engineer will measure the transverse markings by the linear foot according to the contract.

 The Engineer will not measure temporary pavement markings including flexible delineator posts with reflector makers or Type I Barricades and temporary signs installed for the longitudinal guidance of public traffic over reconstructed areas, cold planed surfaces, newly paved surfaces or other unmarked or scarified areas for payment.

The Engineer will measure the temporary pavement markings and temporary signs installed as ordered by the Engineer for special temporary traffic patterns on a force account basis, if the contract specifies payment in the proposal.

The Contractor shall consider the work required for the removal of pavement markings incidental to the various contract items, except as provided in the proposal or elsewhere in the contract. If the contract stipulates that the Engineer will make payment for the removal of pavement markings, the Engineer will measure the removal of pavement markings.

(B) The Engineer will measure the pavement markers per each for the types shown in the proposal.

(C) The Engineer will measure the painted stripes that are twelve (12) inches wide or less as a single stripe. The Engineer will measure the painted stripes over twelve (12) inches wide as two (2) stripes. The Engineer will measure the double stripes that are twelve (12) inches or less in total width including the transverse space between the stripes as a single stripe.

The Engineer will measure the longitudinal pavement markings by the linear foot according to the contract. Longitudinal gaps for skip striping that are 30 feet or less will be included in the measurement.

The Engineer will measure the transverse markings by the linear foot according to the contract."

113	Pay Item	Pay Unit
114		
115	Inch Pavement Striping (Tape, Type, or	
116	Thermoplastic Extrusion)	Linear Foot
117		
118	Pavement Arrow (Tape, Type, or Thermoplastic	
119	Extrusion)	Each
120		
121	Pavement Word (Tape, Type, or Thermoplastic	
122	Extrusion)	Each
123		
124	Type Pavement Marker	Each
125		
126		
127		
128		
129		
130	END OF SECTION 629	
131		