

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17
- 18
- 19
- 20
- 21
- 22
- 23
- 24
- 25
- 26
- 27
- 28
- 29
- 30
- 31
- 32
- 33
- 34
- 35
- 36
- 37
- 38
- 39
- 40
- 41
- 42
- 43
- 44
- 45
- 46
- 47
- 48

(I) Amend 712.02 Epoxy – Resin Adhesive to read as follows:

(II) Amend **712.04(A) Non-shrink Grout** by revising the first and second paragraphs at lines 31 and 38 to read as follows:

(III) Amend **712.04(A) Non-shrink Grout** by revising the value of expansion (percent) at age 28 days in Table 712.04-2 – Compressive Strength Requirements at line 46 to read 0.02.”

“Epoxy Grout. Submit six copies of product brochures and a certificate of compliance from manufacturer or supplier affirming that proposed material conforms to ASTM C881 and is appropriate for the intended use. The epoxy grout shall be able to support and carry sustained creep tensile loads. The use of the epoxy grout shall conform to the manufacturer’s recommendations. The color of the exposed materials shall closely match the surrounding material.”

ER-23(001)
712-1a

10/15/20