

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	39	109

INDEX TO BRIDGE DRAWINGS

SHEET NO.	DESCRIPTION	SHEET NO.	DESCRIPTION	SHEET NO.	DESCRIPTION
S0.1	INDEX TO BRIDGE DRAWINGS	S4.1	ELEVATION AT PIER NO. 2 (PIER NOS. 3, 5, & 6 SIM.)	S11.1	CONCRETE REPAIR NOTES
S0.2	BRIDGE GENERAL NOTES	S4.2	SECTIONS AT PIER NO. 2 (PIER NOS. 3 TO 6 SIM.)	S11.2	CONCRETE REPAIR NOTES
S0.3	BRIDGE GENERAL NOTES	S4.3	SECTIONS AT PIER NO. 2 (PIER NOS. 3, 5 & 6 SIM.)	S11.3	DECK SLAB SOFFIT SPALLS
S0.4	SYMBOLS AND ABBREVIATIONS	S4.4	CONC. SEAT AT PIER NO. 2 (PIER NOS. 3, 5 & 6 SIM.)	S11.4	DECK SLAB SOFFIT SPALLS TABLE
				S11.5	DECK SLAB SOFFIT SPALLS TABLE
				S11.6	DECK SLAB SOFFIT SPALLS TABLE
S1.1	BRIDGE LAYOUT PLAN AND ELEVATION	S5.1	ELEVATION AT PIER NO. 4	S11.7	SOFFIT REPAIR DETAILS
		S5.2	SECTIONS	S11.8	SOFFIT REPAIR DETAILS
		S5.3	SECTION	S11.9	SOFFIT REPAIR DETAILS
S2.1	DEMOLITION PLAN AND ELEVATION	S5.4	CONCRETE SEAT AT PIER NO. 4	S11.10	GIRDER SPALLS AND DELAMINATIONS
S2.2	DEMOLITION AT PIER NO. 1 (LIHUE SIDE)			S11.11	GIRDER SPALLS AND DELAMINATIONS TABLE
S2.3	DEMOLITION AT PIER NO. 1 (KAPAA SIDE)			S11.12	GIRDER REPAIR DETAILS
S2.4	DEMOLITION AT PIER NO. 2 (PIER NOS. 3, 5, & 6 SIM.)	S6.1	CREEP BLOCK PLAN AT PIER NO. 1	S11.13	GIRDER REPAIR DETAILS
S2.5	DEMOLITION AT PIER NO. 4	S6.2	CREEP BLOCK SECTIONS AT PIER NOS. 1 & 7	S11.14	GIRDER REPAIR DETAILS
S2.6	DEMOLITION AT PIER NO. 7 (LIHUE SIDE)	S6.3	CREEP BLOCK PLAN AND SECTIONS AT PIER NO. 7		
S2.7	DEMOLITION AT PIER NO. 7 (KAPAA SIDE)	S6.4	CREEP BLOCK PLAN AT PIER NOS. 2-6		
S2.8	DEMOLITION DETAILS	S6.5	CREEP BLOCK SECTIONS AT PIER NOS. 2-6	S12.1	CONSTRUCTION SEQUENCE
S2.9	STEEL DEMOLITION PLAN AT PIER NO. 1				
S2.10	STEEL DEMOLITION ELEVATIONS AT PIER NO. 1	S7.1	ELASTOMERIC BEARING PAD		
S2.11	STEEL DEMOLITION SECTIONS AT PIER NO. 1				
S2.12	STEEL DEMOLITION AT PIER NO. 7				
S2.13	END POST DEMOLITION, ELEVATION AND SECTION	S8.1	EXPANSION JOINT AND GIRDER REPAIR		
S3.1	ELEVATION AT PIER NO. 1 (LIHUE SIDE)	S9.1	PRODUCTION DRILLED SHAFT AT PIERS		
S3.2	ELEVATION AT PIER NO. 1 (KAPAA SIDE)	S9.2	DRILLED SHAFT SCHEDULE		
S3.3	SECTION AT PIER NO. 1	S9.3	LOAD TEST SHAFT		
S3.4	SECTION				
S3.5	SECTIONS				
S3.6	REINFORCING AT SPANS 1 & 8 AND SPANS 2 & 7	S10.1	TYP. END POST PLAN AND ELEVATION		
S3.7	REINFORCING PLANS AT SPANS 1-2 AND SPANS 8-7	S10.2	TYP. END POST SECTIONS AND DETAIL		
S3.8	CONCRETE SEAT AT PIER NO. 1	S10.3	METAL GUARDRAIL TYPE 3 THRIE BEAM AND APPURTENANCES DETAILS		
S3.9	CONCRETE SEAT AT PIER NO. 1				
		S10.4	METAL GUARDRAIL TYPE 3 THRIE BEAM AND APPURTENANCES DETAILS		

ORIGINAL
PLAN

SURVEY PLOTTED BY
DATE

NOTE BOOK

DESIGNED BY
QUANTITIES BY
CHECKED BY

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50001 INDEX.DWG PLOT TIME: 04-05-21, 3:32 PM

CALVIN T. MIYAKURA

LICENSED
PROFESSIONAL
ENGINEER

NO. 8133-S

HAWAII, U.S.A.

THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin Miyakura

4-30-22

SIGNATURE EXPIRATION DATE OF THE LICENSE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

INDEX TO BRIDGE DRAWINGS

KUHIO HIGHWAY

Repairs to Wallua River Bridge

Fed. Aid Project No. ER-23(001)

Scale: As Noted Date: Apr. 2021

SHEET No. S01 OF 4 SHEETS

BRIDGE GENERAL NOTES

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	40	109

1. GENERAL SPECIFICATIONS: Hawaii Department of Transportation, Standard Specifications for Road and Bridge Construction, 2005, together with Special Provisions prepared for this contract.

2. DESIGN SPECIFICATIONS:

- A. AASHTO LRFD Bridge Design Specifications Ninth Edition (2020) including all subsequent interim revisions and editions.
- B. State of Hawaii Department of Transportation Highways Division "Design Criteria for Bridges and Structures" dated August 8, 2014 including subsequent interim revisions.
- C. AASHTO Guide Design Specifications for Bridge Temporary Works, 2nd Edition (2017).

3. LOADS:

- A. Dead Loads: Concrete self weight assumed to be 160 pcf.
- B. Live Load: AASHTO HL-93 Loading.
- C. Seismic Loads:
In accordance with (AASHTO) 2014 LRFD Bridge Design Specifications, 7th Edition, including the 2015 Interim Revision Edition. Peak Ground Acceleration ($PGA = 0.065g$), modified by the Site Coefficient ($F_{PGA} = 1.6$) to give a spectrum acceleration, $A_S = 0.104g$. Short period acceleration at 0.2 seconds ($S_S = 0.143g$) modified by the site coefficient ($F_a = 1.600$) to give the short period spectrum acceleration, $S_{PS} = 0.228g$. Long period acceleration at 1.0 seconds ($S_1 = 0.042g$) modified by the Site Coefficient ($F_V = 2.400$) to give the long period spectrum acceleration, $S_{D1} = 0.100g$. Site Class = D. Seismic Zone = 1. Operational Category = Essential.
- D. Utility Load: An allowance of 150 plf on each side of bridge for utility loads has been provided for in the design.
- E. Railing Test Level: TL-3
- F. Future wearing surface: 25 psf curb to curb.

4. MATERIALS:

- A. All concrete properties shall be as noted below:

Item No.	Structural Parts	Minimum Compressive Strength, f'c (28 Days)	Maximum Water/Cement (W/C)	Included Admixtures*
(1)	Drilled Shafts	5,000 psi	0.45	4.(B)
(2)	Shaft Cap Beam	6,000 psi	0.40	4.(B), 4.(C), 4.(D)
(3)	End Beam	6,000 psi	0.40	4.(B), 4.(C), 4.(E)
(4)	All Others	5,000 psi	0.45	4.(B)

*Refer to notes 4.(B) through 4.(E) in this section

4. MATERIALS (Cont.):

- B. Amine carboxylate corrosion inhibiting water-based admixture such as Cortec MCI 2005 NS or approved equal shall be added at a dosage of 24 ounces per cubic yard.
- C. Shrinkage reducing admixture such as Eclipse 4500 or Masterlife SRA 20 or approved equal shall be added at a dosage of 128 ounces per cubic yard or as recommended by the manufacturer.
- D. Alkali resistant structural glass fiber such as CEMFIL, ANTI-CRAK HP67/36 or approved equal shall be added to the concrete mix. The dosage rate shall be 15 lbs per cubic yard for CEMFIL or the equivalent amount of approved equal to achieve similar properties as the glass dosage. The fiber shall be added to the concrete as recommended by the manufacturer during the mixing process.
- E. A structural fiber such as 2 1/4" long Forta Ferro Fiber or approved equal shall be added to the concrete mix. The dosage rate shall be 7.5 lbs per cubic yard or the equivalent amount of approved equal to achieve similar properties as the glass dosage. The fiber shall be added to the concrete as recommended by the manufacturer during the mixing process.
- F. The use of calcium chloride in any concrete is prohibited.
- G. All concrete exposed within 7 days of placement shall be cured using Sinak Lithium Cure 1000 or approved equal at a coverage rate of no less than 400 sq. ft. per gallon.
- H. All reinforcing steel shall be ASTM A615 Grade 60 deformed bars unless otherwise noted.
- I. Epoxy for anchoring deformed bars shall be HILTI-RE 500V30 or approved equal. Manufacturer's recommendations shall be followed.

5. REINFORCEMENT:

- A. The covering measured from the surface of the concrete to the face of any reinforcing bars shall be as follows, except as otherwise shown:
- (1) Deck Slabs
a. Top Bars = 2 1/2"
b. Bottom Bars = 1 1/2"
- (2) Concrete cast against and permanently exposed to earth = 3"
- (3) All others unless otherwise noted = 2"
- B. Reinforcing bars shall be detailed in accordance with the latest edition of the AASHTO LRFD bridge design specifications unless otherwise noted.

5. REINFORCEMENT (Cont.):

- C. Minimum clear spacing between parallel bars shall be 1 1/2 times the diameter of bars (for non bundled bars). In no case shall the clear distance between the bars be less than 1 1/2 times the maximum size of the coarse aggregate or 1 1/2", whichever is greater.
- D. All dimensions relating to reinforcing bars are to centers of bars unless otherwise noted.
- E. Reinforcing bars shall be securely tied at all intersections and lap splices except where the spacing of intersections is less than one foot in each direction, in which case alternate intersections shall be tied.

6. ELASTOMERIC BEARING PADS:


- A. Top of concrete surfaces receiving elastomeric bearing pads shall be finished with a steel trowel to a smooth level surface to the elevation shown on the plans. Grind down high spots as needed to provide an even bearing surface to 1/16"± tolerance.
- B. To prevent displacement, the bottom of bridge bearing pads shall be secured to the top of the raised piers with adhesives recommended by the Manufacturer and approved by the Engineer.

7. CONSTRUCTION NOTES:

- A. The Contractor shall verify all dimensions and site conditions and shall report any discrepancies in writing to the Engineer before commencing work or ordering materials.
- B. The Contractor shall verify all site conditions and not rely upon these plans for existing, dimensions, elevations and azimuths, stream channel location, roads, roadway gutters, curbs and sidewalks, etc. Conditions may differ from those shown.
- C. The Contractor shall be solely responsible for the protection of adjacent properties, utilities and existing and new structures from damage due to construction. Repairing any damage shall be at the Contractor's own expense, to the satisfaction of the Engineer.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
No.	DESIGNED BY	" "
	CHECKED BY	" "

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID-WBS-50002 NOTES.DWG PLOT TIME: 04-05-21, 3:32 PM



STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

BRIDGE GENERAL NOTES

KUHIO HIGHWAY

Repairs to Wailua River Bridge

Fed. Aid Project No. ER-23(001)

Scale: None Date: Apr. 2021

SHEET No. 502 OF 4 SHEETS

BRIDGE GENERAL NOTES

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	41	109

7. CONSTRUCTION NOTES (Cont.):

- D. The Contractor shall verify the location of all utility lines and notify the respective owners before commencing with excavation, and any temporary piling or sheeting.
- E. Except as otherwise noted, all vertical dimensions are measured plumb.
- F. For concrete finish see Standard Specifications and Special Provisions.
- G. Construction joints may be relocated or additional ones added subject to the approval of the Engineer.
- H. Unless otherwise noted, all exposed concrete edges shall be chamfered 3/4" x 3/4".
- I. The Contractor shall verify the location and size of all existing reinforcing bars prior to drilling.
- J. Location of drilled holes shown in plans are approximate. Prior to placing holes in concrete, the Contractor shall locate all reinforcing steel anchor bolts, thru bolts holes, etc. and adjust the location of the drilled holes to be clear all of them. Final hole locations are subject to the approval of the Engineer.
- K. Drilled holes in existing concrete for reinforcing steel dowels shall not be left unfilled for more than 8 hours. Epoxy in drilled holes shall be able to develop the full strength of the dowels prior to pouring concrete around reinforcing steel dowels. Follow all epoxy manufacturer's recommendations for dowel, drilling and epoxy. Coring of holes will not be allowed unless approved by Engineer.
- L. Contractor shall unplug, clean existing drains and manholes at the start of the project and maintain them during the entire duration of the project.
- M. When only portions of concrete are to be demolished, the interface between the demolished concrete and the concrete that is to remain shall have a 3/4 inch deep sawcut around the entire perimeter of the demolished area.
- N. Construction joints between separate pours shall not be feather edged. All joints shall be made square and vertical prior to pouring, unless otherwise noted.
- O. The concrete surfaces which new concrete is poured against shall be roughened to a full amplitude of 1/4 of an inch and cleaned.
- P. All existing reinforcing shall remain in place and shall not be damaged in any way unless otherwise noted.

7. CONSTRUCTION NOTES (Cont.):

- Q. All existing reinforcing that is to remain in place shall have a minimum concrete cover of 1 1/2". All concrete, rust and other deleterious material that affects bonding to the concrete shall be removed from the reinforcing steel before concrete is poured around it.
- R. The Contractor shall submit working drawings and calculations for the proposed temporary work platform, new bridge construction, jacks, temporary shoring for existing bridge, and existing bridge superstructure. The existing bridge superstructure shall be checked for all temporary conditions during construction. Temporary work platform, jacks and temporary shoring shall follow the design criteria stated in Items 1, 2 and 3 in the Bridge General Notes. During construction the existing bridge superstructure shall be able to carry all present loads. The drawings and calculations shall be stamped by a licensed Hawaii Structural Engineer. The drawings and calculations shall be found acceptable by the Engineer before any construction work is to proceed.
- S. Lead and bronze is present on the bridge. Cost for the removal, handling, and disposing of lead and bronze shall be considered incidental to the Proposal Schedule Item 202.0100 - Removal of Concrete.

8. GENERAL:

- A. All items not shown on the proposal schedule will not be paid for separately and shall be considered incidental to the various pay items.
- B. Standard Plans refer to all structures in general, except for modifications as may be required for special conditions. For such modifications refer to the corresponding detailed drawings.
- C. Plans of the existing bridge are available for review from the Highways Design Branch located at the State Department of Transportation, Highways Division, Kakuhihewa Building, Room 609, 601 Kamokila Boulevard, Kapolei, HI 96707.
- D. Existing structure has not been checked with the design loads in Item 3. Design loads in item 3 are applicable only to the design of new concrete elements and elastomeric bearing pads shown in the structural plans.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
No.	DESIGNED BY	" "
	QUANTITIES BY	" "
	CHECKED BY	" "

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50002 NOTES.DWG PLOT TIME: 04-05-21, 3:32 PM)

CALVIN T. MIYAKURA

LICENSED PROFESSIONAL ENGINEER

NO. 8133-S

HAWAII, U.S.A.

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Calvin Miyakura

4-30-22

SIGNATURE EXPIRATION DATE OF THE LICENSE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

BRIDGE GENERAL NOTES

KUHIO HIGHWAY

Repairs to Wallua River Bridge

Fed. Aid Project No. ER-23(001)

Scale: None Date: Apr. 2021

SHEET No. 50.3 OF 4 SHEETS

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50004-SYMB-ABBREV.DWG PLOT TIME: 04-05-21 3:33 PM

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
No.	DESIGNED BY	" "
	QUANTITIES BY	" "
	CHECKED BY	" "

SYMBOLS AND ABBREVIATIONS

⌘	And	Demo.	Demolish, Demolition	GDI	Grated Drain Inlet	OG	Outside Girder,
@	At	Det.	Detail	GFRP	Glass Fiber Reinforced		Outbound Girder
∅	Diameter	Dia.	Diameter		Polymer Rebar	Perf.	Perforated
≥	Greater Than or Equal to	Diaph.	Diaphragm	Gr.	Grade	PL	Plate
≤	Less Than or Equal to	Dim.	Dimension	Grd.	Ground	PCC	Portland Cement Concrete
#	Number	Dist.	Distance	GRP	Grouted Rubble Pavement	PC	Point of Curvature
		DO	Ditto			PCF	Pounds per Cubic Foot
Abut.	Abutment	Dwls.	Dowels	Ht.	Height	P(e)	Effective Prestress Force
Abbr.	Abbreviation	Dn.	Down	(H)	Hinge		After All Losses
Add.	Additional	Dbf.	Double	Horiz., H	Horizontal	PPM	Parts Per Million
Alt.	Alternate	DI	Drain Inlet, Ductile Iron	HDOT	State of Hawaii Department	PSF	Pounds per Square Foot
AB	Anchor Bolt	Dwg., Dwgs.	Drawing, Drawings		of Transportation	PSI, psi	Pounds per Square Inch
AC	Asphaltic Concrete	DS	Drilled Shaft	HDPE	High Density Polyethylene	PLF	Pounds per Linear Foot
Approx.	Approximate			HS	High strength	PI	Point of Intersection
Az.	Azimuth	E	East	HECO	Hawaiian Electric Company		of Tangents
		EA, Ea., ea.	Each			PIVC	Point of Intersection of
Bk.	Back	EF	Each Face	IB	Inbound		Vertical Curve
Bal.	Balance	EFH	Each Face Horizontal	In.	Inch	PT	Point of Tangency
B	Baseline	EFV	Each Face Vertical	ID	Inside Diameter	Pt., Pts.	Point, Points
Bm.	Beam	EW	Each Way	IF	Inside Face	PRC	Point of Reverse Curvature
Brg., Brgs.	Bearing, Bearings	EPE	Existing Edge of Pavement	Int.	Interior	PVC	Polyvinyl Chloride
BVC	Beginning of Vertical Curve	EPS	Expanded Polystyrene	Inv.	Invert	Prestr.	Prestressed
Bet.	Between	ES	Edge of Shoulder			P/S	Prestressed Strands
BF	Both Faces	Elec.	Electrical	Jt.	Joint	PB	Pull Box
BW	Both Ways	EMH	Electrical Manhole				
BFE	Bottom of Footing Elevation	EI., Elev.	Elevation	K	Kips	Rad., R	Radius
Bot., Bott., B	Bottom	Emb.	Embankment	KF	Kip Foot	RF	Rear Face
BOF	Bottom of Footing	EVC	End of Vertical Curve	KSF	Kips Per Square Foot	Rebar	Reinforcing Bar
Br.	Bridge	Eq.	Equal	KSI	Kips Per Square Inch	Ref.	Reference
Blt.	Bolt	Est.	Estimated	KLF	Kips Per Linear Foot	Reinf.	Reinforced, Reinforcing,
		Exc.	Excavation				Reinforcement
Cant.	Cantilever	Excl.	Excluding	L	Length	Req'd.	Required
CIP	Cast Iron Pipe	Exist., Ex.	Existing	lb., lbs., LBS.	Pound, Pounds	Ret.	Retaining
	Cast-In-Place	Exp., (E)	Expansion	Ltg. Std.	Lighting Standard	ROW	Right of Way
☉	Center line	EJ	Expansion Joint	LF, Lin. Ft.	Linear Feet/Foot	Rdwy.	Roadway
CG	Center of Gravity	Ext.	Exterior	LS	Lump Sum		
cc	Center to Center			Longit.	Longitudinal	Sect.	Section
CFCW	Continuous Flashing Compound	(F)	Fixed			SRW	Segmental Retaining Wall
	Waterproofing	FA	Force account	M	Modified	Sht.	Sheet
Cl.	Class	FB	Flat Bar	MH	Manhole	Sim.	Similar
Clr.	Clearance	FC	Compression Stresses	Max.	Maximum	Sl.	Slope
CO	Clean Out	f'c	Specified Compressive Strength	Mech.	Mechanical	S	South
Col.	Column		of Concrete at 28 days	Min.	Minimum	Spc., Spg.	Spaces, Spacing
Conc.	Concrete	f'ci	Specified Compressive Strength	Misc.	Miscellaneous	Sprd.	Spread
CBW	Concrete Barrier Wall		of Concrete at Time of Initial	MPH	Miles Per Hour	Spec.	Specification
CMU	Concrete Masonry Unit		Prestress			SF	Square Feet
CRM	Concrete Rubble Masonry	FF	Far Face, Front Face	NF	Near Face	SY	Square Yard
Conn.	Connection	Fig.	Figure	N	North	SS	Stainless Steel
Const.	Construction	Fin. Gr.	Finish Grade	NIC	Not in Contract	Std.	Standard
CJ	Construction Joint	FRP	Fiberglass Reinforced Plastic	No.	Number	Sta.	Station
Cntl. Jt.	Control Joint	FT	Tensile Stresses	NTS	Not to Scale	Stiff.	Stiffener
CLSM	Controlled Low Strength	Ftg.	Footing			Stirr.	Stirrup
	Material	Ft.	Feet, Foot	O/S	Offset	Stl.	Steel
Cont.	Continuous			oc	On Center	Str.	Straight
CSL	Crosshole Sonic Log	Ga.	Gage, Gauge	Opn'g	Opening		
CF	Cubic Feet	Galv.	Galvanized	OB	Outbound		
CY, Cu. Yd.	Cubic Yard	G, Gir.	Girder	OD	Outside Diameter		

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	42	109

Struct.	Structure
SE	Super Elevation
Symm.	Symmetrical
Tan.	Tangent
TC	Continuity Tendons
Temp.	Temporary
TD	Deck Tendon
Thk.	Thick
T	Top
T⊕B	Top and Bottom
TCE	Top of Column
	(and Bent Cap Soffit) Elevation
TOD	Top of Deck
TOP	Top of Pier
TFE	Top of Footing Elevation
Tot.	Total
Transv.	Transverse
TS	Structural Tubing
TSS	Tendon For Girder in Simply
	Supported Condition
Typ.	Typical
Undergrd.	Underground
UHPC	Ultra High Performance Concrete
Var.	Varies
Vert., V	Vertical
VC	Vertical Curve
VESLMC	Very Early Strength Latex
	Modified Concrete
W/C	Water/Cement
w/	With
W	West
WWF	Welded Wire Fabric
WW	Wingwall
WP	Work Point, Working Point
WS	Water Surface
XJS	Expansion Joint System
Yr.	Year

THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.
Calvin T. Miyakura
4-30-22
SIGNATURE EXPIRATION DATE OF THE LICENSE



STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION



SYMBOLS AND ABBREVIATIONS

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: None Date: Apr. 2021



SHEET No. **50.4** OF **4** SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	43	109



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.
Calvin Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	ADD. 44	109



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

DEMOLITION PLAN AND ELEVATION

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: As Noted Date: Apr. 2021


SHEET No. S21 OF 13 SHEETS

8/27/21	2	ADD. 4 - Revised Demolition
DATE		REVISION

ORIGINAL PLAN	DATE
DRAWN BY	
DESIGNED BY	
QUANTITIES BY	
CHECKED BY	
No.	

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOIT\01 CAD\08-27-21\ADD4 DEMO PLAN-ELEV ADD4.DWG PLOT TIME: 08-27-21, 11:05 AM

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	ADD. 45	109



ORIGINAL PLAN	DATE
DRAWN BY	
DESIGNED BY	
NOTED BY	
CHECKED BY	
NO.	

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-001\01 CAD\08-27-21\ADD4 DEMO P1-P7 ADD4.DWG PLOT TIME: 08-27-21 11:05 AM

8/27/21	2	ADD. 4 - Revised Demolition
DATE		

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara

SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

DEMOLITION AT PIER NO. 1 (LIHUE SIDE)

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: As Noted Date: Apr. 2021

SHEET No. S2.2 OF 13 SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	ADD. 46	109

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOO\01 CAD\08-27-21\ADD4 DELTA\WBS-50202 DEMO P1-P7 ADD4.DWG PLOT TIME: 08-27-21 11:05 AM



ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	
No.		

Existing 3-1" Square Dowels to be Partially Removed, See Sheet S2.5, Typ.

Existing 2'-0x2'-0"x3'-0" Rocker Bearings to be Removed, Typ.

Existing 8"x2'-0"x3/4" Lead Plate, T&B to be Removed, Typ.

2 Portion of Existing Pier Above El. (-)4.0 to be Removed



NOTE:
Existing steel frame bearings not shown for clarity. See sheets S2.9 to S2.13 for demolition details.

SECTION A
Scale: 3/8" = 1'-0" S2.3 | S2.3



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.
Calvin Miyajima
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22



STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
DEMOLITION AT PIER NO. 1 (KAPAA SIDE)
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)
Scale: As Noted Date: Apr. 2021
SHEET No. S2.3 OF 13 SHEETS

ELEVATION - PIER NO. 1 (KAPAA SIDE)
Scale: 3/8" = 1'-0"

8/27/21	2 Add. 4 - Revised Demolition
DATE	

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	ADD. 47	109

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOIT\01 CAD\08-27-21\404 DELTA\WBS-50202 DEMO P1-P7 ADD4.DWG PLOT TIME: 08-27-21 11:05 AM



SECTION A
Scale: 3/8" = 1'-0"

LEGEND:
 Extent of Demolition



ELEVATION - PIER NO. 2
(PIER NOS. 3, 5 AND 6 SIMILAR)
Scale: 3/8" = 1'-0"

8/27/21	2	ADD. 4 - Revised Demolition
DATE		

CALVIN T. MIYAKAWA
LICENSED PROFESSIONAL ENGINEER
NO. 8133-S
HAWAII, U.S.A.
THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.
Signature: Calvin Miyakawa
EXPIRATION DATE OF THE LICENSE: 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
DEMOLITION AT PIER NO. 2
(PIER NOS. 3, 5, & 6 SIM.)
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)
Scale: As Noted Date: Apr. 2021
SHEET No. S2.4 OF 13 SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	ADD. 48	109



DEMOLITION DETAIL

AT GIRDER

Scale: 3/4" = 1'-0"

1
S2.5 S2.5


DEMOLITION DETAIL

AT INTERIOR GIRDER

Scale: 3/4" = 1'-0"

3
S2.5 S2.5

Note:
See S2.5/S8.1
for girder repair detail.



DEMOLITION DETAIL

AT END BEAM

Scale: 3/4" = 1'-0"

2
S2.5 S2.5

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

DEMOLITION AT PIER NO. 4

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: As Noted
Date: Apr. 2021



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Calvin Miyajima
4-30-22

SIGNATURE
REVISION
EXPIRATION DATE OF THE LICENSE

ORIGINAL PLAN	DATE
DRAWN BY	
DESIGNED BY	
NOTED BY	
CHECKED BY	
NO.	



DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOO\01 CAD\08-27-21\ADD4.DWG PLOT TIME: 08-27-21 11:06 AM

ELEVATION - PIER NO. 4

Scale: 3/8" = 1'-0"

8/27/21	2	Add. 4 - Revised Demolition
DATE		

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	ADD. 49	109




NOTE:

Existing steel frame bearings not shown for clarity. See sheet S2.12 for demolition details.

LEGEND:

Extent of Demolition



8/27/21	2	ADD. 4 - Revised Demolition
DATE		

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.
Calvin Miyajima
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION



DEMOLITION AT PIER NO. 7 (LIHUE SIDE)

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: As Noted Date: Apr. 2021

SHEET No. S2.6 OF 13 SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	ADD. 50	109



NOTE:

Existing steel frame bearings not shown for clarity. See sheet S2.12 for demolition details.

LEGEND:

Extent of Demolition

SECTION

Scale: 3/8" = 1'-0"

ELEVATION - PIER NO. 7 (KAPAA SIDE)
Scale: 3/8" = 1'-0"

8/27/21		ADD. 4 - Revised Demolition
DATE		

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.
Calvin Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

DEMOLITION AT PIER NO. 7 (KAPAA SIDE)

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)





Scale: As Noted Date: Apr. 2021

SHEET No. S2.7 OF 13 SHEETS

ORIGINAL PLAN	DATE
DESIGNED BY	
TRACED BY	
NOTED BY	
CHECKED BY	
NO.	

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DO\01 CAD\08-27-21\ADD4.DWG PLOT TIME: 08-27-21 11:06 AM

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	51	109



ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
No.	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50202 DEMO P1-P7.DWG PLOT TIME: 04-05-21, 3:38 PM

CALVIN T. MIYAKURA
LICENSED PROFESSIONAL ENGINEER
NO. 8133-S
HAWAII, U.S.A.

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Calvin Miyakura
4-30-21
SIGNATURE EXPIRATION DATE OF THE LICENSE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION


DEMOLITION DETAILS

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: As Noted
Date: Apr. 2021

SHEET No. **S28** OF **13** SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	52	109



PIER NO. 1 PLAN
Scale: 1/2" = 1'-0"
A
S2.9 | S2.9

- NOTES:**
1. Remove all structural steel including added plates, bolts, nuts, bearing pads, and concrete pedestals.
 2. For additional steel details see sheets S2.10 and S2.11.
 3. For concrete demolition details see sheets S2.2 and S2.3.

LEGEND:

 Steel to be Removed




THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.
Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
STEEL DEMOLITION PLAN
AT PIER NO. 1
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)
Scale: As Noted Date: Apr. 2021
SHEET No. **S29** OF **13** SHEETS

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
No. _____	DESIGNED BY	" "
	QUANTITIES BY	" "
	CHECKED BY	" "

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50209 DEMO P1 STDWG PLOT TIME: 04-05-21 3:38 PM

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	53	109




ELEVATION - PIER NO. 1 (LIHUE SIDE) A
 Scale: 1/2" = 1'-0" S2.9 | S2.10

NOTES:

1. Remove all structural steel including added plates, bolts, nuts, bearing pads, and concrete pedestals.
2. For additional steel details see sheet S2.11.
3. For concrete demolition details see sheets S2.2 and S2.3.

LEGEND:

- Extent of Concrete Demolition See shts. S2.2 and S2.3
- Steel to be Removed



ELEVATION - PIER NO. 1 (KAPAA SIDE) B
 Scale: 1/2" = 1'-0" S2.9 | S2.10



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.



Calvin T. Miyahara
 SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
 DEPARTMENT OF TRANSPORTATION
 HIGHWAYS DIVISION
STEEL DEMOLITION ELEVATIONS
AT PIER NO. 1
KUHIO HIGHWAY
 Repairs to Wailua River Bridge
 Fed. Aid Project No. ER-23(001)

Scale: As Noted Date: Apr. 2021

SHEET No. **S2.10** OF **13** SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	54	109



- NOTES:**
1. Remove all structural steel including plates, bolts, nuts, and bearing pads.
 2. For concrete demolition details see sheets S2.2 and S2.3.

- LEGEND:**
- Extent of Concrete Demolition See shts. S2.2 and S2.3
 - Steel to be Removed

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
No.	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID WBS-50209 DEMO P1 STD.DWG PLOT TIME: 04-05-21, 3:38 PM

CALVIN T. MIYAHARA

LICENSED PROFESSIONAL ENGINEER

NO. 8133-S

HAWAII, U.S.A.

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Signature

4-30-22

SIGNATURE EXPIRATION DATE OF THE LICENSE

STATE OF HAWAII

DEPARTMENT OF TRANSPORTATION

HIGHWAYS DIVISION

STEEL DEMOLITION SECTIONS

AT PIER NO. 1

KUHIO HIGHWAY

Repairs to Wailua River Bridge





Fed. Aid Project No. ER-23(001)

Scale: As Noted

Date: Apr. 2021

SHEET No. S2.11 OF 13 SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	55	109



**TYPICAL SECTION - PIER NO. 7
(AT GIRDERS)**
Scale: 3/8" = 1'-0"

- NOTES:**
1. Remove all structural steel including plates, bolts, nuts, and bearing pads.
 2. For concrete demolition details see sheets S2.6 and S2.7.

- LEGEND:**
- Extent of Concrete Demolition
See shts. S2.6 and S2.7
 - Steel to be Removed



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.
Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

STEEL DEMOLITION AT PIER NO. 7

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: As Noted Date: Apr. 2021

SHEET No. **S2.12** OF **13** SHEETS

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
No.	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID WBS-50212 DEMO P7 STL DEMO.DWG PLOT TIME: 04-05-21 3:40 PM


FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	56	109

NOTES:

1. Verify location of all utilities.
2. Highway signage may be removed to accomodate demolition but must be returned to its original condition at completion.


LEGEND:

 Extent of Demolition



ELEVATION (KAPAA MAUKA)

Scale: 3/4" = 1'-0"



SECTION

Scale: 3/4" = 1'-0"

A
S2J3 S2J3



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22


STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
**END POST DEMOLITION,
ELEVATION AND SECTION**
KUHIO HIGHWAY

Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: As Noted Date: Apr. 2021

SHEET No. S2J3 OF 13 SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	57	109



Note:

The Contractor shall investigate site conditions at the shaft locations before installing the shafts. Notify the Engineer immediately of any obstructions that may interfere with the installation of the shafts.

**ELEVATION - PIER NO. 1 (LIHUE SIDE)
(PIER NO. 7 (KAPAA SIDE) SIMILAR)**

Scale: 3/8" = 1'-0"



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.


Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
ELEVATION AT PIER NO. 1 (LIHUE SIDE)
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: As Noted Date: Apr. 2021

SHEET No. S31 OF 9 SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	59	109



SECTION AT PIER NO. 1
(PIER NO. 7 SIMILAR)
Scale: 3/8" = 1'-0"

S3.2

A
S3.1 S3.3



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE: 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

SECTION AT PIER NO. 1

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)


Scale: As Noted Date: Apr. 2021

SHEET No. **S3.3** OF **9** SHEETS

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
No. _____	DESIGNED BY	" "
	QUANTITIES BY	" "
	CHECKED BY	" "

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50301 ELEV-SECT P1&2.DWG PLOT TIME: 04-05-21 3:41 PM

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	60	109



SECTION
 Scale: 3/4" = 1'-0"
 S3.1 S3.4
 S3.2



THIS WORK WAS PREPARED BY
 ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
 SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

SECTION
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: As Noted
Date: Apr. 2021

SHEET No. **S3.4** OF **9** SHEETS


ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	"
No.	DESIGNED BY	"
	QUANTITIES BY	"
	CHECKED BY	"

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50301 ELEV-SECT P1&2.DWG PLOT TIME: 04-05-21 3:42 PM

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	61	109

Lihue
(Span 1)

Kapaa
(Span 2)




SECTION

A

Scale: 3/4" = 1'-0"

S3.2 S3.5



ENLARGED SECTION

B

Scale: 3/4" = 1'-0"

S3.5 S3.5

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
No.	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50301 ELEV-SECT P1&2.DWG PLOT TIME: 04-05-21 3:42 PM



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Signature: *Calvin T. Miyahara*
 EXPIRATION DATE OF THE LICENSE: 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

SECTIONS

KUHIO HIGHWAY


Repairs to Wailua River Bridge

Fed. Aid Project No. ER-23(001)


Scale: As Noted Date: Apr. 2021

SHEET No. S3.5 OF 9 SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	62	109



SECTION - SPANS 1 AND 8
Scale: 1/2" = 1'-0"



SECTION - SPANS 2 AND 7
Scale: 1/2" = 1'-0"




THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.


Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
**REINFORCING AT SPANS 1 & 8
AND SPANS 2 & 7**
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)
Scale: As Noted Date: Apr. 2021
SHEET No. **536** OF **9** SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	63	109



PLAN AT END BEAM
(SPANS 1-2 AND 8-7)
Scale: 3/4" = 1'-0"



PLAN (SPANS 1-2 AND 8-7)
Scale: 3/4" = 1'-0"

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
No. _____	DESIGNED BY	" "
	QUANTITIES BY	" "
	CHECKED BY	" "

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50301 ELEV-SECT P1&2.DWG PLOT TIME: 04-05-21 3:42 PM

CALVIN T. MIYAHARA
LICENSED PROFESSIONAL ENGINEER
NO. 8133-S
HAWAII, U.S.A.

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Calvin Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22


STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

REINFORCING PLANS
AT SPANS 1-2 AND 8-7
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: As Noted
Date: Apr. 2021


SHEET No. **S3.7** OF **9** SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	64	109




CONC. SEAT DETAIL AT SPAN 1
(SPAN 8 SIM.)

Scale: 3/4" = 1'-0"



CONC. SEAT DETAIL AT SPAN 2
(SPAN 7 SIM.)

Scale: 3/4" = 1'-0"



Note:

- Concrete seat shall not exceed 6" in height unless approved by the Engineer.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
No. _____	DESIGNED BY	" "
	QUANTITIES BY	" "
	CHECKED BY	" "

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50301 ELEV-SECT P1&2.DWG PLOT TIME: 04-05-21 3:43 PM



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

CONCRETE SEAT AT PIER NO. 1

KUHIO HIGHWAY


Repairs to Wailua River Bridge

Fed. Aid Project No. ER-23(001)



Scale: As Noted

Date: Apr. 2021

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	65	109



CONC. SEAT SECTION
(PIER NO. 7 SIMILAR)
Scale: 1" = 1'-0"



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION


CONCRETE SEAT AT PIER NO. 1

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)


Scale: As Noted Date: Apr. 2021

SHEET No. **S39** OF **9** SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	67	109



SECTION PIER NO. 2
(PIER NOS. 3 TO 6 SIM.)
Scale: 3/8" = 1'-0"



SECTION PIER NO. 2
(PIER NOS. 3 TO 6 SIM.)
Scale: 3/8" = 1'-0"

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
No.	DESIGNED BY	" "
	QUANTITIES BY	" "
	CHECKED BY	" "

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50401 ELEV-SECT P2.3.5.6.DWG PLOT TIME: 04-05-21 3:44 PM



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22


STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

SECTIONS AT PIER NO. 2
(PIER NOS. 3 TO 6 SIM.)
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)


Scale: As Noted
Date: Apr. 2021

SHEET No. **S4.2** OF **4** SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	68	109



SECTION
(PIER NOS. 3, 5, & 6 SIM.) A
Scale: 3/8" = 1'-0"



SECTION
(PIER NOS. 3, 5, & 6 SIM.) B
Scale: 3/8" = 1'-0"



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

SECTIONS AT PIER NO. 2
(PIER NOS. 3, 5 & 6 SIMILAR)
KUHIU HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)


Scale: As Noted
Date: Apr. 2021

SHEET No. **S4.3** OF **4** SHEETS


ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
No.	DESIGNED BY	" "
	QUANTITIES BY	" "
	CHECKED BY	" "

DRAWING NAME: Z:\00_OHGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID WBS-50401 ELEV-SECT P2.3.5.DWG PLOT TIME: 04-05-21 3:44 PM

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	69	109



CONC. SEAT SECTION
(PIER NOS. 3, 5, & 6 SIM.)
Scale: 1" = 1'-0"
A
S4.1 | S4.4



CONC. SEAT SECTION
(PIER NOS. 3, 5, & 6 SIM.)
Scale: 1" = 1'-0"
B
S4.1 | S4.4

- Note:
- Concrete seat shall not exceed 6" in height unless approved by the Engineer.

THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.
Calvin T. Miyahara
SIGNATURE
EXPIRATION DATE OF THE LICENSE
4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

CONC. SEAT AT PIER NO. 2
(PIER NOS. 3, 5 & 6 SIMILAR)
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)


Scale: As Noted Date: Apr. 2021

SHEET No. **S4.4** OF **4** SHEETS


ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
No. _____	DESIGNED BY	" "
	QUANTITIES BY	" "
	CHECKED BY	" "

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50401 ELEV-SECT P2,3,5,6.DWG PLOT TIME: 04-05-21 3:44 PM)

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	71	109



SECTION A
Scale: 3/8" = 1'-0"
S5.1 S5.2



SECTION B
Scale: 1/2" = 1'-0"
S5.1 S5.2



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

SECTIONS

KUHIO HIGHWAY

Repairs to Wailua River Bridge

Fed. Aid Project No. ER-23(001)


Scale: As Noted
Date: Apr. 2021

SHEET No. **S5.2** OF **4** SHEETS

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
No.	DESIGNED BY	" "
	QUANTITIES BY	" "
	CHECKED BY	" "

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\BBS-50501 ELEV-SECT P4.DWG PLOT TIME: 04-05-21 3:45 PM

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	72	109



SECTION A
Scale: 1/2" = 1'-0" S5.3 S5.3

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
No. _____	DESIGNED BY	" "
	QUANTITIES BY	" "
	CHECKED BY	" "

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50501 ELEV-SECT P4.DWG PLOT TIME: 04-05-21 3:45 PM



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

SECTION


KUHIO HIGHWAY

Repairs to Wailua River Bridge


Fed. Aid Project No. ER-23(001)

Scale: As Noted
Date: Apr. 2021

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	73	109



CONC. SEAT DETAIL A
 Scale: 1" = 1'-0" S5.1 S5.4



CONC. SEAT DETAIL B
 Scale: 1" = 1'-0" S5.4 S5.4

- Note:**
- Concrete seat shall not exceed 6" in height unless approved by the Engineer.



THIS WORK WAS PREPARED BY
 ME OR UNDER MY SUPERVISION.
Calvin T. Miyahara
 SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

CONCRETE SEAT AT PIER NO. 4

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: As Noted Date: Apr. 2021

SHEET No. **S5.4** OF **4** SHEETS


ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
No.	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50501 ELEV-SECT P4.DWG PLOT TIME: 04-05-21 3:45 PM


FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	74	109

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-20-21 BID R\SD\WBS-S0601 S0602 CREEP BLK P1-7.DWG PLOT TIME: 04-15-21, 1:58 PM)

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	"
No.	DESIGNED BY	"
	QUANTITIES BY	"
	CHECKED BY	"



CREEP BLOCK
PLAN AT PIER NO. 1
Scale: 3/4" = 1'-0"



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.
Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

CREEP BLOCK PLAN AT PIER NO. 1
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)


Scale: As Noted Date: Apr. 2021

SHEET No. **S6J** OF **4** SHEETS


FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	75	109

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50601 S0602 CREEP BLK P1-7.DWG PLOT TIME: 04-05-21 3:46 PM

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	"
No.	DESIGNED BY	"
	QUANTITIES BY	"
	CHECKED BY	"



CREEP BLOCK SECTION A
Scale: 1" = 1'-0"



CREEP BLOCK SECTION B
Scale: 1" = 1'-0"



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION


CREEP BLOCK SECTIONS AT PIER NOS. 1 & 7
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)
Scale: As Noted Date: Apr. 2021

SHEET No. **S62** OF **4** SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	76	109


DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-20-21 BID RVS\DWG-S0601 S0602 CREEP BLK P1-7.DWG PLOT TIME: 04-15-21, 1:58 PM

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
No.	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	




**CREEP BLOCK
PLAN AT PIER NO. 7**
Scale: 3/4" = 1'-0"
S6.3 S6.3

Note:
Contractor to probe area to locate abutment and retaining wall foundations. Inform the Engineer of any conflicts with the drilled shaft and drilled shaft cap.



SECTION B
Scale: 1/2" = 1'-0"
S6.3 S6.3




SECTION C
Scale: 1/2" = 1'-0"
S6.3 S6.3



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.
Calvin T. Miyahara
4-30-22
SIGNATURE EXPIRATION DATE OF THE LICENSE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
CREEP BLOCK PLAN AND SECTIONS AT PIER NO. 7
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)
Scale: As Noted Date: Apr. 2021
SHEET No. **S6.3** OF **4** SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	77	109



CREEP BLOCK
PLAN AT PIER NOS. 2-6
Scale: 3/4" = 1'-0"

A
S6.4 | S6.4

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
No.	DESIGNED BY	" "
	QUANTITIES BY	" "
	CHECKED BY	" "

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50604 S0605 CREEP BLK DET 2-6.DWG PLOT TIME: 04-05-21 3:47 PM



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

CREEP BLOCK PLAN AT PIER NOS. 2-6

KUHIO HIGHWAY


Repairs to Wailua River Bridge

Fed. Aid Project No. ER-23(001)


Scale: As Noted Date: Apr. 2021

SHEET No. S6.4 OF 4 SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	78	109



CREEP BLOCK SECTION A
Scale: 1" = 1'-0"



CREEP BLOCK SECTION B
Scale: 1" = 1'-0"



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

CREEP BLOCK SECTIONS AT PIER NOS. 2-6

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)


Scale: As Noted Date: Apr. 2021

SHEET No. **S6.5** OF **4** SHEETS


ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
No.	DESIGNED BY	" "
	QUANTITIES BY	" "
	CHECKED BY	" "

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID WBS-S0604 S0605 CREEP BLK DET 2-6.DWG PLOT TIME: 04-05-21 3:47 PM


FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	79	109




ELASTOMERIC BEARING PAD, TYPE I 1
Scale: 3" = 1'-0" S7.1 S7.1




ELASTOMERIC BEARING PAD, TYPE IV 4
Scale: 3" = 1'-0" S7.1 S7.1



ELASTOMERIC BEARING PAD, TYPE II 2
Scale: 3" = 1'-0" S7.1 S7.1



ELASTOMERIC BEARING PAD, TYPE V 5
Scale: 3" = 1'-0" S7.1 S7.1



ELASTOMERIC BEARING PAD, TYPE III 3
Scale: 3" = 1'-0" S7.1 S7.1

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	"
No.	DESIGNED BY	"
	QUANTITIES BY	"
	CHECKED BY	"

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 ELAS BRG PADD.DWG PLOT TIME: 04-05-21 3:48 PM




THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
ELASTOMERIC BEARING PAD
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)
Scale: As Noted Date: Apr. 2021

SHEET No. **S7.1** OF **1** SHEETS


FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	80	109



- NOTES:**
- As-built plans call for a 1-inch wide joint. The joint may be wider, verify in field before ordering the expansion joint seal.
 - Joint Seal manufacturer's recommendations shall be followed
 - The cost of the joint seal shall be considered incidental to Section 503 - Concrete Structures.



EXPANSION JOINT DEMOLITION
PIER NOS. 1 AND 7

Not to Scale




TYPICAL EXPANSION JOINT REPAIR
PIER NOS. 1 AND 7

Not to Scale



TYPICAL GIRDER REPAIR DETAIL
Scale: 3/4" = 1'-0"



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

EXPANSION JOINT AND GIRDER REPAIR

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: As Noted Date: Apr. 2021

SHEET No. **S8.J** OF **1** SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	82	109

DRILLED SHAFT SCHEDULE							
Drilled Shaft Mark	Pier No. 1	Pier No. 2	Pier No. 3	Pier No. 4	Pier No. 5	Pier No. 6	Pier No. 7
Drilled Shaft Diameter	6'-0"	6'-0"	6'-0"	6'-0"	6'-0"	6'-0"	6'-0"
Estimated Drilled Shaft Tip Elevation	(-) 75	(-) 135	(-) 130	(-) 125	(-) 125	(-) 125	(-) 105
Length of Shaft "L"	85'-0"	144'-0"	138'-0"	133'-0"	132'-0"	131'-0"	111'-0"
"L1"	50'-0"	70'-0"	70'-0"	70'-0"	70'-0"	70'-0"	70'-0"
Length of Permanent Steel Casing "L3"	60'-0"	60'-0"	60'-0"	60'-0"	60'-0"	60'-0"	60'-0"
Strength I Limit State Compressive Demand (KIPS)	1,400	1,900	1,800	1,800	1,800	1,900	1,400

NOTE:

30-#11 Vertical reinforcing bars terminate at "L1". In addition the spiral reinforcing changes from #7 @ 4" to #7 @ 9" at "L1".

ORIGINAL PLAN NOTE BOOK No. _____	SURVEY PLOTTED BY _____	DATE _____
	DRAWN BY _____	" "
	TRACED BY _____	" "
	DESIGNED BY _____	" "
	QUANTITIES BY _____	" "
	CHECKED BY _____	" "

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50901 PROD DS.DWG PLOT TIME: 04-05-21 3:49 PM



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

DRILLED SHAFT SCHEDULE

KUHIO HIGHWAY

Repairs to Wailua River Bridge

Fed. Aid Project No. ER-23(001)



Scale: As Noted Date: Apr. 2021

SHEET No. 592 OF 3 SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	83	109

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-50803 DS LOAD TESTING PLOT TIME: 04-05-21, 3:49 PM

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	"
No.	DESIGNED BY	"
	QUANTITIES BY	"
	CHECKED BY	"



60-#11 Cont. Vert. Bars, ASTM A706 Equally Spaced

SECTION B S9.3 | S9.3

Scale: 1" = 1'-0"



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Signature: Calvin Miyahara
EXPIRATION DATE OF THE LICENSE: 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

LOAD TEST SHAFT

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)


Scale: As Noted Date: Apr. 2021

SHEET No. S9.3 OF 3 SHEETS


FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	86	109

NOTES:


- A. The work necessary to connect guardrail to the concrete end post shall include all labor, materials, tools, equipment and incidentals necessary to complete the work and will not be paid for separately.
- B. Lap terminal connector and rail elements in the direction of traffic to prevent snagging.
- C. Bolts shall have sufficient length when installed to ensure that the nut is at least flush but should not project more than 1/4". The Contractor will not be allowed to cut, grind or otherwise alter the bolt to meet this requirement unless it is done during the fabrication of the bolt prior to galvanizing.
- D. The first 25'-0" of guardrail adjoining the "Terminal Connector" shall be placed tangent to the concrete transition front face or parallel to the roadway, unless conditions at the site renders it impossible to do so. Flare point to be determined in field.
- E. Head of all bolts shall be placed on the traffic side of the rail.
- F. All W6x8.5, W6x9 and W6x15 guardrail posts shall be clearly stamped during fabrication "W6x8.5", "W6x9", or "W6x15", respectively, on each post.




5/8"-11 UNC, 14" Long Guardrail Bolt




5/8"-11 UNC, 10" Long Guardrail Bolt





5/8"-11 UNC, 2" Long Guardrail Bolt




5/8"-11 UNC, 1 1/4" Long Guardrail Bolt




7/8"-9 UNC Heavy Hex Nut




7/8"-9 UNC, 16" Long Heavy Hex Head Bolt




5/8" Dia. Plain USS Washer




5/8-11 UNC Heavy Hex Nut




ELEVATION
TERMINAL CONNECTOR
Scale: 1" = 1'-0"




SINGLE DOUBLE
SECTION THRU RAIL ELEMENT
Scale: 1 1/2" = 1'-0"



(Use at posts where splices do not occur.)
BACKUP PLATE
Scale: 1" = 1'-0"




RAIL SPLICE
Scale: 1" = 1'-0"



TRANSITION SECTION
Scale: 1" = 1'-0"

ORIGINAL PLAN	DATE
SURVEY PLOTTED BY	
DRAWN BY	
DESIGNED BY	
QUANTITIES BY	
CHECKED BY	
NO.	

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WB5-S1003 GRAL DTLS.DWG PLOT TIME: 04-05-21 3:50 PM


 THIS WORK WAS PREPARED BY
 ME OR UNDER MY SUPERVISION.
 Calvin Miyajima
 SIGNATURE
 EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
 DEPARTMENT OF TRANSPORTATION
 HIGHWAYS DIVISION
**METAL GUARDRAIL TYPE 3 THRIE BEAM
 AND APPURTENANCES DETAILS**
 KUHIO HIGHWAY
 Repairs to Wailua River Bridge
 Fed. Aid Project No. ER-23(001)
 Scale: As Noted Date: Apr. 2021
 SHEET No. **S10.3** OF **4** SHEETS

METAL GUARDRAIL TYPE 3 THRIE BEAM AND APPURTENANCES DETAILS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	88	109

PREPARATION OF SUBSTRATE AND REINFORCING STEEL

FOR SPALL REPAIRS:

1. "Defective Concrete" as noted on the drawings refers to "spalls", "delaminations" and "honeycombing."
2. Extent of defective concrete is approximate and may vary. The Contractor shall sound all concrete in the designated general areas (shown on the plans and identified in the schedule) before proceeding with repair work, so as to identify any additional repair area(s) not explicitly shown on the plans.
3. The defective concrete shall be completely removed to sound substrate and beyond the extent of the existing reinforcing. The Contractor shall take necessary precautions to avoid damaging the underlying sound concrete.
4. The defective concrete shall be squared by saw-cutting and chipping the concrete at the perimeter beyond the removal area a minimum of 1 inch to attain a 3/4 inch maximum depth and to prevent feather edge conditions. Exercise great care to avoid cutting or damaging any existing embedded steel reinforcing. Angles between adjacent saw-cuts around the perimeter shall not be less than 90 degrees and the shape of each patch shall not be irregular.
5. For any embedded reinforcement within the repair area, additional concrete shall be removed to attain a minimum 1 inch clear space measured radially around the bars.
6. Existing concrete surfaces within the repair areas shall be roughened to achieve a Concrete Surface Profile equal to CSP 6-8 in accordance with International Concrete Repair Institute (ICRI) Guideline 310-2 to ensure proper adhesion with repair material.
7. All exposed concrete surfaces and reinforcing bars in the repair area shall be needle gunned to remove all scale, loose rust, debris and deteriorated concrete. Any areas not patched within 48 hours after needle gunning shall be recleaned.
8. Any reinforcement in repair area which has lost more than 25 percent of its cross-sectional area shall be called to the attention of the Engineer. Repair shall be in accordance with typical concrete repair details, see sheet S11.2.
9. Immediately prior to placement of bonding agent and repair material, the repair area shall be cleaned of all dust and debris with high-pressure, oil-free compressed air at a minimum of 100 psi. Patch area shall then be washed with clean water so that exposed concrete surface is saturated, but with no water accumulation on the surface.
10. Repair material manufacturer's representative shall be present for initial repair to ensure proper preparation and application techniques are being utilized.
11. For Bidding purposes, Contractor shall assume an average spall depth of 4".

APPLICATION OF SPALL REPAIR MATERIALS:

1. All exposed steel shall be liberally coated with two 20 mil coats of bonding agent. The coating shall be complete with no skips, pin holes or holidays around the entire surface of the exposed steel. The first coat shall be allowed to dry 3 hours prior to application of the second coat. The second coat shall also be allowed to dry a minimum of 30 minutes prior to the placement of the repair material. Care shall be taken to avoid applying the coating material to the concrete substrate. Repair material shall be placed within the open time of coating application.
2. The Contractor shall not secure forms by powder actuated fastenings. All holes and spalls caused by temporary attachments shall be patched. All inserts shall be removed or shall be stainless steel with minimum 3/4 inch cover after form removal.
3. Repair material shall be applied in thicknesses per manufacturer's recommendations. When thicknesses exceed maximum for neat material, it shall be extended with aggregate as recommended by manufacturer.
4. Snap ties and Inserts shall be plastic or stainless steel.
5. All concrete repairs shall be made smooth and level with the existing concrete surface unless a built-up section is required to maintain 1 inch minimum concrete cover.
6. The repair material shall be vibrated, rodded, or tamped during placement to consolidate the pour and fill all corners of the patch or form with no voids.
7. There shall be no cold joints in the field of the repair.
8. The repaired surface finish profile shall match the original surface finish profile.
9. Apply a curing compound as recommended by the manufacturer. Remove curing from any surface where bonding is needed after curing is complete.
10. Repair areas shall be allowed to cure 4 hours minimum with no vehicular traffic applied directly above or within 6 feet horizontally of the repair area. The Contrator shall schedule the work accordingly to allow repairs to attain min. concrete compressive strength of 3,000 psi prior to reopening to traffic.
11. See Specifications Section 680 for Repair Material.
12. Submit 6 copies of repair material manufacturer's material data and work recommendations.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
No.	DESIGNED BY	" "
	QUANTITIES BY	" "
	CHECKED BY	" "

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-S1101 SPALL NOTES.DWG PLOT TIME: 04-05-21 3:51 PM



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22


STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION	
CONCRETE REPAIR NOTES	
<u>KUHIO HIGHWAY</u>	
<u>Repairs to Wailua River Bridge</u>	
<u>Fed. Aid Project No. ER-23(001)</u>	
Scale: None	Date: Apr. 2021
SHEET No. S11J OF 14 SHEETS	

REPLACEMENT SCHEDULE			
SIZE OF EXISTING REINFORCING		SIZE OF NEW REPLACEMENT REINFORCING	MIN. LENGTH OF WELD EACH SIDE (lw)
SQUARE	ROUND		
3/8"	#3	#4	2"
	#4	#4	2"
1/2"	#5	#5	2 1/2"
5/8"	#6	#6	3 1/2"
3/4"	#7	#7	4"
7/8" OR 1"	#8	#8	5"


NOTES:

- Replacement reinforcing shall be spliced to existing reinforcing on the opposite face of the concrete repair so as not to reduce the existing clear cover.
- For welding of #3, #4, and #5 replacement reinforcing, welding may be performed on one side only, if lw is increased to lw1 as shown below.
- For bidding purposes, contractor shall assume 1 Lb. of rebar required per square foot of defective concrete repair.

SIZE OF REPLACEMENT REINFORCING OR DOWEL	MINIMUM LENGTH OF WELD ONE SIDE lw1
#3	4"
#4	4"
#5	5"



REBAR REPLACEMENT ELEVATION



tw = Weld Thickness
db = Bar Diameter
lw = Length of Weld Each Side
lw2 = Length of Weld One Side
(See Steel Replacement Schedule)

SECTION A

SPLICE FOR #8 BARS AND SMALLER



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

SIGNATURE: Calvin Miyahara
EXPIRATION DATE OF THE LICENSE: 4-30-22

STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION	
CONCRETE REPAIR NOTES	
KUHIO HIGHWAY	
Repairs to Wailua River Bridge	
Fed. Aid Project No. ER-23(001)	
Scale: None	Date: Apr. 2021
SHEET No. 511.2 OF 14 SHEETS	


ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
No.	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-51101 SPALL NOTES.DWG PLOT TIME: 04-05-21 3:51 PM

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	90	109

To Lihue

To Kapaa



Legend:

S## Soffit Defect No.

Note:

For soffit spall sizes, see sheets S11.4 to S11.6.

ORIGINAL PLAN

NOTE BOOK

No. _____

SURVEY PLOTTED BY _____

DRAWN BY _____

DESIGNED BY _____

CHECKED BY _____

DATE _____

DATE _____

DATE _____

DATE _____

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WB5-S1103 SOFFIT.DWG

PLOT TIME: 04-05-21, 3:51 PM

CALVIN T. MIYAMURA

LICENSED PROFESSIONAL ENGINEER

NO. 8133-S

HAWAII, U.S.A.

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Signature

4-30-22

SIGNATURE EXPIRATION DATE OF THE LICENSE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

DECK SLAB SOFFIT SPALLS

KUHIO HIGHWAY

Repairs to Wailua River Bridge

Fed. Aid Project No. ER-23(001)

Scale: As Noted Date: Apr. 2021

SHEET No. **S11.3** OF **14** SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	91	109

DECK SOFFIT SPALLS AND DELAMINATIONS									
DEFECT NO.	REPAIR TYPE	LENGTH	WIDTH	TOTAL (sf)	LENGTH	SIDE WIDTH	TOTAL (sf)	TOTAL (sf)	REMARKS
S1	SC	6	1.5	9	6	1	6	15	
S2	SC	5.5	1.5	8.25	5.5	1	5.5	13.75	
S3	SC	4	1.5	6	4	1	4	10	
S4	SC	3	1	3	3	0.5	1.5	4.5	
S5	S	5	1.5	7.5	-	-	-	7.5	
S6	S	15	4	60	-	-	-	60	
S7	SC	2	2	4	2	0.5	1	5	
S8	SC	10.5	1.5	15.75	10.5	1	10.5	26.25	Exposed Rebar
S9	S	8	2.5	20	-	-	-	20	
S10	S	2	2	4	-	-	-	4	Exposed Rebar
S11	S	3	2	6	-	-	-	6	
S12	SC	3.5	2	7	3.5	0.5	1.75	8.75	
S13	S	8.5	1.5	12.75	-	-	-	12.75	Exposed Rebar
S14	SC	12	1.5	18	3.5	1	3.5	21.5	Exposed Rebar
S15	S	1	1	1	-	-	-	1	
S16	S	2	2	4	-	-	-	4	
S17	SC	3	1.5	4.5	3	0.5	1.5	6	
S18	S	0.5	0.5	0.25	-	-	-	0.25	Exposed Rebar
S19	S	12	5	60	-	-	-	60	Exposed Rebar
S20	S	19	4	76	-	-	-	76	
S21	S	0.5	0.5	0.25	-	-	-	0.25	Exposed Rebar
S22	S	1	1	1	-	-	-	1	Exposed Rebar
S23	S	5	2	10	-	-	-	10	
S24	S	3	3	9	-	-	-	9	
S25	S	5	3	15	-	-	-	15	
S26	S	3	1	3	-	-	-	3	
S27	S	4	1	4	-	-	-	4	Exposed Rebar
S28	S	1	1	1	-	-	-	1	
S29	S	6	1	6	-	-	-	6	Exposed Rebar
S30	S	5	1	5	-	-	-	5	Exposed Rebar
S31	S	1	1	1	-	-	-	1	
S32	S	2	1	2	-	-	-	2	Exposed Rebar
S33	S	4	1	4	-	-	-	4	
S34	S	1	1	1	-	-	-	1	

Note: All dimensions in units of feet.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
No.	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	

DRAWING NAME: Z:\00_OHGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-S1104-S TABLE.DWG PLOT TIME: 04-05-21 3:52 PM)



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

DECK SLAB SOFFIT SPALLS TABLE

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: None Date: Apr. 2021

SHEET No. 511.4 OF 14 SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	92	109

DECK SOFFIT SPALLS AND DELAMINATIONS									
DEFECT NO.	REPAIR TYPE	LENGTH	WIDTH	TOTAL (sf)	LENGTH	SIDE WIDTH	TOTAL (sf)	TOTAL (sf)	REMARKS
S35	S	2	1	2	-	-	-	2	Exposed Rebar
S36	S	14	5	70	-	-	-	70	
S37	S	1	1	1	-	-	-	1	
S38	S	10	4	40	-	-	-	40	
S39	S	3	2	6	-	-	-	6	
S40	S	3	1	3	-	-	-	3	Exposed Rebar
S41	S	6.5	1.5	9.75	-	-	-	9.75	Exposed Rebar
S42	S	2	1	2	-	-	-	2	
S43	S	3	1	3	-	-	-	3	
S44	S	3	1.5	4.5	-	-	-	4.5	
S45	S	0.5	1	0.5	-	-	-	0.5	
S46	S	1	0.5	0.5	-	-	-	0.5	
S47	S	3	2	6	-	-	-	6	
S48	S	11	4	44	-	-	-	44	Exposed Rebar
S49	S	3	1	3	-	-	-	3	
S50	S	2	2	4	-	-	-	4	
S51	S	1	1	1	-	-	-	1	
S52	S	1	1	1	-	-	-	1	Exposed Rebar
S53	S	1	1	1	-	-	-	1	
S54	S	1	1	1	-	-	-	1	Exposed Rebar
S55	S	1	1	1	-	-	-	1	Exposed Rebar
S56	S	1	1	1	-	-	-	1	Exposed Rebar
S57	S	2	1.5	3	-	-	-	3	
S58	S	0.5	0.5	0.25	-	-	-	0.25	Exposed Rebar
S59	S	2	2	4	-	-	-	4	
S60	S	1.5	1	1.5	-	-	-	1.5	
S61	S	6	3	18	-	-	-	18	
S62	S	0.5	0.5	0.25	-	-	-	0.25	Exposed Rebar
S63	S	3	3	9	-	-	-	9	
S64	S	6.5	1	6.5	-	-	-	6.5	
S65	S	1	1	1	-	-	-	1	Exposed Rebar
S66	S	1	0.5	0.5	-	-	-	0.5	
S67	S	2	1	2	-	-	-	2	
S68	S	3.5	1	3.5	-	-	-	3.5	

Note: All dimensions in units of feet.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
No.	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-S1104-S TABLE.DWG PLOT TIME: 04-05-21 3:52 PM



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION
DECK SLAB SOFFIT SPALLS TABLE
<u>KUHIO HIGHWAY</u> <u>Repairs to Wailua River Bridge</u> <u>Fed. Aid Project No. ER-23(001)</u>
Scale: None Date: Apr. 2021
SHEET No. S11.5 OF 14 SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	93	109

DECK SOFFIT SPALLS AND DELAMINATIONS									
DEFECT NO.	REPAIR TYPE	LENGTH	WIDTH	TOTAL (sf)	LENGTH	SIDE WIDTH	TOTAL (sf)	TOTAL (sf)	REMARKS
S69	S	6	5	30	-	-	-	30	Exposed Rebar
S70	S	4	2.5	10	-	-	-	10	
S71	S	3	2	6	-	-	-	6	
S72	S	2	1	2	-	-	-	2	
S73	S	0.5	0.5	0.25	-	-	-	0.25	
S74	S	2	1	2	-	-	-	2	
S75	S	4	2	8	-	-	-	8	
S76	S	2	1	2	-	-	-	2	Exposed Rebar
S77	S	2.5	1.5	3.75	-	-	-	3.75	
S78	S	1	1	1	-	-	-	1	
S79	S	2	2	4	-	-	-	4	
S80	S	2	1	2	-	-	-	2	
S81	S	2.5	1	2.5	-	-	-	2.5	
S82	S	1.5	1.5	2.25	-	-	-	2.25	
S83	S	1	1	1	-	-	-	1	
S84	S	1.5	1.5	2.25	-	-	-	2.25	
S85	S	4	1.5	6	-	-	-	6	
S86	S	3	3	9	-	-	-	9	
S87	S	1	1	1	-	-	-	1	
TOTAL (sf)				739			35.25	774.25	

NOTES:

- All dimensions in units of feet.
- Additional spalls and delaminations may be discovered. In addition spalls may be larger than anticipated. These areas shall be repaired and will be paid for under Pay Item 680.0500 Additional Spall Repair.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
	DRAWN BY	
	TRACED BY	
	DESIGNED BY	
NOTE BOOK	QUANTITIES BY	
	CHECKED BY	
	No.	

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-S1104 S TABLE.DWG PLOT TIME: 04-05-21 3:52 PM)




THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22


STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION	
DECK SLAB SOFFIT SPALLS TABLE	
KUHIIO HIGHWAY	
Repairs to Wailua River Bridge	
Fed. Aid Project No. ER-23(001)	
Scale: None	Date: Apr. 2021
SHEET No. S11.6 OF 14 SHEETS	

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	94	109




Existing Defective Area = $X \times Y$

EXISTING DECK SOFFIT PLAN




EXISTING DECK SECTION




Notes:

1. Detail shall be used only where repairs exceed 6 sq. ft.
2. Dowels may be adjusted up to 2" in any horizontal direction along soffit to avoid damaging existing embedded reinforcing.
3. Dissimilar metals shall not touch and/or shall be separated with a teflon tape.
4. Stainless steel dowels shall be considered incidental to Section 680.1000 - Defective Concrete Repairs - Type "S".

DETAIL
Scale: 3" = 1'-0" 2
S11.7 S11.7



DECK SOFFIT REPAIR PLAN





DECK REPAIR SECTION

CONCRETE REPAIR DETAILS - TYPE "S"
Scale: 1 1/2" = 1'-0" 1
S11.7 S11.7

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
No.	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-S1107 S.DTL.S.DWG PLOT TIME: 04-05-21, 3:53 PM


 THIS WORK WAS PREPARED BY
 ME OR UNDER MY SUPERVISION.

 SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

SOFFIT REPAIR DETAILS

KUHIO HIGHWAY


Repairs to Wailua River Bridge

Fed. Aid Project No. ER-23(001)

Scale: As Noted Date: Apr. 2021


SHEET No. **S11.7** OF **14** SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	95	109




Existing Defective Area = $X \times Y$


SIDE ELEVATION
EXISTING DECK SOFFIT



SIDE ELEVATION
DECK SOFFIT REPAIR




EXISTING DECK SECTION



DECK REPAIR SECTION

CONCRETE REPAIR - TYPE "SE"
Scale: 1 1/2" = 1'-0"



Notes:

1. Detail shall be used only where repairs exceed 6 sq. ft.
2. Dowels may be adjusted up to 2" in any horizontal direction along soffit to avoid damaging existing embedded reinforcing.
3. Dissimilar metals shall not touch and/or shall be separated with a teflon tape.
4. Stainless steel dowels shall be considered incidental to Section 680.2000 - Defective Concrete Repairs - Type "SE" and "SC".

DETAIL
Scale: 3" = 1'-0"



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

SOFFIT REPAIR DETAILS

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)


Scale: As Noted Date: Apr. 2021

SHEET No. 511.8 OF 14 SHEETS


ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
No.	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WB5-51107 S.DTL5.DWG PLOT TIME: 04-05-21, 3:53 PM

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	96	109




EXISTING DECK SECTION



DECK REPAIR SECTION

CONCRETE REPAIR - TYPE "SC"

Scale: 1 1/2" = 1'-0"



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

SOFFIT REPAIR DETAILS

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)


Scale: As Noted Date: Apr. 2021

SHEET No. S11.9 OF 14 SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	97	109

To Lihue

To Kapaa



Legend:

G## Girder Defect No.

Notes:

- For girder spall sizes, see sheet S9.11.
- End beams and diaphragms shall be treated as girders for spalls and delaminations.

GIRDER SPALLS AND DELAMINATIONS
Scale: 1" = 20"

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
No.	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-S1110 GIRDER.DWG PLOT TIME: 04-05-21, 3:53 PM



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
GIRDER
SPALLS AND DELAMINATIONS
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)
Scale: As Noted Date: Apr. 2021
SHEET No. **S11.10** OF **14** SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	98	109

GIRDER SPALLS AND DELAMINATIONS											
DEFECT NO.	REPAIR TYPE	LENGTH	HEIGHT	TOTAL (sf)	LENGTH	BOTTOM WIDTH	TOTAL (sf)	TOTAL (sf)	SPAN NO.	GIRDER NO.	LOCATION/ REMARKS
G1	GV	2.5	1.5	3.75	-	-	-	3.75	2	4	
G2	GC	1	0.5	0.5	1	1	1	1.5	2	-	End Beam at Pier
G3	GC	2	0.5	1	2	0.5	1	2	2	3	
G4	GV	5	1	5	-	-	-	5	3	1	
G5	GC	3	1	3	3	1	3	6	3	-	End Beam at Pier
G6	GC	3	1	3	3	0.5	1.5	4.5	3	3	
G7	GC	3	0.5	1.5	3	1	3	4.5	3	3	
G8	GC	7	1	7	7	0.5	3.5	10.5	3	2	Exposed rebar
G9	GC	4	1	4	4	1	4	8	3	1	
G10	GV	1	1	1	-	-	-	1	3	1	
G11	GV	3	2	6	-	-	-	6	3	1	
G12	GV	5	2	10	-	-	-	10	4	1	
G13	GV	3	1	3	-	-	-	3	4	3	Exposed rebar
G14	GC	5	1	5	5	0.5	2.5	7.5	4	4	
G15	GV	3	2	6	-	-	-	6	4	1	
G16	GV	2.5	0.5	1.25	-	-	-	1.25	5	4	
G17	GC	4	2	8	4	0.5	2	10	5	4	Exposed stirrup
G18	GV	1	0.5	0.5	-	-	-	0.5	5	3	
G19	GV	3	1	3	-	-	-	3	5	3	
G20	GV	1.5	1	1.5	-	-	-	1.5	5	-	End Beam at Pier
G21	GV	1	1	1	-	-	-	1	6	4	
TOTAL (sf)								96.5			

NOTES:

- All dimensions in units of feet.
- Additional spalls and delaminations may be discovered. In addition spalls may be larger than anticipated. These areas shall be repaired and will be paid for under Pay Item 680.0500 Additional Spall Repair.
- End beams and diaphragms shall be treated as girders for spalls and delaminations.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
No.	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	

DRAWING NAME: Z:\00 ONGOING\20-016-WAILUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-S1111 G TABLE.DWG PLOT TIME: 04-05-21 3:54 PM




THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22


STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
GIRDER
SPALLS AND DELAMINATIONS TABLE
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)
Scale: None Date: Apr. 2021

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	99	109




Existing Defective Area = $X \times Y$


BEAM ELEVATION



BEAM SECTION



BEAM ELEVATION



BEAM SECTION

CONCRETE REPAIR - TYPE "GV"
 Scale: 1 1/2" = 1'-0"



ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	"
No.	DESIGNED BY	"
	QUANTITIES BY	"
	CHECKED BY	"

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-S1112 G.DTL.DWG PLOT TIME: 04-05-21, 3:54 PM



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
 SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22


STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

GIRDER REPAIR DETAILS


KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: As Noted Date: Apr. 2021
SHEET No. **S11.12** OF **14** SHEETS


FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	100	109




BEAM SOFFIT PLAN



BEAM SECTION



BEAM SOFFIT PLAN



BEAM SECTION

CONCRETE REPAIR - TYPE "GH"
 Scale: 1 1/2" = 1'-0"

1
 S11.13 S11.13

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
No.	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	

DRAWING NAME: Z:\00 ONGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-S11.12 G.DTL.DWG PLOT TIME: 04-05-21, 3:55 PM




THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Calvin T. Miyahara
 SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22


STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

GIRDER REPAIR DETAILS
KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)
Scale: As Noted Date: Apr. 2021
SHEET No. S11.13 OF 14 SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	101	109



BEAM SECTION



BEAM SECTION

CONCRETE REPAIR - TYPE "GC"

Scale: 1 1/2" = 1'-0"

1
S11.14 S11.14



THIS WORK WAS PREPARED BY
ME OR UNDER MY SUPERVISION.

Calvin T. Miyama
SIGNATURE EXPIRATION DATE OF THE LICENSE 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION


GIRDER REPAIR DETAILS

KUHIO HIGHWAY
Repairs to Wailua River Bridge
Fed. Aid Project No. ER-23(001)

Scale: As Noted Date: Apr. 2021

SHEET No. **S11.14** OF **14** SHEETS

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	ER-23(001)	2021	102	109



PIER CONSTRUCTION SEQUENCE:

1. The Contractor shall submit a work plan that includes all stages of work for approval by the Engineer.
2. Install BMPs. See Civil plans.
3. Construct shoring at piers.
4. Disconnect girder from piers by removing existing dowels.
5. Raise bridge girders. See Temporary Shoring notes for criteria.
6. Remove existing structural steel supports, concrete piers and columns, portion of existing girders, and rocker bearings at piers.
7. Repair bridge girders and construct end beams.
8. Drilled Shafts may be constructed between Stages 2 and 5.
9. Construct Drilled Shaft Cap.
10. Install Elastomeric Bearings after the concrete in the Shaft Cap attains a compressive strength of 4000 psi and has a minimum age of 7 days.
11. Lower bridge girders onto elastomeric bearing.
12. Final Bottom of Girder Elevations Shall Match Existing Bottom of Girder Elevations. Deflections of Drilled Shaft Cap Due to Dead Loads and Compression of the Bearing Pad Shall be Taken into Account when Determining Final Elevations. The Final Bottom of Girder Elevation Calculations Shall be Part of the Work Plan.
13. Repeat Stages 1 to 9 for remaining piers.
14. Construct Creep Blocks.
15. Remove temporary shoring. Repair any damage to existing structure.
16. Remove BMPs. See Civil plans.

CONSTRUCTION SEQUENCE

Scale: 1" = 20"

TEMPORARY SHORING NOTES:

1. All girders at the same pier shall be raised and lowered at the same time. Jacks must be used on both sides of all piers.
2. Bridge girders shall not be raised more than 1/2" higher than it's existing elevation.
3. Raising of bridge girders may begin at any pier and in any order. Raising of bridge girders at multiple piers concurrently is permitted.
4. Bearings, jacks, and temporary shoring must be sufficient in carrying the loads shown on sheet S0.3. Supports need not be designed for concrete shrinkage forces or movements. See General Note 7.R.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
No.	DESIGNED BY	
	CHECKED BY	

DRAWING NAME: Z:\00_OHGOING\20-016-WALLUA RVR BR SCOUR-DOT\01 CAD\04-05-21 BID\WBS-S1201 CONSTR SEQ.DWG PLOT TIME: 04-05-21 3:56 PM



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

Signature: Calvin Miyahara
EXPIRATION DATE OF THE LICENSE: 4-30-22

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

CONSTRUCTION SEQUENCE

KUHIO HIGHWAY

Repairs to Wailua River Bridge

Fed. Aid Project No. ER-23(001)

Scale: As Noted Date: Apr. 2021

SHEET No. S121 OF 1 SHEETS