## GENERAL NOTES

- 1. The scope of work for this project includes reconstructing weakened pavement areas; cold planing existing pavement; resurfacing; installing centerline and reference survey monuments; removing existing drain inlets, concrete gutters, pavement markers and traffic signs; installing new drain inlets, concrete gutters, pavement markers and traffic signs; and dressing shoulders.
- 2. The Contractor is reminded of the requirements of Subsection 108.01 -Subcontracts.
- 3. The Contractor's attention is directed to the following Sections of the Special Provisions: Subsection 107.13 - Public Convenience and Safety; Subsection 107.21 - Contractor's Responsibility For Utility Property And Services; and Section 645 -Traffic Control.
- 4. At the end of each day's work, the Contractor shall remove all equipment and other obstructions to permit free and safe passage of public traffic.
- 5. The existence and location of underground utilities, manholes, monuments and structures as shown on the plans are from the latest available data but the accuracy is not guaranteed. The encountering of other obstacles during the course of work is possible. The Contractor shall be held liable for any damages incurred to the existing facilities and/or improvements as a result of his operations.
- 6. The exact locations and limits or areas to be filled with leveling course, excavated, reconstructed and cold planed shall be determined in the field by the Engineer.
- 7. All work on this project shall be conducted during daytime between 8:30 A.M. and 3:30 P.M. All lanes shall be open to traffic during peak hours from 6:30 A.M. to 8:30 A.M., during afternoon peak hours from 3:30 P.M. to 6:30 P.M. and during off work hours. Only one lane of highway shall be closed at any other time. Failure of the Contractor to open all lanes of traffic during the times specified above shall result in assessment of liquidated damages as specified in Section 108.09 of the Special Provisions.
- 8. The Contractor shall notify the Engineer in writing, two (2) weeks prior to starting paving operations.
- 9. The Contractor shall remove and dispose of all existing raised pavement markers and traffic tapes prior to the overlaying of Asphalt Concrete. This work shall be considered incidental to Asphalt Concrete Pavement, Mix No. IV and will not be paid for separately.
- 10. All holes, depressions and wheel ruts shall be filled and compacted with Asphalt Concrete Pavement, Mix No. V prior to resurfacing. This work will be paid for under Asphalt Concrete Pavement, Mix No. IV.
- 11. Smooth riding connections shall be constructed at all limits of resurfacing, including the beginning and end of project, connecting approaches, side streets and driveways as shown on the plans.
- 12. Trimming and dressing of shoulder, sidewalk and bus turnout shall consist of clearing, grubbing, grading, reshaping and compacting the unpaved shoulders with suitable material as shown on the plans and/or as directed by the Engineer. Suitable materials shall include materials from roadway excavation, including topsoil and base material therefrom, and if necessary. additional materials from borrow outside the limits of the right of way. Asphalt concrete removed from cold planing, reconstruction and roadway excavation shall not be used for dressing of shoulder, sidewalk or bus turnout. This work shall be considered incidental to the various contract items.
- 13. Earth swale shall be graded to drain. This work shall be considered incidental to the various contract items.
- 14. Existing drainage system will be functional at all times during construction. The Contractor is to furnish materials, equipment, labor, tools and incidentals necessary to maintain flow. This work shall be considered incidental to various contract items.

- 15. The Contractor shall provide for access to and from all existing driveways, sidewalks and ADA access rooutes, and side streets and cross streets at all times. This work shall be considered incidental to the various contract items, and will not be paid for separately.
- 16. All saw cutting work shall be considered incidental to Asphalt Concrete Pavement, Mix No. IV and will not be paid for separately.
- 17. Install new Type II Object Marker on all utility poles or trees that are within the State Highway Right-of-Way and within 30 feet of the roadway edge of pavement as directed by the Engineer. Refer to Standard Plan TE-17.
- 18. Prior to his resurfacing operations, the Contractor shall be responsible for locating, preserving and marking all utility \$ highway facilities that will require adjustments to the new finished pavement grade. Additionally, the Contractor shall submit to the Engineer a list of all items, including water, drainage, sewer, electrical, telephone and cable utilities to be adjusted to the new finished grade.
- 19. After completion of resurfacing, the Contractor and the Engineer will test for, and determine ponding areas (i.e. low spots within the resurfaced area). It shall be the responsibility of the Contractor to correct and resurface and/or repair all such ponding areas.
- 20. Contractor shall exercise extreme caution to preserve BENCHMARKS (Survey Monuments). Whenever the center of a Survey Monument is less than three (3) feet from the edge of construction, the Contractor shall retain a Licensed Land Surveyor to reference the location of said Survey Monument.
  - Benchmarks that are disturbed or destroyed shall be restored under a Licensed Land Surveyor's direction. Copies of field notes, descriptions and new values of the new benchmark shall be sent to the Department of Transportation, Highways Division, Cadastral Engineering Section, for review and approval prior to construction.
- 21. All asphalt concrete materials from cold planing, reconstruction and roadway excavation operations shall become the property of the Contractor. The Contractor shall remove and dispose these materials at no cost to the State.
- 22. Any work specified in the contract but not listed separately in the proposal schedule shall be considered incidental to other various contract items and shall not be paid for separately.

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR		TOTAL SHEETS
HAWAII	HAW.	56C-01-04M	2005	3	19

\_\_\_ Existing Metal Guardrail

Adjusted and/or Relocated

Metal Guardrail

OAMA Existing Sewer Manhole

\*SMH Adjusted Sewer Manhole

• Adjusted or Reconstructed

Frame/Cover

•<sub>SMH</sub> New Sewer Manhole

©<sub>mon.</sub> Existing Monument

---d--24--- Existing 24" Drain Line

Monument

O<sub>MON</sub>. New Monument

——S—12— New 12" Sewer Line

\_\_\_\_ New Metal Guardrail

## **LEGEND**

New Construction Areas Cold Planing Areas Reconstruction Areas 

Resurfacing Limits

Existing Power Pole Existing Electric Manhole Adjusted Elec. MH Frame/Cover Existing Telephone Manhole

Adjusted Tel. MH Frame/Cover Existing 12" Water Line

Existing Water Manhole Adjusted Water MH Frame/Cover Existing Water Air Valve

Adjusted Water Air Valve Existing Water Valve Box Adjusted Water Valve Box

Water Valve Box Below Exist. A.C. Pavement (to be Adjusted)

Existing Water Meter Adjusted Water Meter

Existing Traffic Sign

New Traffic Sign

○Admh Existing Storm Drain Manhole \*SDMH Adjusted Storm Drain Manhole Frame/Cover □gdi Existing Grated Drop Inlet

□<sub>GDI</sub> Adjusted Grated Drop Inlet

STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION

## GENERAL NOTES AND LEGEND

<u>KUHIO HIGHWAY RESURFACING</u> Vicinity of Moloaa Project No. 56C-01-04M

Date: May 2005

SHEET No. 1 OF 1 SHEETS

SURVEY
DRAWN
TRACED
DESIGNED
QUANTIT