

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-M-04-14M	2014	3	11

GENERAL NOTES

1.

The scope of work includes resurfacing of existing pavement and upaved areas; cold planing, reconstruction of weakened pavement areas, installation of signs, water valves, application of longitudinal joint stabilizer. In addition, removal of existing chain link fences and install new chain link fences and gates. Furthermore, install grated drop inlets with dry well per plan and specification.
2.

Asphalt swales shall follow areas where flow directional lines will exit toward Keolani Place.
3.

Prior to removal of chain link fence Contractor shall notify Project Engineer on a schedule to remove existing fence.
4.

The Contractor's attention is directed to Subsection 107.13 - Public Convenience and Safety: Section 645 - Traffic Control and Subsection 104.04 Maintenance of Traffic.
5.

At the end of each day's work, the Contractor shall remove all equipment and other obstructions to permit free and safe passage of public traffic.
6.

The existence and location of underground utilities, manholes, monuments and structures as shown on the plans are from the latest available data but the accuracy is not guaranteed. The encountering of other obstacles during the course of work is possible. The Contractor shall be held liable for any damages incurred to the existing facilities and/or improvements as a result of his operations.
7.

The exact locations and limits or areas to be reconstructed and cold planed shall be determined in the field by the Engineer.
8.

Prior to resurfacing, the existing surface shall be cleaned as described in Section 310 of the Standard Specifications and as amended. Payment shall be considered incidental to Item No. 401.0500 - Hot Mix Asphalt (HMA) Pavement.
9.

The Contractor shall notify the State in writing, two (2) weeks prior to starting paving operations.
10.

The Contractor shall remove and dispose of all existing raised pavement markers prior to the overlaying of Asphalt Concrete. This work shall be considered incidental to Hot Mix Asphalt (HMA) Pavement and will not be paid for separately.
11.

Unless directed by the Engineer, connections shall be cold planed at all limits of resurfacing including the beginning and end of project, connecting approaches, side streets and driveways.
12.

Existing drainage system will be functional at all times during construction. The Contractor is to furnish materials, equipment, labor, tools, and incidentals necessary to accomplish maintenance of flow, the cost of which shall be considered incidental to the various contract items.
13.

Contractor shall adjust pipe casings of existing centerline survey monument whether shown or not on the plans, in accordance with Standard Plan D-07 or any other method as directed by the Engineer to suit field condition. Contractor to verify existing conditions prior to construction. Adjustment of centerline monument will be paid for at the Contract Unit Price regardless of method used. Contractor shall clean existing monuments to expose survey pins.

14.

Replace existing fencing noted on plans.
15.

To avoid impacts to listed Seabirds, no nighttime work will be allowed. However, if nighttime work becomes a necessary measure to complete the project objectives, then the artificial lighting to be used will be shielded with the bulb pointed directly at the ground when work is taking place.
16.

Construction and restoration of all existing highway facilities within State highway baseyard shall be done in accordance with all applicable sections of the current "Standard Specifications For Road and Bridge Construction" and the Project Plans and Special Provisions.
17.

All work to remove temporary facilities by the Contractor shall be considered incidental to the various contract items in the proposal.
18.

The Contractor shall exercise care when performing work in or adjacent to the State highway right-of-way. Damages to the existing facilities shall be immediately reported to the respective utility company, private owner, and/or County/City/State agency. The repair work shall be done at the Contractor's expense.
19.

No material and/or equipment shall be stockpiled or otherwise stored within the Highway Baseyard except at locations designated in writing and approved by the Engineer.
20.

All construction signs shall be left in place until all construction items have been completed unless otherwise directed by the Engineer. The Contractor shall obtain prior approval from the Engineer to remove construction signs.
21.

After the project is completed, the Contractor shall restore grades and ground cover within the project limits and surrounding areas affected by the project to a condition equal or better than the existing condition prior to construction.
22.

Before digging near any utility facilities the Contractor shall call Hawaii's One-Call Center at 1-866-423-7287.

LEGEND

- Reconstruction Areas
- Cold Planing Areas
- Resurfacing Limits
- Existing 12" Water Line
- Existing Fire Hydrant
- Existing Monument
- Adjusted Monument
- Existing Traffic Sign With 1 Post
- Existing Traffic Sign With 2 Posts
- Existing Single Metal Guardrail
- New Single Metal Guardrail
- Existing Double Metal Guardrail
- RM-3
- RM-4
- Adjusted Sewer MH Frame/Cover
- Adjusted Water MH Frame/Cover
- Adjusted Water Valve Box
- Existing Telephone Pole
- Existing Power Pole
- Existing Edge of Pavement
- Existing Edge of Shoulder
- New Chainlink Fence
- Existing Fence
- Water Flow

ORIGINAL PLAN	DESIGNED BY	DATE
NOTE BOOK	TRACED BY	4/1/06
QUANTITIES BY	CHECKED BY	

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

GENERAL NOTES AND LEGEND

MAUI DISTRICT BASEYARD  
Repair and Maintenance of Buildings and Grounds  
Project No. HWY-M-04-14M

Date: May, 2014

SHEET No. 1 OF 1 SHEETS