


GENERAL NOTES

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-M-02-23M	2023	3	34

LEGEND



Reconstruction Areas



Existing Sewer Manhole



Existing Monument



Existing Storm Drain Manhole



New Traffic Sign

- The scope of work for this project consists of installing Raised Crosswalks (AC paving), Multi-Lane Roadway Raised Crosswalk pavement markings, pavement landing pads, concreted sidewalks, curb ramps, traffic control devices, and the adjustment of existing water valve boxes at various locations on the island of Molokai. The installation of Raised Crosswalks (AC paving) is defined as the installation of speed humps and speed tables as designated by the Raised Crosswalk locations.
- The Contractor will provide all necessary traffic control measures required for the closure of State Highways within the project limits. The Contractor shall notify HDOT at least two (2) weeks in advance of any work being scheduled to allow proper notification of closures.
- The Contractor's attention is directed to the following Sections of the Standard Specifications and Special Provisions; Subsection 104.09 - Maintenance of Traffic; Subsection 104.11 - Utilities and Services; Subsection 105.09 - Coordination Between the Contractors; Subsection 107.06 - Contractor Duty Regarding Public Convenience; Subsection 107.12 - Protection of Persons and Property; and Section 645 - Work Zone Traffic Control.
- Contractor shall submit a Traffic Control Plan (TCP) and schedule at least 15 working days before the start of work for review and approval.
- The existence and location of underground utilities, manholes, monuments and structures as shown on the plans are from the latest available data but the accuracy is not guaranteed. The encountering of other obstacles during the course of work is possible. The Contractor shall be held liable for any damages incurred to the existing facilities and/or improvements as a result of his operations.
- Dressing of shoulder shall consists of clearing, grubbing, grading, reshaping, and compacting the unpaved shoulders with suitable excavated materials as shown on the plans and/or as directed by the Engineer. This work shall be considered incidental to the various contract items.
- All construction signs shall be left in place until all construction items have been completed. Contractor shall obtain prior approval from the Engineer to remove construction signs.
- All lanes shall be open to traffic during the morning peak hours from 6:00 a.m. to 8:30 a.m. during afternoon peak hours from 3:00 p.m. to 6:00 p.m. off work hours. Only one lane of highway shall be closed at any other time.
- The Contractor shall not leave more than 1½" drop-off at the edge of pavement, at the end of each work day. Whenever the Contractor leaves a 1½" drop-off, the Contractor shall install delineators and barricades along the edge of the pavement. This work, which includes furnishing, installing, cleaning, maintaining correct placement and removing when required, shall be considered incidental to various contract items.
- At the end of each day's work, the Contractor shall remove all equipment and other obstructions to permit free and safe passage of public traffic.
- The Contractor shall provide for access to and from all existing sideroads and driveways at all times.
- Contractor shall submit an Erosion Control Plan and schedule at least 15 working days before the state of work for review and approval.

- Existing drainage system shall be functional at all times during construction. The Contractor shall furnish materials, equipment, labor, tools and incidentals necessary to maintain flow. This work shall be considered incidental to the various contract items and will not be paid for separately.
- Smooth riding connections shall be constructed at all times on the project, including the beginning and end of the project, connecting approaches, side streets, walkways and driveways shown on the plans and/or as directed by the Engineer.
- The Contractor shall adjust flush to finish grade all manhole, valve, pull box, and handhole frames and covers, including those not shown on the plans, if there is a change in grade due to construction of the project. If the proposal does not show a contract item, the Engineer will consider them incidental to the various contract items.

Section 7 of the Endangered Species Act:

- To avoid impacts to listed Hawaiian seabirds, nighttime construction is not anticipated. If nighttime construction does occur, it shall be scheduled to avoid the seabird fledging period, September 15 through December 15. If nighttime construction occurs during other times of the year, all lighting shall be fully shielded and directed toward the ground so the bulb can only be seen from below to avoid attracting adult seabirds as they travel from the ocean to their breeding areas. Any required outdoor lighting shall have the appropriate automatic motion sensor switches and timer controls to turn off lights when there is no human activity in the vicinity. Where fences extend above vegetation, integrate durable scare tape or bird deterrent into the fence to increase visibility and minimize fence strikes.
- To avoid impacts to the Hawaiian hoary bat, no woody plants (e.g., trees and shrubs) taller than 15 feet shall be trimmed, removed, or disturbed during the hoary bat birthing and pup rearing season, June 1 through September 15.
- To avoid impacts to the Blackburn's sphinx moth, all work will occur on an existing roadway and be within the State highway right-of-way. The shoulder areas within the right-of-way are maintained on a regular basis to limit the growth of vegetation and avoid attraction of the Blackburn's sphinx moth. No critical habitat is located within the State highway right-of-way.
- To avoid impacts to the Hawaiian Stilt, no standing water will be allowed within the construction area(s) to eliminate any water resources.
- No above or below ground utilities will be moved or realigned with this project.
- No highway lighting will be installed or replaced with this project.

HRS Chapter 6E:

- In the unlikely event that subsurface historic resources, including human skeletal remains, structural remains, cultural deposits, artifacts, sand deposits, or sink holes are identified during the demolition and/or construction work, cease work in the immediate vicinity of the find, protect the find from additional disturbance, and contact the State Historic Preservation Division, at (808) 652-1510.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
	DRAWN BY	2/23
	DESIGNED BY	
	CHECKED BY	
NOTE BOOK	NOTED BY	
	CHECKED BY	

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

GENERAL NOTES & LEGEND

RAISED CROSSWALKS
AT VARIOUS LOCATIONS, MOLOKAI
Project No. HWY-M-02-23M

Date: February, 2023

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE	2/23
		DRAWN BY	J
		DESIGNED BY	J/K
		CHECKED BY	
NOTE BOOK	QUANTITIES BY	me/lay	
		SA/rlngnaden	

NOTES FOR CONSTRUCTION WITHIN STATE RIGHT-OF-WAY

1.

The Contractor shall obtain Permit to Perform Work upon State Highways from the Maui District Engineer, State Highways, at 650 Palapala Drive, prior to commencement of work within the State's highway right-of-way.
2.

Removal, construction and restoration of all existing highway facilities within the State's right-of-way, including the legal relations and responsibility to the public, shall be in accordance with the current Hawaii Standard Specifications for Road and Bridge Construction, and the Specifications for Installation of Miscellaneous Improvements within State Highways, of the State Highways Division.
3.

Work may not be performed between the peak hours of 6:00 a.m. to 8:30 a.m. and from 3:00 p.m. to 6:00 p.m., Monday through Friday, except State holidays, unless when otherwise approved in writing by the District Engineer.
4.

During work hours, only one lane of traffic shall be closed, unless otherwise approved in writing by the District Engineer. All lane closures must be approved by HDOT fifteen (15) working days in advance. All lane closures and detours shall require advisory signs and an advertisement per section 645.03 of the Standard Specifications.
5.

At certain locations, "NO LANE CLOSURE" will be allowed during the "Back To School Jam", Thanksgiving weekend, Christmas/New Year Period and at other times as directed by the Highways Division.
6.

The Contractor shall provide, install, and maintain all necessary signs, lights flares, barricades, markers, cones, and other protective facilities, and shall take all necessary precautions for the protection, convenience, and safety of public traffic. All such protective facilities and precautions to be taken shall conform with the "Administrative Rules of Hawaii Governing the Use of Traffic Control Devices at Work Sites on or Adjacent to Public Streets and Highways", adopted by the Director of Transportation, and the "U.S. Federal Highway Administration MUTCD - Manual on Uniform Traffic Control Devices, Part VI - Temporary Traffic Control, 2009 Edition",
7.

No material and/or equipment shall be stockpiled or otherwise stored within the highway right-of-way, except at locations designated in writing and approved by the District Engineer.
8.

The Contractor shall exercise care to minimize damages to existing highway improvements. All damages shall be repaired by the Contractor, at his expense, to the satisfaction of the District Engineer.
9.

All regulatory, guide, and construction signs and barricades shall have a high-intensity Type III or IV retroreflective background.
10.

The Contractor shall inform the State Highway's Permit Office (873-3535) by noon Wednesday, one week prior to closing any lanes.
11.

Driveways shall be kept open unless the owners of the properties using these rights-of-way are otherwise provided for satisfactorily.
12.

Where pedestrian walkways exist they shall be maintained in a safe and passable conditions, or other facilities for pedestrians shall be provided. Passages between walkways at intersections shall likewise be provided. All walkways shall conform to ADA requirements.
13.

The Contractor shall exercise care when performing work in or adjacent to the State highway right-of-way. Damages to the existing facilities shall be immediately reported to the respective utility companies, and/or City or State agencies. The repair work shall be done at the Contractor's expense.
14.

Highway lights shall be operational during construction. Should work be necessary, the contractor shall notify the State Highways' Highway Lighting Supervisor (873-3535), three (3) working days prior to commencing work.
15.

The Permit to Perform Work upon State Highways may be revoked because of default in any of the following, but not limited to, conditions:

a.

Work performed before of after permitted hours.

b.

Failure to maintain roadway surfaces in a smooth and safe condition.

c.

Failure to clean up construction debris generated from project work.

d.

Failure to provide proper traffic control.

e.

Failure to replace damaged pavement markings and signs.

f.

Failure to maintain highway lights and traffic signals systems.

g.

Failure to address public complaints to the satisfaction of the District Engineer.

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-M-02-23M	2023	4	34

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

GENERAL NOTES

RAISED CROSSWALKS

AT VARIOUS LOCATIONS, MOLOKAI

Project No. HWY-M-02-23M

Date: February, 2023

SHEET No. 2 OF 2 SHEETS