

GENERAL NOTES

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-M-02-05M	2005	3	44

- ORIGINAL PLAN

SURVEY PLOTTED BY

DATE

7/05

NOTED BOOK

DRAWN BY

TRACED BY

DESIGNED BY

CHECKED BY

maui

maui

maui

maui

maui
1. The scope of work for this project includes removing and disposing of existing curb, gutter, concrete sidewalk, curb ramps, pavement markings and striping; installing concrete curbs, curb and gutter, curb ramps, and concrete and asphalt concrete sidewalks and asphalt concrete pavement; adjusting utility pull box, traffic signal pull boxes, installing pedestrian push buttons, installing pavement marking, striping and relocation of signs.

2. The Contractor is reminded of the requirements of Subsection 108.01 - Subletting of Contract, which requires him to perform work amounting to not less than 30 percent of the total contract cost less deductible items. Non-compliance with this Subsection may be grounds for rejection of bid.

3. The Contractor's attention is directed to the following Sections of the Special Provisions Subsection 107.13 - Public Convenience and Safety; Subsection 107.21 - Contractor's Responsibility For Utility Property And Services; and Section 645 - Traffic Control.

4. At the end of each day's work, the Contractor shall remove all equipment and other obstructions to permit free and safe passage of public traffic.

5. The existence and location of underground utilities, manholes, monuments, buried railroad tracks, and concrete pavements, and other structures as shown on the plans are from the latest available data but the accuracy is not guaranteed. The Contractor shall make an independent check on the ground by probing and/or with the various utility companies and governmental agencies to verify the exact locations and depths of the existing utilities and obstructions. The Contractor shall exercise proper care in excavating in the area. Whenever connections of new utilities to existing utilities are shown on the plans, the Contractor shall expose the existing lines at the proposed connection to verify their location and depth prior to excavating for the new lines. The Contractor shall be held liable for any damages incurred to the existing facilities and/or improvements as a result of his operations.

6. The Contractor shall notify the Engineer prior to starting paving operations.

7. Existing drainage system will be functional at all times during construction. The Contractor is to furnish materials, equipment, labor, tools and incidentals necessary to maintain flow. This work shall be considered incidental to various contract items.

8. The Contractor shall provide and maintain for access to and from all existing driveways, sidewalks and ADA access routes, and side streets and cross streets at all times. This work shall be considered incidental to the various contract items and will not be paid for separately.

9. All saw cutting work shall be considered incidental to Section 650 - Curb Ramps.

10. Temporary bench marks indicated on the plans may fall within the new curb ramps. The Contractor shall establish new temporary benchmarks, under the supervision of a licensed surveyor, outside the limits of the new work. This work shall be considered incidental to Section 650 - Curb Ramps.

11. Smooth riding connections shall be constructed at all times of the project, including the beginning and end of project, connecting approaches, side streets, walkways and driveways as shown on the plans and/or as directed by the Engineer.

12. The Contractor shall be solely responsible for the protection of adjacent properties, utilities and existing structures from the damages due to construction. Repairing of any damage shall be at the Contractor's own expense, to the satisfaction of the owner.

13. The Contractor shall clean and remove all accumulation of aggregates along the roadside within 10 feet of the edge of pavement. This work shall be considered incidental to the various contract items and will not be paid for separately.

14. Removal and disposal of existing curb and gutter, curb, sidewalk and asphalt concrete pavement, curb, sidewalk and any debris shall be considered incidental to Section 650 - Curb Ramps and will not be paid for separately.

15. Concrete sidewalk shall be reinforced with 6x6 W1.4xW1.4 welded wire fabric.

16. Dressing of sidewalk shall consist of clearing and grubbing, grading, reshaping and compacting with suitable material the area adjacent to the improvement as shown on the plans and/or as directed by the Engineer and shall be considered incidental to sidewalk.

17. Provide smooth transition where new sidewalk construction meets the existing grade or sidewalk.

18. All curb angle points within the curb ramps shall be rounded with R=6".

19. The Contractor shall provide and maintain a temporary pedestrian-safe and easily accessible route or detour with barricades in or near the work zone. This temporary route or detour shall be stable, firm and slip-resistant and shall be American With Disabilities Act compliant (This only applies if existing surface is non-ADA compliant). This work shall be incidental to all contract items and will not be paid for separately.

20. The Contractor shall remove and dispose of all existing raised pavement marker, thermo line markings, traffic tapes, and epoxy adhesives prior to the overlaying of Asphalt Concrete Pavement, Mix No. V and will not be paid for separately. These work items shall be considered incidental to Section 650 - Curb Ramps.

21. Removal of existing pavement marking and striping shall be incidental to contract Item 629.1013 and Item 629.1022.

22. All curb ramps transitions (walkways, curbs) shall be considered incidental to Section 650 - Curb Ramps.

23. No material and/or equipment shall be stockpiled or otherwise stored within highway right-of-way except at locations designated in writing and approved by the Engineer. If use of a location is approved by the Engineer, the Contractor shall obtain a permit to use the property within the highway right-of-way from the State Highways Right-Of-Way branch at telephone no. (808)692-7332.

24. After the project is completed, the Contractor shall restore grades and ground cover disturbed as a result of the project to a condition equal or better than existing before such damage or injury was done.

25. Existing utilities shall remain in service and in place at all times. If relocation of the existing utilities is required by the Contract Documents or for the Contractor's convenience, interruption of service shall be kept to a minimum and shall be done at the Contractor's expense with the approval of the affected utility company.

26. The Contractor shall verify all dimensions and details shown on the drawings prior to the start of construction. Any discrepancy shall be immediately brought to the attention of the Engineer.

27. Construction outside the Hawaii Department of Transportation (HDOT) right-of-way and State acquired parcels are subject to approval by HDOT and the affected owner.

28. All construction work shall be done in accordance with the standards and specifications of the HDOT as amended, unless otherwise specified by the contract plans and specifications.

29. No Contractor shall perform any construction operation so as to cause falling rocks, soil or debris in any form to fall, slide or flow into existing City drainage systems, or adjoining properties, streets or natural watercourses. Should such violations occur, the Contractor may be cited and the Contractor shall immediately make all remedial actions necessary.

30. Elevations are indicated on each sheet.

31. Tack coat shall be incidental to the various asphalt concrete pavement items.

32. The Contractor shall be held liable for any damages incurred to the existing landscaping as a result of his operations.

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

GENERAL NOTES

CURB RAMP REPAIRS AT
VARIOUS LOCATIONS, MAUI
Project No. HWY-M-02-05M

Date: February, 2005

SHEET No. CA-2 OF 7 SHEETS

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-M-02-05M	2005	4	44

GENERAL NOTES (CONT'D.)

33. Contractor to remove and salvage existing lava rock curbs within construction areas. Clean and deliver salvaged lava rock curbs to State's Maintenance baseyard at 650 Palapala Drive. Contact (873-3535) 1-week prior to delivery.
34. The Contractor shall hire a professional surveyor with a current license to practice in the State of Hawaii to establish and verify boundary lines.
35. Contractor shall notify the State construction inspector before commencement of work on any site with trees in close proximity (20'±).
36. Contractor shall comply with conditions as stated in the project NPDES Notice of General Permit Coverage (NGPC).

PAVING AROUND MANHOLES

1. The Contractor shall place hot asphalt concrete around manholes and compact properly with a vibrating plate compactor.
2. If a plate compactor is not used, the Contractor shall use a pneumatic roller to roll the area around the manhole which is not rolled by the steel roller.
3. The Contractor shall fog seal or brush emulsion seal on the material placed as backfill on the area around the manhole that was not compacted by the roller. Black sand shall be used to blot out the area if the fog is too heavy.

NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES) REQUIREMENTS

1. The Contractor shall obtain and comply with the National Pollutant Discharge Elimination System (NPDES) requirements for Maui District permit projects. This is available at the Maui District office at 650 Palapala Drive (ph. 873-3535). Due to potential cost impacts, the Contractor needs to be aware of these requirements.
2. The Contractor shall complete and submit a Contractor's certification of NPDES compliance, including completion of the best management practice (BMP) checklist and submittal of a written BMP plan and drawings, prior to issuance of the permit to perform work upon State highways.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	X
NOTES	TRACED BY	X
NOTES	CHECKED BY	X
NOTES	QUANTITIES BY	X
NOTES	CHECKED BY	X

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

GENERAL NOTES

CURB RAMP REPAIRS AT
VARIOUS LOCATIONS, MAUI
Project No. HWY-M-02-05M

Date: February, 2005

SHEET No. CA-3 OF 7 SHEETS

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-M-02-05M	2005	5	44

CONSTRUCTION NOTES
WITHIN COUNTY RIGHT-OF-WAY

- Contractor shall obtain permit to perform work on County highways from the Development Services Administration two weeks prior to the commencement of work.
- Standard Detail Drawings and Standard Specifications of the Department of Public Works shall be included as part of the construction plans.
- All construction work shall strictly conform to applicable sections of the 1994 Hawaii Standard Specifications for Road, Bridge, and Public Works Construction, and the September 1984 "Standard Details" for Public Works Construction of the Department of Public Works.
- If existing utilities, whether or not shown on plans, are damaged during repair such utilities.
- Contractor shall provide, install and maintain all necessary signs, lights, flares, barricades, and other protective devices for the protection, safety and convenience of the public, according to the "Manual on Uniform Traffic Control Devices for Streets and Highways", 2000, and to the rules and regulations governing the use of traffic control devices at work sites on/or adjacent to public streets and highways adopted by the highway safety coordinator and the U.S. Federal Highway Administration "Manual on Uniform Traffic Control Devices for Highway Construction and Maintenance Operations" dated 2001.
- The Director of Public Works and/or the Director of the Department of Water Supply has the right to stop construction should any work be found contrary to the approved construction plan or detrimental to the public's interest.
- The Contractor shall schedule a pre-construction meeting with the Development Services Administration five (5) days prior to commencement of construction.
- The Contractor shall, at his own expense, keep the project area and surrounding area free from dust nuisance. The work shall be in conformance with the Air Pollution Control Standards and Regulations of the State Department of Health and County Grading Ordinance.
- The Contractor shall remove all silt and debris resulting from his work and deposited in drainage facilities, roadways and other areas. The cost incurred for any necessary remedial action ordered by the Director of Public Works shall be paid by the Contractor.
- Construction debris and wastes shall be deposited at an appropriate work site. The Contractor shall inform the Director of Public Works of the location of the disposal sites. The disposal site must fulfill the requirements of the Grading Ordinance.
- The Contractor shall submit a TIFF and five (5) copies of the "As-Builts" drawings prior to the final approval of the improvements.
- If the clearance between a wastewater line and a new or existing waterline is eighteen inches (18") or less, the wastewater line shall be concrete-jackefed in accordance with the Standard Details of Public Works Construction dated September 1984.
- Should historic sites such as walls, platforms, pavements, or mounds, or remains such as artifacts burials, concentration of shell or charcoal be encountered during construction activities, work shall cease immediately in the immediate vicinity of the find and the find shall be protected from further damage. The Contractor and/or landowner shall immediately contact the State Historic Preservation Division @ (243-5169), which will assess the significance of the find and recommend an appropriate mitigation measure, if necessary.

14. Pursuant of Maui County Code Section 3.44.015(C), the County of Maui is not responsible for any park, roadway, easement (including but not limited to drainage, sewer, access, reclaimed water, or irrigation easement), or any other interest in real property shown on this map or shown on these plans, unless the Maui County Council has accepted its dedication by a resolution approved by a majority of Council's Members at a regular or special meeting of the Maui County Council.

ORIGINAL PLAN	DESIGNED BY	DATE
NOTED BY	2/05	
QUANTITIES BY		
CHECKED BY		

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

GENERAL NOTES

CURB RAMP REPAIRS AT
VARIOUS LOCATIONS, MAUI
Project No. HWY-M-02-05M

Date: February, 2005

SHEET No. CA-4 OF 7 SHEETS

WATER POLLUTION AND EROSION CONTROL NOTES:

A. GENERAL:

1. The Contractor is reminded of the requirements of Section 209 - Water Pollution and Erosion Control, in the Special Provisions. Section 209 describes but is not limited to: submittal requirements; scheduling of a water pollution and erosion control conference with the Engineer; construction requirements; method of measurement; and basis of payment.
2. The Contractor shall follow the guidelines in the "Best Mangement Practices Manual for Construction Sites in Honolulu", dated May 1999 in developing, installing and maintaining the Best Management Practices (BMP) for the project.
3. The Engineer may assess liquidated damages of up to \$27,500 for non-compliance of each BMP requirement and each requirement stated in Section 209, for every day of non-compliance. There is no maximum limit on the amount assessed per day.
4. The Engineer will deduct the cost from the progress payment for all citations received by the Department for non-compliance, or the Contractor shall reimburse the State for the full amount of the outstanding cost incurred by the State.
5. For projects that require an NPDES Permit from the Department of Health, install a rain gage prior to any field work including the installation of any site-specific best management practices. The rain gage shall have a tolerance of at least 0.05 inches of rainfall, and have an opening of at least one-inch in diameter. Install the rain gage on the project site in an area that will not deter rainfall from entering the gage opening. The rain gage installation shall be stable and plumbed. Do not begin field work until the rain gage is installed and site-specific best management practices are in-place.

B. WASTE DISPOSAL:

1. Waste Materials

All waste materials shall be collected and stored in a securely lidded metal dumpster. The dumpster shall meet all local and State solid waste management regulations. All trash and construction debris from the site shall be deposited in the dumpster. The dumpster shall be emptied a minimum of twice per week or as often as is deemed necessary. No construction waste materials shall be buried onsite. The Contractor's supervisory personnel shall be instructed regarding the correct procedure for waste disposal. Notices stating these practices shall be posted in the office trailer and the Contractor shall be responsible for seeing that these procedures are followed.

2. Hazardous Waste

All hazardous waste materials shall be disposed of in the manner specified by local or State regulations or by the manufacturer. The Contractor's site personnel shall be instructed in these practices and shall be responsible for seeing that these practices are followed.

3. Sanitary Waste

All sanitary waste shall be collected from the portable units a minimum of once per week, or as required.

C. EROSION AND SEDIMENT CONTROL INSPECTION AND MAINTENANCE PRACTICES:

1. All control measures shall be inspected at least once each week and following any rainfall event of 0.5 inches or greater.
2. All measures shall be maintained in good working order. If repair is necessary, it shall be initiated within 24 hours after the inspection.
3. Built-up sediment shall be removed from silt fence when it has reached one-third the height of the fence.
4. Silt screen or fence shall be inspected for depth of sediment, tears, to verify that the fabric is securely attached to the fence posts or concrete slab and to verify that the fence posts are firmly in the ground. The bottom of the silt screen shall be inspected and verified that it is buried a minimum of 6 inches below the existing ground.
5. Temporary and permanent seeding and planting shall be inspected for bare spots, washouts and healthy growth.

6. A maintenance inspection report shall be made promptly after each inspection by the Contractor.
7. The Contractor shall select a minimum of three personnel who shall be responsible for inspections, maintenance and repair activities and filling out the inspection and maintenance report.
8. Personnel selected for the inspection and maintenance responsibilities shall receive training from the Contractor. They shall be trained in all the inspection and maintenance practices necessary for keeping the erosion and sediment controls used onsite in good working order.

D. GOOD HOUSEKEEPING BEST MANAGEMENT PRACTICES:

1. Materials Pollution Prevention Plan

- a. Applicable materials or substances listed below are expected to be present onsite during construction. Other materials and substances not listed below shall be added to the inventory.

Concrete	Fertilizers
Detergents	Petroleum Based Products
Paints (enamel and latex)	Cleaning Solvents
Metal Studs	Wood
Tar	Masonry Block

- b. Material Management Practices shall be used to reduce the risk of spills or other accidental exposure of materials and substances to storm water runoff. An effort shall be made to store only enough product as is required to do the job.

- c. All materials stored onsite shall be stored in a neat, orderly manner in their appropriate containers and if possible under a roof or other enclosure.

- d. Products shall be kept in their original containers with the original manufacturer's label.

- e. Substances shall not be mixed with one another unless recommended by the manufacturer.

- f. Whenever possible, a product shall be used up completely before disposing of the container.

- g. Manufacturer's recommendations for proper use and disposal shall be followed.

- h. The Contractor shall conduct a daily inspection to ensure proper use and disposal of materials onsite.

2. Hazardous Material Pollution Prevention Plan

- a. Products shall be kept in original containers unless they are not resealable.
- b. Original labels and material safety data sheets (MSDS) shall be retained.
- c. Surplus products shall be disposed of according to manufacturers' instructions or local and State recommended methods.

3. Onsite and Offsite Product Specific Plan

- a. The following product specific practices shall be followed onsite:

- 1) Petroleum Based Products:
All onsite vehicles shall be monitored for leaks and receive regular preventive maintenance to reduce the chance of leakage. Petroleum products shall be stored in tightly sealed containers which are clearly labeled. Any asphalt substances used onsite shall be applied according to the manufacturer's recommendation.
- 2) Fertilizers:
Fertilizers used shall be applied only in the minimum amounts recommended by the manufacturer. Once applied, fertilizer shall be worked into the soil to limit exposure to storm water. Storage shall be in a covered shed. The contents of any partially used bags of fertilizer shall be transferred to a sealable plastic bin to avoid spills.

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-M-02-05M	2005	6	44

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
	DRAWN BY	
	NOTED BY	
	CHECKED BY	

STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION
WATER POLLUTION & EROSION CONTROL NOTES
<u>CURB RAMP REPAIRS AT</u> <u>VARIOUS LOCATIONS, MAUI</u> <u>Project No. HWY-M-02-05M</u>
Date: February, 2005
SHEET No. CA-5 OF 7 SHEETS

WATER POLLUTION AND EROSION CONTROL NOTES: -Cont.

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-M-02-05M	2005	7	44

D. GOOD HOUSEKEEPING BEST MANAGEMENT PRACTICES: -Cont.

3) Paints:

All containers shall be tightly sealed and stored when not required for use. Excess paint shall not be discharged to the highway drainage system but shall be properly disposed of according to manufacturers' instructions or State and local regulations.

4) Concrete Trucks:

Concrete trucks shall be allowed to wash out or discharge drum wash water only at a designated site. Water shall not be discharged in the highway drainage system or waters of the United States. The Contractor shall contact Drinking Water Branch, Department of Health at 586-4258 to receive permission to designate a disposal site. The Contractor shall clean disposal site as required or as requested by the Owner's representative.

b. Offsite Vehicle Tracking:

A stabilized construction entrance shall be provided to help reduce vehicle tracking of sediments. The paved street adjacent to the site entrance shall be cleaned daily or as required to remove any excess mud, cold planed materials, dirt or rock tracked from the site. Dump trucks hauling material from the construction site shall be covered with a tarpaulin.

4. Spill Control Plan

a. A spill prevention plan shall be posted to include measures to prevent and clean up each spill.

b. The Contractor shall be the spill prevention and cleanup coordinator. The Contractor shall designate at least three site personnel who shall receive spill prevention and cleanup training. These individuals shall each become responsible for a particular phase of prevention and cleanup. The names of responsible spill personnel shall be posted in the material storage area and in the office trailer onsite.

c. Manufacturers' recommended methods for spill cleanup shall be clearly posted and site personnel shall be made aware of the procedures and the location of the information and cleanup supplies.

d. Materials and equipment necessary for spill cleanup shall be kept in the material storage area onsite.

e. All spills shall be cleaned up immediately after discovery.

f. The spill area shall be kept well ventilated and personnel shall wear appropriate protective clothing to prevent injury from contact with a hazardous substance.

g. Spills of toxic hazardous material shall be reported to the appropriate State or local government agency, regardless of the size.

E. PERMIT REQUIREMENTS:

1. A National Pollutant Discharge Elimination System (NPDES) Permit is required for Construction Activities of one acre or more. The Contractor shall submit to the Engineer four sets of the Water Pollution and Erosion Control Submittals as detailed in Subsection 209.04 of the specifications.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
07/14/05	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	

STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION
WATER POLLUTION & EROSION CONTROL NOTES
<u>CURB RAMP REPAIRS AT</u> <u>VARIOUS LOCATIONS, MAUI</u> <u>Project No. HWY-M-02-05M</u>
Date: February, 2005
SHEET No. CA-6 OF 7 SHEETS