


FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	360AB-01-02M	2002	7	41

### GENERAL NOTES

- All hardware, posts and fasteners shall be hot-dip zinc coated galvanized after fabrication. No punching, drilling or cutting will be permitted after galvanizing.
- Where conditions require, special post lengths in increments of 6 inches may be specified.
- All fasteners, posts, and rail elements (i.e. FBB03, PWE01, RWM02b, etc.) shall conform to the latest edition and amendments of "A Guide to Standardized Highway Barrier Rail Hardware", a report prepared and approved by the AASHTO-AGC-ARTBA Joint Cooperative Committee, Subcommittee On New Highway Materials, Task Force 13 Report. Dimensions of fastners, posts and rail elements have been converted from metric units into their present form.
- The Recycled Plastic Block or Offset Block shall be approved by the State.
- All new guardrail systems (system consists of total length of guardrail including both end treatments) shall include the Additional Paved Area.
- After the guardrail posts are installed in the paved area, the Contractor shall fill/seal around each guardrail post and all cracks in the paved area caused during the guardrail post installation. If required by the inspector/engineer, the Contractor shall tamper the paved area around the guardrail post prior to filling/sealing. All costs associated with this work shall not be paid for separately, but shall be considered incidental to the various guardrail items.
- When standards for the fill slope area cannot be met, a site specific, engineer approved design may be used.
- New A.C. pavement at guardrails shall extend 6 feet longitudinally beyond terminal ends.
- Reflector Markers (RM-5) mounted on guardrails shall be spaced every 60 feet. Spacing of RM-5's on Horizontal Curves shall comply with Table III-1 of the MUTCD. RM-5's shall not be installed on Terminal Sections.

GUARDRAIL TYPE	DIMENSION	
	H	A
Strong Post w/W Beam	1'-9 <sup>5</sup> / <sub>8</sub> "	1'-6"
Rubrail	2'-0"	1'-6"
Modified Thrie Beam	2'-0"	2'-0"




THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION.  
*Corey H. Kogutsky*  
 DATE: 4/30/02


STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**GUARDRAIL DETAILS & NOTES**  
  
HANA HIGHWAY  
REPAIRS AND MAINTENANCE  
PROJECT NO. 360AB-01-02M  
Scale: NTS  
Date: March, 2001


SHEET No. 1 OF 7 SHEETS




RECYCLED POLYETHYLENE  
OFFSET BLOCK (TYPE II)




RECYCLED PLASTIC BLOCKOUT (TYPE I)



STEEL POST AND BLOCK DETAIL



REFLECTOR MARKER (RM-5) DETAIL AND TYPICAL INSTALLATION





ELEVATION


TYPICAL GUARDRAIL INSTALLATION

SURVEY PLOTTED BY	DATE
DRAWN BY	
DESIGNED BY	
CHECKED BY	
NO.	

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	360AB-01-02M	2002	8	41




**STRONG POST W-BEAM GUARDRAIL**  
**(SGR04a)**




**STRONG POST W-BEAM GUARDRAIL WITH**  
**RECYCLED OFFSET BLOCK OR PLASTIC BLOCKOUT**

NOTE:  
All Holes are  
3/4" Dia.


W6x9.0  
Structural  
Shape




**W-BEAM STRONG POST (PWE01)**



DESIGNATOR	L
FBB01	1 3/8"
FBB02	2"
FBB03	10"




**GUARDRAIL BOLTS AND**  
**RECESSED NUT**




DESIGNATOR	BASE METAL THICKNESS
RWB01a	12 Gauge

**W-BEAM BACK-UP-PLATE (RWB01a)**



DESIGNATOR	BASE METAL THICKNESS
RWM02a	12 Gauge

**2 SPACE W-BEAM GUARDRAIL (RWM02a)**



THIS WORK WAS PREPARED BY ME OR UNDER  
MY SUPERVISION AND CONSTRUCTION OF THIS  
PROJECT WILL BE UNDER MY OBSERVATION.  
DATE: 4/30/02

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**STRONG POST W-BEAM GUARDRAIL**

HANA HIGHWAY  
REPAIRS AND MAINTENANCE  
PROJECT NO. 360AB-01-02M


Scale: NTS Date: March, 2001

SHEET No. 2 OF 7 SHEETS


SURVEY PLOTTED BY	DATE
DRAWN BY	
DESIGNED BY	
CHECKED BY	
ORIGINAL PLAN	
NOTE BOOK	
NO.	






FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	360AB-01-02M	2002	9	41




W-BEAM TERMINAL CONNECTOR (RWE02b)




W-BEAM END SECTION (FLARED RWE01a)



W-BEAM END SECTION (BUFFER RWE06a)



W-BEAM END SECTION (ROUNDED RWE03a)




THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION.  
 DATE: 4/30/22



STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

STRONG POST W-BEAM GUARDRAIL  
  
HANA HIGHWAY  
REPAIRS AND MAINTENANCE  
PROJECT NO. 360AB-01-02M  
Scale: NTS Date: March, 2001


FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	360AB-01-02M	2002	10	41




Design speed mph	a:b
68	15:1
62	13:1
56	12:1
50	11:1
43	10:1
37	9:1
31	7:1





Section A-A



Section B-B  
(With Rubrail)



Section C-C  
(With Rubrail)



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION.  
*Corey H. Kogale*  
 DATE: 4/30/02

General Notes


1. A 6:1 or flatter slope is desirable. However, a steeper or flatter existing slope may be used.
2. Height of guardrail may be tapered down in elevation to maintain 3'-8" maximum height.
3. All posts are 8'-0" in length from where the guardrail flares away from the shoulder back to the post anchor. Posts for the post anchor are 6'-0" long.
4. Variable Paved Gutter offsets may be used to fit field conditions.
5. The Guardrail Posts shall be located away from the gutter/swale invert.
6. All fasteners, posts, blocks and rail elements shall conform to the latest edition and amendments of "A Guide to Standardized Highway Barrier Rail Hardware," a report prepared and approved by the AASHTO-AGCARTBA Joint Cooperative Committee.

BACKSLOPE ANCHOR TERMINAL (WITH 6:1 PAVED GUTTER AND TYPE "A" FLARE)


STATE OF HAWAII  
 DEPARTMENT OF TRANSPORTATION  
 HIGHWAYS DIVISION  
**TYPE "A" FLARE**

HANA HIGHWAY  
 REPAIRS AND MAINTENANCE  
 PROJECT NO. 360AB-01-02M  
 Scale: NTS  
 Date: March, 2001


FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	360AB-01-02M	2002	11	41



**Steel Plate - 1/2"**  
(Hot-dip Zinc Coated Galvanized  
Welded or Bolted to Post)




**Square Washer**  
(3/16" Thick - Hot-dip  
Zinc Coated Galvanized)




3 - 7/8"Ø holes to be field drilled in rail and attached to steel plate with 7/8"Ø hex bolts 1 5/16" long with square washer

1"Ø holes to be field drilled in rail and through post flange. Attach to steel plate with 7/8"Ø hex bolts 2" long with square washer



**Front View**




**Elevation**

### RUBRAIL ANCHOR DETAILS


### Note:

All fasteners, posts, blocks and rail elements shall conform to the latest edition and amendments of "A Guide to Standardized Highway Barrier Rail Hardware," a report prepared and approved by the AASHTO-AGCARTBA Joint Cooperative Committee.




3 - 7/8"Ø holes to be field drilled in rail and attached to steel plate with 7/8"Ø hex bolts 1 5/16" long with square washer

1"Ø holes to be field drilled in rail and through post flange. Attach to steel plate with 7/8"Ø hex bolts 2" long with square washer




**Front View**



**Elevation**

### POST ANCHOR DETAILS

### BACKSLOPE ANCHOR TERMINAL END ANCHORAGE DETAILS (TYPE "A" FLARE)



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION.  
DATE: 4/30/02

### STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION TYPE "A" FLARE



HANA HIGHWAY  
REPAIRS AND MAINTENANCE  
PROJECT NO. 360AB-01-02M

Scale: NTS Date: March, 2001


SHEET No. 5 OF 7 SHEETS





FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	360AB-01-02M	2002	12	41



STEEL POST GUARDRAIL  
WITH RUBRAIL



ANCHOR ASSEMBLY  
CONCRETE BLOCK ANCHOR




CONCRETE BLOCK ANCHOR  
(2' X 2' X 3')

BACKSLOPE ANCHOR TERMINAL END ANCHORAGE DETAILS  
TYPE "A" FLARE)

Note:

All fasteners, posts, blocks and rail elements shall conform to the latest edition and amendments of "A Guide to Standardized Highway Barrier Rail Hardware," a report prepared and approved by the AASHTO-AGCARTBA Joint Cooperative Committee.



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION.  
*Corey H. Kocasky*  
DATE: 4/30/02


STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

TYPE "A" FLARE


HANA HIGHWAY  
REPAIRS AND MAINTENANCE  
PROJECT NO. 360AB-01-02M  
Scale: NTS Date: March, 2001  
SHEET No. 6 OF 7 SHEETS

SURVEY PLOTTED BY	DATE
DRAWN BY	
DESIGNED BY	
CHECKED BY	
ORIGINAL PLAN	
NOTE BOOK	
NO.	


FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	360AB-01-02M	2002	13	41




PLAN




ELEVATION




PARTIAL VIEW OF POST 1




SECTION A-A  
(@ Post #2)




SECTION B-B  
(Typical @ Post 3 - 7)  
NOTE: RAIL NOT BOLTED @ POST #3



IMPACT HEAD CONNECTING DETAIL



IMPACT HEAD REFLECTOR  
MARKER INSERT  
DETAIL



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION.  
DATE: 4/30/02

# GENERAL NOTES

1. Breakaway posts are required with the FLEAT Terminal.
2. All bolts, nuts, cable assemblies, cable anchors and bearing plates shall be galvanized.
3. The soil tubes shall not protrude more than 4" above ground (measured along a 5' cord). Site grading may be necessary to meet this requirement.
4. The soil tubes may be driven with an approved driving head. Soil tubes shall not be driven with the post in the tube. If the tubes are placed in drilled holes, the backfill material must be satisfactorily compacted to prevent settlement.
5. When rock is encountered during excavation, a 12" Dia. post hole, 20" deep may be used if approved by the engineer. Granular material will be placed in the bottom of the hole approx. 2 1/2" deep to provide drainage. The soil tubes will be field cut to length, placed in the hole and backfilled with adequately compacted material excavated from the hole.
6. The breakaway cable assembly must be taut. A locking device, (vice grips or channel lock pliers) should be used to prevent the cable from twisting when tightening nuts.
7. (R) or (L) indicates right or left Impact Head Reflector Marker (IHRM).
8. The stripes for IHRM shall slope downward at an angle of 45° towards the side of the end treatment that traffic is to pass.

ITEM NO.	QTY.	BILL OF MATERIALS
F3000	1	IMPACT HEAD
F1303	1	W-BEAM GUARDRAIL END SECTION, 12 GA.
F1304	1	W-BEAM GUARDRAIL CENTER SECTION, 12 GA.
G1203	1	W-BEAM GUARDRAIL, 12 GA.
S730	2	*FOUNDATION SOIL TUBE, 6" x 8" x 72"
E750	1	BEARING PLATE
S760	1	CABLE ANCHOR BOX
E770	1	BCT CABLE ANCHOR ASSEMBLY
E780	1	GROUND STRUT
PB620	2	STEEL BREAKAWAY END POST
PB621	5	STEEL BREAKAWAY LINE POST
	5	RECYCLED PLASTIC BLOCKOUT OR OFFSET BLOCK
	1	IMPACT HEAD REFLECTOR MARKER - IHRM(R) OR (L)
		HARDWARE
B580122	25	5/8" Dia. x 1 1/4" SPLICE BOLT, POST #2
B580754	2	5/8" Dia. x 7 1/2" HEX BOLT
B341004	2	3/4" Dia. x 10" HEX BOLT
B581002	5	5/8" Dia. x 10" H.G.R. BOLT (POST 3 THRU 7)
N050	32	5/8" Dia. H.G.R. NUT (SPLICE 24, SOIL TUBES 2, POST 2 THRU 7, 6)
N030	2	3/4" Dia. HEX NUT
W050	6	H.G.R. WASHER
W030	4	3/4" ID WASHER
N100	2	1" ANCHOR CABLE HEX NUT
W100	2	1" ANCHOR CABLE WASHER
B140404	2	1/4" x 4" HEX BOLT
N014	2	1/4" HEX NUT
W014	4	1/4" WASHER
SB58A	8	CABLE ANCHOR BOX SHOULDER BOLT
N055A	8	1/2" A325 STRUCTURAL NUT
W050A	16	1 1/16" OD x 9/16" ID A325 STR. WASHER

Foundation Tube Options For Posts 1 & 2  
 \*6'-0" Split Foundation Tubes S730  
 \*6'-0" Solid Foundation Tubes E731  
 \*5'-0" Foundation Tubes S735 W/Soil Plates SP600  
 \*4'-6" Foundation Tubes E735 W/Soil Plates SP600

STATE OF HAWAII  
 DEPARTMENT OF TRANSPORTATION  
 HIGHWAYS DIVISION  
**FLEAT-350**  
**FLARED ENERGY ABSORBING TERMINAL**  
 HANA HIGHWAY  
 REPAIRS AND MAINTENANCE  
 PROJECT NO. 360AB-01-02M  
 Scale: NTS Date: March, 2001  
 SHEET No. 7 OF 7 SHEETS