

<u>ELECTRICAL SYMBOLS</u>		FED. R DIST.
		HAW.


SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
	EXST. 150W HPS STREET LIGHT				
	REMOVE EXST. STREET LIGHT STANDARD, DEMOLISH EXST. CONC. BASE 2 FT. BELOW FINISH GRADE. BACKFILL PIT TO 95% COMPACTION; RESTORE SIDEWALK OR GRASS PER CITY REQUIREMENTS	A	NEW TYPE "A" METRIC TRAFFIC SIGNAL PULLBOX (APPROX. 22" X 28"), SEE DETAIL A/E-10	NEW	NEW TYPE 1 TRAFFIC SIGNAL STANDARD, SEE PLAN FOR HEIGHT, SEE DET. A/E-14, AND SHEETS E-12, E-13, E-14, E-17
		B	NEW TYPE "B" METRIC TRAFFIC SIGNAL PULLBOX (APPROX. 28" X 40"), SEE DETAIL B/E-10		RELOCATED TYPE 1 TRAFFIC SIGNAL STANDARD, PROVIDE NEW CONC. BASE PER C&C STANDARDS & DET. A/E-15, AND SHEETS E-12, E-13, E-14, E-17
	RELOCATED STREET LIGHT STANDARD, SEE DETAILS A/E-18 & B/E-18	C	NEW TYPE "C" METRIC TRAFFIC SIGNAL PULLBOX (APPROX. 28" X 57"), SEE DETAIL C/E-10		EXST. TYPE 1 TRAFFIC SIGNAL STANDARD TO REMAIN
			EXST. PULLBOX OR HANDHOLE, SEE PLAN FOR SIZE		REMOVE TYPE 1 TRAFFIC SIGNAL STANDARD, DEMOLISH EXST. CONC. BASE 2 FT. BELOW FINISH GRADE. BACKFILL PIT TO 95% COMPACTION; RESTORE SIDEWALK OR GRASS PER STATE REQUIREMENTS
			EXST. TRAFFIC SIGNAL CONTROLLER		
			RELOCATED TRAFFIC SIGNAL CONTROLLER		
			EXST. PULLBOX TO BE DEMOLISHED, BACKFILL PIT TO 95% COMPACTION		RELOCATED TYPE II TRAFFIC SIGNAL STANDARD, WITH NEW TRAFFIC SIGNAL HEADS AND NECESSARY MOUNTING BRACKETS AND ACCESSORIES
			EXST. STREET LIGHT DUCTLINE & WIRING TO REMAIN		
	RELOCATED TRAFFIC SIGNAL HEAD, PROVIDE NECESSARY MTG. BRACKETS AND ACCESSORIES		EXST. TRAFFIC SIGNAL DUCTLINE & WIRING TO REMAIN		
			EXST. TRAFFIC SIGNAL CONDUITS & WIRING TO REMAIN		
	NEW TRAFFIC SIGNAL HEAD RYG, PROVIDE NECESSARY MOUNTING BRACKETS AND ACCESSORIES		EXST. TRAFFIC SIGNAL CONDUIT & WIRING, WIRING TO BE REMOVED AND CONDUIT ABANDONED IN PLACE.		NEW TYPE II TRAFFIC SIGNAL STANDARD, WITH NEW TRAFFIC SIGNAL HEADS AND NECESSARY MOUNTING BRACKETS AND ACCESSORIES (WITH NEW 30' MAST ARM INDICATED)
	EXST. TRAFFIC SIGNAL HEAD TO REMAIN		NEW TRAFFIC SIGNAL CONDUIT & WIRING		
	RELOCATE TRAFFIC SIGNAL HEAD		NEW TRAFFIC SIGNAL CONDUIT & WIRING. SAWCUT AND PATCH EXST. AC PAVEMENT, SIDEWALK, CURB & GUTTER, SEE NOTE 1 ON PLAN SHEET		
	RELOCATED RYG & TRAFFIC SIGNAL HEAD, PROVIDE NECESSARY MTG. BRACKETS AND ACCESSORIES				
	EXST. RYG & TRAFFIC SIGNAL HEAD TO REMAIN		EXST. OVERHEAD TRAFFIC SIGNAL CABLES TO REMAIN		
	RELOCATE RYG & TRAFFIC SIGNAL HEAD				
	EXST. OPTICON DETECTOR TO REMAIN		EXST. UNDERGROUND ELEC./SIGNAL CONDUITS & CABLES TO REMAIN		
	RELOCATE OPTICON DETECTOR		STREET LIGHT DUCTLINE & WIRING, SEE DUCT SECTIONS		
	RELOCATED PEDESTRIAN TRAFFIC SIGNAL HEAD, PROVIDE NECESSARY MTG. BRACKETS AND ACCESSORIES		EXST. UNDERGROUND ELEC./SIGNAL CONDUITS WITH NEW WIRE AND CABLES BY OTHERS		
	NEW PEDESTRIAN TRAFFIC SIGNAL HEAD, PROVIDE NECESSARY MTG. BRACKETS AND ACCESSORIES		BREAK LINE TO BEGIN AND END DUCT SECTION TYPE		
	EXST. PEDESTRIAN TRAFFIC SIGNAL HEAD TO REMAIN		ELECTRIC/SIGNAL DUCTLINE WITH DESIGNATORS; INDICATES TYPE "A" DUCT SECTION WITH "1-2 ELEC" DUCTS. SEE SHEET E-2 FOR DUCT SECTION AND CONDUIT SCHEDULES		
	RELOCATE PEDESTRIAN TRAFFIC SIGNAL HEAD, PROVIDE NECESSARY MTG. BRACKETS AS REQUIRED				
			NEW TYPE "A" METRIC STREET LIGHTING PULLBOX. (APPROX. 22" X 28"), SEE DETAIL A/E-10		
	RELOCATED OPTICON DETECTOR, PROVIDE NECESSARY MTG. BRACKETS AND ACCESSORIES		ADJUST EXISTING PULLBOX TO BE FLUSH WITH NEW FINISH GRADE		
	NEW OPTICON DETECTOR, PROVIDE NECESSARY MOUNTING BRACKETS AND ACCESSORIES, SEE DET. E-16				
	NEW PEDESTRIAN PUSHBUTTON SHALL MEET CURRENT AMERICAN WITH DISABILITIES ACT (ADA) ACCESSIBILITY GUIDELINES AND WILL BE SUBJECT TO ENGINEER'S APPROVAL SEE SHEETS E-14, E-17				
	EXST. CCTV SYSTEM CAMERA TO REMAIN				
	REMOVE EXST PEDESTRIAN PUSHBUTTON				

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION

Andrew L. Miyamoto

RONALD H. S. HO & ASSOC., INC. ELECTRICAL ENGINEERS

<i>Date</i>	<i>Revision</i>

	STATE OF HAWAII
	DEPARTMENT OF TRANSPORTATION
	HIGHWAYS DIVISION
	<u>ELECTRICAL SYMBOLS</u>
THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION <i>Andrew I. Miyamoto</i> 12-73-02	<u>PEDESTRIAN FACILITIES and ADA COMPLIANCE</u> <u><i>At Various Locations On Oahu, Phase II</i></u> <u><i>Federal Aid Project No. CMAQ-0.300(87)</i></u> SCALE: AS NOTED DATE:
RONALD N. S. HO & ASSOC., INC. ELECTRICAL ENGINEERS	SHEET No. E-1 OF 18 SHEETS

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-0300(87)	2002	76	145

GENERAL CONSTRUCTION NOTES

- Trenching to be by hand digging near and across existing utility lines.
- Unless otherwise requested by the Board of Water Supply, minimum clearance between water lines and conduits shall be:
 - Horizontal = 3 feet
 - Vertical = 6 inches
- Adjust new conduit alignment, if required to provide clearances. If conduit cannot be realigned, adjustments to existing water system shall be performed in accordance with standards of the Board of Water Supply.
- Minimum clearance between highway light standards and fire hydrants shall be 3 feet.
- Underground utilities shown hereon are for information only. No guarantee is made on the accuracy or completeness of said information.
- All new and existing concrete pullbox and handhole covers which are located in new finished sidewalks shall be provided with new exposed aggregate concrete covers to match new exposed aggregate concrete sidewalk finish.
- Where necessary, reconstruction of sidewalk, gutter and driveway areas shall conform to the standard details of the governmental agency having jurisdiction over the work.
- The Contractor shall be responsible for removal of all silt and debris resulting from his work and deposited in drainage facilities, roadways and other areas. The cost for any necessary remedial action by the Chief Engineer shall be payable by the Contractor.
- The Contractor, at his own expense, shall keep the project area free from dust nuisance. The work shall be in conformance with the air pollution control standards and regulations of the State Department of Health.

Date Revision




THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION
Andrew L. Miyasato
 RONALD N. S. HO & ASSOC., INC.
 ELECTRICAL ENGINEERS


STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION GENERAL CONSTRUCTION AND HECO NOTES I

PEDESTRIAN FACILITIES and ADA COMPLIANCE
 At Various Locations On Oahu, Phase II
 Federal Aid Project No. CMAQ-0300(87)
 SCALE: AS NOTED DATE:


SHEET No. E-2 OF 18 SHEETS



TYP. LOWER HANDHOLE & SEAT ADJUSTMENT DETAIL
NOT TO SCALE




TYP. RAISED HANDHOLE & SEAT ADJUSTMENT DETAIL
NOT TO SCALE



NOTES:

- Provide Pavement Structure as Shown or Match Existing Pavement Structure, Whichever is Greater.
- Install 8 Mil. Thick Orange Color Warning Tape 4" Wide, Entire Length. Tape should read "Warning - Stop Digging - Call Verizon Hawaii. Communications Cable Below. Failure to Comply could result in Legal Action".

TYPICAL TRENCH RESTORATION DETAIL
NOT TO SCALE



DUCT ENCASEMENT DETAILS
NOT TO SCALE


ORIGINAL PLAN	DATE
SURVEY PLOTTED BY	
DESIGNED BY	
NOTE BOOK	
QUANTITIES BY	
CHECKED BY	
No.	

LAST SAVE: 12/05/02 @ 07:23:22 BY: RM PLOT SC 1'-0"=1'

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-0300(87)	2002	77	145


Electrical Plan Notes:

- 1-2"C With Cable Complement Required for Pedestrian and Traffic Signal Heads and Push Buttons, See Duct Section A, Sheet E-2.
- Penetrate Handhole for New Conduit Entry. Repair to Match Exst.
- Provide Type 1-10 Standard Installed. Provide New Necessary Mounting Equipment & Accessories as Required and as Shown on the Plans. Relocate Traffic Signal Heads onto Pole. Provide New ADA Compliant Pedestrian Push Button, See Details on Sheets E-12, E-13, E-14, E-17.
- Replace Existing Traffic Signal Pullbox with New Type C Pullbox, Flush with New Finish Grade.



LIKELIKE HWY/WILSON STREET TRAFFIC SIGNAL PLAN SCALE: 1"=10'

Date Revision



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION
Andrew I. Miyasato
RONALD N. S. HO & ASSOC., INC.
ELECTRICAL ENGINEERS

STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION LAYOUT PLAN - 1 LIKELIKE HIGHWAY/WILSON STREET TRAFFIC SIGNAL PLAN

PEDESTRIAN FACILITIES and ADA COMPLIANCE
At Various Locations On Oahu, Phase II
Federal Aid Project No. CMAQ-0300(87)
SCALE: AS NOTED DATE:
SHEET No. E-3 OF 18 SHEETS

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-0300(87)	2002	78	145

Electrical Plan Notes:

- 1

1-2"C With Cable Complement Required for Pedestrian and Traffic Signal Heads and Push Buttons, See Duct Section A, Sheet E-2.
- 2

Relocate Exst Traffic Signal Standard onto New Concrete Base. Provide New Necessary Mounting Equipment & Accessories as Required and as shown on the Plans, and Relocate Traffic Signal Heads as shown on the Plans, onto New Concrete Base. Demolish Exst Concrete Base 2Ft Below Finish Grade. Remove Exst Pedestrian Push Button and Provide New ADA Compliant Pedestrian Push Buttons. See Details on Sheets E-12, E-13, E-14, E-17.
- 3

Penetrate Handhole for New Conduit Entry. Repair to Match Exst.
- 4


Provide Type 1-10 Standard Installed. Provide New Necessary Mounting Equipment & Accessories as Required and as Shown on the Plans. Relocate Traffic Signal Heads onto Pole. Provide new ADA Compliant Pedestrian Push Button, See Details on Sheets E-12, E-13, E-14, E-17.
- 5

Exst Traffic Signal Standard to Remain, Contractor shall Provide Necessary Accessories as Directed by City Inspector to Adjust Standard to New Finish Grade. Provide New Necessary Mounting Equipment & Accessories as Required and as shown on the Plans, and Relocate Traffic Signal Heads as shown on the Plans, Provide New ADA Compliant Pedestrian Push Button, See Details on Sheets E-12, E-13, E-14, E-17. Coordinate Push Button Location With New Ramp Contractor.
- 6

Replace Existing Traffic Signal Pullbox with New Type A Pullbox, Flush with New Finish Grade.
- 7

Intercept Existing Traffic Signal Conduits with New Type "C" Traffic Signal Handhole. Demolish Existing Traffic Signal Pullbox.

Date Revision



STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION



LAYOUT PLAN 4
KOKOHEAD AVENUE/HARDING AVENUE
TRAFFIC SIGNAL PLAN

PEDESTRIAN FACILITIES and ADA COMPLIANCE
At Various Locations On Oahu, Phase II
Federal Aid Project No. CMAQ-0300(87)

SCALE: AS NOTED DATE:
SHEET No. E-4 OF 18 SHEETS


ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DESIGNED BY	
QUANTITIES BY	CHECKED BY	
No.		

LAST SAVE: 12/02/02 @ 07:41:34 BY: RMI PLOT 30: 1100
C:\WORK\PROJECTS\2002\KOKO HEAD\KOKO HEAD E2D.MXD




KOKO HEAD AVENUE/HARDING AVENUE TRAFFIC SIGNAL PLAN
SCALE: 1"=10'

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-0300(87)	2002	80	145




Notes:


- 1 1-2" C With Cable Complement Required for Pedestrian and Traffic Signal Heads and Push Buttons, See Duct Section A, Sheet E-2.
- 2 Relocate Exst Traffic Signal Standard onto New Concrete Base. Provide New Necessary Mounting Equipment & Accessories as Required and as shown on the Plans, and Relocate Traffic Signal Heads as shown on the Plans, onto New Concrete Base. Demolish Exst Concrete Base 2Ft Below Finish Grade. Remove Exst Pedestrian Push Button and Provide New ADA Compliant Pedestrian Push Buttons. See Details on Sheets E-12, E-13, E-14, E-17.
- 3 Penetrate Handhole for New Conduit Entry. Repair to Match Exst.
- 4 Provide Type 1-10 Standard Installed. Provide New Necessary Mounting Equipment & Accessories as Required and as Shown on the Plans. Relocate Traffic Signal Heads onto Pole. Provide new ADA Compliant Pedestrian Push Button, See Details on Sheets E-12, E-13, E-14, E-17.
- 5 Exst Traffic Signal Standard to Remain, Contractor shall Provide Necessary Accessories as Directed by City Inspector to Adjust Standard to New Finish Grade. Provide New Necessary Mounting Equipment & Accessories as Required and as shown on the Plans, and Relocate Traffic Signal Heads as shown on the Plans, Provide New ADA Compliant Pedestrian Push Button, See Details on Sheets E-12, E-13, E-14, E-17. Coordinate Push Button Location With New Ramp Contractor.
- 6 Replace Existing Traffic Signal Pullbox with New Type A Pullbox, Flush with New Finish Grade.



CASTLE JUNCTION TRAFFIC SIGNAL PLAN
SCALE: 1"=10'



Date	Revision



STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
LAYOUT PLAN 6
CASTLE JUNCTION
TRAFFIC SIGNAL PLAN
PEDESTRIAN FACILITIES and ADA COMPLIANCE
At Various Locations On Oahu, Phase II
Federal Aid Project No. CMAQ-0300(87)
SCALE: 1"=10' DATE:


ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
DRAWN BY		
DESIGNED BY		
CHECKED BY		

LAST SAVE: 12/17/02 @ 11:16:15 BY: GRIFFIN, M.D.
Z:\ROAD PROJECTS\22001\0606-const\station\REFS-ADA-BR-X2D-CASTLEJUNCTION

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-0300(87)	2002	81	145

Electrical Plan Notes:


- 1-2"C with Cable Complement Required for Street Light Connection, See Duct Section A, Sheet E-2.
- Locate Existing Street light Pullbox, Replace with New Type A Pullbox, Flush with New Finish Grade.
- Relocate Existing Street Light, Provide New Concrete Base, Wiring and Conneciton, Complete and in Place.



Date	Revision



SURVEY PLOTTED BY	DATE
DRAWN BY	
REVISIONS BY	
NOTE BOOK	
QUANTITIES BY	
CHECKED BY	
No.	

LAST SAVE: 12/13/02 @ 09:04:55 BY: TE PLAT SC: 1-10
2: VACUUM PROJECT: 2001 V07 Jan-10p XREFS: X20-PAUC



KAMEHAMEHA HIGHWAY/HAWAII PACIFIC UNIVERSITY ELECTRICAL PLAN

SCALE: 1"=10'



STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
LAYOUT PLAN - 7
KAMEHAMEHA HIGHWAY/HAWAII PACIFIC UNIVERSITY ELECTRICAL PLAN
PEDESTRIAN FACILITIES and ADA COMPLIANCE
At Various Locations On Oahu, Phase II
Federal Aid Project No. CMAQ-0300(87)
SCALE: AS NOTED
DATE:

SHEET No. E-7 OF 18 SHEETS


FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-0300(87)	2002	82	145

Electrical Plan Notes:

- 1-2" C With Cable Complement Required for Pedestrian and Traffic Signal Heads and Push Buttons, See Duct Section A, Sheet E-2.
- Relocate Exst Traffic Signal Standard onto New Concrete Base. Provide New Necessary Mounting Equipment & Accessories as Required and as shown on the Plans, and Relocate Traffic Signal Heads as shown on the Plans, onto New Concrete Base. Demolish Exst Concrete Base 2Ft Below Finish Grade. Remove Exst Pedestrian Push Button and Provide New ADA Compliant Pedestrian Push Buttons. See Details on Sheet E-12, E-13, E-14, E-17.
- Penetrate Handhole for New Conduit Entry. Repair to Match Exst.
- Demolish Exst Traffic Signal Pullbox
- Exst Traffic Signal Standard to Remain, Contractor shall Provide Necessary Accessories as Directed by City Inspector to Adjust Standard to New Finish Grade. Provide New Necessary Mounting Equipment & Accessories as Required and as shown on the Plans, and Relocate Traffic Signal Heads as shown on the Plans, Provide New ADA Compliant Pedestrian Push Button, See Details on Sheets E-12, E-13, E-14, E-17. Coordinate Push Button Location with New Ramp Contractor.
- Replace Existing Traffic Signal Pullbox with New Type C Pullbox, Flush with New Finish Grade.
- Provide Type 1-10 Traffic Signal Standard Installed. Provide New Necessary Mounting Equipment & Accessories as Required and as Shown on the Plans. Provide New Traffic Signal Heads onto Pole. Provide New ADA Compliant Pedestrian Pushbutton, See Details on Sheets E-22, E-23, E-30, E-31.

DATE	SURVEY PLOTTED BY
DATE	DESIGNED BY
DATE	CHECKED BY


LAST DATE: 12/15/02 © 09:35:38 BY: TE PLOT 82: 1-10
KANEHE DRIVE/TRAFFIC SIGNAL PLAN



KANEHE BAY DRIVE/MOKULELE DRIVE TRAFFIC SIGNAL PLAN


SCALE: 1"=10'

10' 5' 0' 10' 20' 30'
SCALE: 1"=10'
GRAPHIC SCALE




STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
LAYOUT PLAN - 8
KANEHEBAY DRIVE/MOKULELE DRIVE
TRAFFIC SIGNAL PLAN
PEDESTRIAN FACILITIES and ADA COMPLIANCE
At Various Locations On Oahu, Phase II
Federal Aid Project No. CMAQ-0300(87)
SCALE: AS NOTED
DATE:
SHEET No. E-8 OF 18 SHEETS

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-0300(87)	2002	84	145




SECTION A-A




SECTION B-B

A TYPE "A" PULLBOX
E-10 OLD TYPE "B"
NOT TO SCALE




SECTION A-A




SECTION B-B

B TYPE "B" PULLBOX (OLD TYPE "C")
E-10 NOT TO SCALE



SECTION A-A



SECTION B-B


C TYPE "C" PULLBOX (OLD TYPE "D")
E-10 NOT TO SCALE

All Dimensions on this Sheet are in Millimeters

DATE	12-13-02
SURVEY PROVIDED BY	STATE OF HAWAII
DESIGNED BY	ANDREW L. MANNING
DRAWN BY	ANDREW L. MANNING
CHECKED BY	ANDREW L. MANNING
NOTED BY	ANDREW L. MANNING
APPROVED BY	ANDREW L. MANNING
DATE	12-13-02

LAST SHEET OF 145 SHEETS

Date Revision




STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
**TRAFFIC SIGNAL
PULLBOX DETAILS I**
PEDESTRIAN FACILITIES and ADA COMPLIANCE
At Various Locations On Oahu, Phase II
Federal Aid Project No. CMAQ-0300(87)
SCALE: AS NOTED DATE:
SHEET No. E-10 OF 18 SHEETS


FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-0300(87)	2002	85	145

GENERAL NOTES FOR TRAFFIC SIGNAL PULLBOX DETAILS ON SHEET E-10

1. Provide a minimum of one 16 x 2.5m copperweld ground rod in each pullbox. When directed by the traffic signal inspector/engineer, install additional ground rods. Cost of ground rods shall be incidental to the pullboxes.
2. All pre-cast concrete pullboxes shall be manufactured in two pieces.
3. The pullbox with cover shall be capable of supporting an ms 18 loading.
4. The maximum weight of the pullbox cover shall not exceed 27 kilograms.
5. The openings for the conduits on all pullboxes shall be pre-cast concrete knockouts.
6. After installing the conduits in the openings of the pullboxes, the Contractor shall fill the excess opening in the pre-cast knockouts with concrete mortar.
7. Prior to installing the pullboxes, the Contractor shall level the bottom of the trench and achieve a minimum of 95% relative compaction of the bottom of the trench.
8. All concrete shall be class A (25MPA, min.)
9. Rebars shall be grade 300 and all lapped splices shall be 360mm minimum.
10. The #57 or #67 size aggregate shall conform to latest version of AASHTO M43 (ASTM D 448).
11. Type "C" pullbox shall be installed in a location protected from vehicular traffic (i.e. raised sidewalk, behind a.c. curbs, traffic signal standard or pipe guards).




PLAN VIEW



ELEVATION

Note: See Highway Lighting and Traffic Signal Pullbox Details on Sht E-10


B E-11 POLYMER CONCRETE COVER NOT TO SCALE




Note: See Highway Lighting and Traffic Signal Pullbox Details on Sht E-10

D E-11 TYPICAL CONSTRUCTION JOINT DETAIL NOT TO SCALE

All Dimensions on this Sheet are in Millimeters Unless Otherwise Shown




C E-11 STREET LIGHT POLE RISER DETAIL NOT TO SCALE



A E-11 TYPICAL FLASHING COMPOUND WATERPROOFING DETAILS NOT TO SCALE

SURVEY PLOTTED BY	DATE
DRAWN BY	
DESIGNED BY	
QUANTITIES BY	
CHECKED BY	
NO.	


LAST SAVE: 12/09/02 @ 09:13:54 BY: E. PLOT 50: 1-0-01
C:\ADDP\PROJECTS\2200\W122001.DWG




STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION TRAFFIC SIGNAL PULLBOX DETAILS II	PEDESTRIAN FACILITIES and ADA COMPLIANCE At Various Locations On Oahu, Phase II Federal Aid Project No. CMAQ-0300(87) SCALE: AS NOTED DATE:
--	---

Date	Revision
------	----------

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-0300(87)	2002	86	145




- NOTES FOR TYPE II STANDARD:
- Standard shall be designed in accordance with "Standard Specifications for Structural Supports for Highway Signs, Luminaires and Traffic Signals".
 - Mounting for signals at intermediate points of mast arm shall be of the adjustable type.
 - Signals shall be centered over lane lines.
 - Submit shop drawings for approval.



A E-12 TYPE I TRAFFIC SIGNAL STANDARD NOT TO SCALE

B E-12 TYPE II TRAFFIC SIGNAL STANDARD NOT TO SCALE

C E-12 TYPE III TRAFFIC SIGNAL STANDARD NOT TO SCALE




D E-12 TYPE 332A TRAFFIC SIGNAL CONTROLLER CABINET DETAIL NOT TO SCALE

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	


LAST DATE 12/12/02
Z:\ACAD\PROJECTS\2002\142-220\142-220.dwg

Date	Revision



STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
TRAFFIC SIGNAL DETAILS I

PEDESTRIAN FACILITIES and ADA COMPLIANCE
At Various Locations On Oahu, Phase II
Federal Aid Project No. CMAQ-0300(87)
SCALE: AS NOTED DATE:
SHEET No. E-12 OF 18 SHEETS




TYPE "C" CONCRETE BASE		
TYPE OF STANDARD	"c"	"d" BARS
II - 18	5'-0"	12 - #6
II - 20	5'-6"	12 - #6
II - 25	6'-0"	12 - #6
II - 30	6'-6"	12 - #8
II - 35	7'-0"	12 - #8
II - 40	8'-0"	12 - #8
III - 18	5'-6"	12 - #6
III - 20	6'-0"	12 - #6
III - 25	6'-6"	12 - #8
III - 30	6'-6"	12 - #8
III - 35	7'-0"	12 - #8
III - 40	8'-0"	12 - #8
III - 45	10'-0"	12 - #8


Typical Standard Designation: II - 25

Type Mast Arm Length

- NOTES:
- Concrete shall be class "B".
 - Type "C" concrete base shall be used for types II and III traffic signal standards.
 - Design lateral pressure: 1,500 psf.
 - Conduit bend is incidental to concrete base.




- NOTES:
- Concrete shall be class "B".
 - Dimensions shall be altered to suit controller cabinet actually furnished.
 - Conduit bends and drain are incidental to concrete base.
 - Refer to cabinet manufacturer's specifications for details of anchor bolts and base setting.
 - All exposed surfaces of concrete base shall be given a Class 2, rubbed finish.




- NOTES:
- Concrete shall be class "B".
 - Type "A" concrete base shall be used for type I-10, I-7 and I-3 standards.
 - Conduit bend is incidental to concrete base construction.

A TYPE "A" CONCRETE BASE
E-13 NOT TO SCALE



B TYPE "C" CONCRETE BASE
E-13 NOT TO SCALE



D TYPE "D" CONCRETE BASE DETAIL
E-13 NOT TO SCALE

C TYPICAL STANDARD & PEDESTAL DETAIL
E-13 NOT TO SCALE

ANDREW L. MYNARD
LICENSED PROFESSIONAL ENGINEER
No. 4340-E
HAWAII, U.S.A.

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION

ANDREW L. MYNARD
12-13-02
RONALD N. S. HO & ASSOC., INC.
ELECTRICAL ENGINEERS

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION


TRAFFIC SIGNAL DETAILS II

PEDESTRIAN FACILITIES and ADA COMPLIANCE
At Various Locations On Oahu, Phase II
Federal Aid Project No. CMAQ-0300(87)

SCALE: AS NOTED DATE:


SHEET No. E-13 OF 18 SHEETS

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-0300(87)	2002	88	145







DETAIL NOTES:

- The pedestrian pushbutton unit shall consist of a one piece assembly with a raise walking man, arrow indication and push button.
- The pushbutton activator shall be of the mushroom plunger type, ADA acceptable, 2 inches in diameter that requires less than 5 lbs. of pressure to activate.
- The raised man and arrows shall be directional and match the directional indication as shown on the plans.
- The pushbutton shall be tamper proof, weatherproof and constructed so that electrical shocks are impossible.
- The color scheme shall be:
White - Man, arrow and pushbutton
Black - Background



A
E-14 PEDESTRIAN PUSHBUTTON DETAILS
NOT TO SCALE



NOTES:


- Stainless steel bands shall be 1/2" wide x .050" thick, minimum. tensile strength shall be 100,000 psi minimum.
- Upper arm, lower arm and vertical support tube shall be of 356 cast aluminum.
- All wiring shall be concealed.
- Vertical tube clamp shall be of malleable iron, grade 32510.
- All aluminum parts shall have an alodine 1200 finish.
- Signal as noted on plans.
- Maintain 16" min. clearance at rear of all programmed faces.

B
E-14 PEDESTRIAN SIGNAL MOUNTING DETAILS
NOT TO SCALE

SURVEY PLOTTED BY	DATE
DRAWN BY	
DESIGNED BY	
QUANTITIES BY	
CHECKED BY	
NO.	

LAST SAVE: 12/06/02 @ 09:16:51 BY: TE PLT 30 T-0-01
2: ACD/PROJETS/2209/W4.2209.18443


Date	Revision
------	----------




STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION TRAFFIC SIGNAL DETAILS III	PEDESTRIAN FACILITIES and ADA COMPLIANCE At Various Locations On Oahu, Phase II Federal Aid Project No. CMAQ-0300(87) SCALE: AS NOTED DATE:
---	---

SHEET No. E-14 OF 18 SHEETS


FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-0300(87)	2002	89	145



TOP OF POLE – ONE WAY MOUNTING



TOP OF POLE – TWO WAY MOUNTING




BRACKET MOUNT – ONE WAY

BRACKET MOUNT – TWO WAY

NOTES:

1. Stainless steel bands shall be 1/2" wide x .050" thick, minimum. tensile strength shall be 100,000 psi minimum.
2. Upper arm, lower arm and vertical support tube shall be of 356 cast aluminum.
3. All wiring shall be concealed.
4. Vertical tube clamp shall be of malleable iron, grade 32510.
5. All aluminum parts shall have an alodine 1200 finish.
6. Signal as noted on plans.
7. Maintain 16" min. clearance at rear of all programmed faces.




ADJUSTABLE MAST ARM ONE WAY MOUNTING AT INTERMEDIATE POINT

A
E-15 VEHICULAR SIGNAL MOUNTING DETAILS
NOT TO SCALE

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DESIGNED BY	
QUANTITIES BY	CHECKED BY	
No.		

LAST SAVE: 12/05/02 @ 08:17:41 BY: TE PLOT 30 1'-0"=1'




STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
TRAFFIC SIGNAL DETAILS IV

PEDESTRIAN FACILITIES and ADA COMPLIANCE
At Various Locations On Oahu, Phase II
Federal Aid Project No. CMAQ-0300(87)


SCALE: AS NOTED DATE:

SHEET No. E-15 OF 18 SHEETS


FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-0300(87)	2002	90	145




TYPICAL VEHICULAR AND PEDESTRIAN SIGNAL MOUNTINGS



A TYPICAL SIGNAL ARRANGEMENTS



B TYPICAL PEDESTAL/MAST ARM INSTALLATION OF EVP DETECTOR



C EVP DETECTOR HORIZONTAL MOUNTING DETAIL

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
	DESIGNED BY	
	CHECKED BY	
	APPROVED BY	
	DATE	

LAST SAVE: 12/05/02 @ 09:18:35 BY: TE PLAT SE 1-0-01
Z:\ACAD\PROJECTS\22091\16-22091-16.dwg

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION

Andrew L. Mays

RONALD N. S. HO & ASSOC., INC. ELECTRICAL ENGINEERS

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION


TRAFFIC SIGNAL DETAILS V

PEDESTRIAN FACILITIES and ADA COMPLIANCE
At Various Locations On Oahu, Phase II
Federal Aid Project No. CMAQ-0300(87)


SCALE: AS NOTED DATE:

SHEET No. E-16 OF 18 SHEETS


FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-0300(87)	2002	92	145



A
E-17 TRAFFIC SIGNAL STANDARD LOCATION @ CURB RAMP TYPE "A"
NOT TO SCALE



B
E-17 TRAFFIC SIGNAL STANDARD LOCATION @ CURB RAMP TYPE "B" MODIFIED
NOT TO SCALE




C
E-17 TRAFFIC SIGNAL STANDARD LOCATION @ CURB RAMP TYPE "B"
NOT TO SCALE

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DESIGNED BY	
QUANTITIES BY	CHECKED BY	
No.		

LAST DATE: 12/02/02 @ 08:54:43 BY: THE PLOT 30 1'-0"=1"


Date	Revision




STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
TRAFFIC SIGNAL DETAILS VI

PEDESTRIAN FACILITIES and ADA COMPLIANCE
At Various Locations On Oahu, Phase II
Federal Aid Project No. CMAQ-0300(87)
SCALE: AS NOTED DATE:
SHEET No. E-17 OF 18 SHEETS


FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-0300(87)	2002	75	145



A
E-18 **STREET LIGHT STANDARD (STATE)**
Not to Scale



B
E-18 **CONCRETE BASE ELEVATION (STATE)**
Not to Scale



Notes:

1. All secondary cables not shown for clarity.

C
E-18 **STREET LIGHT WIRING DIAGRAM**

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	

LAST DATE 12/02/03
Z:\ACAD\PROJECTS\22001\18.2201-1848

Date	Revision
------	----------

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION

Andrew L. Miyasato

12-13-03

RONALD N. S. HO & ASSOC., INC. ELECTRICAL ENGINEERS

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

STREET LIGHTING DETAILS

PEDESTRIAN FACILITIES and ADA COMPLIANCE
At Various Locations On Oahu, Phase II
Federal Aid Project No. CMAQ-0300(87)

SCALE: AS NOTED DATE:

SHEET No. E-18 OF 18 SHEETS