


INDEX TO DRAWINGS	
SHEET NO.	DESCRIPTION
1	TITLE SHEET
2	STANDARD PLANS SUMMARY
3	GENERAL NOTES, LEGEND, AND ABBREVIATIONS
4	GRADING NOTES
5 – 8	UTILITY NOTES
9 – 11	WATER POLLUTION AND EROSION CONTROL NOTES
12	BEST MANAGEMENT PRACTICE NOTES AND DETAILS
13	EROSION CONTROL PLAN – KAMEHAMEHA HIGHWAY
14	EROSION CONTROL PLAN – KANEEOHE BAY DRIVE
15 – 16	BIOSWALE TYPICAL SECTION
17 –21	BIOSWALE PLANS – INTERSTATE ROUTE H-3
22 – 29	BIOSWALE PROFILES – INTERSTATE ROUTE H-3
30	BIOSWALE PLAN AND PROFILE – KAMEHAMEHA HIGHWAY
31	KAHEOHE BAY DRIVE BMP RETROFIT PLAN
32	KAHEOHE BAY DRIVE BMP RETROFIT SECTIONS
33	KAHEOHE BAY DRIVE BMP RETROFIT DETAILS
34 – 35	BIOSWALE DETAILS
36	FREEWAY WORK ZONE SIGNING PLAN, NOTES & DETAILS
37	LOW SPEED UNDIVIDED HIGHWAY WORK ZONE SIGNING PLAN, NOTES & DETAILS
38 – 39	TRAFFIC CONTROL PLANS INTERSTATE ROUTE H-3
40 – 42	TRAFFIC CONTROL PLANS – KAMEHAMEHA HIGHWAY
43	TRAFFIC CONTROL PLANS – KANEEOHE BAY DRIVE


FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-02-11R	2014	1	43






STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION  
HONOLULU, HAWAII

PLANS FOR  
**MISCELLANEOUS PERMANENT  
BEST MANAGEMENT PRACTICES  
ON OAHU**  
PROJECT NO. HWY-0-02-11R

DISTRICT OF KOOLAUPOKO  
ISLAND OF OAHU




ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
	TRACED BY	
	CHECKED BY	
	QUANTITIES BY	
	CHECKED BY	




DEPARTMENT OF TRANSPORTATION STATE OF HAWAII	
APPROVED:	
DIR. OF TRANSPORTATION	DATE


FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-02-11R	2014	12	43




INLET PROTECTION  
AT GRATED DROP INTAKE (GDI)  
Not to Scale




INLET PROTECTION  
AT EXISTING CATCH BASIN  
Not to Scale



H3 JOHN A. BURNS FREEWAY (STATE)



SECTION A-A  
Not to Scale  
GRAVEL BAG CHECK DAM DETAIL - H3 STATION 637+05  
Not to Scale



FIBER ROLL DETAIL  
Not to Scale

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

SIGNATURE: \_\_\_\_\_ EXPIRATION DATE OF THE LICENSE: 04/30/14

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**BEST MANAGEMENT PRACTICE DETAILS**

MISCELLANEOUS PERMANENT BEST MANAGEMENT PRACTICES ON OAHU



PROJECT NO. HWY-0-02-11R

Scale: Not to Scale Date: May, 2012


ORIGINAL PLAN	DATE
DRAWN BY	
CHECKED BY	
NOTED BY	
QUANTITIES BY	
CHECKED BY	
N#	

T:\16523A-Permanent BMP\Cadd\Sheets/misc/G-11.dgn

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-02-11R	2014	13	43



GRAVEL BAG CHECK DAM DETAIL  
Not to Scale





THIS WORK WAS PREPARED BY ME  
OR UNDER MY SUPERVISION.

SIGNATURE \_\_\_\_\_


STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**EROSION CONTROL PLAN**  
**KAMEHAMEHA HIGHWAY**  
**MISCELLANEOUS PERMANENT BEST**  
**MANAGEMENT PRACTICES ON OAHU**  
PROJECT NO. HWY-0-02-11R  
Scale: 1"=40' Date: April, 2014


FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-02-11R	2014	14	43



**SILT FENCE SECTION**  
Scale: NTS



**SANDBAG DAM SECTION**  
Scale: NTS



ORIGINAL PLAN	DATE
DRAWN BY	
CHECKED BY	
NOTED BY	
QUANTITIES BY	
CHECKED BY	
DATE	

T:\16523A-Permanent BMP\Cadd\Sheets\ECF\KBD\_BMP\_1.dgn

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.


SIGNATURE \_\_\_\_\_ EXPIRATION DATE OF THE LICENSE 04/30/14

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**EROSION CONTROL PLAN**  
**KANEHOE BAY DRIVE**  
**MISCELLANEOUS PERMANENT BEST MANAGEMENT PRACTICES ON OAHU**  
**PROJECT NO. HWY-0-02-11R**

Scale: 1"=20' Date: April, 2014

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-02-11	2011		41



SURVEY PLOTTED BY	DATE
DRAWN BY	
CHECKED BY	
NOTE BOOK	
CHECKED BY	
N°	

GERALD D. ANDRADE  
LICENSED PROFESSIONAL ENGINEER  
No. 10377-C  
HAWAII, U.S.A.

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.


SIGNATURE \_\_\_\_\_ EXPIRATION DATE OF THE LICENSE 04/30/12

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

MISCELLANEOUS PERMANENT BEST MANAGEMENT PRACTICES ON OAHU  
PROJECT NO. HWY-0-02-11

Scale: \_\_\_\_\_ Date: March, 2012

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-02-11	2011		41



SURVEY PLOTTED BY	DATE
DRAWN BY	
REVIEWED BY	
QUANTITIES BY	
CHECKED BY	

ORIGINAL PLAN	Nº
NOTE BOOK	


THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

SIGNATURE \_\_\_\_\_ EXPIRATION DATE OF THE LICENSE 04/30/12

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

MISCELLANEOUS PERMANENT BEST  
MANAGEMENT PRACTICES ON OAHU  
PROJECT NO. HWY-0-02-11  
Scale: \_\_\_\_\_ Date: March, 2012

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-02-11	2011		41



SURVEY PLOTTED BY	DATE
DRAWN BY	
CHECKED BY	
QUANTITIES BY	
CHECKED BY	
ORIGINAL PLAN	
NOTE BOOK	
N°	

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

SIGNATURE \_\_\_\_\_ EXPIRATION DATE OF THE LICENSE 04/30/12


STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

MISCELLANEOUS PERMANENT BEST  
MANAGEMENT PRACTICES ON OAHU  
PROJECT NO. HWY-0-02-11

Scale: \_\_\_\_\_ Date: March, 2012



FED. ROAD DIST. NO.	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HWY-0-02-11	2011		41



SURVEY PLOTTED BY	DATE
DRAWN BY	
CHECKED BY	
NOTE BOOK	
QUANTITIES BY	
CHECKED BY	
N°	

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

SIGNATURE \_\_\_\_\_ EXPIRATION DATE OF THE LICENSE 04/30/12

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

MISCELLANEOUS PERMANENT BEST  
MANAGEMENT PRACTICES ON OAHU  
PROJECT NO. HWY-0-02-11


Scale: \_\_\_\_\_ Date: March, 2012

SHEET No. \_\_\_\_\_ OF \_\_\_\_\_ SHEETS





FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-02-11	2011		41



SURVEY PLOTTED BY	DATE
DRAWN BY	
CHECKED BY	
NOTED BY	
QUANTITIES BY	
CHECKED BY	
ORIGINAL PLAN	
NOTE BOOK	
N°	

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

SIGNATURE \_\_\_\_\_ EXPIRATION DATE OF THE LICENSE 04/30/12


STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

MISCELLANEOUS PERMANENT BEST MANAGEMENT PRACTICES ON OAHU  
PROJECT NO. HWY-0-02-11

Scale: \_\_\_\_\_ Date: March, 2012



FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-02-11	2011		41



SURVEY PLOTTED BY	DATE
DRAWN BY	
CHECKED BY	
NOTE BOOK	
QUANTITIES BY	
CHECKED BY	

GERALD D. ANDRADE  
LICENSED PROFESSIONAL ENGINEER  
No. 10377-C  
HAWAII, U.S.A.

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

MISCELLANEOUS PERMANENT BEST  
MANAGEMENT PRACTICES ON OAHU  
PROJECT NO. HWY-0-02-11

Scale: Date: March, 2012

THIS WORK WAS PREPARED BY ME  
OR UNDER MY SUPERVISION:

SIGNATURE EXPIRATION DATE OF THE LICENSE

04/30/12

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-02-11	2011		41

Install Inlet Protection

Install Inlet Protection

Install Inlet Protection


Install Inlet Protection

Install Inlet Protection

Install Inlet Protection

Contractor's Staging and Area

SURVEY PLOTTED BY	DATE
DRAWN BY	
CHECKED BY	
NOTE BOOK	
QUANTITIES BY	
CHECKED BY	



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.


SIGNATURE \_\_\_\_\_ EXPIRATION DATE OF LICENSE 03/30/12

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

MISCELLANEOUS PERMANENT BEST MANAGEMENT PRACTICES ON OAHU  
PROJECT NO. HWY-0-02-11

Scale: \_\_\_\_\_ Date: March, 2012

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-02-11	2011		41



SURVEY PLOTTED BY	DATE
DRAWN BY	
CHECKED BY	
NOTE BOOK	
QUANTITIES BY	
CHECKED BY	
N°	

GERALD D. ANDRADE  
LICENSED PROFESSIONAL ENGINEER  
No. 10377-C  
HAWAII, U.S.A.


THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

SIGNATURE \_\_\_\_\_ EXPIRATION DATE OF THE LICENSE 04/30/12

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

MISCELLANEOUS PERMANENT BEST MANAGEMENT PRACTICES ON OAHU  
PROJECT NO. HWY-0-02-11

Scale: \_\_\_\_\_ Date: March, 2012



**Note:**


- 1) Restore area to equivalent of original condition once construction is completed.
- 2) Contractor shall ensure proper protection for Equipment Storage Area.

**EQUIPMENT STORAGE AREA**  
**Not to Scale**



# Hard Surface Guard™

## End-of-Run Details



### Maintenance

Perform maintenance as required. Inspect following rainfall events and at least daily during prolonged rainfall. Maintain to provide an adequate sediment holding capacity. Debris shall be removed daily and sediment shall be removed when the sediment accumulation reaches 50% of the barrier height. Removed sediment shall be incorporated in the project at designated locations.


**Important:** All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application, and disclaims any liability regarding its use. ERTEC Environmental System's only obligations are those in the ERTEC Environmental Systems Standard Terms and Conditions of Sale for this product, and in no case will ERTEC Environmental Systems or its distributors be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Specifications are subject to change without notice. In addition, ERTEC Environmental Systems reserves the right to make changes, without notification to Buyer, to processing or materials that do not affect compliance with any applicable specification.

**\*\* NOT TO SCALE \*\***

#	Date	Revisions	ERTEC Environmental Systems <a href="http://www.ertecsystems.com/">http://www.ertecsystems.com/</a>		ERTEC		File Name: Ertec_Installation_Details_HSG.Dwg
1	02/28/07	Initial Drawings					
2	00/00/00						
3	00/00/00		1150 Ballena Blvd. Suite 250 Alameda, CA 94501		P. 866-521-0724 F. 510-521-3972		Layout Name: P2 End-of-run
4	00/00/00						Default Print Size: 8.5" x 11" Page 2 of 4



## Hard Surface Guard™

### Angled Installation - 90°



**Note:**

1. To bend Hard Surface Guard™ around obstacles, first slit flap and gasket through to the horizontal crease - with sharp knife or shears.
2. Then bend to desired angle, in either direction, as shown.



**Note:**


1. If bend is in this direction, locate gravel bag at the angle to prevent underflow

### Maintenance

Perform maintenance as required. Inspect following rainfall events and at least daily during prolonged rainfall. Maintain to provide an adequate sediment holding capacity. Debris shall be removed daily and sediment shall be removed when the sediment accumulation reaches 50% of the barrier height. Removed sediment shall be incorporated in the project at designated locations.


**Important:** All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application, and disclaims any liability regarding its use. ERTEC Environmental System's only obligations are those in the ERTEC Environmental Systems Standard Terms and Conditions of Sale for this product, and in no case will ERTEC Environmental Systems or its distributors be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Specifications are subject to change without notice. In addition, ERTEC Environmental Systems reserves the right to make changes, without notification to Buyer, to processing or materials that do not affect compliance with any applicable specification.

**\*\* NOT TO SCALE \*\***

#	Date	Revisions	ERTEC Environmental Systems			File Name:
1	02/28/07	Initial Drawings	<a href="http://www.ertecsystems.com/">http://www.ertecsystems.com/</a>			Ertec_Installation_Details_HSG.Dwg
2	00/00/00		1150 Ballena Blvd.		Layout Name: P3 Angled Installation - 90°	
3	00/00/00		Suite 250			
4	00/00/00		Alameda, CA 94501			
P. 866-521-0724 F. 510-521-3972						
Default Print Size: 8.5" x 11"						
Page: 3 of 4						


### Anchor Details

## Masonry Nails




1. Install nails flush with netting so that gasket is in good contact with surface.
2. Install 4 to 5 nails per each seven foot segment. Use HILTI X-ZF 1½" fasteners with 23mm pre-mounted steel washer (X-ZF 32 P8 S23) or equivalent with automatic powder-actuated hand tool.

## Gravel Bags, Snake Bags




1. Install anchor flap facing upstream. Place small snake bags or equivalent (gravel bags) containing clean, pea-sized graded gravel every 2.5 feet. Additional bags can be placed on the flap as necessary to assure good gasket to surface contact.

### Bonding Agent



**1. Install bonding agent between gasket and surface. Use PaverBond, Liquid Nails, or other equivalent. Anchor with gravel bags or other weights until set.**

## Concrete Anchors




1. Install anchors flush with netting so that gasket is in good contact with surface.
2. Install 4 to 5 anchors per each seven foot segment. Use Red Head Redi-Drive or Hammer Set  $\frac{1}{4}" \times 1\frac{1}{4}"$  anchors or equivalent.

Perform maintenance as required. Inspect following rainfall events and at least daily during prolonged rainfall. Maintain to provide an adequate sediment holding capacity. Debris shall be removed daily and sediment shall be removed when the sediment accumulation reaches 50% of the barrier height. Removed sediment shall be incorporated in the project at designated locations.

**Important:** All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application, and disclaims any liability regarding its use. ERTEC Environmental System's only obligations are those in the ERTEC Environmental Systems Standard Terms and Conditions of Sale for this product, and in no case will ERTEC Environmental Systems or its distributors be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Specifications are subject to change without notice. In addition, ERTEC Environmental Systems reserves the right to make changes, without notification to Buyer, to processing or materials that do not affect compliance with any applicable specification.

**\*\* NOT TO SCALE \*\***

#	Date	Revisions	ERTEC Environmental Systems <a href="http://www.ertecsystems.com/">http://www.ertecsystems.com/</a>			File Name: Erec_Installation_Details_HSG.Dwg
1	02/28/07	Initial Drawings				Layout Name: P4 Anchor Details
2	00/00/00					Default Print Size: 8.5" x 11"
3	00/00/00					Page: 4 of 4
4	00/00/00					



The Green Snake Bag is a specially engineered UV resistant monofilament geotextile fabric bag intended to be filled with coarse sand or fine clean gravel for use as a sediment control device.

The Green Snakes Bags are commonly used as gravel “wattles” catch basin/curb inlet protection, grated inlet protection, check structures, filter berms, sediment control devices, etc ( see back of brochure for function and common uses )

The Green Snake bag unique physical properties woven seams ( which gives the bag overall strength stronger than traditional welding, gluing and standard sewing seams ). Material makeup ( which gives the Snake bag the ability to conform to irregular terrain better than traditional woven polypropylene bags of similar construction ) and the high UV rating 3 to 7 years ( depending on color ) makes the snake bag the chose for most sediment control projects.

The material is designed to withstand moderate road traffic which is superior over the traditional poly or burlap sand bags that have been used in the past for sediment control as well as their fixed high filtration design enables the sediment laden water turbidity to be reduced as the water passes through a series of snake bags on its way to the drain outlet.

## Physical Properties:

Fabric Structure:	Woven	Yarn: High density polyethylene
Physical Property:	Test Method:	( MEAN ) Roll Value
Grab Tensile Strength:	ASTM D4632	W326/F216 lbs
Fabric Weight:	D-5261	5 oz/sq./yd.
Mullen Burst Strength	ASTM D3786	376 lbs./in/sq.
Water Flow	ASTM D4491	180 gal/ft./sq./min.
UV Resistance ( @2000 hrs )	ASTM D4355	> 70%

Sizing: lengths and diameters can be custom to project needs please see your local distributor for information and availability in your area.

## SILT FENCE REPLACEMENT

20 " *Anaconda Bags* above dry channel ( river underground )

- note toe berm function & curb function above
- Sinks Canyon WY 4-11-05



3 YEARS LATER

## INSTALLATION INSTRUCTIONS:

The green snake bag can be filled with clean coarse sand or gravel ( up to  $\frac{3}{4}$  " ).

For Larger Diameter Anaconda Bags up to 20 " to 24 " 1 " to 1 1/4 " minus gravel should be used.

Caution should be taken not to over fill the bag..... Bags should be placed with the flap side down and the tied end on the flap which creates a seal where the 2 bags intersect. For higher follow areas, 2 row of bags can be installed side by side staggering joints.

## FUNCTIONS:

Snake bags is a practical BMP that can serve multiple functions at the same time.

- Surface protection either on a slope or in a channel
- Minimization of concentrated flows
- Velocity reduction either on slopes or in channels
- Sediment capture



## APPLICATIONS:

Snake bags are suitable for multiple applications:

- *Disrupting concentrated flows*
- *Capturing sediment by ponding*
- *Used in place of silt fence*
- *Rock check dams*
- *Ridge diversions*
- *Pipe socks*
- *Level spreader*
- *Redirecting concentrated flows*
- *Anchoring other devices*
- *Used as toe berms*
- *Rock outlet protection*
- *Inlet protection*
- *Mulch filled filter bags*
- *Oil absorption containment*

Or part of the structure of sediment basins, sediment traps, storm drain diversions, and structural stabilization of streams.



## Mirafi<sup>®</sup> 170N

Mirafi<sup>®</sup> 170N is a needlepunched nonwoven geotextile composed of polypropylene fibers, which are formed into a stable network such that the fibers retain their relative position. Mirafi<sup>®</sup> 170N is inert to biological degradation and resists naturally encountered chemicals, alkalis, and acids.

Mechanical Properties	Test Method	Unit	Minimum Average Roll Value	
			MD	CD
Grab Tensile Strength	ASTM D4632	N (lbs)	801 (180)	801 (180)
Grab Tensile Elongation	ASTM D4632	%	50	50
Trapezoid Tear Strength	ASTM D4533	N (lbs)	334 (75)	334 (75)
CBR Puncture Strength	ASTM D6241	N (lbs)	2003 (450)	
Apparent Opening Size (AOS) <sup>1</sup>	ASTM D4751	mm (U.S. Sieve)	0.15 (100)	
Permittivity	ASTM D4491	sec <sup>-1</sup>	1.4	
Flow Rate	ASTM D4491	l/min/m <sup>2</sup> (gal/min/ft <sup>2</sup> )	4278 (105)	
UV Resistance (at 500 hours)	ASTM D4355	% strength retained	70	

<sup>1</sup> ASTM D 4751: AOS is a Maximum Opening Diameter Value

Physical Properties	Test Method	Unit	Typical Value
Weight	ASTM D5261	g/m <sup>2</sup> (oz/yd <sup>2</sup> )	251 (7.4)
Thickness	ASTM D5199	mm (mils)	1.7 (67)
Roll Dimensions (width x length)	--	m (ft)	4.5 x 91 (15 x 300)
Roll Area	--	m <sup>2</sup> (yd <sup>2</sup> )	418 (500)
Estimated Roll Weight	--	kg (lb)	111 (245)

**Disclaimer:** TenCate assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. TenCate disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.

© 2011 TenCate Geosynthetics North America  
Mirafi<sup>®</sup> is a registered trademark of Nicoln Corporation

