



# GEOLABS, INC.

Geotechnical Engineering

## Soil Classification Log Key

(with deviations from ASTM D2488)

### GEOLABS, INC. CLASSIFICATION\*

GRANULAR SOIL (- #200 <50%)	COHESIVE SOIL (- #200 ≥ 50%)
<ul style="list-style-type: none"> <li>• <b>PRIMARY</b> constituents are composed of the largest percent of the soil mass. Primary constituents are capitalized and bold (i.e., <b>GRAVEL, SAND</b>)</li> <li>• <b>SECONDARY</b> constituents are composed of a percentage less than the primary constituent. If the soil mass consists of 12 percent or more fines content, a cohesive constituent is used (<b>SILTY</b> or <b>CLAYEY</b>); otherwise, a granular constituent is used (<b>GRAVELLY</b> or <b>SANDY</b>) provided that the secondary constituent consists of 20 percent or more of the soil mass. Secondary constituents are capitalized and bold (i.e., <b>SANDY GRAVEL, CLAYEY SAND</b>) and precede the primary constituent.</li> <li>• <b>accessory descriptions</b> compose of the following:               <ul style="list-style-type: none"> <li>with some: &gt;12%</li> <li>with a little: 5 - 12%</li> <li>with traces of: &lt;5%</li> </ul>               accessory descriptions are lower cased and follow the Primary and Secondary Constituents (i.e., <b>SILTY GRAVEL with a little sand</b>)             </li> </ul>	<ul style="list-style-type: none"> <li>• <b>PRIMARY</b> constituents are based on plasticity. Primary constituents are capitalized and bold (i.e., <b>CLAY, SILT</b>)</li> <li>• <b>SECONDARY</b> constituents are composed of a percentage less than the primary constituent, but more than 20 percent of the soil mass. Secondary constituents are capitalized and bold (i.e., <b>SANDY CLAY, SILTY CLAY, CLAYEY SILT</b>) and precede the primary constituent.</li> <li>• <b>accessory descriptions</b> compose of the following:               <ul style="list-style-type: none"> <li>with some: &gt;12%</li> <li>with a little: 5 - 12%</li> <li>with traces of: &lt;5%</li> </ul>               accessory descriptions are lower cased and follow the Primary and Secondary Constituents (i.e., <b>SILTY CLAY with some sand</b>)             </li> </ul>
<b>EXAMPLE:</b> Soil Containing 60% Gravel, 25% Sand, 15% Fines. Described as: <b>SILTY GRAVEL</b> with some sand	

### RELATIVE DENSITY / CONSISTENCY

Granular Soils			Cohesive Soils			
N-Value (Blows/Foot)		Relative Density	N-Value (Blows/Foot)		PP Readings (tsf)	Consistency
SPT	MCS		SPT	MCS		
0 - 4	0 - 7	Very Loose	0 - 2	0 - 4		Very Soft
4 - 10	7 - 18	Loose	2 - 4	4 - 7	< 0.5	Soft
10 - 30	18 - 55	Medium Dense	4 - 8	7 - 15	0.5 - 1.0	Medium Stiff
30 - 50	55 - 91	Dense	8 - 15	15 - 27	1.0 - 2.0	Stiff
> 50	> 91	Very Dense	15 - 30	27 - 55	2.0 - 4.0	Very Stiff
			> 30	> 55	> 4.0	Hard

### MOISTURE CONTENT DEFINITIONS

Dry: Absence of moisture, dry to the touch

Moist: Damp but no visible water

Wet: Visible free water, usually soil is below water table

### ABBREVIATIONS

WOH: Weight of Hammer

WOR: Weight of Drill Rods

SPT: Standard Penetration Test Split-Spoon Sampler

MCS: Modified California Sampler

PP: Pocket Penetrometer

### GRAIN SIZE DEFINITION

Description	Sieve Number and / or Size
Boulders	> 12 inches (305-mm)
Cobbles	3 to 12 inches (75-mm to 305-mm)
Gravel	3-inch to #4 (75-mm to 4.75-mm)
Coarse Gravel	3-inch to 3/4-inch (75-mm to 19-mm)
Fine Gravel	3/4-inch to #4 (19-mm to 4.75-mm)
Sand	#4 to #200 (4.75-mm to 0.075-mm)
Coarse Sand	#4 to #10 (4.75-mm to 2-mm)
Medium Sand	#10 to #40 (2-mm to 0.425-mm)
Fine Sand	#40 to #200 (0.425-mm to 0.075-mm)

Plate

A-0.2

\*Soil descriptions are based on ASTM D2488-09a, Visual-Manual Procedure, with the above modifications by Geolabs, Inc. to the Unified Soil Classification System (USCS).