			YEAR	NO.	
HAWAII	HAW.	61D-01-23	2024	44	87

## NOTES:

- 1. The permittee shall make minor adjustments at intersections, driveways, bridges, structures, etc., to fit field conditions.
- Cones or delineators shall be extended to a point where they are visible to approaching traffic.
- Traffic control devices shall be installed such that the sign or device farthest from the work area shall be placed first. The others shall then be placed progressively toward the work area.
- Regulatory and warning signs within the construction zone that are in conflict with the Traffic Control Plans shall be removed or covered. All signs shall be restored upon completion of the work.
- 5. Flaggers and/or police officers shall be in sight of each other or in direct communication at all times.
- 6. When required by the issuing office, the permittee shall install a flashing arrow signal as shown on the Traffic Control Plans.
- Sign spacing (L), taper lengths (T) and spacings of cones or delineators shall be as shown in Table 1, unless otherwise noted on the Traffic Control Plans.
- 8. All traffic lanes shall be a minimum of 10 feet wide.
- All construction warning signs shall be promptly removed or covered to preclude the display of inapplicable sign messages (i.e., when signs have messages on both faces).
- 10. At the end of each day's work or as soon as the work is completed, the permittee shall remove all traffic control devices no longer needed to permit free and safe passage of public traffic. Removal shall be in the reverse order of installation.
- Replace permanent pavement markings and traffic signs upon completion of each phase of work.
- All work zone traffic control devices shall be compliant with Chapter 6 of the MUTCD.



STATE OF HAWAII DEPARTMENT OF TRANSPORTATION

## TRAFFIC CONTROL NOTES

KAILUA ROAD INTERSECTION IMPROVEMENTS
Vicinity of Uluca Street and Ulumanu Drive
Project No. 6ID-01-23

Scale: N/A

Date: DEC, 2023

SHEET No. 1 OF 1

SHEETS