

NOTE:
INSTALL RAISED PAV'T. MARKERS
TYPE A, C & H. SEE SHT. 40 FOR
DETAIL.

I.B. CURVE DATA #1
 $\Delta = 20^\circ 56' 56''$
 $\Delta/2 = 10^\circ 28' 28''$
 $R = 445'$
 $T = 82.27'$
 $C = 161.80'$
 $L_c = 162.70'$

I.B. CURVE DATA #2
 $\Delta = 43^\circ 02' 43''$
 $\Delta/2 = 21^\circ 31' 21.5''$
 $R = 442.28'$
 $T = 174.42'$
 $C = 324.52'$
 $L_c = 332.28'$

O.B. CURVE DATA #4
 $\Delta = 61^\circ 45' 00''$
 $\Delta/2 = 30^\circ 52' 30''$
 $R = 446'$
 $T = 266.66'$
 $C = 457.74'$
 $L_c = 480.67'$

O.B. CURVE DATA #5
 $\Delta = 10^\circ 04' 41''$
 $\Delta/2 = 5^\circ 02' 20.5''$
 $R = 712'$
 $T = 62.78'$
 $C = 125.08'$
 $L_c = 125.24'$

PROVIDE SMOOTH
CONNECTION TO
EXT'G. 10% S.E.

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HES-063- 1(12)	1980	9	44

