

Boring Log Legend

UNIFIED SOIL CLASSIFICATION SYSTEM (USCS)

MAJOR DIVISIONS			USCS		TYPICAL DESCRIPTIONS
COARSE-GRAINED SOILS	GRAVELS	CLEAN GRAVELS		GW	WELL-GRADED GRAVELS, GRAVEL-SAND MIXTURES, LITTLE OR NO FINES
		LESS THAN 5% FINES		GP	POORLY-GRADED GRAVELS, GRAVEL-SAND MIXTURES, LITTLE OR NO FINES
		GRAVELS WITH FINES		GM	SILTY GRAVELS, GRAVEL-SAND-SILT MIXTURES
		MORE THAN 12% FINES		GC	CLAYEY GRAVELS, GRAVEL-SAND-CLAY MIXTURES
	SANDS	CLEAN SANDS		SW	WELL-GRADED SANDS, GRAVELLY SANDS, LITTLE OR NO FINES
		LESS THAN 5% FINES		SP	POORLY-GRADED SANDS, GRAVELLY SANDS, LITTLE OR NO FINES
		SANDS WITH FINES		SM	SILTY SANDS, SAND-SILT MIXTURES
		MORE THAN 12% FINES		SC	CLAYEY SANDS, SAND-CLAY MIXTURES
FINE-GRAINED SOILS	SILTS AND CLAYS	LIQUID LIMIT LESS THAN 50		ML	INORGANIC SILTS AND VERY FINE SANDS, ROCK FLOUR, SILTY OR CLAYEY FINE SANDS OR CLAYEY SILTS WITH SLIGHT PLASTICITY
				CL	INORGANIC CLAYS OF LOW TO MEDIUM PLASTICITY, GRAVELLY CLAYS, SANDY CLAYS, SILTY CLAYS, LEAN CLAYS
				OL	ORGANIC SILTS AND ORGANIC SILTY CLAYS OF LOW PLASTICITY
	SILTS AND CLAYS	LIQUID LIMIT 50 OR MORE		MH	INORGANIC SILT, MICACEOUS OR DIATOMACEOUS FINE SAND OR SILTY SOILS
				CH	INORGANIC CLAYS OF HIGH PLASTICITY
				OH	ORGANIC CLAYS OF MEDIUM TO HIGH PLASTICITY, ORGANIC SILTS
			HIGHLY ORGANIC SOILS		

NOTE: DUAL SYMBOLS ARE USED TO INDICATE BORDERLINE SOIL CLASSIFICATIONS

LEGEND



2-INCH O.D. STANDARD PENETRATION TEST
3-INCH O.D. MODIFIED CALIFORNIA SAMPLE
SHELBY TUBE SAMPLE
GRAB SAMPLE
CORE SAMPLE

LL LIQUID LIMIT
PI PLASTICITY INDEX
TV TORVANE SHEAR (tsf)
PEN POCKET PENETROMETER (tsf)
∇ WATER LEVEL OBSERVED IN BORING

GEOTECHNICAL NOTES

- A geotechnical engineering report entitled "Geotechnical Engineering Exploration, Fort Weaver Road (Route76) Widening, Near Lalaunui Street, Ewa, Oahu, Hawaii" dated June 24, 2002 has been prepared by Geolabs, Inc. A copy of the report is on file at the office of the Engineer for review by the Contractor.
- For boring locations, see Sheets 18 to 23.
- The information presented in the logs of borings depict the subsurface conditions encountered at that specified location and at the time of the field exploration only. Variations of subsoil conditions from those depicted in the logs of borings may occur between and beyond the borings.
- The penetration resistance shown on the logs of borings indicate the number of blows required for the specific sampler type used. The blow counts may need to be factored to obtain the Standard Penetration Test (SPT) blow counts.
- The data given is for general information only. Bidders shall examine the site and the boring data and draw their own conclusions therefrom as to the character of materials to be encountered. The Engineer will not assume responsibility for variations of subsoil quality or conditions other than at the boring locations shown and at the time the borings were taken.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
	DESIGNED BY	
	CHECKED BY	
No.		

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

BORING LOG
LEGEND AND NOTES
FORT WEAVER ROAD WIDENING
NEAR LAULAUNUI STREET

FEDERAL AID PROJECT NO. CMAQ-076-1(8)
SCALE: AS NOTED
DATE: October 2003

SHEET No. 1 OF 5 SHEETS

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION







BORING LOGS 1 AND 2

FORT WEAVER ROAD WIDENING
NEAR LAULAUNUI STREET

FEDERAL AID PROJECT NO. CMAQ-076-1(8)

SCALE: AS NOTED DATE: October 2003







SHEET No. 2 OF 5 SHEETS







		GEOLABS, INC. Geotechnical Engineering				FORT WEAVER ROAD (ROUTE 76) WIDENING NEAR LAULAUNUI STREET EWA, OAHU, HAWAII				Log of Boring 2	
Other Tests	Moisture Content (%)	Dry Unit Weight (pcf)	Core Recovery (%)	RQD (%)	Penetration Resistance (blows/foot)	Pocket Pen. (tsf)	Depth (feet)	Sample Graphic	USCS	Approximate Ground Surface Elevation (feet MSL): 60 *	
										Description	
LL=46 PI=27	16				19				MH	Brown CLAYEY SILT, very stiff, damp (fill)	
	15	102			90				CL	Brown SILTY CLAY, hard, damp (alluvium)	
	16	101			40		5				
	15				24		10				
	26				21		15		ML	Brown SILT, very stiff, dry (alluvium)	
										Boring terminated at 16.5 feet	
							20				
							25				
Date Started: March 26, 2002									Water Level: ∇ Not Encountered		
Date Completed: March 26, 2002											
Logged By: S. Latronic									Drill Rig: CME-55		
Total Depth: 16.5 feet									Drilling Method: 4" Auger		
Work Order: 4870-00									Driving Energy: 140 lb. wt., 30 in. drop		

PRINTING LOG DOT 4870-00.PLT GEOLABS.DOT 4/1/02

ORIGINAL PLAN	SURVEY PLOTTED BY _____	DATE _____
NOTE BOOK	DRAWN BY _____	" "
	TRACED BY _____	" "
	DESIGNED BY _____	" "
	QUANTITIES BY _____	" "
No. _____	CHECKED BY _____	" "

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-076-1(8)	2004	101	127

		GEOLABS, INC. Geotechnical Engineering					FORT WEAVER ROAD (ROUTE 76) WIDENING NEAR LAULAUNUI STREET EWA, OAHU, HAWAII				Log of Boring 3	
Other Tests	Moisture Content (%)	Dry Unit Weight (pcf)	Core Recovery (%)	RQD (%)	Penetration Resistance (blows/foot)	Pocket Pen. (tsf)	Depth (feet)	Sample Graphic	USCS	Approximate Ground Surface Elevation (feet MSL): 56 *		
										Description		
	8	98			42				GW	2-inch ASPHALTIC CONCRETE		
	17				8				MH	Reddish brown SANDY GRAVEL, dense, damp (fill)		
	24	98			15		5			Brown CLAYEY SILT, medium to stiff, damp (alluvium)		
	15				50/.3'		10		SM	Light brown SILTY SAND AND GRAVEL, dense, damp (weathered tuff)		
	7				37/.5' +50/.3'		15			Boring terminated at 15.9 feet		
							20					
							25					
Date Started: March 25, 2002								Water Level: ∅ Not Encountered				
Date Completed: March 25, 2002												
Logged By: F. Meyer								Drill Rig: CME-55				
Total Depth: 15.9 feet								Drilling Method: 4" Auger w/ TC Bit				
Work Order: 4870-00								Driving Energy: 140 lb. wt., 30 in. drop				

		GEOLABS, INC.		FORT WEAVER ROAD (ROUTE 76) WIDENING NEAR LAULAUNUI STREET EWA, OAHU, HAWAII					Log of Boring 4		
Geotechnical Engineering											
Other Tests	Moisture Content (%)	Dry Unit Weight (pcf)	Core Recovery (%)	RQD (%)	Penetration Resistance (blows/foot)	Pocket Pen. (tsf)	Depth (feet)	Sample Graphic	USCS	Approximate Ground Surface Elevation (feet MSL): 52 *	
										Description	
	9				15				GW	4-inch ASPHALTIC CONCRETE	
	23	99			25				CH	Reddish brown SANDY GRAVEL, loose to medium, damp (fill)	
	22				18		5			Brown SILTY CLAY, stiff, damp (alluvium)	
	18				50/.3'		10		SM	Light brown SILTY SAND, dense, damp	
	16				50/.3'		15			Boring terminated at 15.3 feet	
							20				
							25				
Date Started: March 25, 2002								Water Level: ∅ Not Encountered			
Date Completed: March 25, 2002											
Logged By: F. Meyer								Drill Rig: CME-55			
Total Depth: 15.3 feet								Drilling Method: 4" Auger w/ TC Bit			
Work Order: 4870-00								Driving Energy: 140 lb. wt., 30 in. drop			

SURVEY PLOTTED BY	DATE
DRAWN BY	" "
TRACED BY	" "
DESIGNED BY	" "
CHECKED BY	" "
NO.	" "

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

BORING LOGS 3 AND 4

FORT WEAVER ROAD WIDENING
NEAR LAULAUNUI STREET

FEDERAL AID PROJECT NO. CMAQ-076-1(8)

SCALE: AS NOTED DATE: October 2003

SHEET No. 3 OF 5 SHEETS

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

BORING LOGS 5 AND 6

FORT WEAVER ROAD WIDENING
NEAR LAULAUNUI STREET

FEDERAL AID PROJECT NO. CMAQ-076-1(8)

SCALE: AS NOTED DATE: October 2003








SHEET No. 4 OF 5 SHEETS








GEOLABS, INC. Geotechnical Engineering										FORT WEAVER ROAD (ROUTE 76) WIDENING NEAR LAULAUNUI STREET EWA, OAHU, HAWAII			Log of Boring 6	
Other Tests	Moisture Content (%)	Dry Unit Weight (pcf)	Core Recovery (%)	RQD (%)	Penetration Resistance (blows/foot)	Pocket Pen. (tsf)	Depth (feet)	Sample Graphic	USCS	Approximate Ground Surface Elevation (feet MSL): 19 *				
										Description				
	27				24				MH	Brown CLAYEY SILT, very stiff, damp (fill)				
	30	88			46									
	21	97			61		5		SM	Orange-brown SILTY SAND, dense, damp (cinder)				
	41				6		10		MH	Brown CLAYEY SILT, medium stiff, moist (alluvium)				
						.25				grades to wet				
	28				53		15		GM	Brownish gray SILTY GRAVEL, dense, moist (alluvium)				
										Boring terminated at 16.5 feet				
							20							
							25							
Date Started: March 26, 2002									Water Level: ▽ 11.1 ft. 4/26/02 1056 HRS					
Date Completed: March 26, 2002									10.6 ft. 3/26/02 1115 HRS					
Logged By: S. Latronic									Drill Rig: CME-55					
Total Depth: 16.5 feet									Drilling Method: 4" Auger					
Work Order: 4870-00									Driving Energy: 140 lb. wt., 30 in. drop					

GEOLABS, INC. 4870-00-01-001-

ORIGINAL PLAN	SURVEY PLOTTED BY _____	DATE _____
NOTE BOOK	DRAWN BY _____	" _____
	TRACED BY _____	" _____
	DESIGNED BY _____	" _____
	QUANTITIES BY _____	" _____
No. _____	CHECKED BY _____	" _____

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	CMAQ-076-1(8)	2004	103	127

		GEOLABS, INC.		FORT WEAVER ROAD (ROUTE 76) WIDENING NEAR LAULAUNUI STREET EWA, OAHU, HAWAII					Log of Boring 7	
Geotechnical Engineering										
Other Tests	Moisture Content (%)	Dry Unit Weight (pcf)	Core Recovery (%)	RQD (%)	Penetration Resistance (blows/foot)	Pocket Pen. (tsf)	Depth (feet)	Sample Graphic	USCS	Approximate Ground Surface Elevation" "(feet MSL): 68 *
										Description
LL=42 PI=20	15	64			8	<0.5			CL	Tannish brown SILTY CLAY with sand, very soft, dry VOID at 0.5 feet grades to dark brown with black mottling, very hard, damp
	20				29	>4.5				
	17	91			15/.1' Ref.	>4.5	5			
	9				30/.5' +15/.3' Ref.		10		SM	Dark brown SILTY SAND, very dense, damp grades with traces of clay
	19				39		15			
	22				55	>4.5	20		MH	Dark brown CLAYEY SILT with sand, very hard, damp
										Boring terminated at 21.5 feet * Elevations estimated from Topographic Survey Map transmitted by KN Consulting Services, Inc. on May 27, 2003.
										</

		GEOLABS, INC.		FORT WEAVER ROAD (ROUTE 76) WIDENING NEAR LAULAUNUI STREET EWA, OAHU, HAWAII					Log of Boring 8		
Geotechnical Engineering											
Other Tests	Moisture Content (%)	Dry Unit Weight (pcf)	Core Recovery (%)	RQD (%)	Penetration Resistance (blows/foot)	Pocket Pen. (tsf)	Depth (feet)	Sample Graphic	USCS	Approximate Ground Surface Elevation" "(feet MSL): 72 *	
										Description	
LL=42 PI=21	7	94			15/.3' Ref.	>4.5			CL	Brown SANDY CLAY with some gravel, hard, dry (fill)	
	18				38	>4.5				grades to SILTY CLAY, very hard	
	17	87			15/.3' Ref.	>4.5	5				
	15				33/.5' +15/.3' Ref.	>4.5	10			grades with black mottling	
	11				30/.3' Ref.		15		SM	Brown strongly cemented SILTY SAND, very dense, damp	
	16				30/.3' Ref.		20			Boring terminated at 20.3 feet	
							25				
Date Started: May 29, 2003								Water Level: ∇ Not encountered			
Date Completed: May 29, 2003											
Logged By: Y. Chiba								Drill Rig: MOBILE B-80			
Total Depth: 20.3 feet								Drilling Method: 4" Auger			
Work Order: 4870-00(B)								Driving Energy: 140 lb. wt., 30 in. drop			

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	" "
	DESIGNED BY	" "
	CHECKED BY	" "
No.		

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

BORING LOGS 7 AND 8

FORT WEAVER ROAD WIDENING
NEAR LAULAUNUI STREET

FEDERAL AID PROJECT NO. CMAQ-076-1(8)

SCALE: AS NOTED DATE: October 2003

SHEET No. 5 OF 5 SHEETS