



FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAWAII	BR-083-1(50)	2005	31	81



**TEMPORARY CRASH ATTENUATOR FOR  
PORTABLE CONCRETE BARRIER TERMINAL PANEL**

Not To Scale



**TEMPORARY CRASH ATTENUATOR FOR  
PORTABLE CONCRETE BARRIER TERMINAL  
PANEL AT DRIVEWAY OR SIDE ROAD**

Not To Scale

SURVEY PLOTTED BY	DATE
DRAWN BY	
CHECKED BY	
QUANTITIES BY	
CHECKED BY	
ORIGINAL PLAN	
NOTE BOOK	
No.	

CHAD M. McDONALD  
LICENSED PROFESSIONAL ENGINEER  
No. 9793-C  
HAWAII, U.S.A.

This work was prepared by me or under my supervision

Chad M. McDonald  
MITSUNAGA & ASSOCIATES, INC. EXP. DATE 4/30/2014

NOTE: Contractor to check and verify dimensions at job before proceeding with work.




STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**BARRIER DETAILS**

KAMEHAMEHA HIGHWAY  
REPLACEMENT OF KOKOLOLO STREAM BRIDGE  
Federal Aid Project No. BR-083-1(50)  
Scale: As Noted Date: August 2004


SHEET No. C-29 OF 51 SHEETS

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAWAII	BR-083-1(50)	2005	32	81



SURVEY PLOTTED BY	DATE
DRAWN BY	
DESIGNED BY	
CHECKED BY	
ORIGINAL PLAN	
NOTE BOOK	
No.	





### TYPICAL DETAIL - PORTABLE CONCRETE BARRIER END TREATMENT

Scale: 1" = 10'-0"

### NOTES:


1. For end treatment, layout, crash cushions and where needed see Project Plans or Special Provisions.
2. Barriers must be pinned together and cannot exceed the Table of Maximum Tapers.
3. The concrete barrier "Standard Installation" design allows for 3'-3" of outward lateral movement if the barrier is struck. Barrier installations that require less than the 3'-3" of outward lateral movement should have stabilization pins.
4. ASTM A-36 steel shall be used for the connection pin, connection loops and stabilization pins. A one piece pin with a 3" rounded top may be used in place of the detailed connection pin if the one piece pin meets ASTM A-36 requirements.
5. A 4" white PVC sleeve may be used to form the lifting hole and if used the sleeve is to be left in place.
6. Concrete shall be Class A and reinforcing shall be Grade 60.
7. Identification and date of design will be as follows:

PROPERTY  
OF HDOT  
OCT 2004

Text letters and numbers shall be shown as on Standard Plan Sht. No. B-01. "PROPERTY OF HDOT" may be changed depending upon ownership. All Portable Concrete Barriers made for HDOT will be subject to rejection, if "PROPERTY OF HDOT" is not imprinted. The Contractor shall bear the cost of the rejected Portable Concrete Barriers.

8. Minimum tangent length for portable Concrete Barrier System shall be 100' (5 units). This minimum does not include the required system length of the Inertial Barrier System.
9. Install steady burn amber lamps on portable concrete barriers @ 20.0' o.c. Installing, maintaining and removing each steady burn amber lamp including changing of batteries and bulbs shall be considered incidental to applicable portable concrete barrier items.
10. The portable concrete barrier shall become the property of the State upon completion of the project and delivered to a location Specified by the Engineer. The delivery shall be incidental to the cost of the barriers.

METAL REINFORCEMENT TABLE				
MARK	LOCATION	BAR SIZE	(NO. BARS)	SKETCH
H-1	Horizontal in Barrier Tied Inside V-1 Bars	#5	(6)	19'-3"
H-2	Centered Above Scuppers Long. & Transversely	#5	(6)	6'-6"
H-3	Tied Above H-1 Bars to Support H-2, Tied to V-1	#4	(2)	1'-6"
S-1	Horizontal in Top of Wing Wall & in Floor Back Wall	#4	(2)	
S-2	Horizontal Around Slots Between V-1's @ Scuppers	#4	(2)	
V-1	Vertical in Barrier (3) Each End & (2) at Each Scupper	#5	(16)	



### STANDARD INSTALLATION

(See Note No. 1)

TABLE A  
SHY LINE OFFSETS \*


DESIGN SPEED (mph)	SHY LINE OFFSETS
70	10.0'
65	9.0'
60	8.5'
55	7.0'
50	6.5'
45	6.0'
40	5.0'
35	4.5'
30	3.5'
≤ 25	2.0'

\* Note: Minimum shy line offset for tangent sections shall be 2'-0".

TABLE B  
MAXIMUM TAPERS  
FOR CONCRETE BARRIER

DESIGN SPEED (mph)	TAPER	
	INSIDE SHY LINE	BEYOND SHY LINE
70	30:1	20:1
65	28:1	19:1
60	26:1	18:1
55	24:1	16:1
50	21:1	14:1
45	18:1	12:1
40	17:1	11:1
35	15:1	9:1
≤ 30	13:1	8:1

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
	DESIGNED BY	
	CHECKED BY	
	CREATED BY	
	NO.	



This work was prepared by me or under my supervision

Chad M. McDermid  
4/30/2014  
MITSUNAGA & ASSOCIATES, INC. EXP. DATE

NOTE: Contractor to check and verify dimensions at job before proceeding with work.

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**PORTABLE CONCRETE BARRIER-2**

**KAMEHAMEHA HIGHWAY**  
**REPLACEMENT OF KOKOLOLO STREAM BRIDGE**  
**Federal Aid Project No. BR-083-1(50)**

Scale: As Noted Date: August 2004

SHEET No. **C-31** OF **51** SHEETS