





FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	NH-083-1(46)	2002	ADD.42	53



TYPICAL DETAIL - PORTABLE CONCRETE BARRIER END TREATMENT  
Scale: 1" = 10'-0"

- NOTES:
- For end treatment, layout, crash cushions and where needed see Project Plans or Special Provisions.
  - Barriers must be pinned together and cannot exceed the Table of Maximum Tapers.
  - The concrete barrier "Standard Installation" design allows for 3'-3" of outward lateral movement if the barrier is struck. Barrier installations that require less than the 3'-3" of outward lateral movement should have stabilization pins.
  - ASTM A-36 steel shall be used for the connection pin, connection loops and stabilization pins. A one piece pin with a 3" rounded top may be used in place of the detailed connection pin if the one piece pin meets ASTM A-36 requirements.
  - A 4" white PVC sleeve may be used to form the lifting hole and if used the sleeve is to be left in place.
  - Concrete shall be Class A and reinforcing shall be Grade 60.
  - Identification and date of design will be as follows:  
PROPERTY OF HDOT  
OCT 2001  
Text letters and numbers shall be shown as on Standard Plan Sht. No. B-01.
  - Minimum tangent length for portable Concrete Barrier System shall be 100' (5 units). This minimum does not include the required system length of the Inertial Barrier System.
  - Install steady burn amber lamps on portable concrete barriers @ 20.0' o.c. Installing, maintaining and removing each steady burn amber lamp including changing of batteries and bulbs shall be considered incidental to applicable portable concrete barrier items.

METAL REINFORCEMENT TABLE				
MARK	LOCATION	BAR SIZE	(NO. BARS)	SKETCH
H-1	Horizontal in Barrier Tied Inside V-1 Bars	#5	(6)	19'-3"
H-2	Centered Above Scuppers Long. & Transversely	#5	(6)	6'-6"
H-3	Tied Above H-1 Bars to Support H-2, Tied to V-1	#4	(2)	1'-6"
S-1	Horizontal in Top of Wing Wall & in Floor Back Wall	#4	(2)	
S-2	Horizontal Around Slots Between V-1's @ Scuppers	#4	(2)	
V-1	Vertical in Barrier (3) Each End & (2) at Each Scupper	#5	(16)	



STANDARD INSTALLATION  
(See Note No. 1)

TABLE A SHY LINE OFFSETS *	
DESIGN SPEED (mph)	SHY LINE OFFSETS
70	10.0'
65	9.0'
60	8.5'
55	7.0'
50	6.5'
45	6.0'
40	5.0'
35	4.5'
30	3.5'
≤ 25	2.0'

TABLE B MAXIMUM TAPERS FOR CONCRETE BARRIER		
DESIGN SPEED (mph)	TAPER	
	INSIDE SHY LINE	BEYOND SHY LINE
70	30:1	20:1
65	28:1	19:1
60	26:1	18:1
55	24:1	16:1
50	21:1	14:1
45	18:1	12:1
40	17:1	11:1
35	15:1	9:1
≤ 30	13:1	8:1

\* Note: Minimum shy line offset for tangent sections shall be 2'-0".

SURVEY PLOTTED BY	DATE
DRAWN BY	
TRACED BY	
NOTED BY	
CHECKED BY	
ORIGINAL PLAN	
NOTE BOOK	
DATE	
NO.	

4/30/02	Revise Reference No. for Steady Burn Lamps per Addendum No. 2.
DATE	REVISION
STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION <b>PORTABLE CONCRETE BARRIER</b> <b>KAMEHAMEHA HIGHWAY</b> <b>DRAINAGE IMPROVEMENTS</b> <b>Vicinity of Kahuku Hospital and</b> <b>Replacement of KII Bridge</b> <b>Federal Aid Project No. NH-083-1(46)</b> Not To Scale Date: April ,2002	
SHEET No. 2 OF 2 SHEETS	