

Amend **Section 645 – Traffic Control Devices** to read as follows:

**“SECTION 645 - WORK ZONE TRAFFIC CONTROL**

**645.01 Description.** This section describes the following:

**(A)** Furnishing, installing, maintaining and subsequently removing work zone traffic control devices, and personnel. Work zone traffic control shall include providing flaggers and police officers.

**(B)** Keeping roads for public traffic open and in passable condition; providing and maintaining temporary access crossings for trails, businesses, parking lots, garages, residences, farms, parks, and other driveways; taking necessary work precautions for the protection, safety, and convenience of the public; should pedestrian facilities exist, taking necessary measures for safe and accessible passage, with route information and ADAAG compliance, for pedestrians traveling through or near work zone.

**(C)** Taking safety and precautionary measures, such as illuminating roadway obstructions during hours of darkness, in accordance with Chapter 286, HRS; Title 19, Subtitle 5, Chapters 127, 128, and 129, HAR; and *MUTCD*.

**645.02 Materials.**

|  |        |
|--|--------|
| Signs                                    | 750.01 |
| Sign Posts                               | 750.02 |
| Fasteners for Signs and Route Markers    | 750.03 |
| Reflector Marker                         | 750.07 |
| Flexible Delineator Posts and Reflectors | 750.08 |
| Traffic Delineators                      | 750.09 |
| Preformed Pavement Marking Tape          | 755.04 |

Submit 10 sets of FHWA approval letters certifying compliance with MASH 2016 for signs, sign supports, barricades, delineators, cones, vertical panels, and other traffic control devices. Use of signs, sign supports, barricades, delineators, cones, vertical panels, and other traffic control devices that are not certified to be NCHRP Report 350 compliant will not be allowed.

Upon request of the Engineer, furnish self-certified MASH 2016 compliant letter from vendor for each type of Category 1 traffic control device, as defined in

MASH 2016, including single-piece traffic cone, single-piece drum, tubular marker, and delineator.

Traffic control devices, including signs, barricades, warning lights, arrow boards, changeable message signs, cones, delineators, and markers, shall conform to the American Traffic Safety Services Association (ATSSA), *Quality Standards for Work Zone Traffic Control Devices* and *MUTCD*.

Protective devices including barricades, warning signs, lights, and temporary signals shall conform to Title 19, Subtitle 5, Chapters 127, 128, and 129, HAR. Reflectorization for protective devices such as barricades, delineators, and warning signs shall conform to Subsection 750.01 – Signs.

**645.03 Construction.** Furnish, install, and maintain barricades, signs, cones, delineators, lights, flashing signals, and other traffic control devices.

Furnish two (2) police officers for each location that requires work zone traffic control. If TCP is included in the contract documents, furnish number of police officers indicated in TCP, whichever is greater.

Furnish, deploy, maintain, and remove two (2) portable changeable message signs (i.e., electronic message boards) for both approaches to each project work area, at locations accepted by the Engineer, seven (7) days prior to start of road work.

Area #1: Sand Island Access Road to Pacific Street

Area #2: Richards Street to Piikoi Street

When directing traffic, flaggers or police officers, or both shall be in direct communication with each other.

**TCP Development.** Contractor shall develop site-specific Traffic Control Plan (TCP) and work schedule based on work hours and lane closure restrictions stipulated in the contract documents.

TCP shall be developed after Contractor conducted field investigation of traffic conditions, including but not limited to, traffic volume counts taken during anticipated work hours, detour routes, interchange ramp & city street traffic signal timing, and public gathering places such as schools, businesses and shopping malls within the project limits and surrounding areas.

Contractor may request multiple individual lane-closures within the project limits at the same time based on, including but not limited to, type of work to be performed, traffic volume, surrounding developments (e.g., schools, businesses) at each proposed work site.

Based on prevailing traffic conditions and other factors, the Engineer may allow up to two (2) individual closures at one time, with distance between individual closures be at least 1-mile apart.

If excessive work zone traffic delays within project limits were observed during construction, the State reserves the rights to suspend TCP if Contractor failed to adjust his work and/or TCP to address traffic concerns brought forth by the State in a timely and responsive manner.

If TCP affects City & County of Honolulu streets, such as but not limited to, traffic detours onto City streets, or traffic control devices placed on City streets, a City & County of Honolulu, Department of Transportation services (DTS) Permit for Street Usage shall be obtained prior to starting work. A TCP stamped by a registered Civil Engineer from the State of Hawaii may be required to obtain the DTS Permit for Street Usage.

**TCP Submittal.** Submit TCP and work schedule for review and acceptance following the procedures established in Subsection 105.04. TCP and schedule shall be accepted by the Engineer prior to starting work in each area. Submit modifications and deviations from accepted TCP following the procedures established in Subsection 105.04. Illegible TCP will not be accepted.

Include the following in TCP and schedule:

- (1) Signs (type, size, designation, and placement).
- (2) Traffic movements shown by arrows.
- (3) Positions of flaggers and police officers.
- (4) Barricades, cones, delineators, and additional traffic control devices and measures necessary for protection of work and public safety; and placement, spacing, distances, and reference points for traffic control devices.
- (5) Layout, drawn to scale, of traffic control devices, including information needed to layout TCP.
- (6) Brief description of work.
- (7) Dates of work.
- (8) Times of day affected.
- (9) Proposed public information sign.
- (10) Proposed news release.
- (11) For lane closures indicate the max. length of roadway to be closed.

143           **(12)** For mobile operations such as rumble strip milling and striping, provide  
144 instruction details for warning sign and flagger deployment.  
145

146           **(13)** Minimum lane width and offset distances to adjacent roadway elements  
147 (e.g., bridge railing, guardrail, portable concrete barrier, etc.)  
148

149           **(14)** Eradicate conflicting pavement striping per Sec. 629.03(D) – Removal  
150 of Existing Pavement Markings. Eradication of existing markings by painting  
151 over them will not be allowed.  
152

153           **(15)** If the work will affect a pedestrian or bike route, show an alternative  
154 route and provide appropriate warning signs.  
155

156           Place sign or device situated farthest upstream from work zone first. Then  
157 place others progressively downstream toward work zone.  
158

159           Extend cones or delineators to point where cones or delineators are visible to  
160 approaching traffic.  
161

162           For signs with messages on both faces, cover inapplicable message before  
163 placement.  
164

165           Keep barricades, construction and warning signs, and other traffic control  
166 devices in good condition. Repair, clean, or replace barricades, signs, or other  
167 devices as required to maintain effectiveness and appearance. The Engineer alone  
168 will decide suitable condition of each barricade, sign, or other traffic control device.  
169

170           Remove or cover regulatory and warning signs that conflict with TCP. Restore  
171 signs upon completion of work or as ordered by the Engineer. Affix object markers to  
172 post(s) of covered sign.  
173

174           Promptly remove or cover construction and warning signs that are not  
175 applicable or not in use.  
176

177           Promptly remove traffic control devices that are no longer needed.  
178

179           Remove traffic control devices in reverse order of installation, starting closest  
180 to work zone and continuing away from work zone.  
181

182           Maintain abutting owners' existing access until replacement access is usable.  
183 Obtain permission from abutting owners, including conditions for closing existing  
184 access. Submit copy of agreement with abutting owners before beginning work in  
185 the affected area.  
186

187           When working on existing facility that will be kept open to traffic, provide  
188 smooth and even surface for public traffic use. Only work on a portion of roadway at  
189 one time, and stage construction from one side to other while routing traffic over  
190 opposite side.

During subgrade and paving operations, paved shoulders may be used for public traffic.

Do not store material or equipment where it will interfere with public traffic. Remove equipment and other obstructions out of right-of-way or clear zone to permit free and safe passage of public traffic during non-working hours or suspension of work. For storage of materials and equipment, see Subsection 105.14 – Storage and Handling of Materials and Equipment.

Notify Fire Department, in writing, at least 24 hours before blocking or closing road access. Keep fire hydrants accessible to Fire Department by not placing material or other obstructions within five feet of fire hydrant or closer than permitted by applicable ordinances, rules, and regulations.

Notify the Engineer and County, including Bus Systems Division, Police Department, Fire Department, Emergency Medical Services, and Department of Health in writing at least five days before start of construction.

**(A) Signs.** Install signs sufficiently ahead of location where operations may interfere with use of road by traffic and at intermediate points where new work crosses or coincides with existing road.

Place signs in accordance with TCP as accepted by the Engineer.

**(B) Construction Signs.** Erect construction signs at the beginning of project and at the end of project at the location indicated by the Engineer. These signs shall remain for the duration of the highway project. Maintain these signs. Place these signs besides the required traffic control signs called for herein.

The construction signs shall be new and become the property of the Contractor.

**(C) Barricades**

**(1) General.** Provide, erect, and maintain necessary barricades suitable for protection of work and safety of the public.

Barricades shall be in good condition. Barricade application and installation shall be in accordance with accepted TCP.

Provide sand bags if required or ordered by the Engineer. Sand bags and installation method shall comply with *MUTCD* and be accepted by the Engineer prior to use. Do not place sand bags on striped barricade rail.

During hours of darkness, install steady burn or flashing lamps on barricades selected by the Engineer. Attach lamps on barricade

ends closest to traveled way and visible to oncoming traffic.

Do not install signs on barricades unless signs and barricades have been crash tested as a unit and accepted under MASH 2016.

**(2) Retroreflectorization.** Retroreflectorize barricade rails and attachment with retroreflective sheeting in accordance with Subsection 750.01(C)(4) - Type III or IV Retroreflective Sheeting (High Intensity) or Subsection 750.01(C)(5) - Hardened Aluminum-Backed Retroreflective Sheeting.

Retroreflectorize both vertical faces of each barricade rail.

**(3) Color.** Provide white colored rails, frames, and braces with front and back rail faces having 6-inch-wide alternating orange or red and white stripes sloping downward toward traveled way at angle of 45 degrees from vertical. Use stripe colors in accordance with the following:

**(a)** Use orange and white stripes for the following conditions:

1. Construction work.
2. Detours.
3. Maintenance work.

**(b)** Use red and white stripes for the following conditions:

1. On roadways with no outlet, such as dead-ends and cul-de-sacs.
2. Ramps or lanes closed for operational purposes.
3. Permanent or semi-permanent closure or termination of roadway.

**(4) Maintenance.** Keep barricades in good condition. Repair, repaint, clean, or replace barricades to maintain effectiveness and appearance. Immediately replace missing or damaged barricades, lamps, sandbags, and other accepted weights.

Clean and repair barricades before relocating to other locations.

**(D) Traffic Delineators.** Install traffic delineators in accordance with accepted TCP.

Maintain traffic delineators in good condition. Immediately replace

missing or damaged traffic delineators.

Clean delineator prior to relocating to new location.

**(E) Cones.** Install traffic cones in accordance with accepted TCP.

Maintain traffic cones. Keep traffic cones clean and in good repair.  
Immediately replace lost, stolen, or damaged traffic cones.

Clean cones prior to relocating to new location.

**(F) Lane Closures.** Lane closures will be allowed only during the following hours:

**(1) Work not requiring lane closure.** Contractor may do work not requiring lane closures during the day-time working hours. Conduct day-time work between the hours of 8:30 A.M. and 3:00 P.M., Monday to Friday.

**(2) Day-time lane closure hours:**

**Nimitz Hwy / Ala Moana Blvd. (Sand Island A/R to Piikoi St.)**

No day-time lane closure will be allowed

**(3) Night-time lane closure hours:**

**Nimitz Hwy / Ala Moana Blvd. (Sand Isl. to Waiakamilo Rd.)**

| <b><u>1-lane closure</u></b> | Inbound              | Outbound *           |
|------------------------------|----------------------|----------------------|
| Sunday                       | 7:00 P.M. - Midnight | 7:00 P.M. - Midnight |
| Monday to Thursday           | Midnight – 5:30 A.M. | Midnight – 5:30 A.M. |
|                              | 7:00 P.M. - Midnight | 7:00 P.M. - Midnight |
| Friday                       | Midnight – 5:30 A.M. | Midnight – 5:30 A.M. |

| <b><u>2-lane closure</u></b> | Inbound              | Outbound *           |
|------------------------------|----------------------|----------------------|
| Sunday                       | 7:00 P.M. - Midnight | 7:00 P.M. - Midnight |
| Monday to Thursday           | Midnight – 4:30 A.M. | Midnight – 2:00 A.M. |
|                              | 7:00 P.M. - Midnight | 7:00 P.M. - Midnight |
| Friday                       | Midnight – 4:30 A.M. | Midnight – 2:00 A.M. |

\* Nimitz Hwy OB contraflow lane coning starts at 2:30 A.M.  
Nimitz Hwy OB contraflow lane terminates east of Alakawa St.

**Nimitz Hwy / Ala Moana Blvd. (Waiakamilo Rd. to South St.)**

| <b><u>1-lane closure</u></b> | Inbound              | Outbound *           |
|------------------------------|----------------------|----------------------|
| Sunday                       | 7:00 P.M. - Midnight | 7:00 P.M. - Midnight |
| Monday to Thursday           | Midnight – 5:00 A.M. | Midnight – 5:00 A.M. |
|                              | 7:00 P.M. - Midnight | 7:00 P.M. - Midnight |
| Friday                       | Midnight – 5:00 A.M. | Midnight – 5:00 A.M. |

| <b><u>2-lane closure</u></b> | Inbound              | Outbound *           |
|------------------------------|----------------------|----------------------|
| Sunday                       | 8:00 P.M. - Midnight | 8:00 P.M. - Midnight |
| Monday to Thursday           | Midnight – 4:30 A.M. | Midnight – 4:30 A.M. |
|                              | 8:00 P.M. - Midnight | 8:00 P.M. - Midnight |
| Friday                       | Midnight – 4:30 A.M. | Midnight – 4:30 A.M. |

\* Nimitz Hwy OB contraflow lane coning starts at 2:30 A.M.  
Nimitz Hwy OB contraflow lane terminates east of Alakawa St.

**Ala Moana Blvd. (South St. to Piikoi St.)**

| <b><u>1-lane closure</u></b> | Both Directions      |
|------------------------------|----------------------|
| Sunday                       | 7:00 P.M. - Midnight |
| Monday to Thursday           | Midnight – 5:30 A.M. |
|                              | 7:00 P.M. - Midnight |
| Friday                       | Midnight – 5:30 A.M. |

| <b><u>2-lane closure</u></b> | Both Directions      |
|------------------------------|----------------------|
| Sunday                       | 7:00 P.M. - Midnight |
| Monday to Thursday           | Midnight – 5:30 A.M. |
|                              | 7:00 P.M. - Midnight |
| Friday                       | Midnight – 5:30 A.M. |

See project plans for additional information on scope of work and coordination during construction.

Exceptions to lane closure hours specified require written acceptance by the Engineer. No increase in contract price or contract time will be given for lane closure restrictions specified.

See Section 107.03 – Working Hours; Night Work of the project Special Provisions for description of Noise Variance hours, noise control conditions and restrictions during weekend and night work.



For island of Oahu, no lane closures will be allowed during 24-hour periods as follows:

- (1) Day preceding holiday (3:00 p.m. to Midnight), except as otherwise specified.
- (2) Holidays (Midnight to Midnight).
- (3) Thanksgiving weekend (Thursday to Sunday).
- (4) Three-week holiday period for Christmas and New Year.
- (5) One-week "Beat-the-School-Jam" period, to be determined, beginning approximately third week of August (first week of University of Hawaii Manoa Session).
- (6) Other dates of events indicated in the contract documents.

No time extension will be given for the above restrictions. The contract time for the project has accounted for any loss of time due to the above restrictions.

Closure of only one lane of traffic will be allowed during lane-closure hours. Keep lanes open to traffic and allow flow at normal posted speed limit during non-lane-closure hours.

If applicable, coordinate lane closures with adjacent project(s) at no increase in contract price or contract time.

Rental fees will be assessed in accordance with Subsection 108.10 – Rental Fees for Unauthorized Lane Closure or Occupancy, for failure to open lanes to traffic during peak hours. Morning and afternoon peak hours shall be from 5:30 a.m. to 8:30 a.m. and 3:00 p.m. to 6:00 p.m., respectively, Monday through Friday.

Before scheduling work, submit requests for detours and lane closures as follows:

- (1) Detours - 8 weeks before implementing detours.
- (2) Lane closures - 6 weeks before implementing lane closures.

Include the following with detour and lane closure requests:

- (1) Explanation of proposed changes to existing traffic pattern.
- (2) Installation schedule for informational and traffic control signs.

(3) Publication schedule for legal notices.

(4) Plan showing proposed informational signs.

(5) Plan showing lane changes or detours in accordance with accepted TCP, including details at beginning of multi-lane highway lane changes and detours.

Detours or lane closures will not be allowed before the Engineer accepts detour or lane closure request.

| TABLE 645-I - FOR TRAFFIC CONTROL PLAN |                                  |                            |                              |  |   |             |              |
|--|----------------------------------|----------------------------|------------------------------|--|---|-------------|--------------|
| POSTED<br>SPEED<br>LIMIT<br>(M.P.H.)   | SIGN<br>SPACING<br>(D)<br>(FEET) | TAPER LENGTH<br>(T) (FEET) |                              | LONGI-<br>TUDINAL<br>BUFFER<br>SPACE<br>(B) (FEET) | SPACING OF CONES OR<br>DELINEATORS (FEET) |             |              |
|  |                                  | W = 12' OR<br>LESS *       | W =<br>GREATER<br>THAN 12' * |  | TAPER                                     | TANGEN<br>T | WORK<br>AREA |
| 20                                     | 250                              | 200                        | W x 17                       | 35   | 20  | 20          | 10           |
| 25                                     | 250                              | 200                        | W x 17                       | 55   | 25  | 25          | 10           |
| 30                                     | 250                              | 250                        | W x 20                       | 85   | 30  | 30          | 10           |
| 35                                     | 250                              | 250                        | W x 20                       | 120  | 35  | 35          | 10           |
| 40                                     | 500                              | 350                        | W x 30                       | 170  | 40  | 40          | 10           |
| 45                                     | 500                              | 550                        | W x 45                       | 220  | 45  | 45          | 10           |
| 50                                     | 1000                             | 600                        | W x 50                       | 280  | 50  | 50          | 10           |
| 55                                     | 1000                             | 700                        | W x 55                       | 335  | 55  | 55          | 10           |
| * W = width of lane or shoulder        |                                  |                            |                              |  |   |             |              |

(G) **Advisory Signs.** Submit advisory sign shop drawings. Construct, install, maintain, and remove four (4) advisory signs (e.g., 2 for each work area) as ordered by the Engineer.

Area #1: Sand Island Access Road to Pacific Street

Area #2: Richards Street to Piikoi Street

Place signs at locations designated by the Engineer. Provide signs, minimum 8 feet wide by 4 feet high, with black letters on orange background, and with three 4.00 pounds/foot flanged channel posts for each sign.

Include starting date and hours of construction in sign message. Use letter heights of 8 inches, Series D. The Engineer will review and accept advisory signs' wording before fabrication. Install advisory signs two weeks before start of construction. Remove advisory signs immediately after construction has been completed or as ordered by the Engineer.

(H) **Advertisement.** Place advertisement in newspaper, as ordered by

Engineer, for the following traffic pattern changes or night work:

- (1) Detours.
- (2) Lane closure.
- (3) Permanent road closure.
- (4) Permanent new route that changes previous route.

Include the following information:

- (1) Map of traffic pattern change limits.
- (2) Map showing lane(s) closure and detour pattern.
- (3) Notice of starting and ending dates and duration.
- (4) Explanation of lane(s) closure or detours in "Notice To Motorist".

Quality of map shall conform to the following requirements:

- (1) No freehand printing or penciling.
- (2) Highlight important features by darkening, cross-hatching, crossing-out, or coloring important words, as necessary.
- (3) Provide maps with minimum size of five columns wide and four columns deep. Lesser width columns may be considered to balance against size of drawing.
- (4) Text specifications.
  - (a) Work being featured - 3/16-inch text.
  - (b) Major roads and features - 1/8-inch text.
  - (c) Other roads and features- first letter of sentence upper case.
  - (d) "NOTICE TO MOTORIST" in upper case.
  - (e) Message - first letter of sentence upper case.
- (5) Line Thickness.
  - (a) Important feature being advertised - line thicker than rest of map.

(b) Directional arrow - bolder than rest of lines shown on map, when important, to show route traffic should use.

(6) Show reference direction such as "TO HONOLULU" with arrow.

Submit the following:

(1) "Notice to Motorists" before placement in newspaper, six weeks before start of work.

(2) Actual size of notice to be published in newspaper. The Engineer will not allow size reduction of notices once accepted. Submit final, camera-ready "Notice to Motorists" advertisement.

Place advertisement for three consecutive days and within one week before traffic pattern changes, in publication as ordered by the Engineer.

#### **645.04 Measurement.**

(A) Traffic control as specified in Subsection 645.03 - Construction will be measured on a contract lump sum basis and will not include any work performed under other specific traffic control contract bid items. Measurement for payment will not apply.


(B) The Engineer will measure additional police officers, additional traffic control devices, and advertisement, if ordered by the Engineer, on a force account basis, in accordance with Subsection 109.06 - Force Account Provisions and Compensation.

(C) The two portable changeable message signs (i.e., electronic message boards) for both approaches to each project work area (e.g., total 4 portable changeable message signs), as accepted by the Engineer, shall not be paid for separately and shall be considered incidental to the contract item No. 645.0100, Traffic Control.

**645.05 Payment.** The Engineer will pay for the accepted traffic control, additional police officers, additional traffic control devices, specific traffic control contract bid items and advertisement at the contract price per pay unit, as shown in the proposal schedule. Payment will be full compensation for the work prescribed in this section and the contract documents.


The Engineer will pay for the following pay items when included in the proposal schedule:

|     |  |                 |
|-----|--|-----------------|
| 515 | <b>Pay Item</b>  | <b>Pay Unit</b> |
| 516 |  |                 |
| 517 | Traffic Control  | Lump Sum        |
| 518 |  |                 |
| 519 | Additional Police Officers, Additional Traffic Control Devices,                    | Force Account   |
| 520 | And Advertisement  |                 |
| 521 |  |                 |
| 522 | An estimated amount for the force account may be allocated in the                  |                 |
| 523 | proposal schedule under “Additional Police Officers And Additional Traffic Control |                 |
| 524 | Devices”, but the actual amount to be paid will be the sum shown on the            |                 |
| 525 | accepted force account records, whether this sum be more or less than the          |                 |
| 526 | estimated amount allocated in the proposal schedule.                               |                 |
| 527 |  |                 |
| 528 | The Engineer will not pay for request submittals. The Engineer will not            |                 |
| 529 | consider claims for additional compensation of late submittals or requests by      |                 |
| 530 | Contractor.  |                 |
| 531 |  |                 |
| 532 |  |                 |
| 533 |  |                 |
| 534 |  |                 |
| 535 |  |                 |
| 536 |  |                 |
| 537 |  |                 |
| 538 |  |                 |
| 539 |  |                 |
| 540 |  |                 |
| 541 |  |                 |
| 542 |  |                 |
| 543 |  |                 |



TWO-LANE HIGHWAY - ONE LANE CLOSED


548  
549  
550  
551



MULTILANE UNDIVIDED HIGHWAY - RIGHT LANE CLOSED

FIGURE 2 - TRAFFIC CONTROL PLAN

552  
553  
554  
555  
556




MULTILANE UNDIVIDED HIGHWAY - LEFT LANE CLOSED

FIGURE 3 - TRAFFIC CONTROL PLAN



557  
558  
559




MULTILANE DIVIDED HIGHWAY - ONE LANE CLOSED

FIGURE 4 - TRAFFIC CONTROL PLAN

560  
561  
562

NH-092-1(030)  
645-18a

12/22/20




MULTILANE HIGHWAY - CENTER LANE CLOSED

FIGURE 5 - TRAFFIC CONTROL PLAN

563  
564  
565

NH-092-1(030)  
645-19a

12/22/20




MULTILANE HIGHWAY - MULTIPLE LANE CLOSED

FIGURE 6 - TRAFFIC CONTROL PLAN

566  
567  
568  
569  
570

"

END OF SECTION 645



WORKING ON SHOULDER OR ROADSIDE  
FIGURE 7 - TRAFFIC CONTROL PLAN

R10/96