

SYMBOL	55005551011	ואו ו כ	BOL .	55005/5701	SYM	BOL	DECADIOTION
ST NEW	DESCRIPTION	EXST	NEW	DESCRIPTION	EXST	NEW	DESCRIPTION
0	Highway Light Standard		[2]	Remove Exst. Type II Traffic Signal Standard,			Exst. Pullbox to be Demolished, Cap Exst Conduit
			[o] *-*-[*	Demolish Exst. Conc. Base 2 Ft. Below Finish		ר×— ״ן ∟ <u>—</u> χJ	& Backfill to 95% Compaction Unless Indicated
			* -*- [*] >	Grade & Backfill Pit to 95% Compaction Unless	·		Otherwise.
			-*- - *>	Indicated Otherwise.	F — ¬		Pullbox or Handhole, See Plan for Size
			. <u>5</u> ₹	Remove Exst. Type III Traffic Signal Standard,	ト十つ		CATV Pullbox
			₩	Demolish Exst. Conc. Base 2 Ft. Below Finish	ド / . カ		Hawaiian Telcom (HTCO) Pullbox/Handhole
			* * *	Grade & Backfill Pit to 95% Compaction Unless	[3]		Hawaiian Telcom (HTCO) Manhole
>	CCTV Camera		-X-1.*>	Indicated Otherwise.	ト		Hawaiian Electric Co (HECO) Pullbox/Handhole
→	RYGA ↑ Traffic Signal Head			Remove Exst. Type I Traffic Signal Standard,			Hawaiian Electric Co (HECO) Manhole
 ->	RYGA ← Programmed Visibility Traffic Signal Head		<u>%</u> -×-[*,	Demolish Exst. Conc. Base 2 Ft. Below Finish			Communication Manhole
*			\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Grade & Backfill Pit to 95% Compaction Unless			Time Warner Telcom 2' X 4' Pullbox
\rightarrow	RYG Traffic Signal Head			Indicated Otherwise.			Hawaiian Telcom (HTCO) 2' X 4' Pullbox
>↓> ↓	RYGA ← Traffic Signal Head		A	Type I Traffic Signal Standard with Traffic Signal			Hawaiian Electric Co (HECO) 2' X 4' Pullbox
-(II) — — —	Pedestrian Traffic Signal Head	o{>		Head, 10' Unless Indicated Otherwise; Pole "A"			
+>⊗→	Opticom Detector, See Detail B/E-28			Indicated, See Detail C/E-26		<u></u> —с—	- Communication Ductline
	New Pedestrian Pushbutton Shall Meet	[<u>[</u>]	₽®	Type II Traffic Signal Standard with Traffic Signal	e		Elec Ductline with Cables
. ⊢⊙↓	Current American with Disabilities Act (ADA)	[Q] >		Heads Mounted on Mast Arm and Standard;	t	*****	Tel Ductline with Cables
	Accessibility Guidelines, See Detail B/E-30		30'	Pole "B" and 30' Mast Arm Length Indicated,	V		Catv Ductline with Cables
⊢ (\$)	Remove Exst Pedestrian Pushbutton	L{>		See Detail A/E-27	e/t	#. · · · · ·	Elec/Tel Ductline with Cables
S S	System Detector Loops, See Sheet E-31	 [桑]		Type III Traffic Signal Standard with Traffic Signal	sc	· •	Signal Corps Underground Cable
In [2]				Heads Mounted on Mast Arm and Standard,	att		AT&T Ductline with Cables
]	Detector Loops, See Sheet E-31			Highway Light Luminaire and Bracket Arm			Remove Exst Traffic Signal Wiring, Cap Exst
						x (Sx-	Ductline & Abandon-In-Place
	Highway Light Pullbox (Old Type "B")					-*-l-*-	Remove Exst Hwy Lt Wiring, Cap Exst Ductline
	Per Standard Plan TE-41					- * - l - * -	& Abandon-In-Place
	Type "A" Metric Highway Light Pullbox			Change in Duct Section Designator			
	(Approx. 22" X 28"), See Detail A/E-32	—-е		Electrical/Signal Ductline with Designator,			
	Type "B" Metric Highway Light Pullbox			Indicates Type "A" Duct Section with "2-4E"			
	(Approx. 28" X 40") , See Detail C/E-32	(2-4E)	A (2-4)	Ducts. See Sheets E-24 & E-25 for Typ Duct			
	Type "C" Metric Highway Light Pullbox			Sections and Conduit Schedule	ΓЛ		HECO 1—Phase Transformer Pad Lot,
	(Approx. 28" X 57") , See Detail D/E-32				ΓŊ	LJ	See Detail D/E-36
	Type "A" Metric Traffic Signal Pullbox	ts	<i>TS</i>	Traffic Signal Exposed Conduit and Wiring	Δ		HECO Pole Mtd Transformer
	(Approx. 22" X 28"), See Detail A/E-32	— ts—	— <i>TS</i> —	Traffic Signal Ductline and Wiring	0		Utility Pole Unless Indicated Otherwise
	Type "B" Metric Traffic Signal Pullbox	— <i>l</i> —	<u> —L —</u>	Highway Light Ductline and Wiring	e-oh		Elec Overhead Lines
	(Approx. 28" X 40"), See Detail C/E-32	l	L	Highway Light Exposed Conduit and Wiring	t-oh		Tel Overhead Lines
	Type "C" Metric Traffic Signal Pullbox		3	Stub, Cap and Mark Conduits	v-oh		CATV Overhead Lines
	(Approx. 28" X 57"), See Detail D/E-32		HB	Enclosed Ckt Bkr	l-oh		Hwy Lt Overhead Lines
	Traffic Signal Pullbox (Old Type "B")	[];	<u></u>	Metering Equipment & Support, See Detail A/E-36			Traffic Signal Fiber Optic Overhead Line
	Per Standard Plan TE-41		C	Traffic Signal Controller and Cabinet,	t/v-oh		Overhead Lines; Tel & CATV Lines Indicated
	Type "C" Metric Communication (Highways) Pullbox			See Detail A/E-26	g-oh		Overhead Guy Wire
	(Approx. 28" X 57"), See Detail D/E-32		ΗÜ	Remove Exst J-Box			Guy Anchor
	Type "B" Metric Communication (Highways) Pullbox	H[<u>J]</u>	HJ	J-Box, See Plan for Size			
	(Approx. 28" X 40"), See Detail C/E-32		I	Traffic Counting Station Equipment and Cabinet,			
	Type "C" Metric Communication (Harbors) Pullbox	Ŷ,		See Detail A/E-26			

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	92AB-01-06M	2006	25	74

SYMBOL NOTES:

1. "X" Through Symbol Indicates Item to be Removed.

<u>UTILITY LEGEND:</u>

----w16--- Exst Water Line, 16" Dia Indicated

—g6— Exst Gas Line, 6" Dia Indicated

—s8— Exst Sewer Line, 8" Dia Indicated

—d24— Exst Drain Line, 24" Dia Indicated

—— f6—— Exst Fuel Oil Line, 6" Dia Indicated

vmh Exst Water Manhole

Added Pullbox Symbol

REVISION

wv Exst Water Valve wm Exst Water Meter

smh Exst Sewer Manhole

sdmh Exst Storm Drain Manhole cb Exst Catch Basin

LICENGED (MOCESSIONAL MOCESSIONAL MOCESSIO

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

LICENSE EXPIRES 4-30-08

DEPARTMENT OF TRANSPORTATION

HIGHWAYS DIVISION

ELECTRICAL SYMBOLS


<u>NIMITZ HIGHWAY AND</u> <u>ALA MOANA BOULEVARD RESURFACING</u> <u>Fort Street to Piikoi Street</u>

Fort Street to Piikoi Street
Project No. 92AB-01-06M
Scale: NONE
Date: April

ale: NONE Date: April 2006

SHEET No. E-2 OF 44 SHEETS

C.O.



GENERAL ELECTRICAL NOTES

- Electrical Work shall be New Unless Indicated Otherwise.
- Existing Electrical Equipment shall Remain Unless Indicated Otherwise.
- The Location of Existing Underground Utilities Shown on Plans are from Existing Records and are Approximations Only. Contractor shall Exercise Caution when Construction Crosses or is in Close Proximity to Existing Underground Utilities. Damages to Utility Companies' Existing Facilities shall be Repaired by the Respective Utility Company and Repair Costs shall be Paid by the Contractor at No Additional Cost to the State.
- 4. For Utility, Traffic Signal and Additional Notes, See Sheets 3 Thru 7, Inclusive.

EQUIPMENT SCHEDULE

The Hawaiian Electric Company (HECO), Hawaiian Telcom (HTCO), Time Warner/Telcom, and State Dept. of Transportation Pullboxes shall be Constructed by the Contractor as Shown in these Drawings & in Accordance with the Following Standard Drawings:

Description

- 2' x 4' HECO Pullbox
- 2' x 4' Precast Concrete Pullbox with Precast Concrete Cover, Provided in Accordance with HECO Standard Drawing No. <u>30–2005</u>.
- 2' x 4' HTCO Pullbox
- 2' x 4' Type 435TB Precast Concrete Pullbox with Two-Piece Steel "Slip-Not" Grip or Polymer "Non-Skid" Covers and Ground Rod, Per HTCO Standard Drawing No. <u>34056</u>. A Minimum of Two Precast Concrete Pullbox Sections shall be Required at Each Pullbox.
- 2' x 4' Time Warner/ Telcom Pullbox
- 2' x 4' Precast Concrete Pullbox with Two-Piece "Slip-Not" Grip Covers, Similar to HTCO Type 435TB (HTCO Standard Drawing No. 34056), Except with "TWTC" Inscribed on Covers.
- Type "A" Traffic Signal, Highway Light Pullbox or Communication (State)
- Type "A" (Metric) Precast Concrete Pullbox with "Non—Skid" Polymer Concrete Cover, Provided in Accordance with Department of Transportation Standard Drawings and Sheet
- Type "B" Traffic Signal Highway Light Pullbox or Communication (State)
- Type "B" (Metric) Precast Concrete Pullbox with "Non—Skid" Polymer Concrete Cover, Provided in Accordance with Department of Transportation Standard Drawings and Sheet
- Type "C" Traffic Signal Highway Light Pullbox or Communication (State)
- Type "C" (Metric) Precast Concrete Pullbox with "Non—Skid" Polymer Concrete Cover, Provided in Accordance with Department of Transportation Standard Drawings and Sheet E-32.
- 19" x 28" (Old Type "B") Traffic Signal or Highway Light Pullbox (State)
- HECO 1-Phase Transformer Pad Lot
- 19" x 28" (Old Type "B") Precast Concrete Pullbox with Cast Iron Frame and Cover, Provided in Accordance with Department of Transportation Standard Drawing TE-41.
- 1-Phase Transformer Pad Lot with Reinforced Concrete Transformer Pad and Ground Rod Per HECO Standard Drawing Nos. 30-5001 & 011249 and Detail D/E-36.

- 5. Existing Highway Lighting and Traffic Signal Pullboxes to Remain shall be Cleaned of Debris and Dirt. Cleaning of Existing Pullbox will not be Paid for Separately, but Considered Incidental to the Various Contract Items.
- 6. Saw Cutting and Repairing of Existing A.C. and Concrete Pavement, A.C., Concrete and Lava Rock Curb, and Concrete Gutter will not be Paid for Separately, but Considered Incidental to the Various Contract Items.
- 7. For Typical Pullbox Group Installation, See Detail B/E-31.
- 8. For Dept. of Transportation Communication Conduit ("IT") Installation, Route "4IT" Conduit to the Type "C" Pullbox and "2IT" Conduit to the Type "B" Pullbox.
- 9. For Concrete Encased Stub-Outs, Omit Concrete Encasement for Last Six Inches of Stub-Out.
- 10. Exsiting Piikoi St/Ala Moana Blvd Traffic Signal System shall Remain Operational Until New Traffic Signal System has been Inspected, Tested and Accepted by the Dept. of Transportation Services - Traffic Signals and Technology Division. If Exst Traffic Signal Equipment is Removed Before the New Traffic Signal System is Operational, the Contractor shall Provide Temporary Traffic Signal Equipment as Necessary. Temporary Work shall be Acceptable to the Engineer. Temporary Work will Not be Paid for Separately, but Considered Incidental to the Various Contract Items.

DEPARTMENT OF TRANSPORTATION SERVICES — TRAFFIC SIGNALS AND TECHNOLOGY DIVISION

- The Contractor shall Notify the Traffic Signals and Technology Division, Department of Transportation Services, Three (3) Working Days Prior to Commencing Work on the Traffic Signal System (phone: 523-4589).
- 2. The Traffic Signal System shall be Kept Operational During Construction. Any Relocation Required shall be Approved by the Traffic Signals and Technology Division, Department of Transportation Services, and Performed and Paid for by the Contractor.
- 3. The Contractor shall be Responsible for Any Damages to Existing Traffic Signal Facilities, Including the Traffic Signal Interconnect System. Any and All Damages to these Facilities shall be Repaired by the Contractor at His Cost in Accordance with the Requirements of the City and County of Honolulu.
- The Contractor shall be Responsible for Any Damages to Existing Traffic Signal Fiber Optic Cable System. Any and All Damages to these Facilities shall be Repaired by the Contractor at His Cost in Accordance with the Requirements of the City and County of Honolulu.
- 5. If the Existing Traffic Signal Loop Detectors are to Remain Inoperable for More than Thirty (30) Calendar Days, the Contractor shall Provide a Temporary Video Detection System While the Loop Detectors are Inoperable. The Temporary Video Detection System will not be Paid for Separately, but Considered Incidental to the Various Contract Items.

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	92AB-01-06M	2006	26	74

DEMOLITION NOTES

- 1. The Contractor shall Verify All Existing Circuit Wiring Prior to Any Demolition Work.
- 2. Remove All Abandoned Wires and Exposed Raceways.
- Existing Traffic Signal System(s) shall Remain Operational at All Times. Contractor shall Provide Temporary Traffic Signal System(s) (Including Video Vehicle Detectors) as Required if the Existing Traffic Signal Equipment are Removed Before the New Traffic Signal System(s) are Operational. Temporary Work shall be Coordinated with and shall be Acceptable to the Engineer. Temporary Traffic Signal System(s) will not be Paid for Separately, but Considered Incidental to the Various Contract Items.
- Existing Loop Detectors that will be Replaced will be Abandoned-in-place. Contractor shall not Reuse Existing Loop Detector Saw Cuts for New Loop Detectors.

DEPARTMENT OF TRANSPORTATION SERVICES -PUBLIC TRANSIT DIVISION NOTES

1. The Contractor shall Notify Oahu Transit Services, Inc., (OTS-THEBUS Contractor), Ed Sniffen (848-4571) or Lowell Tom (848-4578), Two Weeks Prior to Construction, Informing them of Location, Scope of Work, Proposed Closure of Any Street or Traffic Lanes, and Need to Relocate Any Bus Stops.



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION

Date: April 2006

DEPARTMENT OF TRANSPORTATION NOTES, EQUIPMENT SCHEDULE

NIMITZ HIGHWAY AND ALA MOANA BOULEVARD RESURFACING Fort Street to Piikoi Street Project No. 92AB-01-06M


Scale: NONE


SHEET No. E-3 OF 44 SHEETS


£ SURVEY PLOTTE
DRAWN BY_____
TRACED BY____
DESIGNED BY____
QUANTITIES BY___
CHECKED BY____

DATE


REVISION









SURVEY PLOTTE
DRAWN BY
TRACED BY
DESIGNED BY
QUANTITIES BY
CHECKED BY







FED. ROAD DIST. NO. PROJ. NO. YEAR 92AB-01-06M

<u>Notes</u>: (Continued)

7 Saw Cut Exst Conc Curb and Gutter Prior to Trench Excavation. Repair Type 2DG Curb and Gutter Per Detail on Civil Sht 14.

Notes:

1 Saw Cut Exst Conc Sidewalk at Scorelines Prior to Trench Excavation. Repair Conc Sidewalk Per Detail on Civil Sht 14.

2 Saw Cut Exst A.C. Pavement Prior to Trench Excavation. Repair Pavement Structure, See Sht E−23.

- to Trench Excavation. Repair Conc Sidewalk Per Detail on Civil Sht 14 and Provide Finish and Gridded Scorelines to Match Exst.
- Detectors, See Detail A/E-31.

APPROVED BY: Dennis M. Nichimum CHIEF, WASTEWATER BRANCH, DPP W 9/25/06 SCALE: GRAPHIC SCALE

8/23/06 Added Approval Block, Rev. Stub Near Sta 160+101t. 5/30/06 Rev Pullbox Locations

REVISION

ALA MOANA BOULEVARD RESURFACING Fort Street to Piikoi Street Project No. 92AB-01-06M Scale: AS NOTED Date: April 2006

DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

HIGHWAY LIGHTING & TRAFFIC SIGNAL

PARTIAL PLAN 6


NIMITZ HIGHWAY AND

/ PAOPESSIONAL ENGINEER No. 7637-E

SHEET No. E-9 OF 44 SHEETS 32R

HIGHWAY LIGHTING & TRAFFIC SIGNAL PARTIAL PLAN 6 SCALE: 1"=20' T.M.K.: 2-1-27

ADD.



FED. ROAD DIST. NO. FISCAL SHEET TOTAL STATE SHEETS 33 HAWAII HAW. 92AB-01-06M 2006

<u>Notes</u>: (Continued)

- 7 Saw Cut Exst. Conc. Curb and Gutter Prior to Trench Excavation. Repair Type 2DG Curb and Gutter per Detail on Civil Sht 14.
- 8 Remove Exst Lava Rock Curb and Saw Cut Exst Conc Gutter Prior to Trench Excavation. Repair Lava Rock Curb and Type 2A Gutter Per Detail on Civil Sht 14.
- 9 Saw Cut Exst Conc Sidewalk at Scorelines Prior to Trench Excavation. Repair Conc Sidewalk Per Detail on Civil Sht 14. Provide Colored Conc Pattern and Finish to Match Exst.



DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION HIGHWAY LIGHTING & TRAFFIC SIGNAL

PARTIAL PLAN 7


NIMITZ HIGHWAY AND ALA MOANA BOULEVARD RESURFACING Fort Street to Piikoi Street Project No. 92AB-01-06M Scale: AS NOTED Date: April 2006


> SHEET No. E-10 OF 44 SHEETS 33

Saw Cut Exst Conc Sidewalk at Scorelines Prior to Trench Excavation. Repair Conc Sidewalk Per Detail on Civil Sht 14.

Saw Cut Exst A.C. Pavement Prior to Trench Excavation. Repair Pavement Structure, See Sht E-23.

- 3 Demolish Exst Pullbox and Intercept Exst Conduit and Wiring with Pullbox Indicated.
- 4 Saw Cut Exst Conc Sidewalk at Scorelines Prior to Trench Excavation. Repair Conc Sidewalk Per Detail on Civil Sht 14 and Provide Finish and Gridded Scorelines to Match Exst.
- 5 Saw Cut Exst Textured Conc Pavement Prior to Trench Excavation. Repair with Conc Sidewalk Per Detail on Civil Sht 14.
- 6 2"C Stub-Out for Future Connection to Loop Detectors, See Detail A/E-31.







5/17/07	Added "2L" Stub-Out at Sta 12+52
8/23/06	Rev Ductline on Northeast Corner, Rev Pullbox Locations Near Sta 163+20
5/30/06	Rev Pullbox Locations Near Sta. 163+20
DATE	REVISION



HIGHWAY LIGHTING & TRAFFIC SIGNAL PARTIAL PLAN 7 SCALE: 1"=20' T.M.K.: 2-1-27, 2-1-29

C.O. ADD.





GRAPHIC SCALE

DATE


REVISION


35R C.O. ADD.


SHEET No. E-12 OF 44 SHEETS


Date: April 2006


Scale: AS NOTED











Notes:

1 Saw Cut Exst Conc Sidewalk at Scorelines Prior to Trench Excavation. Repair Conc Sidewalk Per Detail on Civil Sht. 14.

2 Saw Cut Exst A.C. Pavement Prior to Trench Excavation. Repair Pavement Structure, See Sht E−23.

3 Demolish Exst Pullbox and Intercept Exst Conduit and Wiring with Pullbox Indicated.

Penetrate Exst Pullbox for Conduits Terminations. Repair to Match Exst.

5 Saw Cut Exst Conc Curb Curb Prior to Trench Excavation. Repair Type 2D Curb Per Detail on Civil Sht 14.

Saw Cut Exst Conc Curb and Gutter Prior to Trench Excavation. Repair Type 2DG Curb and Gutter per Detail on Civil Sht 14.

7 Saw Cut Exst Conc Curb Prior to Trench Excavation. Repair Type 3D Curb Per Detail on Civil Sht 14.

Saw Cut Exst Conc. Curb and Gutter Prior to Trench Excavation. Repair Type 3D Curb and Type 2A Gutter Per Detail on Civil Sht 14.



DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION HIGHWAY LIGHTING & TRAFFIC SIGNAL

PARTIAL PLAN 13 NIMITZ HIGHWAY AND

ALA MOANA BOULEVARD RESURFACING Fort Street to Piikoi Street

Project No. 92AB-01-06M
Scale: AS NOTED Date: April Date: April 2006

SHEET No. E-16 OF 44 SHEETS



HIGHWAY LIGHTING & TRAFFIC SIGNAL PARTIAL PLAN 13

SCALE: 1"=20' T.M.K.: 2-1-56 SCALE: GRAPHIC SCALE

Relocated "2L" Stub—Out Near Sta 35+60 Rt, Added "2TS" Stub—Out Near Sta 35+60 Rt

3/01/07 Added "2-2L" Across Koula St (Northside)


8/23/06 Del & Added Hwy Lt Stub Near Sta 36+00 Lt & Rt, Added Approval Block, Rev Stub Near Sta 37+30 Lt DATE REVISION

C.O. 39R

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	92AB-01-06M	2006	40R	74

<u>Notes:</u>

- 1 Saw Cut Exst Conc Sidewalk @ Scorelines Prior to Trench Excavation. Repair Conc Sidewalk Per Detail on Civil Sht 14.
- Saw Cut Exst A.C. Pavement Prior to Trench Excavation. Repair Pavement Structure, See Sheet E-23.
- Saw Cut Exst Conc Curb and Gutter Prior to Trench Excavation. Repair Type 2DG Curb and Gutter per Detail on Civil Sht 14.
- 4 Saw Cut Exst Conc Curb Prior to Trench Excavation. Repair Type 3D Curb Per Detail on Civil Sht 14.



PROFESSIONAL ENGINEER

APPROVED BY:

CHIEF, WASTEWATER BRANCH, DPP W

9/25/06

To Waikiki --->

SURVEY PLOTTE
DRAWN BY_____
TRACED BY____
DESIGNED BY____
QUANTITIES BY___
CHECKED BY____

HIGHWAY LIGHTING & TRAFFIC SIGNAL PARTIAL PLAN 14 SCALE: 1"=20' T.M.K.: 2-1-56

8/23/06 Added Approval Block

NIMITZ HIGHWAY AND ALA MOANA BOULEVARD RESURFACING Fort Street to Piikoi Street

DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION

HIGHWAY LIGHTING & TRAFFIC SIGNAL

PARTIAL PLAN 14


Project No. 92AB-01-06M Date: April 2006 SHEET No. E-17 OF 44 SHEETS




1"=20' SCALE: GRAPHIC SCALE

REVISION DATE


40R





Notes:

- 1 Saw Cut Exst Conc Sidewalk at Scorelines Prior to Trench Excavation. Repair Conc Sidewalk Per Detail on Civil Sht 14.
- 2 Saw Cut Exst A.C. Pavement Prior to Trench Excavation. Repair Pavement Structure, See Sht E-23.
- 3 Saw Cut Exst Conc Curb Prior to Trench Excavation. Repair Type 2D Curb Per Detail on Civil Sht 14.
- 4 Saw Cut Exst Conc Curb and Gutter Prior to Trench Excavation. Repair Type 3D Curb and Type 2A Gutter Per Detail on Civil Sht 14.





DEPARTMENT OF TRANSPORTATION

HIGHWAY LIGHTING & TRAFFIC SIGNAL

PARTIAL PLAN 16

NIMITZ HIGHWAY AND ALA MOANA BOULEVARD RESURFACING

Fort Street to Piikoi Street

Project No. 92AB-01-06M Scale: AS NOTED Date: April 2006

SHEET No. E-19 OF 44 SHEETS

HIGHWAY LIGHTING & TRAFFIC SIGNAL PARTIAL PLAN 16 SCALE: 1"=20' T.M.K.: 2-3-01


GRAPHIC SCALE


9/25/06


APPROVED BY:


CHIEF, WASTEWATER BRANCH, DPP IN

5/17/07 Rev & Added Stub-Outs Near Sta 3+50 8/23/06 Added Ductline on North Side & Approval Block DATE REVISION









FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	92AB-01-06M	2006	46	74

<u>Notes:</u>

- 1 Saw Cut Exst A.C. Curb Prior to Trench Excavation. Repair Type 6 Curb Per Detail on Civil Sht 14.
- 2 Saw Cut Exst A.C. Pavement Prior to Trench Excavation. Repair Pavement Structure, See Sheet E-23.
- 3 Saw Cut Exst Conc Curb and Gutter Prior to Trench Excavation. Repair Type 3D Curb and Type 2A Gutter Per Detail on Civil Sht 14.



DEPARTMENT OF TRANSPORTATION HIGHWAY LIGHTING & TRAFFIC SIGNAL

PARTIAL PLAN 20

NIMITZ HIGHWAY AND ALA MOANA BOULEVARD RESURFACING

Fort Street to Piikoi Street


Date: April 2006 SHEET No. E-22A OF 44 SHEETS


Project No. 92AB-01-06M Scale: AS NOTED

HIGHWAY LIGHTING & TRAFFIC SIGNAL PARTIAL PLAN 20 T.M.K.: 2-3-05

SCALE: GRAPHIC SCALE

Added Ductline REVISION






FED. ROAD DIST. NO. STATE PROJ. NO. FISCAL SHEET NO. SHEETS

HAWAII HAW. 92AB-01-06M 2006 C.0.48 74

Notes:

- 1 Saw Cut Exst Conc Sidewalk at Scorelines Prior to Trench Excavation. Repair Conc Sidewalk Per Detail on Civil Sht 14.
- 2 Saw Cut Exst A.C. Pavement Prior to Trench Excavation. Repair Pavement Structure, See Sheet E-23.
- 3 Demolish Exst Pullbox and Intercept Exst Conduit and Wiring with Pullbox Indicated.
- 4 Saw Cut Exst Conc Curb and Gutter Prior to Trench Excavation. Repair Type 3D Curb and Type 2A Gutter Per Detail on Civil Sht 14.
- 5 Saw Cut Exst Conc Roadway at Construction Joint Prior to Trench Excavation. Repair Conc Raadway to Match Exst, See Sht E-23.
- 6 Saw Cut Exst A.C. Curb Prior to Trench Excavation. Repair Type 6 Curb Per Detail on Civil Sht 14.
- 7 Penetrate Exst Pullbox for Conduit Entry. Repair to Match Exst.





DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

HIGHWAY LIGHTING & TRAFFIC SIGNAL PARTIAL PLAN 22

NIMITZ HIGHWAY AND

ALA MOANA BOULEVARD RESURFACING


Fort Street to Piikoi Street

Fort Street to Piikoi Street

Project No. 92AB-01-06M

Scale: AS NOTED Date: April 2006

SHEET No. E-22C OF 44 SHEETS



FISCAL SHEET YEAR NO. FED. ROAD PROJ. NO. DIST. NO. 2006 (.0.49 HAWAII 92AB-01-06M

<u>Notes:</u>

- Saw Cut Exst Conc Sidewalk at Scorelines Prior to Trench Excavation. Repair Conc Sidewalk Per Detail on Civil Sht 14.
- 2 Saw Cut Exst A.C. Pavement Prior to Trench Excavation. Repair Pavement Structure, See Sheet E-23.
- Demolish Exst Pullbox and Intercept Exst Conduit and Wiring with Pullbox Indicated.
- Saw Cut Exst Conc Curb and Gutter Prior to Trench Excavation. Repair Type 3D Curb and Type 2A Gutter Per Detail on Civil Sht 14.
- 5 Saw Cut Exst Conc Roadway at Construction Joint Prior to Trench Excavation. Repair Conc Roadway to Match Exst, See Sht E-23.
- Saw Cut Exst A.C. Curb Prior to Trench Excavation. Repair Type 6 Curb Per Detail on Civil Sht 14.
- Saw Cut Exst Conc Curb and Gutter Prior to Trench Excavation. Repair Type 2D Curb and Type 2A Gutter Per Detail on Civil Sht 14.



DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION HIGHWAY LIGHTING & TRAFFIC SIGNAL

PARTIAL PLAN 23


NIMITZ HIGHWAY AND ALA MOANA BOULEVARD RESURFACING


Fort Street to Piikoi Street Project No. 92AB-01-06M
Scale: AS NOTED Date: April

Date: April 2006 SHEET No. E-22D OF 44 SHEETS

DATE


REVISION






51R

C. O.




ADD. 52R



** Notes For Backfill Section (1)

- 1. If Trench Aligned Transverse to Direction of Travel, 1 Foot on Each Side of Trench.
- 2. If Trench Aligned Along Direction of Travel, to Edge of Lane in which Edge of Trench is Located.
- 3. Smoothness of Paved Surfaces:
 The Distance from the Paved Surface to the Testing Edge
 of a Ten-foot Straight Edge Between Two Points of Contact
 shall not Exceed 3/16".
- 4. Case 2 Occus at:
 Approx Sta No 144+60 to 145+10 North—Bound Lanes,
 Approx Sta No 142+50 to 143+00 South—Bound Lanes,
 Approx Sta No 139+20 to 140+20 Median,
 Fort St. Intersection Northwest and Southwest Coners.
- 5. Case 3 Occus at: Queen St. to End of Project — West Bound, Right Lane.
- 6. Dowel to Exst Conc Pavement Per Detail on Civil Sht 17.



2 BACKFILL SECTION
WITHIN STATE RIGHT-OF-WAY
UNDER EXISTING CONCRETE SIDEWALK
OR GRASSED AREA [2]

5/30/06 Rev Case 1 Backfill Section

REVISION

DATE

FED. ROAD DIST. NO. STATE PROJ. NO. FISCAL SHEET TOTAL SHEETS

HAWAII HAW. 92AB-01-06M 2006 53 74

STATE RIGHT-OF-WAY BACKFILL NOTES

Trench Backfill Material "B" 1. Sand Equivalent ≥ 2

2. 8" Max. Lift Loose

3. 95% Compaction

Trench Backfill Material "A"

Sand Equivalent ≥ 20
 8" Max. Lift Loose

3. 95% Compaction


777 1

If Material Below Duct is Not Equivalent to Backfill Material "A", Excavate Material & Provide 3" Backfill Material "A", See Above

Concrete — 3" Encasement, 2500 PSI Compressive Strength @ 28 Days.

Notes:

- Sawcutting & Repairing of Exst
 A.C. Pavement shall not be Paid
 for Separately, but Considered
 Incidental to the Various
 Contract Items.
- 2 Sawcutting & Repairing of Exst Conc Pavement shall not be Paid for Separately, but Considered Incidental to the Various Contract Items.



THIS WORK WAS PREPARED BY ME
OF UNDER MY SUPPRISION.

LICENSE EXPIRES 4-30-08

TATE OF HAWAII
OF TRANSPORTATION

DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

TYPICAL BACKFILL SECTIONS (STATE)

NIMITZ HIGHWAY AND

ALA MOANA BOULEVARD RESURFACING

Fort Street to Piikoi Street


Project No. 92AB-01-06M


Scale: AS NOTED


Date: April 2006

SHEET No. E-23 OF 44 SHEETS

ADD. 53







OR GRASSED AREA

UNDER EXISTING CONCRETE SIDEWALK

.

UNDER EXISTING

ROADWAY

TRENCH RESTORATION NOTES:

- 1. Not Used.
- 2. Pavement Structure shall be Equal or Better Than Existing Pavement in Thickness and Quality.
- 3. Conditions Where Trench Runs Perpendicular or Skew to the Travel Way Direction and/or Longitudinal Trenches Less Than Ten Feet in Length shall be Repayed A Minimum of Four Feet Wide with Trench Centered Within the Paved Width (T-Section) or the Paved Area shall be the Trench Width Plus an Additional One Foot on Each Side of the Trench (T-Section), Whichever is Greater. The Length of the Repaved Trench shall be Repaved A Recommended Two Feet in Added Length to Each End of the Trench.
- 4. Trenches Running Longitudinally to the Travel Way on Roadways Where the Paved Travel Way is 36 Feet or Less shall be Repayed to the Trench Width Plus an Additional One Foot on Each Side of the Trench (T-Section) with a Recommended Two Feet in Added Length to Each End of the Longitudinal Trench. The Replaced Pavement shall have a Minimum Thickness of Four Inches of Asphalt Concrete or Match the Existing Pavement Thickness, Whichever is Greater.
- 5. Trenches Running Longitudinally to the Travel Way on Roadways Where the Paved Travel Way is Greater Than 36 Feet shall be Cold Planned a Minimum of Two Inches and Repayed to the Original Grade. The Paving shall be a Minimum Width of One Lane Not Exceeding 15 Feet in Width with a Minimum of Two Feet in Added Length to Each End of the Longitudinal Trench. The Replacement Pavement Within the Trench Limits, Plus an Additional One Foot on Each Side of the Trench (T—Section), shall have a Minimum Thickness of Four Inches of Asphalt Concrete or Match the Existing Pavement Thickness, Whichever is Greater.
- 6. Pavement Markings Restore Pavement Stripings, Raised Pavement Markers and Pavement Markings Whether Shown or Not on the Plans Within the Repaved Areas as Defined Above.

For Lane and Edge Stripings Restoration, Extend 12" From the Limit of Work.

Contractor to Match Width (Whichever is Greater) and Color of Striping, Type of Raised Pavement Markers, Pavement Words, and Pavement Directional Arrow.

<u>CITY RIGHT-OF-WAY BACKFILL NOTES:</u>

Type "A" Backfill — Earth & Gravel. Rock Size to be 1" Max & the Mixture to Contain Not More Than 50% by Volume of Rock Particles. The Material shall be Nonexpansive. 95% Compaction.

Type "B" Backfill — Earth & Gravel. Mixture Must Pass A 1/2" Mesh Screen & Contain Not More Than 20% by Volume of Rock Particles. 95% Compaction.




Note — If Normal Material at Bottom of Trench is Not Type "B", an Additional 3" shall be Excavated & Type "B" Backfill Provided.





Concrete - 3" Encasement, 2500 PSI Compressive Strength @ 28 Days.

DATE

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	92AB-01-06M	2006	55	74







<u>TYPICAL DUCT</u> SECTIONS (CITY) NOT TO SCALE


THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.


DEPARTMENT OF TRANSPORTATION TYPICAL BACKFILL & DUCT SECTIONS (CITY) NIMITZ HIGHWAY AND

ALA MOANA BOULEVARD RESURFACING Fort Street to Piikoi Street

Project No. 92AB-01-06M Scale: AS NOTED Date: April 2006 REVISION SHEET No. E-25 OF 44 SHEETS

TYPICAL BACKFILL SECTIONS (CITY) NOT TO SCALE






otes:	
Stan	dard
with	AASH

- shall be Designed in Accordance HTO "Standard Specification for Structural Supports for Highway Signs, Luminaires and Traffic Signals", Dated 2001 Traffic Signal Standard and Arm Assembly shall Withstand 105 M.P.H. Sustained Winds with 1.14 Gust Factor without Permanent Deformation.
- 2. Submit Shop Drawings for Approval.
- 3. For Signal Head Mountings, See Details A/E-29, A/E-30.


TYPE OF STANDARD	"A"
TYPE I-13	13
TYPE I-10	10
TYPE 1-8	8
TYPE 1-3	3

Typical Designation:



TYPE I STANDARD AND PEDESTAL INSTALLATION NOT TO SCALE


Conc Base, See D.O.T.—Hwys Std Plan TE—38.



TYPE 332A TRAFFIC SIGNAL CONTROLLER CABINET DETAIL NOT TO SCALE

Approx. 24" PVC Conduits, Sch. 40 Concrete Encased (To Pullbox), See Plan for Size & Quantity Drain 1" Conduit – Ground Rod-5/8" Dia x 10'–0", Copper Cladded Steel Core Slope towards Drain

<u>PLAN</u>



SECTION "A"

SECTION "B"

Notes:

- 1. Concrete shall be class "B".
- 2. Dimensions shall be altered to suit controller cabinet actually furnished.
- 3. Conduits bends and drain are incidental to concrete
- 4. Refer to Cabinet Manufacturer's Specifications for details of anchor bolts and base setting.
- 5. All exposed surfaces of concrete base shall be given a class 2, rubbed finish.

DATE



FISCAL SHEET

56

SHEETS

YEAR

2006

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.

DEPARTMENT OF TRANSPORTATION TRAFFIC SIGNAL DETAILS

NIMITZ HIGHWAY AND ALA MOANA BOULEVARD RESURFACING

Fort Street to Piikoi Street Project No. 92AB-01-06M Scale: AS NOTED Date: April 2006


CONTROLLER CABINET CONCRETE BASE
NOT TO SCALE


REVISION SHEET No. E-26 OF 44 SHEETS

FED. ROAD DIST. NO.

STATE

92AB-01-06M






SINGLE-LINE DIAGRAM (TRAFFIC SIGNAL SYSTEM AT PIIKOI ST)

DATE

REVISION



ELEVATION

Min.

5° Tilt

<u>Notes:</u>

Continuous Taper-

Round Galvanized

Steel Shaft, 7 Ga Min

Handhole with Cover—

Anchor Bolt Plate —

and Cover

Base Setting-

See A E-2/1E-28

1. Standard shall be Designed in Accordance with AASHTO "Standard Specifications for Structural Supports for Highway Signs, Luminaires and Traffic Signals", Dated 2001. Interim Revisions. Traffic Signal Standard and Arm Assembly shall Withstand 105 M.P.H. Sustained Winds with 1.14 Gust Factor withoout Permanent Deformation. See Specifications for Additional Requirements.

-Conc Base,

See Struct

Dwg Sht 67

Continuous Taper Round Galvanized

Steel Mast Arm, 7 Ga Min

Mast Arm Length as Indicated on Plan

Varies, 12'-0" Max


— Number of Signals as Indicated on Plan. Signals


Shall be Centered over

Lane Lines

- 2. Mounting for Signals at Intermediate Locations on the Mast Arm shall be of the Adjustable Type.
- 3. Size, Length, Bolt Circle Diameter, and Embedded Depth of Anchor Bolts shall be as Recommended by the Manufacturer.
- 4. Contractor shall Submit Shop Drawings to the Engineer for
- 5. Handhole shall be Opposite of Traffic Flow.
- 6. For Signal Head Mountings, See Details A/E-29, A/E-30.









THIS WORK WAS PREPARED BY ME OB UNDER MY SUPERVISION.

DEPARTMENT OF TRANSPORTATION TRAFFIC SIGNAL DETAILS II


NIMITZ HIGHWAY AND ALA MOANA BOULEVARD RESURFACING Fort Street to Piikoi Street Project No. 92AB-01-06M

SHEET No. E-27 OF 44 SHEETS

Scale: AS NOTED


57

Date: April 2006




CONDUIT DETAILS FOR TRAFFIC SIGNAL/HWY. LIGHTING STANDARD

-28 Not to Scale



FED. ROAD DIST. NO. STATE PROJ. NO. FISCAL YEAR NO. SHEETS
HAWAII HAW. 92AB-01-06M 2006 58 74




TYPICAL PEDESTAL/TYPE T.S.S. MOUNTING OF EVP DETECTOR



REVISION

DATE



DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

TRAFFIC SIGNAL DETAILS III

<u>NIMITZ HIGHWAY AND</u> <u>ALA MOANA BOULEVARD RESURFACING</u> <u>Fort Street to Piikoi Street</u>


Fort Street to PIIKOI Street

Project No. 92AB-01-06M


Scale: AS NOTED Date: April 2006

SHEET No. E-28 OF 44 SHEETS


FISCAL SHEET TOTAL YEAR NO. SHEETS FED. ROAD DIST. NO. PROJ. NO. STATE HAW. 92AB-01-06M 2006



TOP OF POLE - ONE WAY MOUNTING




TOP OF POLE - TWO WAY MOUNTING



BRACKET MOUNT - ONE WAY

DATE

<u>BRACKET MOUNT - TWO WAY</u>



MOUNTING AT INTERMEDIATE POINT

ADJUSTABLE MAST ARM MOUNTING NOTES:

- Stainless Steel Bands shall be 1/2" Wide x .050" Thick, Minimum. Tensile Strength shall be 100,000 PSI Minimum.
- 2. Upper Arm, Lower Arm and Vertical Support Tube shall be of 356 Cast Aluminum.
- 3. All Wiring shall be Concealed.
- 4. Vertical Tube Clamp shall be of Malleable Iron, Grade 32510.
- 5. All Aluminum Parts shall have an Alodine 1200 Finish.

GENERAL NOTES:

- 1. Signal Head shall be as Noted on Plans.
- 2. Maintain 16" Min. Clearance at Rear of All Programmed Faces.



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION

DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION TRAFFIC SIGNAL DETAILS IV


<u>NIMITZ HIGHWAY AND</u> ALA MOANA BOULEVARD RESURFACING Fort Street to Piikoi Street


Project No. 92AB-01-06M
Scale: AS NOTED

Date: April 2 Date: April 2006 REVISION SHEET No. E-29 OF 44 SHEETS

VEHICULAR SIGNAL MOUNTING DETAILS


Not to Scale






TYPICAL SENSOR LOOP SAWCUT DETAIL

Exst Curb




TYPICAL SENSOR LOOP LAYOUT


NOTES ON CONSTRUCTION AT END OF SAWCUT




TYPICAL SENSOR LOOP WIRING DIAGRAM

TYPICAL SENSOR LOOP DETAILS







FED. ROAD DIST. NO.

HAWAII

STATE

HAW.

PROJ. NO.

92AB-01-06M


FISCAL SHEET TOTAL YEAR NO. SHEETS

2006

LOOP DETECTOR DETAILS, TYPICAL PULLBOX GROUP PLAN

NIMITZ HIGHWAY AND ALA MOANA BOULEVARD RESURFACING Fort Street to Piikoi Street Project No. 92AB-01-06M Scale: AS NOTED Date: April 2006

SHEET No. E-31 OF 44 SHEETS



GENERAL NOTES:

SURVEY PLOTTI
DRAWN BY
TRACED BY
QUANTITIES BY
CHECKED BY
CHECKED BY

- 1. The Location of Inductance Loops, Pullboxes and Cabinets/Junction Boxes shall be Staked Out in the Field by the Contractor and Approved by the Engineer Prior to Installation.
- 2. The Contractor shall Inform the Engineer at Least Three Days Prior to Saw—Cutting Pavement and Installing Inductance Loops.
- 3. Continuity of Inductance Loops and Lead—In Wires shall be Tested and Warranted for One Year from Date of Acceptance by the Contractor.
- 4. Upon Completion of Conduit Roadway Crossing, Pull In In—Bound Lanes Loop Detectors Cable and Class 1 BL Sensor Cables. Cables shall be Tested for Acceptance Before and After Installation into Conduit.
- 5. The Contractor shall Restore All Affected Areas to their Original Condition. This Item of Work shall not be Paid for Separately, but shall be Considered Incidental to Work of Other Paid Items.
- 6. The Contractor shall Verify the Location of the Existing Utilities and Underground Structures Whether or Not Shown on Plans.
- 7. The Contractor shall Assume that Existing Underground Utilities not Shown on the Plans may Exist, therefore, the Contractor shall Contact the Different Utility Companies for Information and Toning.
- 8. The Contractor shall be Held Liable for Any Damages Incurred to the Existing Utilities and Underground Structures as a Result of their Operations. All Damaged Portions shall be Replaced in Accordance with the Standards and Specifications of the Affected Utility Company at No Cost to the State.
- 9. Changes to the Contract Plans and Specifications shall not be Permitted, Unless Otherwise Authorized by the Engineer Upon Written Justification and Request for Approval by the Contractor.
- 10. Highway Crossing Sleeve shall be Provided with Minimum 36" Cover.

Connecting Layout of Loop Lead—In Wires to Terminal Block Inside Cabinet

BOTTOM OF TERMINAL BLOCK

TERMINAL BLOCK WIRING

DETAILS - STATION 16

LOOP LAYOUT NOTES:

- 1. Detector Loop shall Consist of Four Turns of 1/C #12 Cable Meeting IMSA Spec 51-5 or Equivalent Embedded in a 3/8 "Minimum Sawcut, Except as Noted.
- 2. Loop and Lead—In to the First Pullbox shall be One Continuous Wire. Lead—In Wires from the Same Loop shall be Twisted in Pairs, Two Turns per Foot. Do not Twist One Loop—Pair with Another Loop—Pairs.
- 3. All Lead—In Wires shall be Crimped with Open End Lugs that will Fit into the Terminal Board Slots Snugly.
- 4. Stagger Traffic Loops on Roadway Less Than 12 Foot Lane Width.
- 5. The Contractor shall Connect the Inductance Wires on Each Terminal Slot.
- 6. The Left Lane in the Direction of Traffic Flow is Designated as Lane 1, and the Lane Next to its Right as Lane 2 and so on as Indicated on Plans.
- 7. Vacuum and Clean Sawcut Thoroughly Before Installing Sensors and/or Cables and Filling with Hot Tar or Epoxy Sealant.

FED. ROAD DIST. NO. STATE PROJ. NO. FISCAL SHEET NO. SHEETS


HAWAII HAW. 92AB-01-06M 2006 C.0.63 R 74

Date: April 2006

C.O. 63R

SHEET No. E-33 OF 44 SHEETS


- 8. All Loop Lead—In Wires in All Enclosures including Pullboxes shall be Identified and Labeled by Direction of Traffic Flow and Lane Number as Shown on Plans.
- 9. All Cable and Wires Terminated Within an Enclosure shall have a Minimum 12" Additional Slack.
- 10. Loops shall be Centered in Each Lane Based on the Final Striping.



DATE

REVISION

FED. ROAD DIST. NO. FISCAL SHEET TOTAL YEAR NO. SHEETS PROJ. NO. STATE 2006 64 HAW. 92AB-01-06M HAWAII



CONDUIT "A" TABLE:


NUMBER OF LANES	4"C	CLASS 1 BL SENSOR LEAD CABLES	2/C #14 LOOP DETECTOR CABLES
2	1	2	2
4	2	4	4

CONDUIT "B" TABLE:

NUMBER OF LANES	4"C	CLASS 1 BL SENSOR LEAD CABLES	2/C #14 LOOP DETECTOR CABLES
2	2	4	4
4	4	8	8


NOTE: All Dimensions and Callouts are Typical Unless Noted on Plan

TYPICAL TRAFFIC COUNTING STATION LAYOUT DETAIL NOT TO SCALE



If Roadway Runs in the North and South Direction the First Letter on the Loop Label should Read N for North and S for South. If Roadway runs in the East and West Direction the First Letter on the Loop Label should Read E for East and W for West






Connecting Layout of Loop Lead-In Wires to Terminal

TYPICAL FOUR-LANE ROADWAY TERMINAL BLOCK **WIRING DETAILS**

NOT TO SCALE

Block Inside Cabinet




BOTTOM OF TERMINAL BLOCK

Connecting Layout of Loop Lead—In Wires to Terminal Block Inside Cabinet

TYPICAL TWO-LANE ROADWAY TERMINAL BLOCK **WIRING DETAILS** NOT TO SCALE

DATE



If Roadway Runs in the North and South Direction the First Letter on the Loop Label should Read N for North and S for South. If Roadway runs in the East and West Direction the First Letter on the Loop Label should Read E for East and W for West



—Indicates Approaching or Trailing Loop -Indicates Lane Number -Indicates Direction*

> Loop Label Legend: E = East

W = West

N = North

S = SouthA = Approaching

T = Trailing



THIS WORK WAS PREPARED BY ME OR LINEDER MY SUPERVISION.

DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION TRAFFIC COUNTING STATION DETAILS I


NIMITZ HIGHWAY AND ALA MOANA BOULEVARD RESURFACING Fort Street to Piikoi Street


Project No. 92AB-01-06M Scale: As Noted Date: April 2006

SHEET No. E-34 OF 44 SHEETS

SURVEY PLOTTE
DRAWN BY...
TRACED BY...
DESIGNED BY...
QUANTITIES BY...
CHECKED BY...

REVISION 64






NOTES ON CONSTRUCTION AT END OF SAWCUT

- 1. Seal Roadway End of Conduit After Installation of Conductors.
- 2. Install Bulkhead Across Conduit Trench.
- 3. Place Hot Tar in Sawcut.
- 4. Backfill Over Conduit with A.C.
- 5. Reconstruct Curb and Gutter as Required.

DETAIL OF SENSOR LOOP/CLASS 1 BL SENSOR INSTALLATION AT EDGE OF ROADWAY



TYPICAL SENSOR LOOP WIRING DIAGRAM

TYPICAL SENSOR LOOP SAWCUT DETAIL

FED. ROAD DIST. NO. FISCAL SHEET TOTAL YEAR NO. SHEETS PROJ. NO. STATE 2006 HAW. 92AB-01-06M HAWAII

NOTES:

—Sensor w/Clips

@ 6" Centers

-Class 1

Sensor Lead Cable (4-Shown)

Provide Number Required. Obtain

Manufacturer's Requirements for

Separation. Provide Appropriate

Clips at 6" Centers

BL Sensor

—Ероху Fill —


Groove

APPROVED BY:


CHIEF, CIVIL ENGINEERING BRANCH, DPP (FOR WORK WITHIN CITY R/W ONLY)

DATE

- 1. BL Sensors shall be Terminated with "BNC" Type Connectors or Connectors Appropriate to the Counting Equipment (Automatic Traffic Recorder).
- 2. BL Sensor shall be Centered in Each Lane Based on the Final Lane Striping. BL Sensor shall be Installed After the Roadway has been Striped.



PLAN VIEW



CURB & GUTTER CONNECTION DETAIL (DPW Std Det R-4 Revised)


> DEPARTMENT OF TRANSPORTATION
> HIGHWAYS DIVISION TRAFFIC COUNTING STATION a/4/06 DETAILS III, MISCELLANEOUS DETAILS

NIMITZ HIGHWAY AND ALA MOANA BOULEVARD RESURFACING 8/23/06 Rev Det "B" Fort Street to Piikoi Street Project No. 92AB-01-06M 5/30/06 Added Det "B" Scale: AS NOTED Date: April 2006 REVISION SHEET No. E-35 OF 44 SHEETS

C.O. ADD. 65

LICENSED PROFESSIONAL


ENGINEER





NOTES:


. . . .

- 1. Contractor shall Make All Electrical Connection to Traffic Counting Station Cabinet, Provide 2—1P50A Breaker, Ground and 2" Conduit.
- 2. All Conduits to Contain a Polyolefin Pull Line. (Jet Line Cat #232 or Equiv)
- 3. Pedestal shall be Hot-Dipped Galvanized After Fabrication.
- 4. All Fastening Bolts, Nuts & Washers shall be Stainless Steel. Provide One Coat Shop Primer & Two Coats of Acrylic Enamel Finish, Color to Match Traffic Counting Station Cabinet.
- 5. Provide 4 Ft Clearance in Front of Meter.
- 6. See One-Line Diagram, This Sheet











TRAFFIC COUNTING STATION ONE-LINE DIAGRAM




NOTES:


- 1. Use 3-Ply Laminated Flexible Plastic, Black-White-Black Thickness: Black Cap Sheet-0.010", White Base Sheet-0.052", Black Base Sheet-0.010".
- Attach to Meter Socket Using Scotch 3M Brand Very High Bond (VHB) Double Coated Acrylic Foam Tape or Equivalent.
- 3. Letters/Numbers shall be 1/16" Stroke, (White in Color).
- 4. Letters/Numbers Area Inscribed by Cutting through "Black Cap Sheet" to Expose White Letters/Numbers.








<u>PLAN VIEW</u>




SECTION "A-A"

NOTES:

- 1. Compressive Strength of Concrete: 3000 PSI In 28 Days.
- 2. Reinforcing Round Deformed Bar shall be Clean & New.
- 3. Cure Concrete by Approved Method.
- 4. Top of Concrete Pad to be Smooth, True & Level, Free from Defects.
- 5. Contractor has Option of Furnishing Cast-In-Place or Precast.
- 6. Minimum Clear Space Around Pad: 8'-0" at Front, 2'-6" at Sides, 2'-0" at Back.



CONCRETE TRANSFORMER PAD DETAIL NOT TO SCALE



DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

TRAFFIC COUNTING

STATION DETAILS IV


NIMITZ HIGHWAY AND
ALA MOANA BOULEVARD RESURFACING
Fort Street to Piikoi Street

 Project No. 92AB-01-06M

 Scale: As Noted
 Date: April 2006

 DATE
 REVISION

 SHEET No. E-36 OF 44 SHEETS



FED. ROAD STATE PROJ. NO. FISCAL SHEET TOTAL SHEETS

HAWAII HAW. 92AB-01-06M 2006 67 74

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION


TYPE II TRAFFIC SIGNAL STANDAR


<u>NUANA DUULEVARD RESURF Fort Street to Piikoi Street</u> <u>Project No. 92AB-01-06M</u>

Scale: As Noted Project No. 92AB-01-0

SHEET No. E37 OF 44 SHEETS

Date: Mar. 2006






CONDUIT BY-PASS BELOW EXISTING BOX DRAIN DETAIL NOT TO SCALE

—"True Dam" Sediment Filter (By Dandy Products, Inc.) or Approved Equal __Exst Catch Basin Gravel Filled Pouch PVC Pipe


<u>Notes:</u>

- 1. Sediment Control Filters Shall Be Constructed and Maintained on All Existing Catch Basins Within Project Limits.
- 2. Contractor Shall Remove Sediment Filters During an Event of Above Normal Rainfall and Replace Filters After Event has Passed.



SEDIMENT CONTROL FILTER AT CATCH BASIN

NOT TO SCALE



Note: Provide PVC Coated GRSC and Steel Reinforcement Until Top of Conc Encasement is Min 18" Below Fin Grade.

SECTION (SR3)

TYPICAL DUCT SECTIONS (STATE)

NOT TO SCALE



FISCAL SHEET TOTAL YEAR NO. SHEETS

2006 (.0.675-)

FED. ROAD DIST. NO.

PROJ. NO.


92AB-01-06M

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION MISCELLANEOUS DETAILS

<u>NIMITZ HIGHWAY AND</u> <u>ALA MOANA BOULEVARD RESURFACING</u> Fort Street to Piikoi Street Project No. 92AB-01-06M

Scale: As Noted Date: April 2006 SHEET No. E-38 OF 44 SHEETS

67S-1



APPROVED BY:

meluni Dabalura
CHIEF, CIVIL ENGINEERING BRANCH, DPP
(FOR WORK WITHIN CITY R/W ONLY)

8/23/06 Added Sht

DATE REVISION

a/4/06