

Dewatering Quantities-Maipalaoa Bridge

Dewatering for Central Piers

*Assume 20gpm infiltration into caisson from caisson-channel lining perimeter

Quantity of water already in caisson:

Assume:

- 1) 8' x 15' rectangular caisson
- 2) Demo one pier at a time
- 3) Dewatering for entire 8 hr work day
- 4) 2 days per pier demo 1 day cut, 1 day cure of lining cap
- 5) High point of water 100 yr storm 2.2 +msl
- 6) Channel invert at piers at -3.75msl

Volume of existing water to be removed from each caisson:

$V = \text{Area of Base} * \text{Height}$

$$V = 8' \times 15' * (2.2' + 3.75')$$

$$V = 714 \text{ cuft}$$

Volume of existing water to be removed from all caissons:

$V = \text{Volume Water} * \text{Number of Piers}$

$$V = 714 \text{ cuft} * 21 \text{ piers}$$

$$V = 14994 \text{ cuft}$$

Total quantity of infiltrating water:

$V = \text{Infiltration rate} * \text{Working Day Hours} * \text{Days to demo all piers}$

$$V = 20 \text{ gpm} * 0.13368056 \text{ cuft/gal} * 8 \text{ hr} * 60 \text{ min/hr} * 42 \text{ days}$$

$$V = 53900 \text{ cuft}$$

Total Caisson Dewatering:

25% Safety Factor

$$V = 14994 \text{ cuft} + 53900 \text{ cuft}$$

$$V = 68894 \text{ cuft}$$

$$\text{VSF} = 86117.5 \text{ cuft}$$

Daily Caisson Dewatering:

25% Safety Factor

$$V = 714 \text{ cuft} + (20 \text{ gpm} * 0.13368056 \text{ cuft/gal} * 8 \text{ hr} * 60 \text{ min/hr})$$

$$V = 1997.333 \text{ cuft}$$

$$\text{VSF} = 2496.667 \text{ cuft}$$