


(Tape, Type III or Thermoplastic Extrusion)

SURVEY PLOT
DRAWN BY X
TRACED BY \_\_
DESIGNED BY \_\_
QUANTITIES B
CHECKED BY \_\_

## <u>NOTES</u>

- 1. Layout of pavement markings and striping shall be done by the Contractor and approved by the Engineer prior to any installation work.
- 2. Existing pavement markings not incorporated in the final traffic pattern shall be removed as directed by the Engineer. Costs shall be incidental to the various pavement marking items.
- 3. Raised pavement markers shall not be installed within crosswalks.
- 4. Final locations of all signs shall be approved by the Engineer prior to any installation work.
- 5. Existing signs not shown on these plans shall remain as posted unless otherwise directed by the Engineer. Removal and disposal of existing signs and/or posts as designated on these plans shall be incidental to the various signing items.
- 6. Final locations of all Stop Lines shall be approved by the Engineer prior to installation.
- 7. All pavement striping shall be as noted on the legend or plans.
- 8. All preformed pavement marking tapes over existing pavement shall be applied with an approved primer as recommended by the tape manufacturer and as approved by the Engineer. The primer shall be allowed to dry to the tacky stage prior to tape application.
- 9. The Contractor shall erect at the beginning of the project and at the end of the project advance construction warning signs placed as indicated on the plans or as directed by the Engineer for the duration of the highway project and shall be maintained by the Contractor. These signs shall be placed in addition to the required traffic control signs called for in Section 645 Traffic Control. The advance construction warning signs shall be new and become the property of the State. The Contractor shall remove, clean, and deliver the signs and posts to the District Baseyard, or as directed by the Engineer, upon the completion of the project.



Not to Scale

Type C Marker

3' 12' 3' 12' 3' 12' 3' 6'

Type C Marker

8" Solid White Stripe w/Type C Markers @ 20' o.c. as shown on Plans (Tape, Type I or Thermoplastic Extrusion)

To Gore

8" White Stripe (Typical) (Tape, Type I or Thermoplastic Extrusion)

LANE DROP MARKING


Not to Scale

FED. ROAD DIST. NO. STATE PROJ. NO. FISCAL YEAR NO. SHEETS

HAWAII HAW. 93A-01-06M 2010 21 36

— Set all crosswalks away from catch basins

-12" Stop Line



Crosswalk Striping -

DETAIL "A"

CROSSWALK STRIPING DETAIL

Not to Scale

DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

PAVEMENT MARKING
LEGEND, DETAILS \$ NOTES

FARRINGTON HIGHWAY
PAVEMENT PREVENTIVE MAINTENANCE
Keananoio Bridge to Palailai Interchange
Project No. 93A-01-06M

Scale: As Noted

Date: March, 2010

SHEET No. 71 OF 14 SHEETS

21