


FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	STP-093-1(026)	2016	22	110


GENERAL NOTES

1. All hardware, posts and fasteners shall be hot-dip zinc coated galvanized after fabrication. No punching, drilling or cutting will be permitted after galvanizing.
2. Where conditions require, special post lengths in increments of 6 inches may be specified.
3. All fasteners, posts, and rail elements (i.e. FBB03, PWE01, RWM02b, etc.) shall conform to the latest edition and amendments of "A Guide to Standardized Highway Barrier Rail Hardware", a report prepared and approved by the AASHTO-AGC-ARTBA Joint Cooperative Committee, Subcommittee On New Highway Materials, Task Force 13 Report. Dimensions of fastners, posts and rail elements have been converted from metric units into their present form.
4. The Recycled Plastic Block or Offset Block shall be approved by the State.
5. All new guardrail systems (system consists of total length of guardrail including both end treatments) shall include the Additional Paved Area.
6. After the guardrail posts are installed in the paved area, the Contractor shall fill/seal around each guardrail post and all cracks in the paved area caused during the guardrail post installation. If required by the inspector/engineer, the Contractor shall tamper the paved area around the guardrail post prior to filling/sealing. All costs associated with this work shall not be paid for separately, but shall be considered incidental to the various guardrail items.
7. When standards for the fill slope area cannot be met, a site specific, engineer approved design may be used.
8. New A.C. pavement at guardrails shall extend 6 feet longitudinally beyond terminal ends.
9. Reflector Markers (RM-5) mounted on guardrails shall be spaced every 25 feet. RM-5's shall not be installed on Terminal Sections. Furnishing and installing of each RM-5 shall be considered incidental to the adjacent guardrail system.


GUARDRAIL TYPE	DIMENSION	
	H	A
Strong Post W-Beam	1'-9 <sup>5</sup> / <sub>8</sub> "	1'-6"
Strong Post Rubrail (W-Beam)	2'-0"	1'-6"
Modified or Strong Post Thrie Beam	2'-0"	2'-0"





TOP  
SIDE  
RECYCLED PLASTIC BLOCKOUT (TYPE I)



RECYCLED POLYETHYLENE  
OFFSET BLOCK (TYPE II)




Exploded View  
(Rail and washer not shown)  
STEEL POST AND BLOCK DETAIL



ELEVATION

TYPICAL GUARDRAIL INSTALLATION



REFLECTOR MARKER (RM-5) DETAIL AND TYPICAL INSTALLATION

STATE OF HAWAII

DEPARTMENT OF TRANSPORTATION

HIGHWAYS DIVISION

GUARDRAIL DETAILS & NOTES

FARRINGTON HIGHWAY RESURFACING

Vicinity of Kili Drive to

Satellite Tracking Station Road

Federal Aid Project No. STP-093-1(026)

Date: April, 2016

SHEET No. 1 OF 9 SHEETS

22




Diagram illustrating the dimensions and components of a PWE01 offset block or blockout. The diagram shows a cross-section of the block with a guardrail on the left. The dimensions are as follows:

- Offset Block or Blockout
- Guardrail
- TRAFFIC (indicated by an upward arrow)
- Offset Block or Blockout
- PWE01
- Dimensions:  $7\frac{5}{8}"$  and  $5\frac{7}{8}"$
- Height:  $4"$

Diagram illustrating the assembly of a 6'-0" high antenna mast. The mast is supported by a base structure. Key components and dimensions are labeled:

- Offset Block or Blockout**: A component mounted on the mast, secured with **Splice Bolts** (labeled **FBB01**) and **RWM02a**.
- Ground Line**: Indicated at the base of the mast.
- PWE01**: A component located below the offset block.
- Dimensions**:
  - The total height of the mast is **6'-0"**.
  - The height from the ground line to the top of the offset block assembly is **1'-9 5/8"**.
  - The height of the offset block assembly is **7"**.


STRONG POST W-BEAM GUARDRAIL  
(SGR04a)




STRONG POST W-BEAM GUARDRAIL WITH  
RECYCLED OFFSET BLOCK OR PLASTIC BLOCKOUT

W6x8.5  
Structural  
Shape

4"



W-BEAM STRONG POST (PWE01)




Mod. Heavy Hex Nut

1" Dia. x  $\frac{1}{16}$ " Recess both sides

$1\frac{1}{4}$ "

$1\frac{1}{16}$ "

### GUARDRAIL BOLTS AND RECESSED NUT



DESIGNATOR	BASE METAL THICKNESS
RWM02a	12 Gauge

2 SPACE W-BEAM GUARDRAIL (RWM02a)

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION





**GUARDRAIL DETAILS & NOTES**  
**FARRINGTON HIGHWAY RESURFACING**  
*Vicinity of Kili Drive to*  
*Satellite Tracking Station Road*  
*Federal Aid Project No. STP-093-(1026)*

*Date: April, 2016*





ORIGINAL PLAN	SURVEY PLOTTED BY _____ DATE _____
NOTE BOOK	DRAWN BY <u>χ</u> _____ DATE <u>χ</u> _____
<u>dd:5ren</u>	DESIGNED BY _____ DATE _____
	TRACED BY <u>χ</u> _____ DATE _____
	QUANTITIES BY _____ DATE _____
	CHECKED BY _____ DATE <u>4-11-59</u>



FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	STP-093-1(026)	2016	24	110



Foundation Tube Options For Posts 1 & 2  
 \*6'-0" Split Foundation Tubes S730  
 \*6'-0" Solid Foundation Tubes E731  
 \*5'-0" Foundation Tubes S735 W/Soil Plates SP600  
 \*4'-6" Foundation Tubes E735 W/Soil Plates SP600



SECTION B-B  
 (Typical @ Post 3 - 7)  
 NOTE: RAIL NOT BOLTED @ POST #3

# GENERAL NOTES

- Breakaway steel posts are required with the FLEAT Terminal.
- All bolts, nuts, cable assemblies, cable anchors and bearing plates shall be galvanized.
- The soil tubes shall not protrude more than 4" above ground (measured along a 5' cord). Site grading may be necessary to meet this requirement.
- The soil tubes may be driven with an approved driving head. Soil tubes shall not be driven with the post in the tube. If the tubes are placed in drilled holes, the backfill material must be satisfactorily compacted to prevent settlement.
- When rock is encountered during excavation, a 12" Dia. post hole, 20" deep may be used if approved by the engineer. Granular material will be placed in the bottom of the hole approx. 2 1/2" deep to provide drainage. The soil tubes will be field cut to length, placed in the hole and backfilled with adequately compacted material excavated from the hole.
- The breakaway cable assembly must be taut. A locking device, (vice grips or channel lock pliers) should be used to prevent the cable from twisting when tightening nuts.
- (R) or (L) indicates right or left Impact Head Reflector Marker (IHRM). Providing and installing of IHRM shall be considered incidental to end treatment.
- The stripes for IHRM shall slope downward at an angle of 45° towards the side of the end treatment that traffic is to pass.

ITEM NO.	QTY.	BILL OF MATERIALS
F3000	1	IMPACT HEAD
F1303	1	W-BEAM GUARDRAIL END SECTION, 12 GA.
G1203	2	W-BEAM GUARDRAIL, 12 GA.
S730	2	*FOUNDATION SOIL TUBE, 6" x 8" x 72"
E750	1	BEARING PLATE
S760	1	CABLE ANCHOR BOX
E770	1	BCT CABLE ANCHOR ASSEMBLY
E780	1	GROUND STRUT
PB620	2	STEEL BREAKAWAY END POST
PB621	5	STEEL BREAKAWAY LINE POST
	5	RECYCLED PLASTIC BLOCKOUT OR OFFSET BLOCK
	1	IMPACT HEAD REFLECTOR MARKER - IHRM(R) OR (L)
HARDWARE		
B580122	25	5/8" Dia. x 1 1/4" SPLICE BOLT, POST #2
B580754	2	5/8" Dia. x 7 1/2" HEX BOLT
B341004	2	3/4" Dia. x 10" HEX BOLT
B581002	5	5/8" Dia. x 10" H.G.R. BOLT (POST 3 THRU 7)
N050	32	5/8" Dia. H.G.R. NUT (SPLICE 24, SOIL TUBES 2, POST 2 THRU 7, 6)
N030	2	3/4" Dia. HEX NUT
W050	6	H.G.R. WASHER
W030	4	3/4" ID WASHER
N100	2	1" ANCHOR CABLE HEX NUT
W100	2	1" ANCHOR CABLE WASHER
B140404	2	1/4" x 4" HEX BOLT
N014	2	1/4" HEX NUT
W014	4	1/4" WASHER
SB58A	8	CABLE ANCHOR BOX SHOULDER BOLT
N055A	8	1/2" A325 STRUCTURAL NUT
W050A	16	1 1/16" OD x 3/16" ID A325 STR. WASHER

SURVEY PLOTTED BY	DATE
DRAWN BY	
DESIGNED BY	
NOTED BY	
CHECKED BY	
ORIGINAL PLAN	
NOTE BOOK	
adj. 1/1/16	
N. 4/1/16	


STATE OF HAWAII  
 DEPARTMENT OF TRANSPORTATION  
 HIGHWAYS DIVISION  
**FLEAT-350**  
**FLARED ENERGY ABSORBING TERMINAL**  
**FARRINGTON HIGHWAY RESURFACING**  
 Vicinity of Kili Drive to Satellite Tracking Station Road  
 Federal Aid Project No. STP-093-1(026)  
 Not to Scale Date: April, 2016  
 SHEET No. 3 OF 9 SHEETS









FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	STP-093-1(026)	2016	26	110



ANCHOR PLATE DETAILS




STANDARD SWAGED FITTING AND STUD



ANCHOR BLOCK DETAIL

1. Concrete, G.R.P., excavation, anchor rod and miscellaneous appurtenances necessary to anchor the guardrail ends shall be incidental to metal guardrail.



ELEVATION

TYPE "G" FLARE END TERMINAL

NOTE:

Type "G" Modified End Terminal is a site specific end terminal with a taper and radial termini. A site specific detailed drawing is required for all Type "G" Modified End Terminal and must receive Engineer's approval.

The taper (flare rate) of the guardrail shall follow the latest edition of AASHTO'S Roadside Design Guide (currently, Table 5.6 - Suggested Flare Rate for Barrier Design, page 5-21, Jan. 1996 edition).

The radius of the radial termini is an Engineer's judgement based on the site evaluation. The Engineer shall consider safety (minimize the spearing & blunt end situation); degree and potential seriousness of the hazard; bicycle and pedestrian accessibility; maintenance equipment accessibility; Right-of-Way availability; the smallest radii the metal w-beam/thrie-beam railing can be constructed (check with supplier/contractor); posted speed limit; angle of vehicle impact; and aesthetics when designing the Type "G" Modified End Terminal.

During construction, the Contractor shall layout the proposed Type "G" Modified End Terminal and receive approval from the Construction Engineer prior to installation.


SURVEY PLOTTED BY	DATE
DRAWN BY	
DESIGNED BY	
QUANTITIES BY	
CHECKED BY	
ORIGINAL PLAN	
NOTE BOOK	
NO.	

13/13/02 Highway Guardrail/End Terminal (Standard Plan TE-59 r1/03/89)


STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION
<b>TYPE "G" FLARE</b>
FARRINGTON HIGHWAY RESURFACING
Vicinity of Kili Drive to
Satellite Tracking Station Road
Federal Aid Project No. STP-093-1(026)
Date: April, 2016

SHEET No. 5 OF 9 SHEETS


FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	STP-093-1(026)	2016	27	110




LONG SPAN OVER CULVERT



LONG SPAN OVER CULVERT




NESTED LONG SPAN STRONG POST  
W-BEAM GUARDRAIL OVER 18'-9" CULVERT  
(MAXIMUM DYNAMIC DEFLECTION OF 3.2 FT.)




(SPLICE IN CENTER OF 12'-6" SPACING)  
NESTED LONG SPAN STRONG POST  
W-BEAM GUARDRAIL OVER 12'-6" CULVERT  
(MAXIMUM DYNAMIC DEFLECTION OF 3.1 FT.)

\*Note: All nested W-Beam splice points shall be staggered.



SECTION A-A



SECTION B-B

NOTE: All Rail Elements Sections are 12'-6" and All Posts are 6' Long

ORIGINAL PLAN	DATE
SURVEY PLOTTED BY	
DRAWN BY	
DESIGNED BY	
NOTED BY	
CHECKED BY	
IN CHARGE	

4/22/04 rdrruby.guardrail/wbeamsdesign

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**NESTED LONG SPAN STRONG POST**  
**W-BEAM GUARDRAIL OVER CULVERT**  
**FARRINGTON HIGHWAY RESURFACING**  
Vicinity of Kili Drive to Satellite Tracking Station Road  
Federal Aid Project No. STP-093-1(026)  
Scale: Not to Scale Date: April, 2016


SHEET No. 6 OF 9 SHEETS




FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	STP-093-1(026)	2016	28	110

General Notes


- All posts are 6'-0" in length within the 50'-0" pay limit for the Modified Type "A-1" Flare without rubrail.
- Whenever swales or a change in grade is encountered within the 50'-0" pay limit for the Modified Type "A-1" Flare, a rubrail shall be installed and all posts shall have a minimum embedment of 4'-0". Post lengths shall be adjusted to provide the minimum embedment.
- All fasteners, posts, blocks and rail elements shall conform to the latest edition and amendments of "A Guide to Standardized Highway Barrier Rail Hardware", a report prepared and approved by the AASHTO-AGCARTBA Joint Cooperative Committee and HDOT's Statewide Guideline for Permanent Highway Safety Hardware.
- Limit of payment for Modified Type "A-1" Flare shall be 50'-0" from End Shoe including Rubrail (when applicable), Anchor Block and GRP work.
- Excavation, Anchor Block, Backfill and GRP work shall be considered incidental to the Modified Type "A-1" Flare.





Design speed mph	a:b
68	15:1
62	13:1
56	12:1
50	11:1
43	10:1
37	9:1
31	7:1



- \* Posts at 3'-1 1/2" o.c.
- \*\* Posts at 1'-6 3/4" o.c.



ANCHOR BLOCK IN CUT SECTION



PLAN - ANCHOR BLOCK IN CUT SECTION

STATE OF HAWAII

DEPARTMENT OF TRANSPORTATION

HIGHWAYS DIVISION

MODIFIED TYPE "A-1" FLARE

FARRINGTON HIGHWAY RESURFACING

Vicinity of Kili Drive to


Satellite Tracking Station Road

Federal Aid Project No. STP-093-1(026)


Scale: Not to Scale

Date: April, 2016


FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	STP-093-1(026)	2016	29	110



### STRONG POST W-BEAM GUARDRAIL



### BACKSLOPE ANCHOR TERMINAL END ANCHORAGE DETAILS MODIFIED TYPE "A-1" FLARE



#### Note:


All fasteners, posts, blocks and rail elements shall conform to the latest edition and amendments of "A Guide to Standardized Highway Barrier Rail Hardware," a report prepared and approved by the AASHTO-AGCARTBA Joint Cooperative Committee and HDOT's Statewide Guideline for Permanent Highway Safety Hardware.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
adl/brt	DESIGNED BY	
4/17/16	QUANTITIES BY	
	CHECKED BY	



STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION
<b>MODIFIED TYPE "A-1" FLARE</b>
FARRINGTON HIGHWAY RESURFACING
Vicinity of Kili Drive to Satellite Tracking Station Road
Federal Aid Project No. STP-093-1(026)
Scale: Not to Scale Date: April, 2016
SHEET No. 8 OF 9 SHEETS



FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	STP-093-1(026)	2016	30	110




**Steel Plate - 1/2"**  
(Hot-dip Zinc Coated Galvanized-  
Welded or Bolted to Post)



3 - 7/8"  $\phi$  holes to be field drilled in rail  
and attached to steel plate with 7/8"  $\phi$  hex  
bolts 1 5/16" long with square washer


1"  $\phi$  holes to be field drilled in  
rail and through post flange.  
Attach to steel plate with 7/8"  $\phi$  hex  
bolts 2" long with square washer

Front View



Elevation


### RUBRAIL ANCHOR DETAILS



3 - 7/8"  $\phi$  holes to be field drilled in rail  
and attached to steel plate with 7/8"  $\phi$  hex  
bolts 1 5/16" long with square washer

1"  $\phi$  holes to be field drilled in  
rail and through post flange.  
Attach to steel plate with 7/8"  $\phi$  hex  
bolts 2" long with square washer


Front View




Elevation

### POST ANCHOR DETAILS

### RUBRAIL DETAIL FOR MODIFIED TYPE "A-1" FLARE (WHEN CALLED FOR IN PLANS)



Plan



Elevation

### STEEL POST GUARDRAIL WITH RUBRAIL

#### Note:

All fasteners, posts, blocks and rail  
elements shall conform to the latest  
edition and amendments of "A Guide to  
Standardized Highway Barrier Rail  
Hardware", a report prepared and  
approved by the AASHTO-AGCARTBA  
Joint Cooperative Committee.

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION  
**MODIFIED TYPE "A-1" FLARE**  
FARRINGTON HIGHWAY RESURFACING  
Vicinity of Kili Drive to  
Satellite Tracking Station Road  
Federal Aid Project No. STP-093-1(026)  
Scale: Not to Scale Date: April, 2016  
SHEET No. 9 OF 9 SHEETS