

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	99C-01-99	2002	4	45

WATER NOTES

- Unless otherwise specified, all materials and construction of water system facilities and appurtenances shall be in accordance with the STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, dated 1994, as amended, of the Hawaii Highways Division, Department of Transportation, and the City and County of Honolulu Board of Water Supply's "WATER SYSTEM STANDARDS" VOLUME 1, DATED 1985, THE "APPROVED MATERIAL LIST AND STANDARD DETAILS FOR WATER SYSTEM CONSTRUCTION", VOLUME 2, DATED 1985, AND THE "WATER SYSTEM EXTERNAL CORROSION CONTROL STANDARDS", VOLUME 3, DATED 1991, and all subsequent amendments and additions. (1)
- All plans approved by the Board of Water Supply are based solely on the adequacy of the water supply. All other features of the water system, such as lines, grades, fittings, drainage, etc., and other features of improvements shall not be the responsibility of the Board of Water Supply.
- The Contractor shall notify BWS Planning and Engineering Division, Construction Section, one week prior to commencing work on the water system.
- The existence and location of underground utilities and structures as shown on the plans are from the latest available data but is not guaranteed as to the accuracy of encountering of other obstacles during the course of the work. The Contractor shall be responsible and pay for all damages to existing utilities. The Contractor shall not assume that where no utilities are shown, that none exist.
- Re-approval shall be required if this project is not under construction with a period of two years.
- The Contractor shall be responsible for the protection of all water lines during construction. The Contractor shall be especially careful when excavating behind water lines, tees, and bends wherever there is a possibility of water line movement due to the removal of the supporting earth beyond the existing reaction blocks. The Contractor shall take whatever measure necessary to protect the water lines, such as constructing special reaction blocks (with BWS approval) and/or modifying his construction method.
- Prior to any excavating, the Contractor shall verify in the field the location of existing water mains, service lateral locations, and appurtenances.
- The contractor shall adjust all meter boxes within the resurfaced area. Prior to resurfacing, BWS will initially locate all water meter boxes that will require adjustments. The Contractor shall then be responsible for "referencing" these meter boxes to facilitate the adjustments. The cost for adjustments shall be made at their respective unit prices in the Bid based on the actual number adjusted. Cost for referencing shall be incidental and shall not be paid directly. Any additional request to BWS to again locate the meter boxes shall be done at the expense of the Contractor. (BWS will charge and bill the Contractor for all cost of said additional work.)

HECO NOTES

- The location of HECO's overhead and underground facilities shown on the plans are from existing records with varying degrees of accuracy and are not guaranteed as shown. The Contractor shall exercise extreme caution whenever construction crosses or is in close proximity of underground lines and shall maintain adequate clearance when operating equipment within or under any overhead lines.
- The Contractor shall comply with the State of Hawaii's Occupational Safety and Health Law (DOSH).
- The Contractor shall obtain an excavation permit from HECO's Technical Division (543-5654) located at 820 Ward Avenue, 4th floor, two weeks prior to starting construction. Please refer to our request number at that time.
- For verification of underground lines or for assistance in supporting and protecting these lines, the Contractor shall call HECO's Underground Division at 543-7871 a minimum of 72 hours in advance.
- When trench excavation is adjacent to or beneath our existing structures or facilities, the Contractor is responsible for:
 - Sheeting and bracing the excavation to prevent slides, cave-ins, and settlements.
 - Protecting existing structures or facilities with beams, struts, or under-pinnings.
- For pole bracing instructions, the Contractor shall call the HECO District Superintendent at (Koolau 261-6084, Waiau 543-4226, Ward 543-7745) a minimum of 72 hours in advance.
- Any work required to relocate HECO facilities shall be done by HECO and the Contractor shall be responsible for all coordination, and for possible costs if applicable.
- Should it become necessary to temporarily relocate any of HECO facilities to enable the Contractor to perform his work in a safe and expeditious manner in fulfilling his contract obligations, these temporary relocations will be done by HECO, or by the Contractor under HECO's supervision, with all costs borne by the Contractor.
- Any unforeseen conflict that would result in the redesign or relocation (either temporary or permanent) of HECO's electrical facilities may be cause for lengthy delays. To avoid such delays, the contractor must notify HECO of the conflict a minimum of 30 days prior to the start of construction.
- Any damage to HECO's facilities will be reported immediately to HECO's Trouble Dispatcher at 548-7961.
- All HECO overhead and underground facilities shall be protected at all times by the Contractor during construction. Costs for damages to HECO facilities shall be borne by the Contractor. This repair work shall be done by HECO, or by the Contractor under HECO's supervision.
- The Contractor shall indemnify, defend and hold harmless HECO from and against all losses, damages, claims and actions, including but not limited to reasonable attorney's fees and costs based upon or arising out of damage to property or injuries to persons, or other tortious acts caused or contributed to by Contractor or anyone acting under its direction or control or on its behalf; provided Contractor's indemnity shall not be applicable to any liability based upon the sole negligence of HECO.

OCEANIC CABLEVISION NOTES

- Oceanic fiber optic lines is also in the telephone manhole underground system on the west side of Kamehameha Highway.
- Contact the Oceanic Inspector 72 hours prior to starting work on CATV infrastructure. Call Moki Place at 625-8378.
- All entrances into the pull box shall be grouted around the conduits and inside surface shall be smooth and flush with the existing wall.

ORIGINAL PLANS	DATE	10/25/99
DESIGNED BY	DATE	
NOTED BY	DATE	
QUANTITIES BY	DATE	
CHECKED BY	DATE	

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION
UTILITY NOTES
KAMEHAMEHA HIGHWAY
SIDEWALK IMPROVEMENTS
Meheula Parkway to Kuahelani Avenue
Project No. 99C-01-99
Date: Aug., 2001

SHEET No. 1 OF 1 SHEETS