



DATE	=	66			2	
SURVEY PLOTTED BY	DRAWN BY	TRACED BY	DESIGNED BY	QUANTITIES BY	CHECKED BY	
ORIGINAL	PLAN		NOTE BOOK		No.	

		FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
		HAWAII	HAW	NH-099-1(031)	2020	95	125
ROAD WORK 1500 FT SUPPLEMENTAL PLATE 24"x18" 1000' 1000'	ROAD WORK AHEAD 	'8"x48" ■	• ● ● ↓	SIGN CONE OR DELINE DIRECTION OF T FLASHING ARROW	RAFFIC		
		1.		contractor shall of through tra	•		<i>.</i>

TRAFFIC CONTROL * PLAN SIMILAR FOR OPPOSITE LANE ALTERATION







FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW	NH-099-1(031)	2020	96	125


GENERAL NOTES FOR TRAFFIC CONTROL PLAN


- 1. The Contractor shall make minor adjustments at intersections, side roads, drainage structures, etc, to fit field conditions.
- 2. Cones or delineators shall be extended to a point where they are visible to approaching traffic.
- 3. Traffic control devices shall be installed such that the sign or device farthest from the work area shall be placed first. The others shall then be placed progressively toward the work area.
- 4. Regulatory and warning signs within the construction zone that are in conflict with the traffic control plans shall be removed or covered. All signs shall be replaced upon completion of the work.
- 5. All regulatory, guide, and construction signs and barricades shall have a high-intensity reflective background.
- 6. Flaggers and/or police officers shall be in sight of each other or in direct communication at all times
- 7. The Contractor shall install a flashing arrow signal as shown on the traffic control plans, unless otherwise authorized by the Engineer.
- 8. Sign spacing (L), taper lengths (T) and spacings of cones or delineators shall be as noted on the traffic control plans, or special provisions.
- 9. All traffic lanes shall be a minimum of 10 feet wide.
- 10. All construction warning signs shall be promptly removed or covered whenever the message is not applicable or not in use.
- 11. The back of all signs used for traffic control shall be marked with the sign owner's name.
- 12. At the end of each day's work or as soon as the work is completed. The permittee shall remove all traffic control devices no longer needed to permit free and safe passage of public traffic. Removal shall be in the reverse order of installation.
- 13. Replace permanent pavement markings and traffic signs upon completion of each phase of work.
- 14. All work zone traffic control devices shall comply with the "Statewide Guidance For Work Zone Traffic Control Devices" Dated September 13, 2000 and the Manual on Uniform Traffic Control Devices (MUTCD) as referenced in the 23 Code of Federal Regulations (CFR), Part 655, Subpart F. The MUTCD shall be recognized as the national standard for traffic control devices on all public roads open to public travel in accordance with 23 U.S.C. 109(d) and 402(a).
- 15. Cones or delineators shall be installed at 25' o.c. max. along tapers.
- 16. Cones or delineators shall be installed at 50' o.c. max. along tangents.
- 17. Posted speed limit along Kamehameha Highway (State) is 55 M.P.H. Speed limit shall be reduced to advisory 25 M.P.H. through all construction work zone diversions.
- 18. Contractor provided two (2) message boards are to be in place 1 week prior to start of work of lane shifts.
- 19. Mobile/roving/moving work zone lane closures for striping work shall not be used.


RO M MCDON ROLLICENSED	STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION
★ PROFESSIONAL ENGINEER ★ No. 9793-C	TYPICAL TRAFFIC CONTROL
AWAILUSP.	PLAN
This work was prepared by me or under my supervision	Kamehameha Hwy, Kamananui Rd and Wilikina Dr
	Rehabilitation Weed Circle to Interstate Route H-2
Chea N Man 4/30/2022	<u>Project No. NH-099-1(031)</u>
MITSUNAGA & ASSOCIATES, INC. EXP. DATE	Scale: As Noted Date: August 2020
NOTE: Contractor to check and verify dimensions at job before proceeding with work.	SHEET No. C94 OF 125 SHEETS
	96



































		FED. RC	AD STATE	FED.	AID	FISCAL	SHEET	TOTAL
		DIST. N	O. HAW	PROJ. NH-099-		YEAR 2020	NO. 102	SHEETS 125
		<u> </u>		L	ege.	n d		<u>.</u>
							Mark	Iraa
							Work A	H Ed
				$\overline{}$	•			c Cone
					▼		Sign	
	<u></u>	2		•-				
·) 				1				
<u>24"x12"</u>			•					
OHAI STREET								
M4-9 30''x24''								
ROAD WORK	CW20-1D 48''x48''							
AHEAD 25 Su	pplemental Plate							
PH SU	24"x18"							
	N MCA			CTATE	OF HA	WAII]
	LICENSED		DEPART	MENT C		NSPOR	TATION	
and	★ PROFESSIONAL ENGINEER No. 9793-C		TRAF	TIC C	<u>:ONT</u>	ROL	PLA	N
*	This work was prepared	_						_
	This work was prepared by me or under my supervis		ehameha H bilitation	Weed Cir	<u>rcle to</u>	Intersta	<u>ate Rou</u>	
		0/2022		<u>ect No.</u>	NH-C		<u>31)</u>	
	NOTE: Contractor to check and verify dimensions at job before proceeding with wo			T No. C '				







			FED. ROAD DIST. NO.	STATE	FED. AID	FISCAL	SHEET	TOTAL
			DIST. NO. HAWAII	HAW	PROJ. NO. NH-099-1(031)	YEAR 2020	NO. 103	SHEETS
					<u>Lege</u>	<u>n d</u>		
							Work A	Area
					•		Traffi Sign	c Cone
	— Cones at 10' о.с.							
				·				
STATE)			 20					
				<u>0</u>	2			
ROAD	W20-1D 48" x 48"							
	48" x 48" oplemental Plate	Ç						
25 MPH SUL	48" x 48"	þ						
25 MPH SUL	48" x 48" oplemental Plate	9						
25 MPH SUL	48" x 48" oplemental Plate	þ						
25 MPH SUL	48" x 48" oplemental Plate 24"x18"				STATE OF H	λWAII		
25 MPH SUL	48" x 48" oplemental Plate 24"x18" XIB" LICENSE PROFESSIO	ED ON TO IONAL	D	EPART	STATE OF HA MENT OF TRA HIGHWAYS DIV	ANSPOR	TATION	
25 MPH SUL	48" x 48" oplemental Plate 24"x18" MC LICENSE PROFESSIC ENGINEE No. 9793-	ED ONAL ER B-C			MENT OF TRA	ANSPOR /ISION		
25 MPH SUL	48" x 48" oplemental Plate 24"x18" M MC LICENSE PROFESSIO ENGINEE	ED IONAL ER J.S.C. A.	 □n <u>Kameha</u>	RAFF ameha f	MENT OF TRA HIGHWAYS DIV FIC CONT	ANSPOR VISION TROL	<u>PLA</u> 1 Wiliki	▶ na_Dr_
25 SUL	48" x 48" oplemental Plate 24"x18" MC LICENSE PROFESSIO ENGINEE No. 9793- Y AWAIL,	ED ONAL ER U.S.F. S. prepared by supervisio	on <u>Kameha</u> <u>Rehabili</u>	RAFF ameha F itation Proj	MENT OF TRA HIGHWAYS DIV FIC CONT Weed Circle to ect No. NH-0	ANSPOR VISION TROL i Rd and Intersta 099-1(03	PLA d Wilikin ate Rour 31)	▶ <u>na Dr</u> te H-2





DATE		-				
DA						
ED BY						
SURVEY PLOTTED BY	DRAWN BY	TRACED BY	DESIGNED BY _	QUANTITIES BY	CHECKED BY	
SUR	DRA			QUA		
ORIGINAL	PLAN		NUTE BOOK		.oN	




DATE	*			
SURVEY PLOTTED BY	DRAWN BY	TRACED BY DESIGNED BY	QUANTITIES BY	CHECKED BY
ORIGINAL	PLAN	NOTE BOOK		No































E						
DATE		:	:	:	2	
SURVEY PLOTTED BY	DRAWN BY	TRACED BY	DESIGNED BY	QUANTITIES BY	CHECKED BY	
ORIGINAL	PLAN		NOTE BOOK		No.	







	FED. ROA DIST. NO.	D STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
	HAWAII	HAW	NH-099-1(031)	2020	112	125
			<u>Lege</u>	<u>n d</u>		
	,				Work ,	Area
			•		Traffi	ic Cone
Conce at 10^{\prime} as			-	-	Sign	
Cones at 10' o.c.						
ROAD WORK AHEAD	7					
V20-1D						
3" <i>x48</i> "						
R MCDON C LICENSED		DEPART	STATE OF HA		TATION	
LICENSED ROFESSIONAL ENGINEER	*		HIGHWAYS DIV	ISION		
No. 9793-C		<u>RAFI</u>	FIC CONT	ROL	PLA	<u>v </u>
This work was prepa by me or under my supe			<u>Hwy, Kamananul</u> Wood Cirolo to			
Chean Mugon	4/30/2022	<u>Proj</u>	<u>Weed Circle to</u> iect No. NH-C	<u> 199-1(03</u>	<u>31)</u>	
MITSUNAGA & ASSOCIATES, INC. NOTE: Contractor to check and verify dimensions at job before proceeding wit			ed D T No. C110 OI	ate: Aug - 125		
			-		12	









DATE			
OTTED BY	TRACED BY	QUANTITIES BY	
ORIGINAL PLAN	NOTE BOOK	No.	











ORIGINAL	DATE DATED BY DATE	
PLAN	DRAWN BY "	
ACOL BEOM	TRACED BY	
NUUE BUUN	DESIGNED BY "	
	QUANTITIES BY ,	
No	CHECKED BY "	

	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
	HAWAII	HAW	NH-099-1(031)	2020	116	125
			<u>Leger</u>	<u>d</u>		
					Work A	rea
					Troffin	Cana
			•		Traffic	CONE
	\		▼		Sign	
	+					
	7777					
Cones at 10' o.c.						
			END ROAD WORK			
			CC20-2A 6" x 24"			
		1	~ // []			
	·					
N MCDON C LICENSED		EPART	STATE OF HA	NSPOR	TATION	
(★ (PROFESSIONAL ENGINEER ★ (CONSED	r l	~ -	HIGHWAYS DIV			
No. 9793-C		KAF	FIC CONT	I ROL	PLA	<u> </u>
This work was prepare by me or under my superv	ed Vision Kameha	meha H	lwy, Kamananui	Rd and	d Wiliki	na Dr
		tation	Weed Circle to	Intersta	ate Rou	
Chear M Myom 4K	^{30/2022} ^{KP. DATE} Scale: A	-	ect No. NH-C ed D	99-1(0) ate: Au		20
MITSUNAGA & ASSOCIATES, INC. EX			- 0		,, <u>_</u> 0	1
NUTSUNAGA & ASSOCIATES, INC. EX NOTE: Contractor to check and verify dimensions at job before proceeding with w	work.	SHEE	No. C114 OF	125	SHEET	












	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
	HAWAII	HAW	NH-099-1(031)	2020	116	125
		Lege	<u>end</u>			
			Direct	ion of D	etour	
		╺	Sign			
OHAI STREET 24" x 12"						
OUTLET 30" x 30"						
24" x12" [OHALSTREET] 24" x12"						
OHAI STREET DETOUR OHAI STREET						
M4-9						
30"x24" 125'						
<pre></pre>						
þ						
				\ A / A !!		
LICENSED	D	EPART	STATE OF HA MENT OF TRA HIGHWAYS DIV	NSPOR	TATION	
(★ PROFESSIONAL ENGINEER No. 9793-C		ΟΗΔ	I ST DETC		ΔΝ	
AWAILUS P.			JI DLIV			
This work was prepared by me or under my supervi			<u>lwy, Kamananui</u> Weed Circle to			
)/2022	<u>Proj</u>	ect No. NH-C	<u>199-1(0)</u>	<u>31)</u>	
MITSUNAGA & ASSOCIATES, INC. EXP NOTE: Contractor to check and verify dimensions at job before proceeding with wo	Scale:		ed D No. C116 OF	ate: Au = 125		
		SHEE			18	ل








	FED. ROA DIST. NC	AD STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
	HAWAII	HAW	NH-099-1(031)	2020	119	125
		<u>Lege</u>	<u>end</u>			
		-		ion of D	etour	
		┲	Sign			
			Ĵ			
		24''	x12''		2	4″x12″
		DET	OUR			\wedge
			4-9			
			x24'' 125'			N20-2
						6″x36″
	+ + +	₩	F +			
			+00			
		 	Q_		<u></u> →	
				1	£	
					· · · ·	
					\backslash	
N MCDC	ONF	DEPARTI	STATE OF HA	NSPOR	TATION	
			HIGHWAYS DIV			
↓ LICENSED PROFESSIONA ENGINEER		· · · · ·	DO CT DE			, 11
► PROFESSIONA ENGINEER No. 9793-C		AVOCA	<u>DO ST DE</u>		PLAN	
★ PROFESSIONA ENGINEER No. 9793-C * AWAII, U.S	repared supervision	<u>hameha F</u> ilitation \	lwy, Kamananu Need Circle to	i Rd and Intersta	d Wilikin ate Rou	n <u>a Dr</u>
★ PROFESSIONA ENGINEER No. 9793-C * AWAII, U.S	repared supervision Kame Rehab	<u>hameha F</u> ilitation \	lwy, Kamananu Need Circle to ect No. NH-C	i Rd and Intersta	d Wilikin ate Rou 31)	<u>na Dr</u> te H-2





DATE	* 		2	=		
SURVEY PLOTTED BY	DRAWN BY	TRACED BY	DESIGNED BY	QUANTITIES BY	CHECKED BY	
ORIGINAL	PLAN	NOOD amon	NULL BUUN		No.	















DATE	*		=	2	2	
SURVEY PLOTTED BY	DRAWN BY	TRACED BY	DESIGNED BY	QUANTITIES BY	CHECKED BY	
ORIGINAL	PLAN	NOOT BEON	NULE BUUN		No.	









FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW	NH-099-1(031)	2020	125	125


<u>Legend</u>

✦


●

Direction of Detour

Sign



ENF	HANCED VEHICLE CLASSIFICATION (EVC) SYSTEM NOTES
1.	The location of new loop sensors and piezo sensors shall staked out in the field by the Contractor and approved by Engineer prior to installation.
2.	The Contractor shall inform the Engineer at least three of prior to saw cutting pavement and installing loop sensors piezo sensors.
-	Pull loop sensor cables and piezo sensor lead cables into where indicated. Cables shall be tested for acceptance b and after installation into conduit.
4.	Piezo lead cables shall be continuous with no splices.
•	The Contractor shall restore all affected areas to their of condition. This item of work shall not be paid for separa shall be considered incidental to work of other paid item
6.	The Contractor shall verify the location of the existing u and underground structures whether or not shown on the
7.	The Contractor shall assume that underground utilities n shown on the plans may exist. The Contractor shall be responsible
	for contacting the different utility companies for informationing.
8.	The Contractor shall be held liable for any damages incu the existing utilities and underground structures as a re- his operations. All damaged portions shall be replaced in accordance with the standards and specifications of the utility company at no cost to the State.
7.	Changes to the contract plans and specifications will not permitted, unless approved by the Engineer in writing.
10.	All cables are to be terminated within the EVC cabinet al have a minimum 12" additional slack.
11.	Highway crossing conduit shall be provided with 36" cover
12.	Saw cuts shall be made by wet cutting only.
3.	Clean away collected dust, dirt, and refuse after saw cut done. The saw cuts shall be cleared by water applied by washer. Residual water within the saw cuts shall be vacuuse of a wet/dry vacuum. The saw cuts shall then be a air compressor.
	After saw cuts are dried, any remaining debris stuck wind cut shall be removed. The saw cuts must be completely of dry before inserting the sensors and filling the voids with Sealant (for loop sensors) or PU200 Piezo Installation Re equivalent (for piezo sensors).



all be by the

e days rs and

nto conduit before

original rately, but ms.

utilities he plans.

not

mation and

curred to result of in ne affected

ot be

and shall

over.

eutting is by pressure acuumed by dried by

vithin the clean and with Loop Resin or

ENHANCED VEHICLE CLASSIFICATION (EVC) SYSTEM NOTES CONTINUED


15. The collected slurry shall be disposed of appropriately (i.e., either placed in a Filter Fabric Lined Filtration Box or in a Filter Fabric Lined Dug Up Retention/Percolation Basin, and after Filtration/Percolation, the Filter Fabric and the retained sediments, disposed of appropriately).


LOOP SENSOR LAYOUT NOTES


- 1. Loop sensors shall consist of four turns of 1C #14 cable (meeting IMSA Spec 51-3 or equivalent) embedded in a 3/8" wide by 4" deep saw cut, except as noted. Loop sensors shall be provided a minimum 2" cover.
- 2. After laying the loop sensor cable in four (4) turns within the 4" deep cut, press 1"-long pieces of backer rod in each foot of the loop and the loop lead saw cut, to anchor the wire in the bottom of the cut before applying the Loop Sealant. Backer rod shall be embedded at least 2" below the top of pavement. The backer rod shall be placed into the saw cut with a blunt object, such as a wooden paint stir stick. No sharp objects (such as a screw driver) shall be used to place the backer rod into the saw cuts.
- 3. Loop sensor and lead cable shall be one continuous wire. Lead wires from the same loop shall be twisted in pairs, five twists per foot, from the edge of paved shoulder to the pull box. Do not twist one loop pair with another loop pair.
- 4. Continuity of loop sensors and lead-in wires shall be tested and warrantied for one year from the date of acceptance by the Engineer.
- 5. Loop sensor lead cables shall be spliced only at the closest pull box to the loop. Splice points of cables shall be suspended near the top of the pull box with a j-hook.
- 6. Splices shall be made by use of a splice kit.
- 7. Stagger loop sensors on roadways with lanes that are less than 12 feet in width, as shown on contract plans or by direction of the Engineer.
- 8. The Contractor shall label the loop and piezo sensor leads clearly to identify traffic direction, lane number, and sequence of loop and piezo sensors in each lane per direction.
- 9. The left-most lane in the direction of traffic flow is designated as Lane 1, and the next lane to its right as Lane 2, and so on as indicated on plans.

	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
	HAWAII	HAW	NH-099-1(031)	2020	ADD.125 S-1	125

	<i>9/09/20</i> Date	A New Shee REVISION	et added	
* C N MCDON PROFESSIONAL ENGINEER No. 9793-C		state of i RTMENT OF T HIGHWAYS D FIC COUNTIN	RANSPORTATIO	
AWAII, U.S.A.	STATI	ON 080000, 0	180008 REPA	IRS
This work was prepared by me or under my supervision		<u>a Hwy, Kamanan</u> n Weed Circle f		
MITSUNAGA & ASSOCIATES, INC. EXP. DATE	<u>Pr</u>	<u>oject No. NH</u>		
NOTE: Contractor to check and verify dimensions at job before proceeding with work.	SHE	ET No	OF 125 SHE	ETS
		AD	D.125 S	-1










FI D	ED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
	HAWAII	HAW	NH-099-1(031)	2020	ADD.125 S-2	125


<u>BOUNDARY LABEL LEGEND</u> ep = Edge of pavement etw = Edge of travelway
LOOP LABEL LEGEND
N = North S = South A = Approaching T = Trailing N 2 T Indicates approaching or trailing loop Indicates lane number Indicates direction
<u>NOTES:</u>
1. All dimensions and callouts are typical unless otherwis on plan.
2. Contractor shall not disturb existing connections to ele and communication service.
3. Contractor shall confirm location of buried utilities an clearance from utility companies prior to installation o sensors.








FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW	NH-099-1(031)	2020	ADD.125 S-3	125











TEMPERATURE SENSOR SAW CUT

	Ra	adius Corners, T
No. CHECKED BY		



EXCAVATION WARNING SIGN DETAIL Not to Scale

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW	NH-099-1(031)	2020	ADD.125 S-5	125

NOTES:

- 1. For sign post detail, see State Standard Plans TE-03A and TE-03B.
- 2. Two (2) warning signs shall be placed on each sign post "Back-to-Back".
- 3. Text on sign shall be centered both ways and shall be black text on yellow background.
- 4. Bottom edge of sign shall be 8' above grade.

	<i>9/09/20</i> date	A New She	eet added
* PROFESSIONAL ENGINEER		HIGHWAYS	TRANSPORTATION
No. 9793-C 44 A HI, U.S.P.	REPLACE	MENT WARN	IING SIGN DETAILS
This work was prepared by me or under my supervision		•••	anui Rd and Wilikina Dr to Interstate Route H-2
MITSUNAGA & ASSOCIATES, INC. EXP. DATE	<u>Pr</u> Scale: As N	o <mark>ject No. Nl</mark> oted	<u>H-099-1(031)</u> Date: August 2020
NOTE: Contractor to check and verify dimensions at job before proceeding with work.		ET No	OF 125 SHEETS
			ADD 125 S-5