

PAVEMENT MARKING NOTES:

1. Location of pavement markers is shown schematically. For exact location of markers in relation to stripe, see Standard Plans T-7, T-8, T-9 & T-10.
2. All pavement striping, legends and symbols shall be retroreflective thermoplastic compound pavement markings.
3. Removal of existing pavement markings shall be considered incidental to the various contract items.
4. Layout of pavement markings and striping shall be done by the Contractor and approved by the Engineer prior to any installation work.
5. Existing pavement markings not incorporated in the final traffic pattern shall be removed as directed by the Engineer. The costs shall be incidental to the various pavement marking items.
6. All pavement striping shall be as noted on the legend or plans.
7. All preformed pavement marking tapes over existing pavement shall be applied with an approved primer as recommended by the tape's manufacturer and as approved by the Engineer. The primer shall be allowed to dry to the tacky stage prior to tape application.
8. Dimension reference point for pavement markings shall be bottom of inside parapet (i.e., location where parapet intersects top of deck).

LEGEND

- ①

4" White Guide Lines (Tape, Type I or Thermoplastic Extrusion)
- ②

6" White Stripe with Type C Raised Pavement Markers @ 40'-0" o.c. (Tape, Type I or Thermoplastic Extrusion)
- ③

6" Yellow Stripe with Type H Raised Pavement Markers @ 40'-0" o.c. (Tape, Type I or Thermoplastic Extrusion)
- ④

8" White Stripe with Type C Raised Pavement Markers @ 20'-0" o.c. (Tape, Type I or Thermoplastic Extrusion)
- ⑤

4" White Profiled Thermoplastic Stripe (10'-0" Long)
See Detail Sht. P-15
Type C Raised Pavement Markers @ 40'-0" o.c.
- ⑥

12" White Transverse Marking (Tape, Type III or Thermoplastic Extrusion)
- ⑦

Lane Drop Marking
- ⑧

6" Yellow Stripe with Type H Raised Pavement Markers @ 20'-0" o.c. and 4" Yellow Profiled Thermoplastic Stripe (10'-0" Long) @ 40'-0" o.c. (Tape, Type I or Thermoplastic Extrusion)
- ⑨

12" Yellow Transverse Shoulder Marking (Tape, Type III or Thermoplastic Extrusion)
- ⑩

12" White Transverse Shoulder Marking (Tape, Type III or Thermoplastic Extrusion)
- ⑪

4" Solid White Stripe with
2' Long 4" White Dash Stripe @ 6' o.c.
with White Flexible Delineators @ 10' o.c. and
2' Offset from Stripe
- HOV Pavement Marking (Tape, Type III or Thermoplastic Extrusion)
- Pavement Word (Thermoplastic Extrusion)
- Pavement Arrow (Tape, Type III or Thermoplastic Extrusion)
- Mile Marker (Tape, Type III or Thermoplastic Extrusion)
- Rumble Strip
See Detail on Sht. P-15A

FED. ROAD DIST. NO.	STATE	FEDERAL AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	NH-HI-1(276)	2020	ADD. 21	214

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	
	DESIGNED BY	
	QUANTITIES BY	
	CHECKED BY	
No.		

	10/28/20	Added Legend Item #10 and #11 and Rumble Strip.
Date	Revision	

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION.
SIGNATURE: *R. M. Uragami* 10/30/22
EXPIRATION DATE OF THE LICENSE

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

PAVEMENT MARKINGS
NOTES & LEGEND

INTERSTATE ROUTE H-1 AIRPORT VIADUCT IMPROVEMENTS
VICINITY OF VALKENBURGH ST. TO MIDDLE ST., PH. 2
FEDERAL-AID PROJECT NO. NH-HI-1(276)

Scale: None Date: Aug. 2020