## LEGEND

STOP

SURVEY
DRAWN
TRACED
DESIGNED
QUANTIT

4 each Type A Raised Pavement Markers
Type CL Raised Pavement Markers @ 40'-0" o.c.

4 each Type J Raised Pavement Markers Type DL Raised Pavement Markers @ 40'-0" o.c.

8" White Stripe with Type CL Raised Pavement Markers @ 20'-0'o.c. (Tape, Type I or Thermoplastic Extrusion)

4" Double Solid Yellow with Type DL Raised Pavement Markers @ 20'-0" o.c. (Tape, Type I or Thermoplastic Extrusion)

4"Double Solid Yellow Stripes with Type HL Raised Pavement Markers @ 20"-0" o.c. (Tape,Type II or Thermoplastic Extrusion)

4" Yellow Edge Stripe with Type HL Raised Pavement Markers @ 40'-0" o.c. (Tape, Type II or Thermoplastic Extrusion)

4"Double Solid White Stripes with Type CL Raised Pavement Markers @ 20"-0" o.c. (Tape,Type I)

Lane Change Restriction Marking
- 4 each Type A Raised Pavement Markers
- Type CL Raised Pavement Markers @ 20'-0" o.c.
- 4" White Stripe (Tape, Type I)

4" or 8" White Edge Stripe with Type CL Raised Pavement Markers @ 40'-0" o.c. (Tape,Type II)

4" White Guide Lines (Thermoplastic Extrusion)

Transverse Median Marking (Tape,Type II or Thermoplastic Extrusion)

Transverse Shoulder Marking (Tape,Type II or Thermoplastic Extrusion)

Channelizing Island or Deceleration Lane Gore (Tape, Type II or Thermoplastic Extrusion)

Crosswalk and Stop Line. All Stop Lines shall be 10'-0" from Crosswalk unless otherwise noted. The circled number indicates the number of lanes for payment. (Thermoplastic Extrusion)

Pavement Arrow (Tape, Type | or Thermoplastic Extrusion)

Pavement Word (Tape, Type | or Thermoplastic Extrusion)


— 4 Each Type J Raised Pavement Markers — Type DL Raised Pavement Markers @ 40'-0" o.c. — Type HL Raised Pavement Markers (Reflective Surface facing no-passing direction) — 4" Single Solid Yellow Stripe (Tape,Type I or Thermoplastic Extrusion)


Extension of Edge Line, 4" Wide x 2'-0" Long
White Stripe @ 10'-0" o.c.w/Type CL Markers
@ 40'-0" o.c.(Thermoplastic Extrusion)

## NOTES

- I. Layout of pavement markings and striping shall be done by the Contractor and approved by the Engineer prior to any installation work.
- 2. Existing pavement markings not incorporated in the final traffic pattern shall be removed as directed by the Engineer. Costs shall be incidental to the various pavement marking items.
- 3. Raised pavement markers shall not be installed within crosswalks.
- 4. Details of Type C,Type D and Type H Markers on Standard Plan Nos.TE-30, TE-31 and TE-32 shall be deleted and replaced with details of Type CL, Type DL and Type HL Markers as shown on this sheet. All references to Type C,Type D and Type H Markers in the plans shall mean Type CL,Type DL and Type HL Markers.
- 5. Final locations of all signs shall be approved by the Engineer prior to any installation work.
- 6. Existing signs not shown on these plans shall remain as posted unless otherwise directed by the Engineer. Removal and disposal of existing signs and/or posts as designated on these plans shall be incidental to the various signing items.
- 7. Final locations of all Stop Lines shall be approved by the Engineer prior to installation.
- 8. All pavement striping shall be as noted on the Legend or plans.
- 9. All preformed pavement marking tapes over existing pavement shall be applied with an approved primer as recommended by the tape manufacturer and as approved by the Engineer. The primer shall be allowed to dry to the tacky stage prior to tape application.
- 10. Quantities of new pavement markings and striping are estimates for bid purposes only.

  Actual pavement marker type or stripe and respective quantities shall be verified in the field by the contractor prior to spall repair work and approved by the Engineer.





FED. AID PROJ. NO.

HAW. HIE-01-92M 1992

FISCAL SHEET TOTAL YEAR NO. SHEETS

TYPE CL Red-Clear Reflective Marker

TYPE DL

Two-Way Yellow Reflective Marker

FED. ROAD STATE

or

TYPE HL One-Way Yellow Reflective Marker

RAISED PAVEMENT MARKER DETAILS

Not to Scale

	CONSTRUCTION	SIGN SUMMARY	
SIGN NO.	LOCATION	MESSAGE	W/POSTS
CG20-2	STA. (-)1+20 LT.	END CONSTRUCTION	1
CW20-1d	STA. (-)1+20 RT.	ROAD CONSTRUCTION AHEAD	1
CG20-2	STA. 67+71 RT.	END CONSTRUCTION	1
CW20-1d	STA. 67+71 LT.	ROAD CONSTRUCTION AHEAD	1
. •		TOTAL	4

PAVEMENT MARKING SUMMARY	/
DESCRIPTION	QUANT ITY
PAVEMENT MARKER TYPE A TYPE CL	150 EA. 20 EA.
TAPE-TYPE I DOUBLE 4-INCH PAVEMENT STRIPE (WHITE)	10 L.F.
TAPE-TYPE II 4" EDGE STRIPE (WHITE)	10 L.F.

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

PAVEMENT MARKING LEGEND, DETAILS & NOTES

INTERSTATE ROUTE H-1
Pearl City Viaduct Repairs
Project No. H1E-01-92M

Scale: As Noted Date: Nov. 1991

SHEET No. T1 OF 1 SHEETS

6