# STANDARD PLANS SUMMARY

FED. ROAD DIST. NO.	STATE		FISCAL YEAR	SHEET	
HAWAII	HAW.	IM-H1-1(219)	1998	2	378

STANDARD PLAN NO.	TITLE	DATE
B-01 •	Notes and Miscellaneous Details	07/01/86
B-02		
B-03 •	Typical Structure Excavation and Backfill Pay Limits	07/01/86
B-04 ·		
B-05		
B-06	Concrete Box Girder	07/01/86
B-07	Concrete Box Girder	07/01/86
B-08	Concrete Box Girder	07/01/86
B-09 ·		
B-10 ·		
B-11 ·		
B-12 ·	Prestressed Concrete Piles	r07/16/90
B-13	Prestressed Concrete Piles	r07/16/90
D-01	Chain Link Fence With Toprail	r03/06/87
D-02 ·	Chain Link Fence Without Toprail	r07/26/90
D-03	Wire Fence With Metal Posts	07/01/86
D-04 •	Typical Details of Curbs and/or Gutters	07/01/86
D-05	Typical Details of Reinforced Concrete Drop Driveway	07/01/86
D-06	Centerline and Reference Survey Monument	07/01/86
D-07 ·	Street Survey Monument	07/01/86
D-08 ·	Landscaping Shrub and Tree Planting	07/01/86
D-09 ·	Field Office	07/01/86
D-10	Field Office	07/01/86
D-11	Project Site Laboratory	07/01/86
D-12	Project Site Laboratory	07/01/86
D-13	Field Office & Project Site Laboratory	07/01/86
H-01 •	Type A. B. C and D Catch Basin	07/01/86
H-02	Type A1, B1, C1 and D1 Catch Basin	07/01/86
H-03	Type A2, B2, C2 and D2 Catch Basin	07/01/86
H-04 🌑	Typical Reinforcing Details for Catch Basins	07/01/86
H-05 •	Type A. B and C Storm Drain Manhole	07/01/86
H-06	Type D and E Storm Drain Manhole	07/01/86
H-07	Type F Storm Drain Manhole	07/01/86
H-08	Catch Basin and Manhole Casting	07/01/86
H-09 <b>•</b>	Type A-9 and A-9P Frames and Grates	07/01/86
H-10	Type A-9B Frames and Grates	07/01/86
H−11 <b>●</b>	Type 61614 and 61214 Grated Drop Inlet	07/01/86
H-12 •	Type 61616 Grated Drop Inlet	07/01/86
H-13 •	61214, 61614 & 61616 Steel Frames and Grates	07/01/86
H-14 ·	61214B Steel Frame and Grates	07/01/86
H-15 ·	61614B Steel Frame and Grates	07/01/86
H-16	Concrete and Cement Rubble Masonry Structures	r10/16/90
H-17 ·	Inlet Structures	r10/16/90
H-18	Flared End Section for Culverts	07/01/86
H-19 ·	Outlet Structures	r02/15/91
^^ -	One and I a Contillation Indial	07/04/06

07/01/86

07/01/86

r10/16/90

r10/16/90

STANDARD PLAN NO	1 1116	DATE
TE-01 •	Miscellaneous Sign Details	07/01/86
TE-02 •	Galvanized Flanged Channel Sign Post Mounting	07/01/86
TE-03	Galvanized Square Tube Sign Post Mounting	07/01/86
TE-04 •	Regulatory Signs	r09/01/8
TE-05 •	Warning Signs	07/01/86
TE-06	Miscellaneous Signs	r11/03/89
TE-07 ·	Reserved	07/01/86
TE-08	Construction Signs	r09/01/87
TE-09 •	Miscellaneous Intersection Signs	r03/06/87
TE-10 ·	Reserved	07/01/86
TE-11 <b>●</b>	Bike Route Sign and Supplementary Plates	07/01/86
TE-12 •	State Route Marker and Auxiliary Markers	07/01/86
TE-13 •	Interstate Route Marker	07/01/86
TE-14 🔷	State Route Marker and Border Detail for Guide Signs	07/01/86
TE-15 •	Route Marker Assemblies	07/01/86
TE-16 <b>(</b>	Miscellaneous Reflector Markers	07/01/86
TE-17 •	Type II Object Markers	07/01/86
TE-18 •	Mileposts	07/01/86
TE-19 ·	Reserved	07/01/86
TE-20 •	Overhead Sign Supports	07/01/86
TE-21 <b>①</b>	Overhead Sign Support, Box Truss Type, Aluminum	07/01/80
TE-22	Foundation Details and Schedules	07/01/86
TE-23 •	Supports for Ground Mounted Guide Sign	r11/03/89
TE-24 •	Breakaway Sign Supports for Ground Mounted Guide Signs	07/01/86
TE-25 •	Laminated Aluminum Sign Panels (Overhead)	07/01/80
TE-26 •	Laminated Aluminum Sign Panels (Ground Mounted)	07/01/86
TE-27	Solid Aluminum Extruded Sign Panel and Accessory Details	07/01/86
TE-28	Guide Signs Luminaire Mountings	07/01/86
TE-29 ·	Reserved	07/01/86
TE-30	Raised Pavement Markers and Striping	r05/09/90
TE-31 •	Miscellaneous Pavement Markings	r05/09/90
TE-32	Miscellaneous Pavement Markings	r05/09/90
TE-33	Miscellaneous Pavement Markings	r11/03/89
TE-34 ·	Reserved	07/01/86
TE-35	Pavement Alphabets, Numbers & Symbols	07/01/86
TE-36 •	Pavement Alphabets, Numbers & Symbols	07/01/86
TE-37	Reserved	07/01/86
TE-38	Traffic Signal System, Miscellaneous Details	r11/03/89
TE-39	Traffic Signal System, Miscellaneous Details	07/01/86
TE-40	Loop Detectors	r11/03/89
TE-41 •	Pullboxes	07/01/86
TE-42	Type III Traffic Signal Standard	07/01/86
TE-43	Concrete Pullbox (2' x 3')	07/01/86
TE-43	Reserved	07/01/86

STANDARD PLAN NO.	1 111 F	DATE
TE-45	Reserved	07/01/86
TE-46	Reserved	07/01/86
TE-47	Reserved	07/01/86
TE-48	Reserved	07/01/86
TE-49 ·	Reserved	07/01/86
TE-50 •	Metal Guardrail	r03/06/87
TE-51	Metal Guardrail	r09/01/87
TE-52	Metal Guardrail with Rubrail	r11/03/89
TE-53	Metal Guardrail with Rubrail at Obstruction	r09/01/87
TE-54	Beam Type Guardrail with Rubrail at Obstruction (Shoulder Installation)	r11/03/89
TE-55	Metal Guardrail Connection to Concrete Barrier	r11/03/89
TE-56	Concrete Barrier Transition	07/01/86
TE-57 ◆	Guardrail Type 3, Thrie Beam	r11/03/89
TE-57A	Guardrail Type 3, Modified Thrie Beam	11/03/89
TE-58 ●	Approach End Flare, One & Two Way Roadway	07/01/86
TE-59 ●	Trailing End Flare, One & Two Way Roadway	r11/03/89
TE-60 ●	Anchor Block Details	07/01/86
TE-61 ·	Breakaway Cable Terminal (BCT)	r11/03/89
TE-62 ·	Breakaway Cable Terminal (BCT)	r09/01/87
TE-63 ·	Guardrail Type 4 (Rigid Barrier)	r09/01/87
TE-64 ●	Portable Concrete Barrier	r11/03/89
TE-65	Guardrail Type 4, Miscellaneous	r09/01/87
TE-66 ●	Barricades	07/01/86
TE-67 ·	Delineation & Pavement Markings at Bridges	07/01/86
TE-68 ·	Wheelchair Ramps	r11/03/89
TE-69	Wheelchair Ramps	r11/03/89

#### NOTE:

STANDARD PLANS APPLICABLE TO THIS PROJECT ARE INDICATED BY A " • " NEXT TO THE STANDARD PLAN NO. (FOR EXAMPLE: D-O7 ● )

02/15/91 | REVISED H-19 10/16/90 REVISED H-16,H-17, H-22 & H-23 07/26/90 REVISED D-02 07/16/90 | REVISED B-12,B-13 05/09/90 REVISED TE-30, TE-31 & TE-32 11/03/89 | REVISED TE-06, TE-23, TE-30, TE-31, TE-32, TE-33, TE-38, TE-40, TE-52, TE-54, TE-55, TE-57, TE-59, TE-61, TE-64, TE-68 & TE-69, ADDED TE-57A 09/01/87 REVISED TE-04, TE-06, TE-08, TE-32, TE-51, TE-53, TE-54, TE-55, TE-57, TE-59, TE-62, TE-63, TE-65 & TE-69

03/06/87 | REVISED D-01, TE-09, TE-40, TE-50, TE-51, TE-57, TE-59, TE-61, TE-63 & TE-64

REVISION

DATE

DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION

### STANDARD PLANS SUMMARY

STATE OF HAWAII

INTERSTATE ROUTE H-1 Kunia Interchange Improvements F. A. I. Project No. IM-H1-1(219)

Date: Oct. 1997 SHEET No. 1 OF SHEETS

H-20

H-22

H-23 ●

H-21

Concrete Spillway Inlet

18" Slotted C.M.P. Drain

Hat Shaped Coupling Band

C.M.P. Coupling Details Standard Joint

#### GENERAL NOTES

- The scope of work for this project consists of modifying the Kunia Interchange including excavation, grading, asphalt concrete pavement, metal guardrails, concrete barriers, retaining walls, fencing, noise walls, highway lighting, drainage improvements, landscaping, sidewalks, traffic signals and pavement striping, marking and signing.
- 2. The Contractor is reminded of the requirements of Subsection 108.01 Subletting of Contract, which requires him to perform work amounting to not less than 50 percent of the total contract cost less deductible items. Non-compliance with this Subsection may be grounds for rejection of bid.
- 3. The Contractor's attention is directed to the following Sections of the Special Provisions: Subsection 107.13 Public Convenience and Safety; Subsection 107.21 Contractor's Responsibility For Utility Property And Services; and Section 645 -Work Zone Traffic Control.
- 4. At the end of each day's work, the Contractor shall remove all equipment and other obstructions to permit free and safe passage of public traffic.
- The existence and location of underground utilities, manholes, monuments and structures as shown on the plans are from the latest available data but the accuracy is not guaranteed. The encountering of other obstacles during the course of work is possible. The Contractor shall be held liable for any damages incurred to the existing facilities and/or improvements as a result of his operations. The Contractor shall be responsible for all utility toning at no additional cost to the State.
- 6. The Contractor shall notify Oahu Transit Services, Inc.'s Ed Sniffen (848-4571) or Lowell Tom (848-4578), two weeks prior to construction, informing them of location, scope of work, proposed closure of any street or traffic lanes, and the need to relocate any bus stop.
- 7. The Contractor shall notify the Engineer in writing, two (2) weeks prior to starting paving operations.
- S. Smooth riding connections shall be constructed at all limits of paving, including the beginning and end of project, connecting approaches, side streets, walkways and driveways as shown on the plans and/or as directed by the Engineer.
- 9. Dressing of shoulder and sidewalk shall consist of clearing, grubbing, grading, reshaping and compacting with suitable material as shown on the plans and/or as directed by the Engineer. This work shall be considered incidental to the various contract items.
- 10. Earth swale shall be graded to drain. This work shall be considered incidental to the various contract items.
- 11. The contractor shall provide for access to and from all existing side streets at all times.
- 12. All saw cutting work shall be considered incidental to the various contract items.
- 3. The subgrade cross-slope shall be parallel to the roadway cross-slope.
- 14. Reference and survey monuments shall be installed at an offset of 4.00 feet from the E.P. on the right shoulder.
- 15. 6-Feet Chain Link Fence with Toprail and Concrete Footing shall be installed at an offset of 1.00 foot from the new R/W line.
- 16. Spot elevations shown on Pavement Grade Plans (Shts. 53-57) are radial to 4.

FED. ROAD DIST. NO. STATE FED. AID PROJ. NO. FISCAL SHEET TOTAL SHEETS

HAWAII HAW. IM-H1-1(219) 1998 3 378

- 17. For Curb, Type 2D details, see Standard Plan D-04. "T" on the detail shall be 12".
- 18. Wherever new guardrail installation crosses paved gutters, the minimum clearance between guardrail post and invert of gutter shall be 6 inches. If guardrail post removal is necessary to maintain the minimum clearance, then nested guardrail shall be installed to span the distance between the adjacent guardrail posts. Prior to construction, the Contractor shall submit a shop drawing showing the proposed guardrail post layout for the acceptance by the Engineer. The nested guardrail elements and other incidentals necessary to complete the work will not be paid for separately and shall be considered incidental to the various guardrail contract items.

### DUST CONTROL NOTES

- 1. The Contractor, at his expense, shall keep the project area and surrounding area free of dust nuisance. The work shall be in conformance with the Air Pollution Control Standards and Regulations of the State Department of Health and the City and County of Honolulu Code.
- 2. The graded or project site that is cleared of vegetation shall be kept damp seven (7) days a week through the use of misters and/or water wagons as necessary. At the end of each day, the site shall be sufficiently dampened so that it will remain moistened during the night. If the use of water causes problems with mud or soil erosion or water pollution or there is a notice by the Board of Water Supply to conserve water in the area, the contractor shall utilize dust control agents approved by the Engineer.
- 3. The Contractor shall conduct his operations so that excavation, embankment, and imported material shall be dampened to prevent dust problems.
- The Contractor shall designate a contact person to whom the State can direct public inquiries and/or complaints regarding fugitive dust. The person shall have the authority to resolve all inquires and complaints in regards to fugitive dust.
- The Contractor shall hire an independent monitoring laboratory to monitor the amount of dust in the air daily or as directed by the Engineer. The monitoring shall begin before the project starts and end 90 days after the final acceptance. Adjustments to the Contractor's dust control means and methods shall be based on the report made by the independent monitoring laboratory. A copy of all reports shall be submitted to the Engineer. This work shall be incidental to the various contract items.

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

### GENERAL NOTES

INTERSTATE ROUTE H-1
Kunia Interchange Improvements
F. A. I. Project No. IM-H1-1(219)

Date: Oct. 1997

SHEET No. 1 OF 1 SHEETS

## NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES) GENERAL NOTES

- (A) Erosion and Sediment Control Inspection and Maintenance Practices.
  - (1) The Contractor shall inspect the erosion and sediment control measures at least once a week or after 0.5 inches of rainfall.
  - (2) The Contractor shall maintain the erosion and sediment control measures according to the contract. If a repair is necessary, the Contractor shall initiate the repairs within twenty-four (24) hours after the inspection such as:
    - (a) When sediment build-up reaches one-third (1/3) the height of the silt fence, the Contractor shall remove and dispose of the sediment build-up from the silt fence.
    - (b) When the depth of the sediment basin reaches ten percent (10%) of the design capacity, the Contractor shall remove and dispose of the sediment build-up.
    - (c) When tears are found on the silt fence, the Contractor shall replace the fabric.
    - (d) The Contractor shall check to see if the fabric is securely attached to the fence posts and to see that the fence posts are firmly in the ground.
    - (e) The Contractor shall inspect the diversion dike and repair the breaches.
    - (f) The Contractor shall inspect temporary and permanent seeding and planting for bare spots, washouts, and healthy growth.
  - (3) The Contractor shall have its personnel make a maintenance inspection report promptly after each inspection. The Contractor shall select a minimum of three (3) personnel who will be responsible for inspection, maintenance, repair activities, and filling out the inspection and maintenance report. Personnel selected for the inspection and maintenance responsibilities will receive training from the Contractor. The Contractor shall train these personnel in the inspection and maintenance practices necessary for keeping the erosion and sediment used onsite according to the contract.
- (B) Submittal Requirements:

SURVEY
DRAWN
TRACED
DESIGNED
QUANTIT

- (1) Construction activities of five (5) acres or more.
  - (a) Storm water discharges into State waters due to construction activities of five (5) acres or more, will require an NPDES permit from the Department of Health (DOH). The Contractor shall submit to the Engineer four (4) sets of Site-Specific Best Management Plans (BMP). The Plans shall be submitted no later than thirty (30) calendar days after the award of Contract.
  - (b) No construction activities will be authorized until the Contractor's Site-Specific BMP has been approved by the Highways Division.
- (2) Construction activities dewatering and/or hydrotesting water.
  - (a) Discharges into State waters due to dewatering and/or hydrotesting activities will require NPDES Permits(s) from DOH. If the Contractor options to discharge dewatering and/or hydrotesting effluent into State waters, the Contractor shall submit to the Engineer four (4) sets of Site-Specific Dewatering and/or Hydrotesting BMP, and four (4) copies of the Quality of Discharge Test results. The Plans and test results shall be submitted no later than thirty (30) calendar days after the award of Contract.
  - (b) No dewatering and/or hydrotesting activities will be authorized until the receipt of the NPDES Permit(s) from DOH.

FED. ROAD	STATE	FED. AID	FISCAL	SHEET	TOTAL
DIST. NO.		PROJ. NO.	YEAR	NO.	SHEETS
HAWAII	HAW.	IM-H1-1(219)	1998	: 4	378

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

### NPDES GENERAL NOTES

INTERSTATE ROUTE H-1
Kunia Interchange Improvements
F. A. I. Project No. IM-H1-1(219)

Date: Oct. 1997

SHEET No. 1 OF 1 SHEETS

### <u>LEGEND</u>

New Pavement Areas - (See Typical Sections for Pavement Structures)  New P.C.C.  Existing Electrical Line  New Electrical Line  Existing Joint Pole  Relocated Joint Pole  Existing Power Pole  Relocated Power Pole  Existing Electric Manhole  Existing Telephone Line  Existing Telephone Manhole  Existing Signal Corps Line  New Signal Corps Line  Existing Cable TV Pullbox  Existing Cable TV Line  Existing Water Line  Existing Water Air Valve  Existing Water Valve Box		Existing Sewer Line New 12" Sewer Line Existing Sewer Manhole Existing 6" Gas Line Existing Gas Valve Box Existing Gas Manhole Existing Monument New Monument Existing 24" Drain Line New 24" RCP Drain Line Existing Storm Drain Manhole New Storm Drain Manhole Frame \$ Cover Existing Grated Drop Inlet New Grated Drop Inlet Existing Catch Basin New Catch Basin New Traffic Sign Existing Traffic Sign Existing Highway Lighting Standard New Highway Lighting Standard
Existing Water Manhole	þ	Existing Highway Lighting Standard
Existing Water Valve Box Existing Water Meter		New Highway Lighting Standard  Existing Traffic Signal Pullbox  New Traffic Signal Pullbox
Existing Fire Hydrant Existing Guard Rail New Guard Rail Existing Right-of-Way		Existing Traffic Signal Control Box Existing Traffic Signal Pole Existing Loop Detectors
New Right-of-Way	203.00	New Loop Detectors Existing Pavement Grade
	/	

New Pavement Grade

### <u>ABBREVIATIONS</u>

A.C., a.c.	Asphalt Concrete
B	Baseline
<i>e.p.</i>	Existing edge of pavement
<i>e.s.</i>	Existing edge of shoulder
E.P.	New Edge of Pavement
E.S.	New Edge of Shoulder
S.E.	Super Elevation
F.W.R.	Fort Weaver Road
P.C.	Point of Curvature
P.C.C.	Point of Compound Curvature (for Alignment)
P.C.C.	Portland Cement Concrete
P.I.	Point of Intersection
P.O.C.	Point on Curvature
<i>P.T.</i>	Point of Tangency
R	Radius
S.B., s.b.	Southbound
N.B., n.b.	Norhtbound

FISCAL SHEET TOTAL YEAR NO. SHEETS FED. ROAD STATE FED. AID PROJ. NO. *378* IM-H1-1(219) 1998 HAWAII HAW. 5

> STATE OF HAWAII DEPARTMENT OF TRANSPORTATION
> HIGHWAYS DIVISION

### LEGEND AND ABBREVIATIONS

INTERSTATE ROUTE H-1 Kunia Interchange Improvements F. A. I. Project No. IM-H1-1(219)

Date: Oct. 1997

SHEET No. 1 OF 1 SHEETS

ojp

@JP

 $\circ pp$ 

°emħ

----AC----

 $\Box c \rho b$ 

---w---12---

°av

 $\Box wm$ 

 $\rightarrow$  fh