
	STATE OF HAWAII
	DEPARTMENT OF TRANSPORTATION
	HIGHWAYS DIVISION
	<u>GUARD RAIL DETAILS</u>
THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION  <i>Benjamin S. Tanaka</i>	<u>INTERSTATE ROUTE H-1 RESURFACING</u> <u>Vic. of Punchbowl Off Ramp to Kapiolani IC</u> <u>F.A.I Project No. 1M-H1-1(234)</u>  Scale: 1"=5'                      Date: June 1, 1999



SURVEY PLOTTED BY

DATE

ORIGINAL PLAN

NO.

DRAWN BY

TRACED BY

NOTED BY

QUANTITIES BY

CHECKED BY

DATE: 03/19/99

SCALE: 1" = 100'

FILE: 9815-184

PM: BST

OPER: SHAF

REVISED: 05/18/99

SCHEDULE--GUARD RAIL (H-1 170+00 to H-1 55+40)*					
DESCRIPTION	FROM	TO	DISTANCE	THREE BEAM GUARD RAIL	SINGLE BEAM GUARD RAIL
Magellan Ave.	170+00	172+46	246'	40'	206'
Magellan Ave./Capt. Cooke	172+73	183+66	1065'	150'	915'
Magellan Ave.	183+97	189+45	500'	145'	355'
H-1 EB Shoulder	180+04	182+04	215'	25'	190'
H-1 WB Shoulder	179+44	183+30	309'	309'	-
H-1 EB Shoulder	190+07	190+91	84'	25'	59'
H-1 WB Shoulder	186+60	187+70	110'	25'	85'
Vineyard Off Ramp(Lt.)	168+00	166+90	110'	25'	85'
Vineyard On Ramp(Rt.)	162+49	166+60	420'	25'	395'
Ward Avenue On Ramp	192+06	194+08	220'	25'	195'
Lunalilo Street	196+25	196+83	58'	58'	-
Ward Avenue On Ramp	194+87	195+07	75'	75'	-
H-1 EB Shoulder	196+79	199+77	298'	25'	273'
H-1 EB Shoulder	199+83	202+94	311'	50'	261'
Lunalilo On Ramp	202+00	202+70	70'	25'	45'
Lunalilo Street	202+00	202+70	70'	25'	45'
Piikoi On Ramp	17+94	20+90	296'	-	296'
Lunalilo Off Ramp	224+36	224+73	37'	37'	-
Lunalilo Street	224+48	224+73	25'	25'	-
Lunalilo Street	227+74	228+89	120'	-	120'
H-1 EB Shoulder	4+93	10+89	596'	54'	542'
H-1 WB Shoulder	11+44	13+42	198'	25'	173'
Ramp "U-1" Shoulder (Rt.)	2+60	7+61	501'	456'	45'
Ramp "U-1" Shoulder (Lt.)	(-)0+46	6+75	721'	279'	442'
H-1 WB Shoulder	14+65	15+53	90'	25'	65'
H-1 EB Shoulder	15+32	18+19	279'	25'	254'
H-1 EB Shoulder	19+14	24+60	550'	25'	525'
H-1 WB Shoulder	19+88	24+60	473'	25'	448'
H-1 EB Shoulder	25+14	30+12	512'	50'	462'
H-1 WB Shoulder	25+14	30+50	523'	25'	498'
H-1 EB Shoulder	33+56	34+36	82'	25'	57'
H-1 EB Shoulder	34+88	37+43	256'	25'	231'
H-1 WB Shoulder	36+00	37+93	192'	25'	167'
H-1 EB Shoulder	41+00	44+45	345'	50'	295'
H-1 WB Shoulder	41+96	46+39	442'	175'	267'
TOTAL			10,399'	2,403'	7,996'

SCHEDULE--GUARD RAIL					
DESCRIPTION	FROM	TO	DISTANCE	THREE BEAM GUARD RAIL	SINGLE BEAM GUARD RAIL
H-1 EB Shoulder	44+50	55+25	1050'	1050'	-
H-1 WB Shoulder	46+39	49+58	323'	323'	-
Ramp "U-3" Shoulder (Rt.)	0+00	3+93	393'	-	393'
Ramp "U-3" Shoulder (Lt.)	1+20	3+81	305'	25'	280'
Ramp "U-5" Shoulder (Rt.)	1+02	6+75	580'	-	580'
Ramp "U-6" Shoulder (Rt.)	-0+40	8+17	829'	-	829'
Ramp "U-8" Shoulder (Lt.)	1+44	2+67	138'	-	138'
Ramp "WL-0" Shoulder (Lt.)	4+74	7+44	272'	-	272'
Ramp "WL-0" Shoulder (Rt.)	6+43	7+88	145'	25'	120'
Ramp "WL-1" Shoulder (Rt.)	5+87	9+00	313'	25'	288'
Ramp "WL-1" Shoulder (Lt.)	7+75	9+90	215'	50'	165'
Old Wai'aleae Rd. Shoulder (Lt.)	3+84	4+08	25'	25'	-
Old Wai'aleae Rd. Shoulder (Lt.)	4+65	4+95	30'	30'	-
Old Wai'aleae Rd. Shoulder (Rt.)	5+06	5+27	22'	22'	-
Old Wai'aleae Rd. Shoulder (Lt.)	6+56	7+15	60'	25'	35'
Ramp "T" (Lt.) Old Wai'aleae Road	3+10	8+76	565'	-	565'
Ramp "T" (Rt.) Old Wai'aleae Road	3+80	8+27	453'	-	453'
Ramp "T" (Lt.) Old Wai'aleae Road	8+73	9+96	115'	-	115'
Ramp "T-1" (Lt.)	9+19	9+73	54'	25'	29'
Vineyard Blvd. Median WB	158+00	159+40	140'	25'	115'
Vineyard Blvd. Shoulder (Rt.)	157+71	158+87	116'	25'	91'
Vineyard Blvd. Median EB	158+66	159+36	75'	25'	50'
Vineyard Blvd. Shoulder EB	154+50	160+20	575'	25'	550'
Kin'au St. Off Ramp (Rt.)	2+50	7+68	540'	50'	490'
Kin'au St. Off Ramp (Lt.)	5+65	7+23	159'	-	159'
Kin'au St. Off Ramp (Rt.)	10+03	13+50	353'	25'	328'
Kapiolani On Ramp (Rt)	11+40	12+00	60'	60'	-
Kapiolani Off Ramp (Lt)	103+84 = 3+84	31+60	2797'	2797'	-
Kapiolani Off Ramp (Rt)	102+33 = 2+33	9+65	732'	732'	-
Kapiolani On Ramp (Rt)	12+60	25+38	1278'	1278'	-
		TOTAL	12,712'	6,667'	6,045'

\* Equation Sta. : H-1 281+75= H-1 1+75

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	55	557


BENJAMIN S. TANAKA

LICENSED PROFESSIONAL ENGINEER

No. 2065-C

HAWAII, U.S.A.

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION



STATE OF HAWAII

DEPARTMENT OF TRANSPORTATION

HIGHWAYS DIVISION

GUARD RAIL SUMMARY

INTERSTATE ROUTE H-1 RESURFACING

Vic. of Punchbowl Off Ramp to Kapiolani 1C

F.A.I. Project No. IM-H1-1(234)




Scale: As Shown      Date: June 1, 1999

SHEET NO. R27 OF 34 SHEETS







FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	55S-2	557



STRONG POST W-BEAM GUARDRAIL (SGR04a)



STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

STRONG POST W-BEAM GUARDRAIL  
INTERSTATE ROUTE H-1 RESURFACING  
Vic. of Punchbowl Off Ramp to Kapiolani IC  
F.A.I Project No. IM-H1-1(234)  
Scale: As Shown Date: June 1, 1999  
SHEET NO. B-2 OF 14 SHEETS

DATE: 05/03/99  
SCALE: 1" = 1'  
FILE: 9815-234

PM: BST  
OPER: SHA  
REVISED: -








SURVEY PLOTTED BY  
DRAWN BY  
CHECKED BY  
NOTED BY

ORIGINAL PLAN  
NO.





FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	55S-4	557



DATE: 05/03/99  
SCALE: 1" = 1'  
FILE: 9815-236


SURVEY PLOTTED BY: \_\_\_\_\_  
DRAWN BY: \_\_\_\_\_  
CHECKED BY: \_\_\_\_\_  
NO. \_\_\_\_\_

PM: BST  
OPER: SHA  
REVISED: -

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION  
**STRONG POST RUBRAIL (W-BEAM) GUARDRAIL**  
INTERSTATE ROUTE H-1 RESURFACING  
Vic. of Punchbowl Off Ramp to Kapiolani IC  
F.A.I Project No. IM-H1-1(234)  
Scale: As Shown Date: June 1, 1999  
SHEET NO. B-4 OF 14 SHEETS




FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	55S-5	557




**TRANSITION SECTION \***

\* Post spacing not to be used for Thrie Beam connection to structures.


**STEEL WASHER FOR 5/8" BOLT**



**HEX BOLT & NUT (FBX16a)**




**W-BEAM STRONG POST (PWE04)**



**BACKUP PLATE (RTB01b)**



(Use at Posts where Splices do not occur)

**SECTION THRU RAIL ELEMENT (RTM02b)**




**RAIL SPLICE**

**END SECTION (BUFFER RTE03b or RTE04b)**





**TRANSITION SECTION (RWT01b)**


Thrie-Beam back-up Plate (At Posts where Splice does not occur)




**GUARDRAIL BOLTS AND RECESSED NUT**




**ELEVATION SECTION (ROUNDED) (RTE02b)**



**ELEVATION TERMINAL CONNECTOR (RTE01b)**



**BACK SIDE FRONT SPACER BLOCK PWB03**






**STRONG POST MODIFIED THRIE-BEAM GUARDRAIL (SGR09b)**

DESIGNATOR	L
FBF01	1 3/8"
FBF02	2"
FBF03	10"

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION  
**STRONG POST MODIFIED THRIE-BEAM GUARDRAIL**  
INTERSTATE ROUTE H-1 RESURFACING  
Vic. of Punchbowl Off Ramp to Kapiolani IC  
F.A.I. Project No. IM-H1-1(234)  
Scale: As Shown Date: June 1, 1999  
SHEET NO. B-5 OF 14 SHEETS

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	55S-6	557



### DETAIL OF GUARDRAIL INSTALLATION AT OBSTRUCTION

#### NOTES:


1. All Guardrail and Concrete Barrier Designs at Obstructions shall be approved by the Engineer.
2. If  $X < 2'-0"$ , Concrete Barrier or special guardrail design.  
 $2'-0" < X < 3'-0"$ , Strong Post Rubrail or Modified Thrie-Beam with reduced post spacing.  
 $3'-0" < X$ , Strong Post W-Beam or Modified Thrie-Beam with 6'-3" post spacing. (Normal Installation)
3. If a pedestrian walkway or bicycle route is located behind the guardrail, the Engineer should install the Modified Thrie-Beam System. The rubrail termini may become a hazard to pedestrians & bicyclists.

STATE OF HAWAII	
DEPARTMENT OF TRANSPORTATION	
HIGHWAYS DIVISION	
GUARDRAIL DETAILS	
(AT OBSTRUCTION)	
INTERSTATE ROUTE H-1 RESURFACING	
Vic. of Punchbowl Off Ramp to Kapiolani IC	
F.A.I Project No. IM-H1-1(234)	
Scale: As Shown	Date: June 1, 1999
SHEET NO. B-6 OF 14 SHEETS	




FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	55S-7	557

- NOTES:
1. Metal Guardrail connection to concrete structures requires End Post Connection. See Structure Plans.
  2. Depending on the existing field conditions, the Engineer shall determine which guardrail end terminal should be installed.
  3. Refer to State's most current approved Product List for NCHRP 350 approved Guardrail End Terminals.



PLAN  
TWO WAY ROADWAY



PLAN  
ONE WAY ROADWAY (DIVIDED HIGHWAY)

SURVEY PLOTTED BY	DATE
DRAWN BY	
CHECKED BY	
DESIGNED BY	
NOTED BY	
CHECKED BY	
ORIGINAL PLAN	
NO.	

DATE: 05/03/99  
SCALE: 1" = 1'  
FILE: 9815-239

PM: BST  
OPER: SHA  
REVISED: -

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION


### GUARDRAIL DETAILS

INTERSTATE ROUTE H-1 RESURFACING  
Vic. of Punchbowl Off Ramp to Kapiolani IC  
F.A.I Project No. IM-H1-1(234)


Scale: As Shown      Date: June 1, 1999

SHEET NO. B-7 OF 14 SHEETS


FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	55S-8	557



ANCHOR PLATE DETAILS




STANDARD SWAGED FITTING AND STUD



ANCHOR BLOCK DETAIL

- Concrete, G.R.P., excavation, anchor rod and miscellaneous appurtenances necessary to anchor the guardrail ends shall be incidental to metal guardrail.



PLAN

ELEVATION

TYPE "G" FLARE END TERMINAL

NOTE:

Type "G" Modified End Terminal is a site specific end terminal with a taper and radial termini. A site specific detailed drawing is required for all Type "G" Modified End Terminal and must receive Engineer's approval.

The taper (flare rate) of the guardrail shall follow the latest edition of AASHTO'S Roadside Design Guide (currently, Table 5.6 - Suggested Flare Rate for Barrier Design, page 5-21, Jan. 1996 edition).

The radius of the radial termini is an Engineer's judgement based on the site evaluation. The Engineer shall consider safety (minimize the spearing & blunt end situation); degree and potential seriousness of the hazard; bicycle and pedestrian accessibility; maintenance equipment accessibility; Right-of-Way availability; the smallest radii the metal w-beam/thrie-beam railing can be constructed (check with supplier/contractor); posted speed limit; angle of vehicle impact; and aesthetics when designing the Type "G" Modified End Terminal.

During construction, the Contractor shall layout the proposed Type "G" Modified End Terminal and receive approval from the Construction Engineer prior to installation.

\* - Provide only where indicated on the Typical Sections and/or Roadway Plans

ORIGINAL PLAN	SURVEY PLOTTED BY _____	DATE _____
NOTEBOOK	DRAWN BY _____	_____
	TRACED BY _____	_____
	DESIGNED BY _____	_____
	QUANTITIES BY _____	_____
No. _____	CHECKED BY _____	_____


STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION
GUARDRAIL DETAILS
INTERSTATE ROUTE H-1 RESURFACING Vic. of Punchbowl Off Ramp to Kapiolani IC F.A.I Project No. IM-H1-1(234)
Scale: As Shown Date: June 1, 1999
SHEET NO. B-8 OF 14 SHEETS








FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	55S-9	557

### General Notes

1. A 6:1 or flatter slope is desirable. However, a steeper or flatter existing slope may be used.
2. Height of guardrail may be tapered down in elevation to maintain 3'-8" maximum height.
3. All posts are 8'-0" in length from where the guardrail flares away from the shoulder back to the post anchor. Posts for the post anchor are 6'-0" long.
4. Variable Paved Gutter offsets may be used to fit field conditions.
5. The Guardrail Posts shall be located away from the gutter/swale invert.
6. All fasteners, posts, blocks and rail elements shall conform to the latest edition and amendments of "A Guide to Standardized Highway Barrier Rail Hardware," a report prepared and approved by the AASHTO-AGCARTBA Joint Cooperative Committee.



Design speed mph	a:b
68	15:1
62	13:1
56	12:1
50	11:1
43	10:1
37	9:1
31	7:1




\* - Provide only where indicated on the Typical Sections and/or Roadway Plans


### BACKSLOPE ANCHOR TERMINAL (WITH 6:1 PAVED GUTTER AND TYPE "A" FLARE)

STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION	
TYPE "A" FLARE	
INTERSTATE ROUTE H-1 RESURFACING	
Vic. of Punchbowl Off Ramp to Kapiolani IC	
F.A.I. Project No. IM-H1-1(234)	
Scale: As Shown	Date: June 1, 1999
SHEET NO. B-9A OF 14 SHEETS	




FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	55S-10	557






**Steel Plate - 1/2"**  
(Hot-dip Zinc Coated Galvanized  
Welded or Bolted to Post)



**Square Washer**  
(3/16" Thick - Hot-dip  
Zinc Coated Galvanized)



**RUBRAIL ANCHOR DETAILS**



**POST ANCHOR DETAILS**

**BACKSLOPE ANCHOR TERMINAL END ANCHORAGE DETAILS**  
**TYPE "A" FLARE)**

**Note:**

All fasteners, posts, blocks and rail elements shall conform to the latest edition and amendments of "A Guide to Standardized Highway Barrier Rail Hardware," a report prepared and approved by the AASHTO-AGCARTBA Joint Cooperative Committee.

SURVEY PLOTTED BY	DATE
DRAWN BY	
TRACED BY	
CHECKED BY	
NOTED BY	
FILED BY	
ORIGINAL PLAN	
NOTEBOOK	
No.	


DATE: 05/03/99  
SCALE: 1" = 1'-0"  
FILE: 9815-242

PM: BST  
OPER: SHA  
REVISED: -


STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION
<b>TYPE "A" FLARE</b>
INTERSTATE ROUTE H-1 RESURFACING Vic. of Punchbowl Off Ramp to Kapiolani IC F.A.I Project No. IM-H1-1(234)
Scale: As Shown Date: June 1, 1999
SHEET NO. 8-9B OF 14 SHEETS









PLAN




ELEVATION





PARTIAL VIEW OF POST 1



SECTION A-A  
at Post #2



SECTION B-B  
typical @ Post 3 - 7



BEARING PLATE (E750)

## GENERAL NOTES

- Wood posts are required with the fleat.
- All bolts, nuts, cable assemblies, cable anchors and bearing plates shall be galvanized.
- The soil tube shall not protrude more than 4" above ground (measured along a 5' cord). Site grading may be necessary to meet this requirement.
- The soil tubes may be driven with an approved driving head. They shall not be driven with the wood post in the tube. If the soil tubes are placed in drilled holes, the backfill material must be satisfactorily compacted to prevent settlement.
- When rock is encountered during excavation, a 12" Dia. post hole, 20" deep may be used if approved by the engineer. Granular material will be placed in the bottom of the hole approx. 2 1/2" deep to provide drainage. The soil tubes will be field cut to length, placed in the hole and backfilled with adequately compacted material excavated from the hole.
- The breakaway cable assembly must be taut. A locking device, (vice grips or channel lock pliers) should be used to prevent the cable from twisting when tightening nuts.
- The wood blockouts shall be "toe nailed" to the rectangular wood posts to prevent them from turning when the wood shrinks.
- For curb installations, the soil tubes and posts shall be installed at the proper ground elevation behind the curb. The posts will require field drilling new holes to accommodate the rail to the post connecting bolt to maintain the proper height of the rail above the gutter pan. The excess post length above the rail will be removed if directed by the engineer.




FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	55S-12	557

ITEM NO.	QTY	BILL OF MATERIALS
S3000	1	IMPACT HEAD
F1303	1	W-BEAM GUARDRAIL END SECTION, 12 GA.
F1304	1	W-BEAM GUARDRAIL CENTER SEC., 12 GA.
G1203	1	W-BEAM GUARDRAIL, 12 GA.
S730	2	*FOUNDATION SOIL TUBE, 6" x 8" x 6'
E740	1	PIPE SLEEVE
E750	1	BEARING PLATE, 8" x 8" x 5/8"
S760	1	CABLE ANCHOR BOX
E770	1	BCT CABLE ANCHOR ASSEMBLY
E780	1	GROUND STRUT
P650	2	5.5" x 7.5" x 45" WOOD POSTS
P671	5	6" x 8" x 6' WOOD CRT POST
P675	5	6" x 8" x 14" TIMBER BLOCKOUT
HARDWARE		
B580122	24	5/8" Dia. x 1 1/4" SPLICE BOLT
B580754	2	5/8" Dia. x 7 1/2" HEX BOLT
B581004	2	5/8" Dia. x 10" HEX BOLT
B581002	1	5/8" Dia. x 10" H.G.R. BOLT (POST 2 ONLY)
B581802	5	5/8" Dia. x 18" H.G.R. BOLT (POST 3-7)
N050	34	5/8" Dia. H.G.R. NUT (SPLICE 24, SOIL TUBES 2, STRUT 2, POST 2, 1; POST 3 THRU 7, 5)
W050	10	5/8" Dia. H.G.R. WASHER
N100	2	1" ANCHOR CABLE HEX NUT
W100	2	1" ANCHOR CABLE WASHER
E350	2	3/8" x 3" LAG SCREW
SB58A	8	CABLE ANCHOR BOX SHOULDER BOLTS
N055A	8	1/2" A325 STRUCTURAL NUTS
W050A	16	1 1/16" OD X 9/16" ID A325 STR. WASHER
Foundation Tube Options For Posts 1 & 2		
*6'-0" Split Foundation Tubes S730		
*6'-0" Solid Foundation Tubes E731		
*5'-0" Foundation Tubes S735 W/Soil Plates SP600		
*4'-6" Foundation Tubes E735 W/Soil Plates SP600		

STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION	
FLEAT-350	
FLARED ENERGY ABSORBING TERMINAL	
INTERSTATE ROUTE H-1 RESURFACING	
Vic. of Punchbowl Off Ramp to Kapiolani IC	
F.A.I Project No. IM-H1-1(234)	
Scale: As Shown	Date: June 1, 1999
SHEET NO. B-10 OF 14 SHEETS	



FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	55S-13	577




PARTIAL VIEW OF POST 1




\*for bearing plate placement, the 5" side should be installed up

BEARING PLATE [E750]




TYPICAL FLARE CONFIGURATION



POSTS 1 thru 8 [P650]

All measurements should be taken from bottom of post



TIMBER BLOCKOUT [P675]

\*\*not supplied by Road Systems.

#### GENERAL NOTES:

- Wood posts are required with the Sequential Kinking Terminal.
- All bolts, nuts, cable assemblies, cable anchors and bearing plates shall be galvanized.
- When the Sequential Kinking Terminal is selected as the end treatment for MBGF installation, the MBGF shall be flared at a rate of 50:1 to prevent the impact head from encroaching on the shoulder.
- The soil tube shall not protrude more than 4" above ground (measured along a 5' cord). Site grading may be necessary to meet this requirement. Soil tubes shall be installed for all wood posts.
- The soil tubes may be driven with an approved driving head. They shall not be driven with the wood post in the tube. If the soil tubes are placed in drilled holes, the backfill material must be satisfactorily compacted to prevent settlement.

#### GENERAL NOTES: (continued)

- When rock is encountered during excavation, a 12" Dia. post hole, 20" deep may be used if approved by the engineer. Granular material will be placed in the bottom of the hole approx. 2 1/2" deep to provide drainage. The soil tubes will be field cut to length, placed in the hole and backfilled with adequately compacted material excavated from the hole.
- The breakaway cable assembly must be taut. A locking device, (vice grips or channel lock pliers) should be used to prevent the cable from twisting when tightening nuts.
- The wood blockouts shall be "toe nailed" to the rectangular wood posts to prevent them from turning when the wood shrinks.
- A special site evaluation should be considered prior to using the Sequential Kinking Terminal where there is less than 25' between the outlet side of the Sequential Kinking Terminal and any adjacent driving lane.

ITEM NO.	QTY	BILL OF MATERIALS
S3000	1	IMPACT HEAD
S1303/S1305	1	W-BEAM GUARDRAIL END SECTION 12 GA. 12.5' or 25'
G1203/G1205	3/1	W-BEAM GUARDRAIL, 12 GA., 12.5' or 25'
E735	8	FOUNDATION SOIL TUBE, 6" x 8" x 4'-6"
SP600	8	SOIL PLATE, 24" x 18" x 1/4"
E740	1	PIPE SLEEVE
E750	1	BEARING PLATE, 8" x 8" x 5/8"
S760	1	CABLE ANCHOR BOX
E770	1	BCT ANCHOR CABLE
E780	1	GROUND STRUT
P650	8	5.5" x 7.5" x 45" WOOD POSTS
P675	6	6" x 8" x 14" TIMBER BLOCKOUT
E3151	1	**IMPACT HEAD OBJECT MARKER (Not Shown)
HARDWARE		
B580122	16/32	5/8" Dia. x 1 1/4" SPLICE BOLT
B580754	16	5/8" Dia. x 7 1/2" HEX BOLT
B581004	8	5/8" Dia. x 10" HEX BOLT
B581002	1	5/8" Dia. x 10" H.G.R. BOLT (POST 2 ONLY)
B581802	6	5/8" Dia. x 18" H.G.R. BOLT (POST 3-8)
N050	47/63	5/8" Dia. H.G.R. NUT (SPLICE 16 / 32, SOIL TUBES 22, STRUT 2, POST 2-8, 7)
W050	23	5/8" Dia. H.G.R. WASHER
N100	2	1" ANCHOR CABLE HEX NUT
W100	2	1" ANCHOR CABLE WASHER
E350	2	3/8" x 3" LAG SCREW
SB58A	8	CABLE ANCHOR BOX SHOULDER BOLTS
N055A	8	1/2" A325 STRUCTURAL NUTS
W050A	16	1 1/16" OD X 9/16" ID A325 STR. WASHER






DATE	DATE
SURVEY PLOTTED BY	DATE
DRAWN BY	DATE
CHECKED BY	DATE
NOTED BY	DATE
NO.	DATE

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION  
**SKT-350**  
**SEQUENTIAL KINKING TERMINAL**  
**INTERSTATE ROUTE H-1 RESURFACING**  
Vic. of Punchbowl Off Ramp to Kapiolani IC  
F.A.I Project No. IM-H1-1(234)  
Scale: As Shown Date: June 1, 1999  
SHEET NO. B-11 OF 14 SHEETS





FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	56	557



ROTATED: 73° 11' 04.08" AT 0.0

SURVEY PLOTTED BY	DATE
DRAWN BY	DATE
DESIGNED BY	DATE
QUANTITIES BY	DATE
CHECKED BY	DATE

DATE: 6/17/98  
SCALE: 1"=10'  
FILE: 9815-195a

ORIGINAL PLAN	NO.
NOTED BY	NO.

THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION

*Benjamin S. Tanaka*

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**IMPACT ATTENUATOR DETAILS**

**INTERSTATE ROUTE H-1 RESURFACING**  
Vic. of Punchbowl Off Ramp to Kapiolani IC  
F.A.I Project No. IM-H1-1(234)


Scale: 1"=10'      Date: June 1, 1999

SHEET NO. R28 OF 34 SHEETS



FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	57	557


TRUE NORTH  
SCALE: 1" = 10'



(WESTBOUND)  
(LUNALILO STREET ON RAMP)  
**IMPACT ATTENUATOR DETAILS**


SCALE: 1"=10'

TRUE NORTH  
SCALE: 1" = 10'



**GUARDGUARD LMC SYSTEM PLAN**

\*Double Nest W-Beam Guardrail



**MEDIUM REACT PLAN**

(WESTBOUND)  
(LUNALILO STREET OFF RAMP)  
**IMPACT ATTENUATOR DETAILS**


SCALE: 1"=10'

TRUE NORTH  
SCALE: 1" = 10'

ROTATED: 73° 11' 04.08"  
AT 0.0

DATE	DATE
SURVEY PLOTTED BY	DESIGNED BY
DRAWN BY	QUANTITIES BY
TRACED BY	CHECKED BY
NOTED BY	
ORIGINAL PLAN	No.

PM: BST  
OPER: SHA #FAI  
REVISED: 10/03/00  
DATE: 6/17/98  
SCALE: 1" = 10'  
FILE: 9815-196





THIS WORK WAS PREPARED BY  
ME OR UNDER MY SUPERVISION

*Benjamin S. Tanaka*



STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION
<b>IMPACT ATTENUATOR DETAILS</b>
INTERSTATE ROUTE H-1 RESURFACING Vic. of Punchbowl Off Ramp to Kapiolani IC F.A.I Project No. IM-H1-1(234)
Scale: 1"=10' Date: June 1, 1999
SHEET NO. R29 OF 34 SHEETS



FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	58	557



(EASTBOUND)  
(BINGHAM STREET OFF RAMP)  
**IMPACT ATTENUATOR DETAILS**  
SCALE: 1"=5'



(WESTBOUND)  
(WILDER AVENUE OFF RAMP)  
**IMPACT ATTENUATOR DETAILS**  
SCALE: 1"=5'

ROTATED: 73° 11' 04.08"  
AT 0.0

PM: BST  
OPER: SHA\*FAI  
REVISED: 09/01/00

DATE: 6/17/98  
SCALE: 1"=5'  
FILE: 9815-197

DATE	SURVEY PLOTTED BY
DATE	DRAWN BY
DATE	DESIGNED BY
DATE	CHECKED BY

THIS WORK WAS PREPARED BY  
 ME OR UNDER MY SUPERVISION  
*Benjamin S. Tanaka*

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION


**IMPACT ATTENUATOR DETAILS**

INTERSTATE ROUTE H-1 RESURFACING  
Vic. of Punchbowl Off Ramp to Kapiolani IC  
F.A.I Project No. IM-H1-1(234)


Scale: 1"=5'      Date: June 1, 1999

SHEET NO. R30 OF 34 SHEETS


FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	59	557



(WESTBOUND)  
(UNIVERSITY AVENUE ON RAMP)  
IMPACT ATTENUATOR DETAILS  
SCALE: 1"=10'




(EASTBOUND)  
(OLD WAIALAE ROAD ON RAMP)  
IMPACT ATTENUATOR DETAILS  
SCALE: 1"=10'




QUARDGUARD LMC SYSTEM PLAN

(EASTBOUND)  
(UNIVERSITY AVENUE OFF RAMP)  
IMPACT ATTENUATOR DETAILS  
SCALE: 1"=10'



MEDIUM REACT PLAN



THIS WORK WAS PREPARED BY  
 ME OR UNDER MY SUPERVISION  
*Benjamin S. Tanaka*

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**IMPACT ATTENUATOR DETAILS**

INTERSTATE ROUTE H-1 RESURFACING  
Vic. of Punchbowl Off Ramp to Kapiolani IC  
F.A.I Project No. IM-H1-1(234)

Scale: 1"=10'      Date: June 1, 1999

SHEET NO. R31 OF 34 SHEETS


ROTATED: 73° 11' 04.08"  
 AT 0.0

DATE: 6/17/98  
 SCALE: 1"=10'  
 FILE: 9815-198


SURVEY PLOTTED BY: \_\_\_\_\_  
 DRAWN BY: \_\_\_\_\_  
 DESIGNED BY: \_\_\_\_\_  
 CHECKED BY: \_\_\_\_\_

ORIGINAL PLAN: \_\_\_\_\_  
 NOTEBOOK: \_\_\_\_\_  
 No.: \_\_\_\_\_

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	60	557



QUARDGUARD SYSTEM PLAN



MEDIUM REACT PLAN

(EAST BOUND)  
(KING STREET OFF RAMP)  
IMPACT ATTENUATOR DETAILS  
SCALE: 1"=10'


ROTATED: 75° 11' 04.08"

AT 0.0

DATE: 6/17/98  
SCALE: 1" = 10'  
FILE: 9815-199

PM: BST  
OPER: SHA\*FAI  
REVISED: 05/04/99

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTED BY	DRAWN BY	
DESIGNED BY	DESIGNED BY	
QUANTITIES BY	QUANTITIES BY	
CHECKED BY	CHECKED BY	




STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION  
**IMPACT ATTENUATOR DETAILS**  
  
INTERSTATE ROUTE H-1 RESURFACING  
Vic. of Punchbowl Off Ramp to Kapiolani IC  
F.A.I Project No. IM-H1-1(234)  
Scale: 1"=10' Date: June 1, 1999  
SHEET NO. R32 OF 34 SHEETS



FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	IM-H1-1(234)	2000	61	557

IMPACT ATTENUATOR SCHEDULE						
LOCATION	QS 3003Y	QS 9003Y	QS 6906Y	QS 9006Y	QUADGUARD LMC - 69" WIDE OR MEDIUM REACT 55-B-72	QUADGUARD LMC - 90" WIDE OR MEDIUM REACT 62-B-090
Kinau St. Off Ramp (EB)						1
Vineyard Blvd. Off Ramp (WB)					1	
Lundilo St. On Ramp (WB)	1					
Lundilo St. Off Ramp (WB)						1
Bingham St. Off Ramp (EB)			1			
Wilder Avenue. Off Ramp (WB)				1		
University Ave. On Ramp (WB)	1					
University Ave. Off Ramp (EB)						1
Old Waialae Rd. On Ramp (EB)		1				
King St. Off Ramp (EB)						1
Kapiolani Blvd. Off Ramp (WB)						1
TOTAL	2	1	1	1	1	5



THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION

*Benjamin S. Tanaka*

STATE OF HAWAII  
DEPARTMENT OF TRANSPORTATION  
HIGHWAYS DIVISION

**IMPACT ATTENUATOR DETAILS  
AND SCHEDULE**


INTERSTATE ROUTE H-1 RESURFACING  
Vic. of Punchbowl Off Ramp to Kapiolani IC  
F.A.I Project No. IM-H1-1(234)

Scale: 1"=10'      Date: June 1, 1999

SHEET NO. R33 OF 34 SHEETS

(WEST BOUND)  
(OLD WAIALAE ROAD ON RAMP)  
IMPACT ATTENUATOR DETAILS


SCALE: 1"=10'



QUARDGUARD LMC SYSTEM PLAN

(WEST BOUND)  
(KAPIOLANI BLVD. OFF RAMP)  
IMPACT ATTENUATOR DETAILS

SCALE: 1"=10'



NOTES:

- Existing Sand Barrels to be Removed.
- See Sheet S30 for Connection Details to Existing Bridge Deck.

ROTATED: 73° 11' 04.08"

AT 0.0

DATE: 6/17/98

SCALE: 1" = 10'

FILE: 9815-200

PM: BST

OPER: SHA #FAL

REVISED: 05/04/99

SURVEY PLOTTED BY: \_\_\_\_\_

DRAWN BY: \_\_\_\_\_

DESIGNED BY: \_\_\_\_\_

CHECKED BY: \_\_\_\_\_

ORIGINAL PLAN: \_\_\_\_\_

NOTEBOOK: \_\_\_\_\_

No. \_\_\_\_\_