STANDARD PLANS SUMMARY

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	NH-H1-1(235)	1999	2	84

STANDARD PLAN NO.	TITLE	DATE
B-01 •	Notes and Miscellaneous Details	07/01/86
B-02		
B-03	Typical Structure Excavation and Backfill Pay Limits	07/01/86
B-04		
B-05		
B-06	Concrete Box Girder	07/01/86
B-07	Concrete Box Girder	07/01/86
B-08	Concrete Box Girder	07/01/86
B-09		
B-10		
B-11		
B-12	Prestressed Concrete Piles	r07/16/90
B-13	Prestressed Concrete Piles	r07/16/90

D-01	Chain Link Fence With Toprail	r03/06/87
D-02	Chain Link Fence Without Toprail	r07/26/90
D-03	Wire Fence With Metal Posts	07/01/86
D-04	Typical Details of Curbs and/or Gutters	07/01/86
D-05	Typical Details of Reinforced Concrete Drop Driveway	07/01/86
D-06 ●	Centerline and Reference Survey Monument	07/01/86
D-07	Street Survey Monument	07/01/86
D-08	Landscaping Shrub and Tree Planting	07/01/86
D-09	Field Office	07/01/86
D-10	Field Office	07/01/86
D-11	Project Site Laboratory	07/01/86
D-12	Project Site Laboratory	07/01/86
D-13	Field Office & Project Site Laboratory	07/01/86

5		
H-01	Type A, B, C and D Catch Basin	07/01/86
H-02	Type A1, B1, C1 and D1 Catch Basin	07/01/86
H-03	Type A2, B2, C2 and D2 Catch Basin	07/01/86
H-04	Typical Reinforcing Details for Catch Basins	07/01/86
H-05	Type A, B and C Storm Drain Manhole	07/01/86
H-06	Type D and E Storm Drain Manhole	07/01/86
H-07	Type F Storm Drain Manhole	07/01/86
H-08	Catch Basin and Manhole Casting	07/01/86
H-09	Type A-9 and A-9P Frames and Grates	07/01/86
H-10	Type A-9B Frames and Grates	07/01/86
H-11 •	Type 61614 and 61214 Grated Drop Inlet	07/01/86
H-12	Type 61616 Grated Drop Inlet	07/01/86
H−13 ●	61214, 61614 & 61616 Steel Frames and Grates	07/01/86
H-14 •	61214B Steel Frame and Grates	07/01/86
H−15 ●	61614B Steel Frame and Grates	07/01/86
H−16 ●	Concrete and Cement Rubble Masonry Structures	r10/16/90
H-17	Inlet Structures	r10/16/90
H–18	Flared End Section for Culverts	07/01/86
H-19	Outlet Structures	r02/15/91
H-20	Concrete Spillway Inlet	07/01/86
H-21	18" Slotted C.M.P. Drain	07/01/86
H-22	C.M.P. Coupling Details Standard Joint	r10/16/90
H-23	Hat Shaped Coupling Band	r10/16/90

STANDARD PLAN NO.	TITLE	DATE	STANDARD PLAN NO.	
TE-01 ●	Miscellaneous Sign Details	07/01/86	TE-45	Reserved
TE-02 ●	Galvanized Flanged Channel Sign Post Mounting	07/01/86	TE-46	Reserved
TE-03 ●	Galvanized Square Tube Sign Post Mounting	07/01/86	TE-47	Reserved
TE-04 ●	Regulatory Signs	r09/01/87	TE-48	Reserved
TE-05 ●	Warning Signs	07/01/86	TE-49	Reserved
TE-06 ●	Miscellaneous Signs	r11/03/89	TE-50	Metal Guardrail
TE-07	Reserved	07/01/86	TE-51	Metal Guardrail
TE-08 ●	Construction Signs	r09/01/87	TE-52	Metal Guardrail with Rubrail
TE-09	Miscellaneous Intersection Signs	r03/06/87	TE−53	Metal Guardrail with Rubrail at O
TE-10	Reserved	07/01/86	TE-54	Beam Type Cuardrail with Rubrai
TE-11	Bike Route Sign and Supplementary Plates	07/01/86	TE-55	Metal Guardrail Connection to Co
TE-12 ●	State Route Marker and Auxiliary Markers	07/01/86	TE-56	Concrete Barrier Transition
TE−13 ●	Interstate Route Marker	07/01/86	TE-57	Guardrail Type 3, Thrie Beam
TE−14 ●	State Route Marker and Border Detail for Guide Signs	07/01/86	TE-57A	Guardrail Type 3, Modified Thrie
TE−15 ●	Route Marker Assemblies	07/01/86	TE-58	Approach End Flare, One & Two
TE−16 ●	Miscellaneous Reflector Markers	07/01/86	TE-59	Trailing End Flare, One & Two W
TE-17 ●	Type II Object Markers	07/01/86	TE-60	Anchor Block Details
TE−18 ●	Mileposts	07/01/86	TE−61	Breakaway Cable Terminal (BCT)
TE-19	Reserved	07/01/86	TE-62	Breakaway Cable Terminal (BCT)
TE-20	Overhead Sign Supports	07/01/86	TE−63	Guardrail Type 4 (Rigid Barrier)
TE-21	Overhead Sign Support, Box Truss Type, Aluminum	07/01/86	TE-64 ●	Portable Concrete Barrier
TE-22	Foundation Details and Schedules	07/01/86	TE−65	Guardrail Type 4, Miscellaneous
TE-23 ●	Supports for Ground Mounted Guide Sign	r11/03/89	TE-66 ●	Barricades
TE-24 ●	Breakaway Sign Supports for Ground Mounted Guide Signs	07/01/86	TE-67 ●	Delineation & Pavement Markings
TE-25	Laminated Aluminum Sign Panels (Overhead)	07/01/86	TE−68	Wheelchair Ramps
TE-26 ●	Laminated Aluminum Sign Panels (Ground Mounted)	07/01/86	TE−69	Wheelchair Ramps
TE-27 ●	Solid Aluminum Extruded Sign Panel and Accessory Details	07/01/86		
TE-28	Guide Signs Luminaire Mountings	07/01/86		
TE-29	Reserved	07/01/86		
TE-30 ●	Raised Pavement Markers and Striping	r05/09/90		
TE−31 •	Miscellaneous Pavement Markings	r05/09/90		
TE-32 ●	Miscellaneous Pavement Markings	r05/09/90		
TE-33	Miscellaneous Pavement Markings	r11/03/89		
TE-34	Reserved	07/01/86		
TE−35 ●	Pavement Alphabets, Numbers & Symbols	07/01/86		
TE−36 ●	Pavement Alphabets, Numbers & Symbols	07/01/86		
TE-37	Reserved	07/01/86		
TE-38	Traffic Signal System, Miscellaneous Details	r11/03/89		•
TE-39	Traffic Signal System, Miscellaneous Details	07/01/86		
TE-40	Loop Detectors	r11/03/89		
TE-41	Pullboxes	07/01/86		
TE-42	Type III Traffic Signal Standard	07/01/86		
TE-43	Concrete Pullbox (2' x 3')	07/01/86		
TE-44	Reserved	07/01/86		
TE-43	Concrete Pullbox (2' x 3')	07/01/86 07/01/86 02 10, 07	/26/90 REVISED D	H-16,H-17, H-22 & H-23 H-02
		07 05 11,	/16/90 REVISED E /09/90 REVISED T /03/89 REVISED T TE-32, TE TE-54, TE TE-64, TE REVISED T TE-51, TE TE-59, TE /06/87 REVISED D	
			ATE	REVISION

STANDARD PLAN NO.	\mathbf{T}	
TE-45	Reserved	07/01/86
TE-46	Reserved	07/01/86
TE-47	Reserved	07/01/86
TE-48	Reserved	07/01/86
TE-49	Reserved	07/01/86
TE-50	Metal Guardrail	r03/06/87
TE-51	Metal Guardrail	r09/01/87
TE-52	Metal Guardrail with Rubrail	r11/03/89
TE-53	Metal Guardrail with Rubrail at Obstruction	r09/01/87
TE-54	Beam Type Cuardrail with Rubrail at Obstruction (Shoulder Installation)	r11/03/89
TE-55	Metal Guardrail Connection to Concrete Barrier	r11/03/89
TE-56	Concrete Barrier Transition	07/01/86
TE-57	Guardrail Type 3, Thrie Beam	r11/03/89
TE-57A	Guardrail Type 3, Modified Thrie Beam	11/03/89
TE-58	Approach End Flare, One & Two Way Roadway	07/01/86
TE-59	Trailing End Flare, One & Two Way Roadway	r11/03/89
TE-60	Anchor Block Details	07/01/86
TE-61	Breakaway Cable Terminal (BCT)	r11/03/89
TE-62	Breakaway Cable Terminal (BCT)	r09/01/87
TE−63	Guardrail Type 4 (Rigid Barrier)	r09/01/87
TE-64 ●	Portable Concrete Barrier	r11/03/89
TE-65	Guardrail Type 4, Miscellaneous	r09/01/87
TE-66 ●	Barricades	07/01/86
TE-67 ●	Delineation & Pavement Markings at Bridges	07/01/86
TE-68	Wheelchair Ramps	r11/03/89
TE-69	Wheelchair Ramps	r11/03/89

NOTE:

STANDARD PLANS APPLICABLE TO THIS PROJECT ARE INDICATED BY A " NEXT TO THE STANDARD PLAN NO. (FOR EXAMPLE: D-07 ●)

STATE OF HAWAII DEPARTMENT OF TRANSPORTATION HIGHWAYS DIVISION

STANDARD PLANS SUMMARY


INTERSTATE ROUTE H-1 RESURFACING Kunia IC to Waikele Stream Bridge F.A.I. Project No. NH-H1-1(235)

No Scale

DATE

Date: Apr. 30, 1999 SHEET NO. 1 OF 1 SHEETS

6/10/981 = 1 9814-21



GENERAL NOTES

- 1. The scope of work for this project consists of repairing and rehabilitating the existing pavement by cold planing, reconstructing weakened pavement and asphaltic concrete paving; surface drainage improvements and culvert/drainage structures; removing and installing guardrails; and installing signs, and pavement markings; highway lighting and other incidentals.
- 2. The Contractor is reminded of the requirements of the Subsection 108.01 Subletting of Contract, which requires him to perform work amounting to not less than 50 percent of the total contract cost less deductible items. Non—compliance with this Subsection may be grounds for rejection of bid.
- 3. The Contractor's attention is directed to the following Sections of the Special Provisions: Subsection 107.13 Public Convenience and Safety; Subsection 107.21 Contractor's Responsibility For Utility Property And Services; and Section 645 Traffic Control.
- 4. At the end of each day's work, the Contractor shall remove all equipment and other obstructions to permit free and safe passage of public traffic.
- 5. The existence and location of underground utilities, manholes, monuments and structures as shown on the plans are from the latest available data but the accuracy is not guaranteed. The encountering of other obstacles during the course of work is possible. The Contractor shall be held liable for any damages incurred to the existing facilities and/or improvements as a result of his operations.
- 6. The exact locations and limits or areas to be filled with leveling course, reconstructed and cold planed shall be determined in the field by the Engineer.
- 7. The Contractor shall notify in writing, the Oahu Transit Services, Inc. Roads Supervision Office, 811 Middle St. Hon. HI 96819 (ph. #848—4571) seven (7) days prior to any paving operations.
- 8. The Contractor shall notify the Engineer in writing, two (2) weeks prior to starting paving operations.
- 9. The Contractor shall remove and dispose of all existing raised pavement markers and preformed pavement marking tape prior to the overlaying Asphalt Concrete. This work shall be considered incidental to Asphalt Concrete Pavement, Mix IV and will not be paid for separately.
- 10. Smooth riding connections shall be constructed at all limits of resurfacing, including the beginning and end of project, and connecting approaches as shown on the plans and/or as directed by the Engineer.
- 11. Existing drainage system will be functional at all times during construction. The Contractor is to furnish materials, equipment, labor, tools and incidentals necessary to maintain flow. This work shall be considered incidental to various contract items.
- 12. Earth swale shall be graded to drain and will be paid under Roadway Excavation.
- 13. All saw cutting work shall be considered incidental to the various contract items.
- 14. The Contractor shall clean and remove any accumulation of aggregates and debris along the roadside within 10 feet of the edge of pavement. This work shall be considered incidental to the various contract items.

15. Base Course shall be either Plant Mix Asphalt Concrete Base Course, Recycled Plant Mix Asphalt Concrete Base Course or Plant Mix Glassphalt Concrete Base Course. Selection will be based on the least expensive base course alternative.

COLD PLANING NOTES

- 1. All saw cutting work shall be considered incidental to the various contract items and will not be paid for separately.
- 2. The exact locations and limits or areas to be cold planed will be determined in the field by the Engineer.
- 3. In cold planing the pavement over an existing structure, the Contractor shall exercise care not to damage any portion of the structure, especially the slab, joints, drain pipes or reinforcement. Any damage to the structure during the cold planing operations shall be repaired by the Contractor at no cost to the State. Repair work shall be as directed by the Engineer, The Contractor shall verify the existing pavement thickness by hand digging at various locations. This work shall be considered incidental to cold planing and will not be paid for separately.
- 4. If a vertical pavement drop—off exists at the end of each day's cold planing and paving, the Contractor shall provide a wedge with a 48:1 minimum transition taper for transverse drop—off, and no steeper than 6:1 along the lane line for longitudinal drop—off, as accepted by the Engineer. This work shall be considered incidental to Cold Planing.
- 5. Cold Planing equipment shall not be used in removing existing A.C. Pavement over concrete gutter unless otherwise indicated. This work shall be incidental to Cold Planing.


ABBREVIATIONS

A.C., a.c.	Asphalt Concrete
₿	Baseline
e.p.	Existing edge of pavement
e.s.	Existing edge of shoulder
E.P.	New Edge of Pavement
E.S.	New Edge of Shoulder
S.E.	Super Elevation
P.C.	Point of Curvature
P.C.C.	Point of Compound Curve (for Alignment)
P.C.C.	Portland Cement Concrete
P.I.	Point on Intersection
P.O.C.	Point on Curvature
P.T.	Point of Tangency
R	Radius
I.B., i.b.	Inbound
O.B., o.b.	Outbound

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	NH-H1-1(235)	1999	3	84

LEGEND

	H—1 Freeway Pavement Weakened Areas Ramp KO Reconstructed Pavement Areas	-6-fh -6-FH \$12"	Existing Fire Hydrant New Fire Hydrant Existing Sewer Line
ППППП	Bridge Approach Reconstruction	<u> </u>	(Size as Indicated)
	Reconstructed Shoulder Lane	— S12"—	New Sewer Line (Size as Indicated)
	Resurfacing Limits	^o smh	Existing Sewer Manhole
e	Existing Electrical Line	[∅] SMH	Adjusted Sewer MH Frame/Cover
——E ——	New Electrical Line	°SMH	New Sewer Manhole
jp	Existing Joint Pole	5MH 	Existing Gas Line
opp.	Existing Power Pole	7	(Size as Indicated)
°emh	Existing Electric Manhole	——G6"——	New Gas Line
^Ø EMH	Adjusted Elec. MH		(Size as Indicated)
0	Frame/Cover	gu	Existing Gas Valve Box
^О ЕМН	New Electric Manhole	^Ø G∨	Adjusted Gas Valve Box
υ	Existing Telephone Line	° _G V	New Gas Valve Box
	New Telephone Line	⁰ gmh	Existing Gas Manhole
°tp	Existing Telephone Pole	^Ø GMН	Adjusted Gas MH
°tmh	Existing Telephone Manhole Adjusted Tele. MH	0	Frame/Cover
^Ø TMH	Frame/Cover	°GMH	New Gas Manhole
отмн	New Telephone Manhole	© mon. Ø	Existing Monument
\$&	Existing Signal Corps Line	MON.	Adjusted Monument New Monument
SC	New Signal Corps Line	MON.	
tw	Existing TV Cable	— d24"—	Existing Drain Line (Size as Indicated)
TV	New TV Cable	24" RCP	New Drain Line
ω12"	Existing Water Line (Size as Indicated)		(Size as Indicated)
W/4 O"	New Water Line	$^{\circ}$ sd m h	Existing Storm Drain Manhole
— W12"—	(Size as Indicated)	[∅] SDMH	Adjusted Storm Drain
ownh	Existing Water Manhole	SDIVITI	MH Frame/Cover
Ø _{WMH}	Adjusted Water MH Frame/Cover	^o SDMH	New Storm Drain Manhole
O	New Water Manhole	\exists_{gdi}	Existing Grated Drop Inlet
°WMH °	Existing Water Air Valve	□GDI	New Grated Drop Inlet
Oav O	Adjusted Water Air Valve	<u>b</u>	Existing Catch Basin
^Ø AV	New Water Air Valve	СВ-	New Catch Basin
OAV	Existing Water Valve Box	þ	Existing Traffic Sign
	Adjusted Water Valve Box	•	New Traffic Sign
Ø₩V	New Water Valve Box	Q	Existing Highway Lighting
^O WV □wm	Existing Water Meter	6	Standard
	Adjusted Water Meter	T	New Highway Lighting Standard
WM	New Water Meter		0 (4) (4)
- WM	New Water Weter		



STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

GENERAL NOTES AND LEGEND

<u>Kunia IC to Waikele Stream Bridge</u>
F.A.I. Project No. NH-H1-1(235)


No Scale

Date: Apr. 30, 1999

SHEET NO. 1 OF 1 SHEETS

PM: BST OPER: SHA,*FAI REVISED: 03/18/99


DATE: 01/27/99 SCALE: 1 = 1 FILE: 9814-68



3

- A. Erosion and Sediment Control Inspection and Maintenance Practices:
 - (1) The Contractor shall inspect the erosion and sediment control measures at least once a week or after 0.05 inches of rainfall, or greater.
 - (2) The Contractor shall maintain the erosion and sediment control measures according to the Contract. If a repair is necessary, the Contractor shall initiate the repairs within twenty—four (24) hours after the inspection such as:
 - (a) When sediment build—up reaches one—third (1/3) the height of the silt fence, the Contractor shall remove and dispose of the sediment build—up from the silt fence.
 - (b) When the depth of the sediment basin reaches ten percent (10%) of the design capacity, the Contractor shall remove and dispose of the sediment build—up.
 - (c) When tears are found on the silt fence, the Contractor shall replace the fabric.
 - (d) The Contractor shall check to see if the fabric is securely attached to the fence posts and to see that the fence posts are firmly in the ground.
 - (e) The Contractor shall inspect the diversion dike and repair the breaches.
 - (f) The Contractor shall inspect temporary and permanent seeding and planting for bare spots, washouts, and healthy growth.
 - (3) The Contractor shall have its personnel make a maintenance inspection promptly after each inspection. The Contractor shall select a minimum of three (3) personnel who will be responsible for inspection, maintenance, repair activities, and filling out the inspection and maintenance report. Personnel selected for the inspection and maintenance responsibilities will receive training from the Contractor. The Contractor shall train these personnel in the inspection and maintenance practices necessary for keeping the erosion and sediment used onsite according to the contract. The maintenance inspection reports shall include duration and estimated volume of storm water discharge.
- (B) Submittal Requirements:
 - (1) Construction activities of five (5) acres or more.
 - (a) Storm water discharge into State waters due to construction activities of five (5) acres or more, will require an NPDES from the Department of Health (DOH). The Contractor shall submit to the Engineer four (4) sets of Site Specific Best Management Plans (BMP). The Plans shall be submitted no later than thirty (30) calendar days after the award of Contract.
 - (b) No construction activities will be authorized until the Contractor's Site—Specific BMP has been approved by the Highways Division.
 - (2) Construction activities dewatering and/or hydrotesting water.
 - (a) Discharges into State waters due to dewatering and/or hydrotesting will require NPDES Permit(s) from DOH. If the Contractor options to discharge dewatering and/or hydrotesting effluent into State waters, the Contractor shall submit to the Engineer four (4) sets of Site—Specific Dewatering and/or Hydrotesting BMP, and four (4) copies of the Quality of Discharge Test results. The Plans and test results shall be submitted no later than thirty (30) calendar days after the award of the contract.
 - (b) No dewatering and/or hydrotesting activities will be authorized until the receipt of the NPDES Permit(s) from DOH.

FED. ROAD	STATE	FED. AID	FISCAL	SHEET	TOTAL
DIST. NO.		PROJ. NO.	YEAR	NO.	SHEETS
HAWAII	HAW.	NH-H1-1(235)	1999	4	84



STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

NPDES GENERAL NOTES

Kunia IC to Waikele Stream Bridge F.A.I. Project No. NH-H1-1(235)


No Scale

Date: Apr. 30, 1999

SHEET NO. 1 OF 1 SHEETS

PM: BST OPER: SHA,CDK,*FAI REVISED: 04/23/99





4