

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DESIGNED BY	
N.	QUANTITIES BY	
	CHECKED BY	

db3ketaeocvieduct042016pcviaduct-Q1

INDEX TO DRAWINGS	
SHEET	DESCRIPTION
Q1	New Concrete Barrier Index & Bridge General Notes
Q2	New Concrete Barrier Layout Plan
Q3	New Concrete Barrier - Pier #21
Q4	New Concrete Barrier - Pier #22
Q5	New Concrete Barrier - Pier #23
Q6	New Concrete Barrier - Pier #24
Q7	New Concrete Barrier Foundation
Q8	New Concrete Barrier Typical Sections

GENERAL NOTES

DESIGN SPECIFICATIONS:

- AASHTO LRFD Bridge Design Specifications, 7th Edition 2014, including all interim revisions.
- State of Hawaii, Department of Transportation, Highways Division, "Design Criteria for Bridges and Structures", August 8, 2014.

CONSTRUCTION SPECIFICATIONS:

- Hawaii Standard Specifications for Road and Bridge Construction 2005, including Special Provisions.

MATERIALS:

- Concrete: 4,000 psi, unless otherwise specified.
- Concrete Admixtures: See Special Provisions.
- Concrete for concrete barriers shall meet the requirements of Section 601, Structural Concrete.
- A shrinkage-reducing admixture (SRA), Tetraguard AS20, manufactured by BASF, or Eclipse, Manufactured by W.R. Grace & Co., or approved equal shall be added to the concrete. The minimum dosage requirement shall be 128 ounces per cubic yard of concrete. The concrete shall have a minimum shrinkage strain of 0.00006 at 28-days and 0.000145 at 56-days according to ASTM C512.
- A corrosion inhibitor amine carboxylate water-based admixture shall be added to the concrete. The minimum dosage shall be 1.5 pints per cubic yard of concrete.
- HMA Pavement, Mix No. 4 shall meet the requirements of Section 401, Hot Mix Asphalt (HMA) Pavement.

REINFORCING STEEL:

- Deformed and Plain Carbon-Steel Bars for Concrete Reinforcement shall meet the requirements of AASHTO M 31M/M 31-10 Grade 60. (ASTM A615/A615M-09 Grade 60).
- Deformed and Plain Carbon-Steel Bars for Concrete Reinforcement to be spliced by welding or otherwise welded shall meet the requirements of AASHTO M 31M/M 31-10 Grade 60. (ASTM A615/A615M-09 Grade 60) and meet the requirements of ASTM A706/A706M-09b.
- Reinforcing Steel for Concrete Barriers shall meet the requirements of Hawaii Specifications Section 602 but will not be paid for separately.

MISCELLANEOUS MATERIALS:

- Preformed Expansion Joint Filler for concrete (bituminous type) shall conform to AASHTO M 33-99 (2012). ASTM D 994-98 (2010).
- Roofing Felt shall conform to ASTM D 226 (09) Type 2 (No. 30).

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-08-14	2016	18	88



STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

NEW CONCRETE BARRIER INDEX & GENERAL NOTES

COMMERCIAL DRIVER'S LICENSE AND
MOTORCYCLE LICENSE TESTING FACILITY
EXAMINATION SITE AND OFFICE RENOVATION
Beneath Interstate Route H-1 Pearl City Viaduct
Project No. HWY-0-08-14

Scale: As Noted Date: March, 2016

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-08-14	2016	20	88



- Notes:**
- Elevations are Similar but Opposite Hand, except for Finish Grade Elevations. Lehua Ave Elevation is to show the Finish Grade Elevations on that side of the columns, which effect the Concrete Barrier Wall height. A minimum Wall height of 4'-6" from Finish Grade must be maintained along the entire Barrier.
 - HMA Pavement over Concrete Barrier Foundation and spacing around existing columns not shown for clarity.

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

NEW CONCRETE BARRIER - PIER #21

COMMERCIAL DRIVER'S LICENSE AND
MOTORCYCLE LICENSE TESTING FACILITY
EXAMINATION SITE AND OFFICE RENOVATION
Beneath Interstate Route H-1 Pearl City Viaduct
Project No. HWY-0-08-14



Scale: As Noted Date: March, 2016

SHEET No. Q3 OF 8 SHEETS

DATE	____
SURVEY PLOTTED BY	____
DESIGNED BY	____
NOTED BY	____
CHECKED BY	____
ORIGINAL PLAN	____
NOTE BOOK	____
QUANTITIES BY	____
CHECKED BY	____

db3.katagovaduct042016.govaduct-Q3

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-08-14	2016	21	88



Notes:
 1. Elevations are Similar but Opposite Hand, except for Finish Grade Elevations. Lehua Ave Elevation is to show the Finish Grade Elevations on that side of the columns, which effect the Concrete Barrier Wall height. A minimum Wall height of 4'-6" from Finish Grade must be maintained along the entire Barrier.
 2. HMA Pavement over Concrete Barrier Foundation and spacing around existing columns not shown for clarity.

DATE	____
SURVEY PLOTTED BY	____
DESIGNED BY	____
TRACED BY	____
NOTE BOOK	____
DESIGNED BY	____
QUANTITIES BY	____
CHECKED BY	____



STATE OF HAWAII
 DEPARTMENT OF TRANSPORTATION
 HIGHWAYS DIVISION

NEW CONCRETE BARRIER - PIER #22

COMMERCIAL DRIVER'S LICENSE AND
 MOTORCYCLE LICENSE TESTING FACILITY
 EXAMINATION SITE AND OFFICE RENOVATION
 Beneath Interstate Route H-1 Pearl City Viaduct
 Project No. HWY-0-08-14

Scale: As Noted Date: March, 2016

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-08-14	2016	22	88



- Notes:**
1. Elevations are Similar but Opposite Hand, except for Finish Grade Elevations. Lehua Ave Elevation is to show the Finish Grade Elevations on that side of the columns, which effect the Concrete Barrier Wall height. A minimum Wall height of 4'-6" from Finish Grade must be maintained along the entire Barrier.
 2. HMA Pavement over Concrete Barrier Foundation and spacing around existing columns not shown for clarity.

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

NEW CONCRETE BARRIER - PIER #23


COMMERCIAL DRIVER'S LICENSE AND
MOTORCYCLE LICENSE TESTING FACILITY
EXAMINATION SITE AND OFFICE RENOVATION
Beneath Interstate Route H-1 Pearl City Viaduct
Project No. HWY-0-08-14

Scale: As Noted Date: March, 2016


SHEET No. Q5 OF 8 SHEETS

PIER NO. 23

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-08-14	2016	23	88



HUGH ST. ELEVATION
Scale: 3/16" = 1'-0"



LEHUA AVE ELEVATION
Scale: 3/16" = 1'-0"

- Notes:**
- Elevations are Similar but Opposite Hand, except for Finish Grade Elevations. Lehua Ave Elevation is to show the Finish Grade Elevations on that side of the columns, which effect the Concrete Barrier Wall height. A minimum Wall height of 4'-6" from Finish Grade must be maintained along the entire Barrier.
 - HMA Pavement over Concrete Barrier Foundation and spacing around existing columns not shown for clarity.

PIER NO. 24

DATE	____
SURVEY PLOTTED BY	____
DESIGNED BY	____
TRACED BY	____
NOTE BOOK	____
QUANTITIES BY	____
CHECKED BY	____


STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

NEW CONCRETE BARRIER - PIER #24
COMMERCIAL DRIVER'S LICENSE AND
MOTORCYCLE LICENSE TESTING FACILITY
EXAMINATION SITE AND OFFICE RENOVATION
Beneath Interstate Route H-1 Pearl City Viaduct
Project No. HWY-0-08-14


Scale: As Noted
Date: March, 2016

SHEET No. 06 OF 8 SHEETS

FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
HAWAII	HAW.	HWY-0-08-14	2016	24	88



FOUNDATION PLAN
Scale: $\frac{3}{8}" = 1'-0"$



NOTE: Only Reinforcing at Elevation Change Shown for Clarity

TYP. SECTION AT COLUMN C
Scale: $\frac{3}{8}" = 1'-0"$

NOTE: New Concrete Barrier & Reinforcing Not Shown. See Sheet Q8 For Typical Section At Column & Between Columns.

ORIGINAL PLAN	SURVEY PLOTTED BY	DATE
NOTE BOOK	DRAWN BY	XXX 1991
DESIGNED BY	XXX 1991	
QUANTITIES BY	XXX 1991	
CHECKED BY	XXX 1991	

db3.katepervaduc1042016.pervaduct-Q7

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HIGHWAYS DIVISION

NEW CONCRETE BARRIER FOUNDATION

COMMERCIAL DRIVER'S LICENSE AND
MOTORCYCLE LICENSE TESTING FACILITY
EXAMINATION SITE AND OFFICE RENOVATION

Beneath Interstate Route H-1 Pearl City Viaduct
Project No. HWY-0-08-14

Scale: As Noted Date: March, 2016

